

WATER MAIN REPLACEMENT - FY24
WATER UTILITIES DEPARTMENT
CITY OF LEE'S SUMMIT, MISSOURI
PHASE 1 - BID NO. 722

11"x17" PLOT WILL BE
HALF SCALE UNLESS
OTHERWISE NOTED

SHEET INDEX:	
GENERAL	
1	COVER SHEET
2	GENERAL NOTES & LEGEND
3	QUANTITIES
4	WATER METER SCHEDULE
WATER PLAN & PROFILES	
5	JOHN KNOX RETIREMENT VILLAGE
6	JOHN KNOX EAST COMMERCIAL DEVELOPMENT
7-9	SUMMIT WOODS #1, #2 & #3
10-14	CEDAR CREEK MALL
15-17	NE COLBERN ROAD #1, #2 & #3
18	NE RICE ROAD
19	NE POLLARD ROAD
20-21	SW MARKET STREET #1 & #2
22-23	SW SCHERER ROAD ABANDONMENT PLANS
24-25	SW SCHERER ROAD #1-1 & #1-2
26	SW SCHERER ROAD #2
27	SW SCHERER LANE
STANDARD DETAILS	
28-36	DETAILS

UTILITY COMPANIES
BEFORE EXCAVATING CALL: 1 (800) DIG-RITE

GAS
SPIRE ENERGY
RICHI GARCIA
(816) 507-0713
richi.garcia@spireenergy.com

ELECTRICITY
EVERGY
PHIL INGRAM
(816) 347-4339
1105 SE US HWY 40
BLUE SPRINGS, MO 64014
phillip.ingram@evergy.com

TELEPHONE
AT&T
CRAIG PERKINS
(816) 275-2721 500
East 8th Street, Room 1152
Kansas City, MO 64106
CP0772@att.com

WATER & WASTEWATER
LEE'S SUMMIT WATER UTILITIES
(816) 969-1940
1200 SE HAMBLIN RD.
LEE'S SUMMIT, MO 64081

STREETS & STORMWATER
PUBLIC WORKS OPERATIONS
DIVISION
(816) 969-1870
1971 SE HAMBLIN RD.
LEE'S SUMMIT, MO 64082


SCHOOLS
LS R-7 SCHOOL DISTRICT
TRANSPORTATION
KEITH HENRY
(816) 986-2405

LS R-7 SCHOOL DISTRICT FIBER
OPTICS
KINZIE WOODERSON
(816) 986-105

CABLE
COMCAST
JIM DUFF
(816) 795-2257
3400 NW DUNCAN RD.
BLUE SPRINGS, MO 64015
james_duff@cable.comcast.com

GOOGLE FIBER
ANDREA SAKLA
(415) 736-9962
908 BROADWAY BLVD.
KANSAS CITY, MO 64105
kc-google-uc@google.com

SPECTRUM
(816) 508-7287
TROY PREWITT, STEVE BAXTER
8221 WEST 119TH STREET
OVERLAND PARK, KS 66213
troy@cablem.com
steve.baxter@twcable.com



VICINITY MAP



NOTE:
KNOWN UNDERGROUND UTILITIES IN THE VICINITY OF THE WORK ARE SHOWN ON THESE PLANS, ALTHOUGH OTHERS MAY EXIST. THE LOCATIONS SHOWN ARE BELIEVED TO BE REASONABLY CORRECT, BUT DO NOT PURPORT TO BE ABSOLUTELY SO. BEFORE STARTING WORK, THE CONTRACTOR SHALL GIVE NOTICE TO AND OBTAIN INFORMATION FROM EACH OWNER AND OPERATOR OF EXISTING UNDERGROUND FACILITIES IN ACCORDANCE WITH THE MISSOURI UNDERGROUND FACILITY SAFETY AND DAMAGE PREVENTION STATUTE (RSMO CHAPTER 319.015 - 319.050).

Project: WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name: COVER SHEET

Drawn By: CNS
Checked By: KLA
Date: 02/22/2024
Project#: 722

1

SUMMARY OF QUANTITIES

<u>ITEM NO.</u>	<u>DESCRIPTION</u>	<u>UNIT</u>	<u>QUANTITY</u>
1	MOBILIZATION	LUMP SUM	1
2	CLEARING AND GRUBBING	LUMP SUM	1
3	DEMOLITION AND REMOVAL	LUMP SUM	1
4	WATER LINE PIPE – 6" PVC	LINEAR FT.	1,547
5	WATER LINE PIPE – 6" HDPE	LINEAR FT.	2,581
6	WATER LINE PIPE – 8" PVC	LINEAR FT.	8,568
7	WATER LINE PIPE – 12" PVC	LINEAR FT.	1,793
8	LOWERING WATER MAIN – 6"	LINEAR FT.	33
9	LOWERING WATER MAIN – 8"	LINEAR FT.	116
10	LOWERING WATER MAIN – 12"	LINEAR FT.	40
11	WATER SERVICE LINE - COPPER (ALL SIZES)	LINEAR FT.	545
12	WATER SERVICE - RE-CONNECTIONS (ALL SIZES)	EACH	87
13	WATER METER WELL	EACH	44
14	WATER METER RELOCATION - REUSE EXISTING METER	EACH	7
15	WATER METER SETTER	EACH	7
16	WATER METER RING AND COVER	EACH	46
17	WATER LINE VALVE – 4" GATE VALVE	EACH	1
18	WATER LINE VALVE – 6" GATE VALVE	EACH	23
19	WATER LINE VALVE – 8" GATE VALVE	EACH	24
20	WATER LINE VALVE – 12" BUTTERFLY OR GATE VALVE	EACH	9
21	WATER LINE VALVE - 20" BUTTERFLY	EACH	4
22	FIRE HYDRANT ASSEMBLY (WITH NEW HYDRANT) (SMALLER THAN 20" MAIN)	EACH	34
23	FIRE HYDRANT ASSEMBLY (WITH NEW HYDRANT) (20 " MAIN)	EACH	13
24	BLOWOFF ASSEMBLY	EACH	1
25	PAVEMENT REPAIR	SQ. YD.	901
26	DRIVEWAYS - CONCRETE RESIDENTIAL	SQ. YD.	25
27	DRIVEWAYS - CONCRETE COMMERCIAL	SQ. YD.	953
28	FENCE (ALL TYPES)	LINEAR FT.	12
29	CURB AND GUTTER (ALL TYPES)	LINEAR FT.	180
30	SIDEWALK - CONCRETE	SQ. YD.	1,438
31	ADA RAMPS - TYPE A	EACH	27
32	ADA RAMPS - TYPE B	EACH	7
33	SOD	SQ. YD.	9,336
34	EROSION CONTROL	LUMP SUM	1
35	TRAFFIC CONTROL	LUMP SUM	1

PIPE INSTALLATION SCHEDULE

SHEET	PROJECT LOCATION	STA.	TO STA.	LENGTH	PROPOSED PIPE	PIPE INSTALLATION
5	JOHN KNOX RETIREMENT VILLAGE	1+00	2+07	107	8" PVC	TRENCH INSTALLATION
5	JOHN KNOX RETIREMENT VILLAGE	4+37	11+76	739	8" FUSIBLE PVC	HDD
/	/	/	/	/	/	/
6	JOHN KNOX EAST COMMERCIAL DEVELOPMENT	1+00	1+75	75	6" PVC	TRENCH INSTALLATION
6	JOHN KNOX EAST COMMERCIAL DEVELOPMENT	1+75	3+30	155	6" CERTALOK PVC	INSTALL THROUGH EXISTING CASING
6	JOHN KNOX EAST COMMERCIAL DEVELOPMENT	3+30	6+13	283	6" PVC	TRENCH INSTALLATION
/	/	/	/	/	/	/
7	SUMMIT WOODS (#1)	1+00	2+10	110	8" CERTALOK PVC	INSTALL THROUGH EXISTING CASING
7	SUMMIT WOODS (#1)	2+10	4+75	265	8" FUSIBLE PVC	HDD
7	SUMMIT WOODS (#1)	4+75	9+17	442	8" PVC	TRENCH INSTALLATION
7	SUMMIT WOODS (#1)	9+17	12+00	283	8" FUSIBLE PVC	HDD
/	/	/	/	/	/	/
8	SUMMIT WOODS (#2)	12+00	21+64	964	8" FUSIBLE PVC	HDD
8	SUMMIT WOODS (#2)	21+64	21+84	20	8" PVC	TRENCH INSTALLATION
8	SUMMIT WOODS (#2)	21+84	23+00	116	8" FUSIBLE PVC	HDD
/	/	/	/	/	/	/
9	SUMMIT WOODS (#3)	23+00	28+71	571	8" FUSIBLE PVC	HDD
/	/	/	/	/	/	/
10	CEDAR CREEK - LINE A	1+00	5+70	470	6" HDPE	SLIPLINE
/	/	/	/	/	/	/
11	CEDAR CREEK - LINE B	1+00	6+81	581	6" FUSIBLE PVC	HDD
/	/	/	/	/	/	/
12	CEDAR CREEK - LINE C-1	1+00	2+17	117	8" FUSIBLE PVC	HDD
12	CEDAR CREEK - LINE C-1	2+17	2+96	79	8" FUSIBLE PVC	TRENCH INSTALLATION
12	CEDAR CREEK - LINE C-1	2+96	12+00	904	8" FUSIBLE PVC	HDD
/	/	/	/	/	/	/
13	CEDAR CREEK LINE C-2	12+00	20+17	817	8" FUSIBLE PVC	HDD
/	/	/	/	/	/	/
14	CEDAR CREEK - LINE E	1+00	3+63	263	6" FUSIBLE PVC	HDD
14	CEDAR CREEK - LINE D	1+00	3+25	225	8" FUSIBLE PVC	HDD
/	/	/	/	/	/	/
15	NE COLBERN RD (#1)	1+00	8+00	700	12" PVC	TRENCH INSTALLATION
/	/	/	/	/	/	/
16	NE COLBERN RD (#2)	8+00	14+20	620	12" PVC	TRENCH INSTALLATION
/	/	/	/	/	/	/
17	NE COLBERN RD (#3)	0+00	3+05	305	8" PVC	TRENCH INSTALLATION
/	/	/	/	/	/	/
18	NE RICE RD	0+00	0+27	27	8" PVC	TRENCH INSTALLATION
18	NE RICE RD	0+27	4+00	373	12" PVC	TRENCH INSTALLATION
18	NE RICE RD	4+00	4+50	50	12" PVC	HDD
18	NE RICE RD	4+50	5+00	50	12" PVC	TRENCH INSTALLATION
/	/	/	/	/	/	/
19	NE POLLARD ST	0+00	7+05	705	8" PVC	TRENCH INSTALLATION
/	/	/	/	/	/	/
20	SW MARKET ST (#1)	1+00	3+60	260	8" FUSIBLE PVC	HDD
20	SW MARKET ST (#1)	3+60	5+40	180	8" PVC	TRENCH INSTALLATION / HDD
20	SW MARKET ST (#1)	5+40	8+50	310	8" FUSIBLE PVC	HDD
/	/	/	/	/	/	/
21	SW MARKET ST (#2)	8+50	14+32	582	8" FUSIBLE PVC	HDD
/	/	/	/	/	/	/
24	SCHERER RD (WTR #1-1)	0+00	9+00	900	6" HDPE	SLIPLINE
/	/	/	/	/	/	/
25	SCHERER RD (WTR #1-2)	9+00	12+26	326	6" HDPE	SLIPLINE
25	SCHERER RD (WTR #1-2)	12+26	12+53	27	6" HDPE	TRENCH INSTALLATION
/	/	/	/	/	/	/
26	SCHERER RD (WTR #2)	0+00	8+60	860	6" HDPE	SLIPLINE
/	/	/	/	/	/	/
27	SCHERER LN	1+00	6+77	577	8" PVC	TRENCH INSTALLATION

NOTES:

1. THE PIPE INSTALLATION SCHEDULE INCLUDES TRENCHLESS INSTALLATION TO MINIMIZE SURFACE DISRUPTION AND RESTORATION. TRENCH EXCAVATION MAY BE REQUIRED IN AREAS WHERE USING TRENCHLESS INSTALLATION IS NOT POSSIBLE. IN THE EVENT TRENCH EXCAVATION IS USED IN AN AREA SCHEDULED FOR TRENCHLESS INSTALLATION, ALL ADDITIONAL COSTS SHALL BE COVERED BY THE CONTRACTOR INCLUDING BUT NOT LIMITED TO PAVEMENT REPAIR, DRIVEWAYS, CURB AND GUTTER, SIDEWALK, AND SOD.
2. WATER MAINS CROSSING A STORM SEWER OR SANITARY SEWER WITHIN 18 INCHES OF VERTICAL SEPARATION SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS WITHIN 10 HORIZONTAL FEET FROM THE CROSSING.
3. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
4. THE CONTRACTOR SHALL NOT SLOPE HDPE PIPE THROUGH A BEND GREATER THAN 22.5 DEGREES.
5. TEMPORARY WATER MAINS SHALL BE REQUIRED IN ALL AREAS WHERE EXISTING SERVICE LINES CONNECT TO WATER MAINS TO BE REPLACED BY CONTRACTOR.

[illegible]

WATER METER SCHEDULE			
SHEET	ADDRESS	METER SIZE	SERVICE LINE SIZE
5	1706 NW O'BRIEN ROAD		
5	1702 NW O'BRIEN ROAD	2"	2"
5	510 NW MURRAY ROAD	2"	2"
5	508 NW MURRAY ROAD	2"	2"
5	506 NW MURRAY ROAD	1.5"	1.5"
5	500 NW MURRAY ROAD	2"	2"
/	/	/	/
6	401 NW MURRAY ROAD	1"	1"
6	425 NW MURRAY ROAD	1"	1"
/	/	/	/
7	1692 NW CHIPMAN ROAD	1"	1"
7	1688 NW CHIPMAN ROAD	2"	2"
7	1684 NW CHIPMAN ROAD	2"	2"
7	1664 NW CHIPMAN ROAD	2"	2"
7	1680 NW CHIPMAN ROAD	1"	1"
7	1680A NW CHIPMAN ROAD	2"	2"
7	1672 NW CHIPMAN ROAD	2"	2"
/	/	/	/
8	1640 NW CHIPMAN ROAD	2"	2"
8	1632 NW CHIPMAN ROAD	2"	2"
8	1600 NW CHIPMAN ROAD	2"	2"
/	/	/	/
10	301 SW WARD ROAD (1,2)	1"	1"
10	302 SW WARD ROAD	1"	1"
10	320 SW WARD ROAD (1,2)	1"	1"
/	/	/	/
11	1101 SW 3RD STREET (1,2)	1"	1"
11	300 SW WARD ROAD (1,2)	1.5"	1.5"
/	/	/	/
12	310 SW WARD ROAD	1.5"	1.5"
12	400 SW WARD ROAD	5/8" X 3/4"	3/4"
12	404 SW WARD ROAD (1,2)	5/8" X 3/4"	3/4"
12	406 SW WARD ROAD (1,2)	5/8" X 3/4"	3/4"
12	408 SW WARD ROAD (1,2)	5/8" X 3/4"	3/4"
12	410 SW WARD ROAD	5/8" X 3/4"	3/4"
12	412 SW WARD ROAD	5/8" X 3/4"	3/4"
12	418 SW WARD ROAD	5/8" X 3/4"	3/4"
12	418 SW WARD ROAD	5/8" X 3/4"	3/4"
12	418 SW WARD ROAD	5/8" X 3/4"	3/4"
12	422 SW WARD ROAD	5/8" X 3/4"	3/4"
12	424 SW WARD ROAD	5/8" X 3/4"	3/4"
/	/	/	/
13	428 SW WARD ROAD	5/8" X 3/4"	3/4"
13	430 SW WARD ROAD	5/8" X 3/4"	3/4"
13	432 SW WARD ROAD	5/8" X 3/4"	3/4"
13	434 SW WARD ROAD (2)	5/8" X 3/4"	3/4"
13	436 SW WARD ROAD	5/8" X 3/4"	3/4"
13	438 SW WARD ROAD	1"	1"
13	444 SW WARD ROAD (1,2,3,5)	1.5"	1.5"
13	450 SW WARD ROAD	1"	1"
13	330 SW WARD ROAD (1,2,3,5)	5/8" X 3/4"	3/4"
13	330 SW WARD ROAD	2"	2"
/	/	/	/
15	913 NE COLBERN ROAD (2)	2"	2"
/	/	/	/
16	1021 NE COLBERN ROAD	1.5"	1.5"

WATER METER SCHEDULE			
SHEET	ADDRESS	METER SIZE	SERVICE LINE SIZE
18	1707 NE RICE ROAD (1,2)	5/8" X 3/4"	3/4"
18	1711 NE RICE ROAD	5/8" X 3/4"	3/4"
18	1711 NE RICE ROAD	2"	2"
18	1737 NE RICE ROAD	5/8" X 3/4"	3/4"
/	/	/	/
19	1725 NE RICE ROAD (1,2)	1"	1"
19	1725 NE RICE ROAD (1,2)	5/8" X 3/4"	3/4"
19	951 NE POLLARD STREET (1,2)	5/8" X 3/4"	3/4"
/	/	/	/
20	1831 SW MARKET STREET (1,2)	5/8" X 3/4"	3/4"
20	1825 SW MARKET STREET (1,2)	1"	1"
20	1820 SW MARKET STREET (1,2)	1"	1"
20	1819 SW MARKET STREET (1,2)	5/8" X 3/4"	3/4"
/	/	/	/
21	1808 SW MARKET STREET (1,2)	5/8" X 3/4"	3/4"
21	1813 SW MARKET STREET (1,2)	5/8" X 3/4"	3/4"
21	1807 SW MARKET STREET (1,2)	5/8" X 3/4"	3/4"
21	1801A SW MARKET STREET (4)	5/8" X 3/4"	3/4" DOUBLE SETTER
21	1801B SW MARKET STREET (1,2,5)	5/8" X 3/4"	
21	1800 SW MARKET STREET (1,2)	1"	1"
21	1803 SW MARKET STREET (1,2)	1"	1"
/	/	/	/
23	2150 SW SCHERER ROAD (1,2)	2"	2"
23	2150 SW SCHERER ROAD (1,2)	6"	6"
23	2050 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
23	1701 SW SCHERER ROAD (1,2)	1"	1"
23	1301 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
23	1301 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
23	1201 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
/	/	/	/
24	2937 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
24	2927 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
24	2919 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
24	2911 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
24	2903 SW SCHERER ROAD (4, 6)	5/8" X 3/4"	3/4" DOUBLE SETTER
24	2903 SW SCHERER ROAD (1,2,5)	5/8" X 3/4"	
24	2841 SW SCHERER ROAD (4, 6)	5/8" X 3/4"	3/4" DOUBLE SETTER
24	2841 SW SCHERER ROAD (1,2,5)	5/8" X 3/4"	
24	2831 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
/	/	/	/
25	2821 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
25	2807 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
/	/	/	/
26	1907 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
26	1825 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
26	1811 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"
26	1727 SW SCHERER ROAD (1,2)	5/8" X 3/4"	3/4"

- NOTES:
(1) INDICATES WATER METER WELL TO BE REMOVED AND REPLACED.
(2) INDICATES WATER METER RING AND COVER TO BE REMOVED AND REPLACED.
(3) INDICATES WATER METER WELL TO BE RELOCATED.
(4) INDICATES RELOCATION OF TWO WATER METERS FROM A DOUBLE SETTER TO TWO NEW METER WELLS.
(5) INDICATES WATER METER SETTER IS TO BE REMOVED AND REPLACED.
(6) INDICATES THE SECOND SERVICE TAP IN THE EXISTING DOUBLE SETTER IS UNUSED. RELOCATE ONE METER TO A NEW METER WELL.

Revision

0

MDMR REVIEW

Notes

ISSUED FOR CONSTRUCTION

Issued:

06/24/2024

02/13/2025

LEE'S SUMMIT

MISSOURI

PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

Project:

WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT. JACKSON COUNTY, MO

Sheet Name:

WATER METER SCHEDULE

Drawn By:

CNS

Checked By:

KLA



Date:

02/22/2024


Project#

722


4



Drawn By:	CNS
Checked By:	KL
Date:	02/22/2024
Project#	72



- NOTES:
1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
 2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
 3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
 4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
 5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
 6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)
 7. TRAFFIC CONTROL ALONG JACOB DR AND PRIVATE DR WILL BE COORDINATED WITH JOHN KNOX VILLAGE. THE OWNER WILL AID WITH THIS COORDINATION.



Notes:

Revision

0

1

2

06/24/2024

MDNR REVIEW

ISSUED FOR CONSTRUCTION

BID ADDENDUM #2

Notes:

Revision

0

1

2

06/24/2024

MDNR REVIEW

ISSUED FOR CONSTRUCTION

BID ADDENDUM #2

LEE'S SUMMIT

MISSOURI

PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

Project:

WATER MAIN REPLACEMENT - FY24

Phase 1 - BID# 722

CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name:

WATER PLAN & PROFILE

Drawn By:

CNS

Checked By:

KLA

Date:

02/22/2024

Project#

722

Professional Engineer

KAREN L. ALLISON

MISSOURI

Professional Engineer



19-000000000000000000

02/22/2024

7

NOTES:

1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)
7. THE 6" WATER MAIN AT STA 17+01 SHOULD BE 6" FPVC AND INSTALLED WITH DIRECTIONAL DRILLING.



Project:	WATER MAIN REPLACEMENT - FY24 PHASE 1 - BID# 722 CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO
Sheet Name:	WATER PLAN & PROFILE
Drawn By:	CNS
Checked By:	KLA
Date:	02/22/2024
Project#	722

LEE'S SUMMIT

MISSOURI

Public Works Engineering Division | 220 SE Green Street | Lee's Summit, MO 64063


Revision	Notes	Issued:
0	MDNR REVIEW	06/24/2024
1	ISSUED FOR CONSTRUCTION	02/13/2025
2	BID ADDENDUM #2	03/06/2025

Professional Engineer

KAREN L. ALLISON



Professional Engineer

2162025



NOTES:

1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)



LEE'S SUMMIT
MISSOURI

PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT. JACKSON COUNTY, MO




WATER PLAN & PROFILE

KAREN L. ALLISON
NUMBER
EX-2023042571
PROFESSIONAL ENGINEER

2025

Drawn By: CNS
Checked By: KLA
Date: 02/22/2024
Project#: 722

9



NOTES:

1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)

LEE'S SUMMIT

MISSOURI

LS

Project: WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name: WATER PLAN & PROFILE

KAREN L. ALLISON

REGISTERED PROFESSIONAL ENGINEER

MISSOURI

25042371

5/6/2025



Drawn By: CNS
Checked By: KLA
Date: 02/22/2024
Project#: 722

10


Issued: 06/24/2024
Notes: 0 MAIN REVIEW
1 ISSUED FOR CONSTRUCTION
2 BID ADDENDUM #2

Revision: 0
1
2

Public Works Engineering Division | 220 SE Green Street | Lee's Summit, MO 64063



- NOTES:
1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
 2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
 3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
 4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
 5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
 6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)



Project:

WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name:

WATER PLAN & PROFILE

Issued:

06/24/2024

Notes:

MDNR REVIEW
ISSUED FOR CONSTRUCTION
BID ADDENDUM #2

Revision:

0
1
2

Drawn By:

CNS

Checked By:

KLA

Date:

02/22/2024

Project#


722

LEE'S SUMMIT
MISSOURI



PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

Professional Engineer
KAREN L. ALLISON
NUMBER
PB-233042371
3/6/2025

11



- NOTES:
1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
 2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
 3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
 4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
 5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
 6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)



Project:

WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name:

WATER PLAN & PROFILE

Drawn By:

CNS

Checked By:

KLA

Date:

02/22/2024

Project#

722

Issued:

06/24/2024

Notes:

MDNR REVIEW
ISSUED FOR CONSTRUCTION
BID ADDENDUM #2


Revision:

0
1
2


LEE'S SUMMIT
MISSOURI

PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

12



- NOTES:
1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
 2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
 3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
 4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
 5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
 6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)



LEE'S SUMMIT
MISSOURI

Public Works Engineering Division | 220 SE Green Street | Lee's Summit, MO 64063

Project: WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name: WATER PLAN & PROFILE


Drawn By: CNS

Checked By: KLA





Date: 02/22/2024

Project#: 722

13



- NOTES:
- 1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
 - 2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
 - 3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
 - 4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
 - 5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
 - 6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)



Project:

WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name:

WATER PLAN & PROFILE

Issued:

06/24/2024

Notes:

MDNR REVIEW
ISSUED FOR CONSTRUCTION
BID ADDENDUM #2

Revision:

0
1
2

Drawn By:

CNS

Checked By:

KLA

Date:

02/22/2024


Project#

722


STATE OF MISSOURI
KAREN L. ALLISON
REGISTERED PROFESSIONAL ENGINEER
#233042371
5/16/2025


LEE'S SUMMIT
MISSOURI
PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

14




- NOTES:**
1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
 2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
 3. FUSED JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
 4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
 5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
 6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)





- NOTES:
1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
 2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
 3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
 4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
 5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
 6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)



Revision

Notes

Issued:

0	MDNR REVIEW	06/24/2024
1	ISSUED FOR CONSTRUCTION	02/13/2025

LEE'S SUMMIT

M I S S O U R I

PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

Project:

WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name:

WATER PLAN & PROFILE

STATE OF MISSOURI

KAREN L. ALLISON

NUMBER

EX-2023042571

PROFESSIONAL ENGINEER

2/13/25

Drawn By:

CNS

Checked By:

KLA





Date:

02/22/2024

Project#

722

16



NE COLBERN RD (#3)

NOTES:

1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)

Issued:

06/24/2024

Notes:

MDNR REVIEW
ISSUED FOR CONSTRUCTION

Revision:

0
1

LEE'S SUMMIT

M I S S O U R I

PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

Project:


WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name:

WATER PLAN & PROFILE


Drawn By: CNS
Checked By: KLA
Date: 02/22/2024
Project#: 722

17




NOTES:

1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)



Revision	Notes	Issued
0	MDNR REVIEW	06/24/2024
1	ISSUED FOR CONSTRUCTION	02/13/2025



Project: WATER MAIN REPLACEMENT - FY24


PHASE 1 - BID# 722

CITY OF LEE'S SUMMIT. JACKSON COUNTY, MO


Sheet Name: WATER PLAN & PROFILE



Drawn By: CNS
Checked By: KLA
Date: 02/22/2024
Project#: 722



- NOTES:
- A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
 - A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
 - FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
 - ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
 - WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
 - WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)



Project:

WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name:

WATER PLAN & PROFILE

LEE'S SUMMIT
MISSOURI

PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

Drawn By:

CNS

Checked By:

KLA

Date:

02/22/2024

Project#

722



Notes:

Revision	Notes	Issued:
0	MDNR REVIEW	06/24/2024
1	ISSUED FOR CONSTRUCTION	02/13/2025

Professional Engineer

KAREN L. ALLISON
NUMBER
EA-2023042571



19



NOTES:

- A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
- A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
- FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
- ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
- WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
- WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)

Project:	Notes:	Issued:	
	Revision:	0	MDNR REVIEW
	1	ISSUED FOR CONSTRUCTION	02/13/2025
WATER MAIN REPLACEMENT - FY24			PUBLIC WORKS ENGINEERING DIVISION 220 SE GREEN STREET LEE'S SUMMIT, MO 64063
PHASE 1 - BID# 722			
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO			
Sheet Name: WATER PLAN & PROFILE			
Drawn By:		CNS	
Checked By:		KLA	
Date:		02/22/2024	
Project#		722	
20			



- NOTES:**
1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
 2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
 3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
 4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
 5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
 6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)

Project:

WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name:

WATER PLAN & PROFILE

Drawn By:

CNS

Checked By:

KLA

Date:

02/22/2024

Project#

722

ISSUED:

06/24/2024

NOTES:

MDNR REVIEW
ISSUED FOR CONSTRUCTION

REVISION:

0
1

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806

807

808

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

880

881

882

883

884

885

886

887

888

889

890

891

892

893

894

895

896

897

898

899

900

901

902

903

904

905

906

907

908

909

910

911

912

913

914

915

916

917

918

919

920

921

922

923

924

925

926

927

928

929

930

931

932

933

934

935

936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

953

954

955

956

957

958

959

960

961

962

963

964

965

966

967

968

969

970

971

972

973

974

975

976

977

978

979

980

981

982

983

984

985

986

987

988

989

990

991

992

993

994

995

996

997

998

999

1000

1001

1002

1003

1004

1005

1006

1007

1008

1009

1010

1011

LEE'S SUMMIT

MISSOURI

PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

21

NOTES:


1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.

2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.



3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.

5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.


6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)
7. REMOVE ALL HYDRANTS ON WATER MAINS THAT ARE TO BE ABANDONED. CLOSE AND ABANDON VALVES ON WATER MAINS THAT ARE ABANDONED.



SW SCHERER ROAD 12" WATER MAIN ABANDONMENT
PLAN VIEW A





SW SCHERER ROAD 12" WATER MAIN ABANDONMENT
PLAN VIEW B




Revision	Notes	Issued
0	MDNR REVIEW	06/24/2024
1	ISSUED FOR CONSTRUCTION	02/13/2025




Drawn By:	CNS
Checked By:	KLA
Date:	02/22/2024
Project#	722



SW SCHERER ROAD 8" WATER MAIN ABANDONMENT
PLAN VIEW C





SW SCHERER ROAD 8" WATER MAIN ABANDONMENT
PLAN VIEW D



NOTES:

- A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
- A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
- FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
- ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
- WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
- WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)
- REMOVE ALL HYDRANTS ON WATER MAINS THAT ARE TO BE ABANDONED. CLOSE AND ABANDON VALVES ON WATER MAINS THAT ARE ABANDONED.



Revision

Notes

Issued:

0

MDNR REVIEW

06/24/2024

1

ISSUED FOR CONSTRUCTION

02/13/2025

LEE'S SUMMIT

M I S S O U R I

PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

Project:

WATER MAIN REPLACEMENT - FY24

Phase:

PHASE 1 - BID# 722

City:

CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name:

WATER PLAN & PROFILE

Drawn By:

CNS

Checked By:

KLA

Date:

02/22/2024

Project#


722

KAREN L. ALLISON

REGISTERED PROFESSIONAL ENGINEER

NUMBER 2023042571

24



- | | |
|--|---|
| <p><u>NOTES:</u></p> | |
| <p>1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.</p> | <p>4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRU BLOCKS AS SHOWN IN THE STANDARD DETAILS.</p> |
| <p>2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.</p> | <p>5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.</p> |
| <p>3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.</p> | <p>6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)</p> |





WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722

WATER PLAN & PROFILE



Drawn By:	CNS
Checked By:	KLA
Date:	02/22/2024
Project#	722



Revision

Notes

Issued:

0	MDNR REVIEW	06/24/2024
1	ISSUED FOR CONSTRUCTION	02/13/2025

Project:

Drawn By:

Checked By:

Date:

Project#

WATER MAIN REPLACEMENT - FY24

CNS

KLA

02/22/2024

722

Phase:

Sheet Name:

PHASE 1 - BID# 722

WATER PLAN & PROFILE

City:


Professional Engineer

CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO



KAREN L. ALLISON
NUMBER
2023042571

Lee's Summit
Missouri

PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063



- NOTES:
1. A MINIMUM OF 42" OF COVER SHALL BE MAINTAINED OVER THE TOP OF THE WATER MAIN TO THE FINISHED GRADE.
 2. A MINIMUM VERTICAL CLEAR DISTANCE OF 18" SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF THE WATER MAIN AND THE OUTSIDE OF ANY SANITARY SEWER AND STORM SEWER CROSSING.
 3. FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT MECHANICAL JOINTS SHALL BE USED WHEN THE 18" MINIMUM VERTICAL CLEAR DISTANCE CAN NOT BE MAINTAINED.
 4. ALL PLUGS, CAPS, DEAD ENDS, TEES, BENDS AND HYDRANTS SHALL BE PROVIDED WITH THRUST BLOCKS AS SHOWN IN THE STANDARD DETAILS.
 5. WATER MAINS INSTALLED PARALLEL TO A STORM SEWER OR SANITARY SEWER WITHIN 10 FEET OF HORIZONTAL SPACING SHALL HAVE FUSED PIPE JOINTS AND MEGALUG STYLE RETAINER GLANDS AT ALL MECHANICAL JOINTS.
 6. WATER MAIN PROFILES ARE BASED ON MINIMUM REQUIRED COVER. EXISTING PIPE DEPTH MAY VARY. STANDARD TRENCH DEPTHS ARE 42"-84" TO TOP OF PIPE. (ALL SHEETS)



Project:

WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO

Sheet Name:

WATER PLAN & PROFILE

LEE'S SUMMIT

M I S S O U R I

LEE'S SUMMIT

M I S S O U R I

PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

Drawn By:

CNS

Checked By:

KLA


Date:

02/22/2024

Project#


722

27




NOTE:
THIS DETAIL NOT TO BE USED FOR PIPE GREATER THAN 12"

STRADDLE BLOCK
NOT TO SCALE




VALVE BOX COVER
NOT TO SCALE

REQUIRED CONCRETE BEARING AREA (SQUARE FEET - SF)					
NOM. DIA. (INCHES)	180 TEE, PLUG	90 BEND	45 BEND	22.5 BEND	11.25 BEND
6	4.7	6.7	4.0	4.0	4.0
8	8.4	11.8	6.4	4.0	4.0
10	13.1	18.5	10.0	5.1	4.0
12	18.8	26.7	14.4	7.4	4.0
14	25.7	36.3	19.6	10.0	5.0
16	33.5	47.4	25.6	13.1	6.6
18	42.4	REST. JT.	32.5	16.5	8.3
20	REST. JT.	REST. JT.	40.1	20.4	10.3
24	REST. JT.	REST. JT.	REST. JT.	29.4	14.8




- NOTES:
1. ALL BENDS WITHOUT RESTRAINED JOINTS SHALL HAVE CONCRETE THRUST BLOCKS INSTALLED FOR RESTRAINT.
 2. MEGA LUGS MAY BE USED ONLY IN CONJUNCTION WITH CONCRETE THRUST BLOCKING.
 3. BEARING AREA MUST BE AGAINST UNDISTURBED SOIL.
 4. DO NOT COVER JOINTS OR BOLTS (WHERE APPLICABLE) WITH CONCRETE.

HORIZONTAL THRUST BLOCKS
NOT TO SCALE




VALVE STEM & BOX EXTENSION
NOT TO SCALE

REQUIRED CONCRETE VOLUME (CUBIC FEET - CF)					
NOM. DIA. (INCHES)	180 TEE, PLUG	90 BEND	45 BEND	22.5 BEND	11.25 BEND
6	50.5	71.4	38.6	19.7	9.9
8	89.8	126.9	68.7	35.0	17.6
10	140.2	198.3	107.3	54.7	27.5
12	202.0	REST. JT.	154.6	78.8	39.6
14	REST. JT.	REST. JT.	210.4	107.3	53.9
16	REST. JT.	REST. JT.	REST. JT.	140.1	70.4
18	REST. JT.	REST. JT.	REST. JT.	177.3	89.1
20	REST. JT.	REST. JT.	REST. JT.	REST. JT.	110.0
24	REST. JT.	REST. JT.	REST. JT.	REST. JT.	158.4




- NOTES:
1. ALL BENDS WITHOUT RESTRAINED JOINTS SHALL HAVE CONCRETE THRUST BLOCKS INSTALLED FOR RESTRAINT.
 2. MEGA LUGS MAY BE USED ONLY IN CONJUNCTION WITH CONCRETE THRUST BLOCKING.
 3. BEARING MUST BE AGAINST UNDISTURBED SOIL.
 4. DO NOT COVER JOINTS OR BOLTS (WHERE APPLICABLE) WITH CONCRETE.

VERTICAL THRUST BLOCKS
NOT TO SCALE



- TO ABANDON WATER VALVE:
1. REMOVE VALVE BOX AND COVER
 2. REMOVE VALVE STEM IF PRESENT
 3. FILL THE WATER VALVE BOX WITH SAND FOLLOWED BY TOP SOIL
 4. ASPHALT, SEED OR SOD OVER WATER VALVE BOX AND MATCH GRADE TO SURROUNDING GRADE
 5. RETURN BOX COVER AND STEM TO CITY OF LEE'S SUMMIT WATER OPERATIONS PERSONNEL.

ABANDONED VALVE
NOT TO SCALE




SIDEWALK/SHARED-USE PATH WITHOUT BUFFER
NOT TO SCALE

SIDEWALK/SHARED-USE PATH WITH BUFFER
NOT TO SCALE

GENERAL NOTES:


- SUBGRADE MUST BE OF STABLE, COMPACTED EARTH AND SHALL BE OVERLAYED WITH 4" COMPACTED DENSE GRADED AGGREGATE BASE.
- 1.5% CROSS SLOPE MUST BE MAINTAINED THROUGH DRIVEWAYS.
- KCMMB 4K CONCRETE MIX SHALL BE REQUIRED FOR ALL SIDEWALKS/SHARED-USE PATHS.
- ALL SIDEWALK/SHARED-USE PATHS SHALL MEET CURRENT PUBLIC RIGHT OF WAY ACCESSIBILITY GUIDELINES (PROWAG).
- AN ISOLATION JOINT SHALL BE PLACED AT A MAXIMUM OF 100 FT. CONSTRUCTION JOINTS SHALL BE PLACED THE SAME WIDTH OF SIDEWALK/SHARED-USE PATHS, BUT NO GREATER THAN 10 FT.
- AN ISOLATION JOINT SHALL BE PLACED WHERE THE SIDEWALK/SHARED-USE PATHS MEETS A RESIDENTIAL DRIVEWAY.
- SHARED-USE PATHS WIDTH SHALL BE 10 FT. WIDE.
- SIDEWALK/SHARED-USE PATHS FINISHING SHALL BE FULL BROOM FINISH OR AS DIRECTED BY CITY INSPECTOR.
- WHITE CURING COMPOUND MUST BE APPLIED UNIFORMLY TO THE CONCRETE SURFACE IMMEDIATELY AFTER FINAL FINISHING.




NOTES:

- PAVEMENT SHALL BE SAWED AND REMOVED WITHOUT DAMAGE TO ADJACENT PAVEMENT.


ASPHALT OR CONCRETE PUBLIC STREET
NOT TO SCALE




TRENCH DETAIL
NOT TO SCALE




GRAVEL DRIVEWAY RESTORATION
NOT TO SCALE



ASPHALT DRIVEWAY RESTORATION
NOT TO SCALE



CONCRETE DRIVEWAY RESTORATION
NOT TO SCALE




TYPE "A" PLATING
NOT TO SCALE
(CITY POSTED SPEEDS OF 35 MPH AND GREATER)

TYPE "B" PLATING
NOT TO SCALE
(CITY POSTED SPEEDS OF 30 MPH OR LESS)

TRENCH PLATE DETAIL

GENERAL NOTES:

- THE CONTRACTOR SHALL PROVIDE ADEQUATE OVERLAP OF PLATE ON ASPHALT TO ASSURE NO SLIPPAGE OF PLATE AND NO COLLAPSING OF TRENCH.
- ALL PLATES SHALL BE ANCHORED SO PLATES DO NOT MOVE OR SHIFT UNDER TRAFFIC.



- NOTES:**
1. WHEN RETAINER GLANDS ARE USED IN LIEU OF ANCHOR FITTINGS, HORIZONTAL THRUST BLOCKS ARE REQUIRED.
 2. GATE VALVE MAY BE BOLTED DIRECTLY TO ANCHOR TEE.
 3. SEE APPROVED PRODUCTS LIST FOR WATER UTILITIES FOR FIRE HYDRANT, VALVES, VALVE BOX LID AND COVER.
 4. BOTTOM HYDRANT FLANGE SHALL BE 2" TO 6" ABOVE FINISHED GRADE.
 5. FOR STREETS WITHOUT CURBS FIRE HYDRANTS SHALL BE PLACED WITHIN 1 FOOT OF THE RW LINE, BUT NOT MORE THAN 10' FROM EDGE OF PAVEMENT. FIRE HYDRANT SHALL NOT BE PLACED IN BOTTOM OF DITCH.
 6. HYDRANT SHALL BE ROTATED AS DIRECTED BY INSPECTOR.

1. FULL LENGTH OF WATER PIPE SHALL BE LOCATED SUCH THAT BOTH JOINTS WILL BE AS FAR FROM THE SEWER AS POSSIBLE.

The image contains two technical diagrams illustrating different methods for connecting a ductile iron pipe to an HDPE pipe.

FLANGE ADAPTER: This diagram shows a cross-section of a ductile iron pipe on the left and an HDPE pipe on the right. They are connected by a central flange adapter. The adapter is secured with a ring and a bolt. Labels include: RING, BOLT, AWWA C153 COMPACT FITTING OR VALVE, HDPE, and DUCTILE IRON.

MJ ADAPTER: This diagram shows a cross-section of a ductile iron pipe on the left and an HDPE pipe on the right. They are connected by an MJ adapter. The connection is sealed with a gasket and secured with a gland ring. Labels include: GASKET, GLAND RING, HDPE, and MJ ADAPTER.

A cross-sectional diagram of a pipe repair. A section of the pipe is filled with concrete, indicated by a stippled pattern. A dimension line above this section is labeled "12\"". An arrow points from the text "FILL PIPE WITH 12\" OF CONCRETE" to the concrete-filled area. Another arrow points from the text "ABANDONED PIPE" to the right-hand portion of the pipe, which is shown as a simple outline.

2' FROM BACK OF CURB

BACK OF CURB

GROUND SURFACE

THRUST BLOCK (SEE NOTE 1)

KEEP WEEPHOLE FREE OF CONCRETE AND FOREIGN MATERIAL

24"x24"x4" SOLID CONCRETE PAD

UNDISTURBED EARTH

PROVIDE MIN. 1/2" CU. YD. OF 3/4" GRANULAR FILL PER AWWA C600 SECTION 4.2.7.2.4

ANCHOR FITTINGS (SEE NOTES 1 & 2)

VALVE LID & COVER

VALVE BOX & BASE

20" MIN 42" MAX

VARIES

6" GATE VALVE

MECHANICAL JOINT (TYP.)

UNDISTURBED EARTH

THRUST BLOCKS

24" MIN

- NOTES:**
1. WHEN RETAINER GLANDS ARE USED IN LIEU OF ANCHOR RESTRAINT FITTINGS, HORIZONTAL THRUST BLOCKS ARE REQUIRED.
 2. GATE VALVE MAY BE BOLTED DIRECTLY TO ANCHOR TEE.
 3. SEE APPROVED PRODUCTS LIST FOR WATER UTILITIES FOR FIRE HYDRANT, VALVES, VALVE BOX LID, AND COVER.
 4. BOTTOM HYDRANT FLANGE SHALL BE 2" TO 6" ABOVE FINISHED GRADE.
 5. FOR STREETS WITHOUT CURBS FIRE HYDRANTS SHALL BE PLACED WITHIN 1 FOOT OF THE R/W LINE, BUT NOT MORE THAN 10' FROM EDGE OF PAVEMENT. FIRE HYDRANT SHALL NOT BE PLACED IN BOTTOM OF DITCH.
 6. HYDRANT SHALL BE ROTATED AS DIRECTED BY INSPECTOR.

VALVE COVER & LID

FINISH GRADE

VALVE COVER & LID

VALVE BOX & BASE

2" DR11 4710 HDPE

FUSED HDPE JOINT OR THREADED TRANSITION TO CONNECT TO A TAPPED CAP

2" HDPE 90° ELBOW

VALVE BLOCKING







INSTALL 2" POLY-WATER VALVE

PROVIDE WEEP HOLE

Revision	Notes:	Issued:
0	MDNR REVIEW	06/24/2024
1	ISSUED FOR CONSTRUCTION	02/13/2025




HYDRANTS AND METERS

Drawn By:	CNS
Checked By:	KLA
Date:	02/22/2024
Project#	722




- ### GENERAL NOTES

1. 3/4" ISOLATION JOINTS WITH 2 (2'-5 BAR) SMOOTH DOWELS SHALL BE PLACED AT RADIUS POINTS AND AT 150' INTERVALS. THESE DOWEL BARS SHALL BE GREASED AND WRAPPED ON ONE END WITH EXPANSION TUBES AND BONDED EITHER THROUGH CASTING IN PLACE OR DRILLING AND BONDING UTILIZING AN EPOXY OR POLYESTER BONDING AGENT ON THE OTHER END.
2. 3" DEEP CONTRACTION JOINTS SHALL BE INSTALLED AT APPROXIMATELY 10' INTERVALS. THESE JOINTS SHALL PASS ACROSS THE ENTIRE CURB SECTION. CONCRETE FILL SHALL HAVE UNIFORM AND SMOOTH FINISH
3. KCMMB 4K CONCRETE SHALL BE USED FOR ALL CURB.
4. ASPHALTIC CONCRETE SURFACE COURSE SHALL CONFORM TO STANDARD SPECIFICATION SECTION 2205.2.
5. CURBS FOR NEW STREETS SHALL BE BUILT ON ASPHALT OR AGGREGATE BASE AS SHOWN IN TYPICAL SECTION DETAIL.
6. WHITE CURING COMPOUND MUST BE APPLIED UNIFORMLY TO THE CONCRETE SURFACE IMMEDIATELY AFTER FINAL FINISHING.
7. ALL DOWELS & TIE BARS SHALL BE EPOXY COATED.
8. ALL TRANSVERSE CONSTRUCTION JOINTS SHALL BE CONSTRUCTED CONSISTENT WITH THE ISOLATION JOINT DETAIL AS PRESENTED IN GENERAL NOTE 1 (ABOVE).




	Project: WATER MAIN REPLACEMENT - FY24 PHASE 1 - BID# 722 CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO			 LEE'S SUMMIT MISSOURI	Revision	Notes:	Issued:
					0	MDNR REVIEW	06/24/2024
					1	ISSUED FOR CONSTRUCTION	02/12/2025
Sheet Name: CURB DETAILS				PUBLIC WORKS ENGINEERING DIVISION 220 SE GREEN STREET LEE'S SUMMIT, MO 64063			
Drawn By: CNS Checked By: KLA Date: 02/22/2024 Project# 722							



8" COMMERCIAL DRIVEWAY

6" RESIDENTIAL DRIVEWAY

DRIVEWAY WITH BUFFER
NOT TO SCALE




8" COMMERCIAL DRIVEWAY

6" RESIDENTIAL DRIVEWAY


DRIVEWAY WITHOUT BUFFER
NOT TO SCALE

GENERAL NOTES


1. SUBGRADE SHALL BE STABLE, COMPACTED EARTH AND SHALL BE OVERLAYED WITH 4" COMPACTED DENSE GRADED AGGREGATE BASE.
2. ALL DRIVE APPROACHES SHALL MEET CURRENT PUBLIC RIGHT OF WAY ACCESSIBILITY GUIDELINES (PROWAG) FOR SLOPE REQUIREMENTS WHEN SIDEWALK IS REQUIRED (SEE ADA RAMP RETROFIT DETAIL GEN-3B, SIDEWALK/SHARED USE PATH RAMP AT DRIVEWAY DETAIL).
3. JOINT AT BACK OF CURB LINE SHALL BE AN ISOLATION JOINT FOR RESIDENTIAL DRIVEWAYS.
4. KCMMB 4K CONCRETE MIX IS REQUIRED FOR ALL CURBS.
5. COMMERCIAL DRIVEWAYS, IN THE PUBLIC RIGHT OF WAY, SHALL BE KCMMB 4K CONCRETE MIX.
6. RESIDENTIAL DRIVEWAYS, IN THE PUBLIC RIGHT OF WAY, KCMMB 4K CONCRETE MIX IS RECOMMENDED. OTHER CONCRETE MIXES NEED TO BE APPROVED BY CITY INSPECTOR.
7. A JOINT MUST BE INSTALLED AT THE RIGHT OF WAY BOUNDARY FOR PROPERTY DELINEATION.
8. WHITE CURING COMPOUND MUST BE APPLIED UNIFORMLY TO THE CONCRETE SURFACE IMMEDIATELY AFTER FINAL FINISHING.
9. 3/4" FROM TOP OF CURB TO FLOWLINE AT DRIVEWAY (TYPE CG-1 CURB ONLY). MUST MAINTAIN ORIGINAL FLOWLINE OF CURB.
10. SIDEWALK ADJOINING CURB SHALL BE 6" THICK, EXTENDING 3' FROM THE DRIVEWAY.
11. THE MAXIMUM WIDTH OF A RESIDENTIAL DRIVEWAY IS 36 FEET WITHIN THE RIGHT OF WAY.



DRIVEWAY TYPICAL SECTION
(NO SIDEWALK OR SHARED-USE PATH)
NOT TO SCALE



DRIVEWAY TYPICAL SECTION
(SIDEWALK OR SHARED-USE PATH WITH BUFFER)
NOT TO SCALE



DRIVEWAY TYPICAL SECTION
(SIDEWALK OR SHARED-USE PATH WITHOUT BUFFER)
NOT TO SCALE

Revision	Notes	Issued:
0	MDNR REVIEW	06/24/2024
1	ISSUED FOR CONSTRUCTION	02/13/2025

LEE'S SUMMIT

MISSOURI

Public Works Engineering Division | 220 SE Green Street | Lee's Summit, MO 64063

Project: WATER MAIN REPLACEMENT - FY24
PHASE 1 - BID# 722
CITY OF LEE'S SUMMIT. JACKSON COUNTY, MO

Sheet Name: DRIVEWAY DETAILS

KAREN L. ALLISON

REGISTERED PROFESSIONAL ENGINEER

NUMBER 2023042571

2/22/2025

Drawn By: CNS
Checked By: KLA
Date: 02/22/2024
Project#: 722

32

3-D VIEW TYPE A SIDEWALK/SHARED-USE RAMP

ALTERNATE DETECTABLE SURFACE LAYOUT

TYPE A SIDEWALK/SHARED-USE RAMP
NOT TO SCALE

SIDEWALK/SHARED-USE PATH & SIDEWALK/SHARED-USE RAMP NOTES:

1. CURB RAMP OPENING, NOT INCLUDING FLARES, SHALL MATCH EXISTING SIDEWALK WIDTH AND OPENING SHALL BE AT LEAST 48" WIDE.
 2. USE 18" LONG #4 EPOXY COATED STEEL BARS @ 24" O.C. EMBED THE BARS 9" IN EACH DIRECTION BY BEING CAST IN PLACE OR DRILLED AND BONDED USING EPOXY RESIN BONDING COMPOUND.
 3. ALL RAMPS, SIDEWALKS, SHARED-USE PATHS SUBGRADE MUST BE OF STABLE, COMPACTED EARTH AND SHALL BE OVERLAYED WITH 4" COMPACTED DENSE GRADED AGGREGATE BASE.
 4. LONGITUDINAL JOINT SPACING TO MATCH WIDTH OF SIDEWALK.
 5. ISOLATION JOINTS SHALL BE PLACED WHERE WALK ABUTS DRIVEWAYS AND SIMILAR STRUCTURES, AND 100' CENTERS MAX.
 6. ADA MAXIMUM RAMP SLOPE = 8.33%
ADA MAXIMUM CROSS SLOPE = 2.0%
- *ROADWAY EXCEPTION:** WHERE EXISTING ROAD PROFILE GRADE DOES NOT ALLOW RAMP TO MEET RAMP SLOPE REQUIREMENT OF 8.33% OR LESS, THE RAMP SHALL BE EXTENDED TO A LENGTH OF 15 FEET TO MATCH EXISTING SIDEWALK. CROSS SLOPE OF RAMP SHALL BE 1.5%, $\pm 0.5\%$.
7. TURNING SPACES SHALL BE 1.5%, $\pm 0.5\%$, SLOPE IN ANY DIRECTION. TURNING SPACES SHALL HAVE A MINIMUM 4'x4' TURNING AREA. TURNING SPACES, WITH A SIDEWALK CURB, SHALL HAVE A 5' TURNING AREA PERPENDICULAR TO THE SIDEWALK CURB.
 8. FOR RETROFIT WORK, SLOPES TO BE DETERMINED IN FIELD BY CONTRACTOR AND APPROVED BY CITY INSPECTOR
 9. RAMP EXTENSION AREA SHALL NOT BE USED AS TRANSITION TO EXISTING SIDEWALK. ANY TRANSITIONS REQUIRED TO MATCH RAMPS TO EXISTING SIDEWALK SHALL REQUIRE REMOVAL AND REPLACEMENT OF ADDITIONAL SIDEWALK BEYOND THE RAMP AREA. SIDEWALK TRANSITION LENGTH SHALL BE EQUAL TO OR GREATER THAN THE WIDTH OF THE EXISTING SIDEWALK. RAMP EXTENSIONS SHALL BE A CONTINUOUS SLOPE.
 10. ALL SIDEWALK AND RAMP CONSTRUCTION SHALL MEET CURRENT PUBLIC RIGHT OF WAY ACCESSIBILITY GUIDELINES (PROWAG).

CONTRACTION JOINT

ISOLATION JOINT

JOINT DETAILS
NOT TO SCALE

SECTION A-A

SECTION B-B

SECTION C-C

TYPE A & B SIDEWALK RAMP
NOT TO SCALE

3-D VIEW TYPE B
SIDEWALK/SHARED-USE RAMP



TYPE B SIDEWALK/SHARED-USE RAMP
NOT TO SCALE

SIDEWALK CURB DETAIL
NOT TO SCALE



CURB & GUTTER DETAIL
AT RAMP
NOT TO SCALE

Revision	Notes:	Issued:
0	MONR REVIEW	06/24/2024
1	ISSUED FOR CONSTRUCTION	02/13/2025







TYPE M SIDEWALK/SHARED-USE RAMP
NOT TO SCALE




SIDEWALK/SHARED USE RAMP
AT DRIVEWAY WITH ADJOINING CURB




SECTION A-A




SECTION B-B



SECTION C-C



CURB & GUTTER DETAIL
AT RAMP
NOT TO SCALE



SIDEWALK CURB DETAIL
NOT TO SCALE

LEGEND


- | | |
|--|----------------------------|
| | SIDEWALK RAMP |
| | TURNING SPACE |
| | DETECTABLE WARNING SURFACE |
| | TRANSITION |

SIDEWALK/SHARED-USE PATH & SIDEWALK/SHARED-USE RAMP NOTES:

- CURB RAMP OPENING, NOT INCLUDING FLARES, SHALL MATCH EXISTING SIDEWALK WIDTH AND OPENING SHALL BE AT LEAST 48" WIDE.
- USE 18" LONG #4 EPOXY COATED TIE BARS @ 24" O.C. EMBED TIE BARS 9" IN EACH DIRECTION.
- ALL RAMPS, SIDEWALKS, SHARED-USE PATHS SUBGRADE MUST BE OF STABLE, COMPACTED EARTH AND SHALL BE OVERLAYED WITH 4" COMPACTED DENSE GRADED AGGREGATE BASE.
- LONGITUDINAL JOINT SPACING TO MATCH WIDTH OF SIDEWALK.
- ISOLATION JOINTS SHALL BE PLACED WHERE WALK ABUTS DRIVEWAYS AND SIMILAR STRUCTURES, AND 100' CENTERS MAX.
- ADA MAXIMUM RAMP SLOPE = 8.33%
ADA MAXIMUM CROSS SLOPE = 2.0%
*ROADWAY EXCEPTION: WHERE EXISTING ROAD PROFILE GRADE DOES NOT ALLOW RAMP TO MEET RAMP SLOPE REQUIREMENT OF 8.33% OR LESS, THE RAMP SHALL BE EXTENDED TO A LENGTH OF 15 FEET TO MATCH EXISTING SIDEWALK. CROSS SLOPE OF RAMP SHALL BE 1.5%, ±0.5%.
- TURNING SPACES SHALL BE 1.5%, ±0.5% SLOPE IN ANY DIRECTION. TURNING SPACES SHALL HAVE A MINIMUM 4'X4' TURNING AREA. TURNING SPACES, WITH A SIDEWALK CURB, SHALL HAVE A 5' TURNING AREA PERPENDICULAR TO THE SIDEWALK CURB.
- FOR RETROFIT WORK, SLOPES TO BE DETERMINED IN FIELD BY CONTRACTOR AND APPROVED BY CITY INSPECTOR
- RAMP EXTENSION AREA SHALL NOT BE USED AS TRANSITION TO EXISTING SIDEWALK. ANY TRANSITIONS REQUIRED TO MATCH RAMPS TO EXISTING SIDEWALK SHALL REQUIRE REMOVAL AND REPLACEMENT OF ADDITIONAL SIDEWALK BEYOND THE RAMP AREA. SIDEWALK TRANSITION LENGTH SHALL BE EQUAL TO OR GREATER THAN THE WIDTH OF THE EXISTING SIDEWALK. RAMP EXTENSIONS SHALL BE A CONTINUOUS SLOPE.
- ALL SIDEWALK AND RAMP CONSTRUCTION SHALL MEET CURRENT PUBLIC RIGHT OF WAY ACCESSIBILITY GUIDELINES (PROWAG).


Project: WATER MAIN REPLACEMENT - FY24		Project# 722
PHASE 1 - BID# 722		
CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO		
Sheet Name: CURB DETAILS		
Drawn By: CNS	Checked By: KLA	Date: 02/22/2024
Project# 722		
34		

	- WORK AREA		- CHANNELIZER
	- SIGN		- ARROW PANEL
	- BARRICADE		- FLAGGER
	- DIRECTION OF TRAVEL		



The figure consists of two diagrams illustrating the placement of various signs and markers along a two-lane highway with a median. The top diagram shows a cross-section of the road with a 100' shoulder, a 10' median, and a 10' shoulder. The bottom diagram shows a cross-section of the road with a 10' shoulder, a 10' median, and a 10' shoulder. The diagrams illustrate the placement of various signs and markers along the road.

* INSTALL SIGNS EVERY 200 FEET THROUGHOUT THE CLOSED LANE OR AS NEEDED




The diagram shows a two-lane road with a central barrier. A car labeled 'A' is on the left lane, moving right, and a car labeled 'H' is on the right lane, moving left. The distance from each car to the barrier is labeled 's'.


GUIDELINES FOR LENGTH OF LONGITUDINAL BUFFER SPACE "B"		MAXIMUM CHANNELIZER SPACING		
		SPEED LIMIT (MPH)	WITHIN TAPER (FEET)	OUTSIDE TAPER (FEET)
		25	25	50
25	35	30	30	60
30	55	35	35	70
35	85	40	40	80
40	120	45	45	90
45	170			

TAPER DIMENSIONS (FEET)				SIGN SPACING "S"		
SPEED LIMIT (MPH)	MINIMUM TAPER LENGTH "L", PER LANE WIDTH "W"			MINIMUM NUMBER OF CHANNELIZERS	SPEED LIMIT (MPH)	SPACING (FEET)
	10	11	12			
25	105	115	125	6	25	100
30	150	165	180	7	30-35	250
35	205	225	245	8	≥ 40	350
40	270	295	320	9		
45	450	495	540	13		

A diamond-shaped sign with the text "ROAD WORK AHEAD".	A diamond-shaped sign with the text "ROAD CLOSED AHEAD".	A diamond-shaped sign with the text "ONE LANE ROAD AHEAD".	A diamond-shaped sign with the text "RIGHT LANE CLOSED AHEAD". An arrow points to the word "LEFT" above the sign.	A diamond-shaped sign with the text "LEFT LANE CLOSED AHEAD". An arrow points to the word "RIGHT" above the sign.	A diamond-shaped sign showing a narrow road ahead with a car icon.
(A) W20-1 36" x 36"	(B) W20-2 36" x 36"	(C) W20-4 36" x 36"	(D) W20-5R 36" x 36"	(E) W20-7a 36" x 36"	(F) W1-4L 36" x 36"
A diamond-shaped sign showing a narrow road ahead with a car icon. An arrow points to the word "LEFT" above the sign.	A rectangular sign with the text "END ROAD WORK".	A circular sign with a red border and a red diagonal line over a left turn arrow.	A rectangular sign with the text "KEEP RIGHT" and a right-pointing arrow.	A rectangular sign with the text "ROAD CLOSED".	A rectangular sign with the text "ROAD CLOSED TO THRU TRAFFIC".
(G) W4-2R 36" x 36"	(H) G20-2 36" x 18"	(I) R3-2 24" x 24"	(J) R4-7a 24" x 30"	(K) R11-2 48" x 30"	(L) R11-4 60" x 30"




***INSTALL SIGNS EVERY 200 FEET THROUGHOUT THE CLOSED LANE OR AS NEEDED**




NOTE:

WHITE BANDS ON BARRICADES AND CHANNELIZERS SHALL BE MADE FROM HIGH INTENSITY SHEETING MATERIAL.




(OPTIONAL ON TWO LANE AND THREE LANE
STREETS WITH SPEEDS LESS THAN 35 MPH)

1. ALL SIGNS, BARRICADES, CHANNELIZERS, MARKINGS AND OTHER TRAFFIC CONTROL DEVICES SHALL CONFORM TO THE LATEST EDITION OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD).
2. ALL TRAFFIC CONTROL DEVICES SHALL BE STANDARD IN SIZE, SHAPE, COLOR, AND MESSAGE, IN GOOD CONDITION, AND RETRO-REFLECTORIZED. ALL SIGNS SHALL BE SECURELY MOUNTED WITH HEIGHT AND LATERAL LOCATION AS DESCRIBED IN THE MUTCD.
3. WARNING LIGHTS SHALL BE USED ON BARRICADES IN PLACE AT NIGHT AND ON WARNING SIGNS WHICH ALERT DRIVERS ABOUT A CHANGE IN ALIGNMENT, TRAFFIC CONTROL, LANE CLOSURE, OR ROAD CLOSURE.
4. FLAGGERS SHALL BE USED WHERE INDICATED ON THE PLANS, WHERE CONSTRUCTION VEHICLES INTERACT WITH NORMAL TRAFFIC, OR WHERE CONSTRUCTION ACTIVITIES IMPOSE A RESTRICTION ON TRAFFIC, AS DIRECTED BY THE CITY TRAFFIC ENGINEER. WHERE FLAGGERS ARE USED, ADVANCE SIGNING SHALL BE ERCTED AS SHOWN IN THE DETAILS OR AS SPECIFIED IN THE MUTCD. FLAGGERS SHALL MEET THE REQUIREMENTS IN THE MUTCD IN REGARD TO CHARACTER, TRAINING, ATTIRE, AND BEHAVIOR.
5. TRIM-LINES ARE THE CITY'S PREFERRED CHANNELIZING DEVICE. CONES MAY NOT BE USED AT NIGHTTIME.
6. TRAFFIC CONTROL DEVICES NOT IN USE OR NOT APPLICABLE SHALL BE EITHER COVERED OR REMOVED FROM THE WORK AREA.
7. THE CONTRACTOR SHALL USE BARRICADES, STREET PLATES, OR FENCING AS NEEDED TO EFFECTIVELY SHIELD PEDESTRIAN AND VEHICULAR TRAFFIC FROM EXPOSED OBJECTS, EXCAVATIONS, AND CONSTRUCTION ACTIVITIES.
8. ACCESS SHALL BE MAINTAINED TO ALL DRIVEWAYS AND SIDE STREETS UNLESS NOTED OTHERWISE ON THE PLANS.
9. NO STREET SHALL BE CLOSED WITHOUT THE APPROVAL OF THE CITY TRAFFIC ENGINEER. THE CONTRACTOR SHALL NOTIFY THE CITY TRAFFIC ENGINEER AT LEAST 10 DAYS IN ADVANCE OF ANY STREET CLOSURE. IF A DETOUR ROUTE AROUND THE CLOSURE IS TO BE PROVIDED, ALL DETOUR SIGNING SHALL BE AS SHOWN ON A PLAN APPROVED BY THE CITY TRAFFIC ENGINEER.
10. CONSTRUCTION VEHICLES PARKED ALONG STREETS SHALL BE LOCATED WITHIN THE WORK AREA (TRAFFIC CONTROL) OR WHERE OTHERWISE NORMALLY PERMITTED. CONSTRUCTION MATERIALS, INCLUDING TRAFFIC CONTROL AND VEHICLES SHALL NOT RESTRICT SIGHT DISTANCE FOR VEHICLES EXITING AT STREETS OR DRIVES.
11. CONSTRUCTION MATERIALS SHALL BE KEPT OFF OF SIDEWALKS, CONSOLIDATED IN ONE LOCATION WITHIN CITY RIGHT-OF-WAY, AND REMOVED DAILY UNLESS OTHERWISE APPROVED BY THE INSPECTOR. DIRT, MUD, AND OTHER CONSTRUCTION DEBRIS ON STREETS AND SIDEWALKS SHALL BE REMOVED IMMEDIATELY.
12. THE CONTRACTOR SHALL NOT PERFORM ANY WORK THAT WILL RESTRICT VEHICULAR TRAFFIC IN ANY WAY BETWEEN THE HOURS OF 7:00 A.M. AND 9:00 A.M. OR 4:00 P.M. AND 6:00 P.M. MONDAY THROUGH FRIDAY UNLESS OTHERWISE INDICATED IN THE SPECIFICATIONS.
13. TRAFFIC LIGHTS SHALL BE SHOWN AT LEAST 11 FEET WIDE UNLESS OTHERWISE AUTHORIZED BY THE CITY TRAFFIC ENGINEER. A "NARROW LANES" SIGN SHALL BE INSTALLED IN ADVANCE OF A LANE WIDTH REDUCTION TO LESS THAN 11 FEET.
14. ALL EDGE DROP-OFFS OF MORE THAN 2 INCHES AND LESS THAN 4 INCHES SHOULD BE PROTECTED BY A WEDGE OR BARRIER AND ALL EDGE DROP-OFFS GREATER THAN 4 INCHES SHALL HAVE EDGE PROTECTION (SEE TRAFFIC CONTROL SPECIFICATIONS FOR EDGE TREATMENT REQUIREMENTS).
15. THE "WORKERS" SYMBOLIC SIGN (MUTCD NO. W21-1a) MAY BE USED INSTEAD OF THE "ROAD WORK AHEAD" SIGN FOR WORK WITH A DURATION OF 12 HOURS OR LESS. THE "END ROAD WORK" SIGN IS NOT REQUIRED TO BE INSTALLED AFTER THE "WORKERS" SIGN.
16. NO TRAFFIC SIGNAL SHALL BE ALTERED OR MODIFIED IN ANY WAY WITHOUT A PLAN APPROVED BY THE CITY TRAFFIC ENGINEER.
17. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING ALL TRAFFIC CONTROL DEVICES ON AN AROUND-THE-CLOCK BASIS, WHETHER OR NOT WORK IS ACTIVELY BEING PURSUED AND ANY DEFICIENCIES NOTED SHALL BE CORRECTED IMMEDIATELY.
18. THE TRAFFIC CONTROL REQUIREMENTS SHOWN ON THESE PLANS ARE MINIMUM REQUIREMENTS ONLY AND DO NOT ATTEMPT TO ADDRESS IN DEPTH THE VARIETY OF SITUATIONS THAT MAY OCCUR ONCE CONSTRUCTION HAS STARTED. IN NO WAY DO THE REQUIREMENTS SHOWN ON THESE PLANS RELIEVE THE CONTRACTOR OF HIS RESPONSIBILITY FOR SELECTING THE PROPER TRAFFIC CONTROL DEVICES AND IMPLEMENTATION PROCEDURES THAT WILL ASSURE THE SAFETY OF DRIVERS, PEDESTRIANS, AND WORKERS AT ALL TIMES.
19. SHOULD THE CONTRACTOR FAIL TO ENFORCE THE TRAFFIC CONTROL PLAN OR FAIL TO CLEAN, REPLACE OR OTHERWISE MAINTAIN THE TRAFFIC CONTROL DEVICES WHEN DIRECTED TO DO SO BY THE CITY TRAFFIC ENGINEER OR REPRESENTATIVE, THE CITY MAY TAKE ONE OR MORE OF THE FOLLOWING ACTIONS:
 - A. EMPLOY ANOTHER AGENCY TO CORRECT DEFICIENCIES IN TRAFFIC CONTROL DEVICES AND DEDUCT THE COST FROM THE CONTRACTOR'S PAY ESTIMATE.
 - B. STOP THE WORK UNTIL DEFICIENCIES ARE CORRECTED.
 - C. SUSPEND ALL PAY ESTIMATES UNTIL DEFICIENCIES ARE CORRECTED, OR
 - D. PLACE THE CONTRACTOR IN DEFAULT.



NO ACCESS ALLOWED



LOCAL ACCESS PERMITTED

	Project: WATER MAIN REPLACEMENT - FY24 PHASE 1 - BID# 722 CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO		LEE'S SUMMIT MISSOURI	Issued: 06/24/2024
	Sheet Name: TRF-1 TRAFFIC CONTROL DETAILS			Revision: 0 MDNR REVIEW 1 ISSUED FOR CONSTRUCTION 02/13/2025
Drawn By: CNS Checked By: KLA Date: 02/22/2024 Project#: 722		PUBLIC WORKS ENGINEERING DIVISION 220 SE GREEN STREET LEE'S SUMMIT, MO 64063		

1. ALL SIGNS, BARRICADES, CHANNELIZERS, MARKINGS AND OTHER TRAFFIC CONTROL DEVICES SHALL CONFORM TO THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD).
2. DETOUR ROUTES ARE NOT REQUIRED TO BE POSTED FOR THE CLOSURE OF A LOCAL STREET.
3. TRAFFIC SHALL ONLY BE DETOURED VIA ARTERIAL AND/OR COLLECTOR STREETS UNLESS OTHERWISE APPROVED BY THE CITY TRAFFIC ENGINEER.
4. WHEN A ROUTE REQUIRES VEHICLES TO MAKE A TURN AT AN INTERSECTION WITH MORE THAN ONE APPROACH LANE, DETOUR SIGNS WITH ADVANCE ARROWS WILL BE REQUIRED AT LEAST 300 FEET IN ADVANCE OF THE INTERSECTION.
5. ADDITIONAL DETOUR SIGNAGE MAY BE REQUIRED BY THE CITY TRAFFIC ENGINEER.
6. REQUESTS TO USE THE CITY'S PORTABLE CHANGEABLE MESSAGE SIGNS SHALL BE MADE TO THE PUBLIC WORKS OPERATIONS DIVISION AND THE CITY TRAFFIC ENGINEER AT LEAST FIVE DAYS IN ADVANCE.



BID ITEM	UNITS	QUANTITY
ARROW PANELS	EA	X
TYPE 2 BARRICADES	EA	X
TYPE 3 BARRICADES	EA	X
CHANNELIZERS	EA	X
CONSTRUCTION SIGNS	SF	X
TEMPORARY CONCRETE TRAFFIC BARRIER	LF	X
TEMPORARY PAVEMENT MARKINGS		
4" WHITE LINE	LF	X
4" YELLOW LINE	LF	X
24" WHITE LINE	LF	X
WARNING LIGHTS	EA	X

THESE APPROXIMATE QUANTITIES ARE PROVIDED SOLELY FOR THE CONTRACTOR'S CONVENIENCE, AND ARE NOT GUARANTEED TO BE A COMPLETE LIST OF MATERIALS NECESSARY FOR TEMPORARY TRAFFIC CONTROL DURING ALL CONSTRUCTION ACTIVITIES.

[illegible]

LS **LEE'S SUMMIT**
MISSOURI
PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

Project:	WATER MAIN REPLACEMENT - FY24 PHASE 1 - BID# 722 CITY OF LEE'S SUMMIT, JACKSON COUNTY, MO
Sheet Name:	TRF-2 TRAFFIC CONTROL DETAILS



Drawn By:	CNS
Checked By:	KLA
Date:	02/22/2024
Project#	722