



1. ALL PAVEMENT MARKINGS SHALL BE APPLIED BY A QUALIFIED CONTRACTOR HAVING A MINIMUM 3 YEARS EXPERIENCE IN TRAFFIC GRADE PAVEMENT MARKING APPLICATIONS.
2. A. PRIVATE DRIVE, TEMPORARY PARKING AREA, AND OTHER PRIVATE AREAS STRIPING REQUIREMENTS:  
  
PAINT SHALL BE A NON-BLEEDING, QUICK-DRYING, ALKYD PETROLEUM BASE PAINT SUITABLE FOR TRAFFIC-BEARING SURFACE AND SHALL MEET FS TTP-85E AND MIXED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS BEFORE APPLICATION.  
  
B. ALL PAVEMENT MARKINGS WITHIN PUBLIC RIGHT-OF-WAY:  
  
THERMOPLASTIC OR PRE-FORMED THERMOPLASTIC ON ASPHALT SURFACES
3. SWEEP AND CLEAN SURFACE TO ELIMINATE LOOSE MATERIAL AND DUST.
4. APPLY TWO (2) COATS OF PAINT AT MANUFACTURER RECOMMENDED RATE WITHOUT THE ADDITION OF THINNER, WITH A MAXIMUM OF 100 SQUARE FEET PER GALLON. APPLY WITH MECHANICAL EQUIPMENT TO PRODUCE UNIFORM STRAIGHT EDGES. AT SIDEWALK, CURBS, AND CROSSWALKS USE A STRAIGHTEDGE TO ENSURE A UNIFORM, CLEAN, AND STRAIGHT STRIPE.
5. THE FOLLOWING ITEMS SHALL BE PAINTED WITH THE COLORS NOTED BELOW:  
A. HANDICAP SYMBOLS: SEE DETAIL THIS SHEET.  
B. PARKING STALL STRIPING: WHITE.

