



## 3-10 Ton R-410A PKGD Unitary Gas/Electric Rooftop

### Job Information

Name	Lees Summit Senior	Tag	RTU-AL1B
Address		Quantity	1
Sales Team	Kansas City Main Office	Model Number	YSC072H3RMA-- D1C1A10000000000 000000000000
Comments			

### General

Unit function	DX cooling, gas heat	Airflow	Convertible configuration
Airflow Application	Downflow	Design Airflow	2370 cfm
Fresh air selection	Econ-dry bulb 0-100% w/ bar relief 3ph	Tonnage	6 Ton Single compressor
Cooling Entering DB	79.10 F	Cooling Entering WB	65.90 F
Ent Air Relative Humidity	49.91 %	Ambient Temp	105.00 F
Heating capacity	Medium gas heat 3ph	Heating EAT	60.00 F
Voltage	208-230/60/3	Design ESP	1.500 in H2O
Supply fan/drive/type/motor	Oversize motor	Evaporator rows	3.00 Each
Evaporator fin spacing	192 Per Foot	Evaporator face area	9.89 sq ft
Evaporator face velocity	240 ft/min	Min. unit operating weight	710.0 lb
Max. unit operating weight	1045.0 lb	ASHRAE 90.1	Yes
Rated capacity (AHRI)	71.00 MBh		

### Main Cooling

Evap Coil Leaving Air Temp (DB)	58.99 F	Evap Coil Leaving Air Temp (WB)	56.30 F
Cooling Leaving Unit DB	59.30 F	Cooling Leaving Unit WB	56.42 F
Gross Total Capacity	69.10 MBh	Gross Sensible Capacity	51.46 MBh
Gross Latent Capacity	17.64 MBh	Net Total Capacity	69.10 MBh
Net Sensible Capacity	51.46 MBh	Net Sensible Heat Ratio	0.74 Number
Fan motor heat	0.00 MBh	Dew Point	54.50 F
Refrig charge (HFC-410A) - ckt 1	5.5 lb	Saturated Discharge Temp Circuit 1	124.42 F
Saturated Suction Temp Circuit 1	48.97 F		

### Main Heating

Input Heating Capacity	120.00 MBh	Output Heating Capacity	97.20 MBh
Output Heating Cap. w/Fan	97.20 MBh	Heating LAT	98.20 F
Heating Delta T	38.20 F		

### Motor/Electrical

Component SP	0.198 in H2O	Total Static Pressure	1.725 in H2O
Field supplied drive kit required	None	Indoor mtr operating power	1.93 bhp
Indoor RPM	1176 rpm	Indoor Motor Power	1.44 kW
Outdoor Motor Power	0.58 kW	Compressor Power	5.94 kW
System Power	7.96 kW	EER @ AHRI Conditions	11.2 EER
MCA	38.00 A	MOP	50.00 A
Compressor 1 RLA	22.40 A	Compressor 2 RLA	0.00 A
Condenser fan FLA	3.30 A	Evaporator fan FLA	6.30 A
SEER/IEER	12.70		




Baseunit			
Height	<b>3.41 ft</b>	Width	<b>4.44 ft</b>
Length	<b>7.39 ft</b>		

Fan			
Indoor Fan Type	<b>FC Centrifugal</b>	Indoor Fan Drive Type	<b>Belt</b>
Outdoor Fan Type	<b>Propeller</b>	Outdoor Fan Drive Type	<b>Direct</b>
Outdoor Fan Quantity	<b>1</b>		

Heat			
Heating Type	<b>Gas Heat</b>	Heating Stages	<b>1</b>

DX Cooling, Gas Heat 3-10 Ton			
Unit controls	<b>Microprocessor controls 3ph</b>	Condenser coil protection	<b>Std condenser coil w/hail guard 3ph</b>
Through the base provisions	<b>Through the base electrical 3ph</b>	Disconnect sw/circuit breaker	<b>Non-fused disconnect</b>

Field installed accessories	
Roof curb	<b>Roof curb</b>



1"




## ELECTRICAL / GENERAL DATA

<div>GENERAL<div>(2)(4)(6)</div></div>			<div>HEATING PERFORMANCE</div> <div>HEATING - GENERAL DATA</div>		
<div>Model:YSC072H<div>Oversized Motor</div></div> <div>Unit Operating Voltage:187-253<div>MCA:</div></div> <div>Unit Primary Voltage:208<div>MFS:</div></div> <div>Unit Secondary Voltage:230<div>MCB:</div></div> <div>Unit Hertz:60</div> <div>Unit Phase:3</div> <div>EER11.2</div> <div>Standard Motor</div> <div>MCA:35.0<div>MCA: N/A</div></div> <div>MFS:50.0<div>MFS: N/A</div></div> <div>MCB:50.0<div>MCB: N/A</div></div>			<div>Heating Model:Medium</div> <div>Heating Input (BTU):120,000</div> <div>Heating Output (BTU):96,000</div> <div>No. Burners:3</div> <div>No. Stages:1</div> <div>Gas Inlet Pressure</div> <div>Natural Gas (Min/Mix):4 1/2"/14"</div> <div>LP (Min/Max):11"/14"</div> <div>Gas Pipe Connection Size:1/2"</div>		
<div>INDOOR MOTOR</div> <div><div>Standard Motor</div><div>Oversized Motor</div><div>Field Installed Oversized Motor</div></div> <div><div>Number:<div>Horsepower:<div>Motor Speed (RPM):<div>Phase:<div>Full Load Amps:<div>Locked Rotor Amps:</div></div></div></div></div><div><div>Number:<div>Horsepower:<div>Motor Speed (RPM):<div>Phase:<div>Full Load Amps:<div>Locked Rotor Amps:</div></div></div></div></div><div><div>Number:<div>Horsepower:<div>Motor Speed (RPM):<div>Phase:<div>Full Load Amps:<div>Locked Rotor Amps:</div></div></div></div></div></div></div></div></div></div></div>					
<div>COMPRESSOR<div>Circuit 1/2</div></div> <div>Number:<div>Horsepower:<div>Phase:<div>Rated Load Amps:<div>Locked Rotor Amps:</div></div></div></div></div>			<div>OUTDOOR MOTOR</div> <div>Number:<div>Horsepower:<div>Motor Speed (RPM):<div>Phase:<div>Full Load Amps:<div>Locked Rotor Amps:</div></div></div></div></div></div>		
<div>POWER EXHAUST ACCESSORY<div>(3)</div><div>(Field Installed Power Exhaust)</div></div> <div>Phase:N/A</div> <div>Horsepower:N/A</div> <div>Motor Speed (RPM):N/A</div> <div>Full Load Amps:N/A</div> <div>Locked Rotor Amps:N/A</div>		<div>FILTERS</div> <div>Type:Throwaway</div> <div>Furnished:Yes</div> <div>Number:4</div> <div>Recommended:16"x25"x2"</div>		<div>REFRIGERANT<div>(2)</div></div> <div>Type</div> <div>Factory Charge</div> <div>Circuit #15.5lb</div> <div>Circuit #2N/A</div>	

### NOTES:

- Maximum (HACR) Circuit Breaker sizing is for installations in the United States only.
- Refrigerant charge is an approximate value. For a more precise value, see unit nameplate and service instructions.
- Value does not include Power Exhaust Accessory.
- Value includes oversized motor.
- Value does not include Power Exhaust Accessory.
- EER is rated at AHRI conditions and in accordance with DOE test procedures.




PACKAGED GAS / ELECTRICAL  
CORNER WEIGHT

## INSTALLED ACCESSORIES NET WEIGHT DATA


ACCESSORY				WEIGHTS			
ECONOMIZER				36.0lb			
MOTORIZED OUTSIDE AIR DAMPER							
MANUAL OUTSIDE AIR DAMPER							
BAROMETRIC RELIEF							
OVERSIZED MOTOR							
BELT DRIVE MOTOR							
POWER EXHAUST							
THROUGH THE BASE ELECTRICAL/GAS (FIOPS)				13.0lb			
UNIT MOUNTED CIRCUIT BREAKER (FIOPS)							
UNIT MOUNTED DISCONNECT (FIOPS)				5.0 lb			
POWERED CONVENIENCE OUTLET (FIOPS)							
HINGED DOORS (FIOPS)				12.0lb			
HAIL GUARD				20.0lb			
SMOKE DETECTOR, SUPPLY / RETURN							
NOVAR CONTROL							
STAINLESS STEEL HEAT EXCHANGER							
REHEAT							
ROOF CURB				78.0lb			
BASIC UNIT WEIGHTS		CORNER WEIGHTS				CENTER OF GRAVITY	
SHIPPING	NET	(A)	222.0 lb	(C)	121.0 lb	(E) LENGTH	(F) WIDTH
806.0lb	710.0 lb	(B)	217.0 lb	(D)	150.0 lb	41"	22"

### NOTE:


1. All weights are approximate.
2. Weights for options that are not listed refer to Installation guide.
3. The actual weight are listed on the unit nameplate.
4. Refer to unit nameplate and installation guide for weights before scheduling transportation and installation of unit.
5. The weight shown represents the typical unit operating weight for the configuration selected. Estimated at +/- 10 % of the nameplate weight.
6. Verify weight, connection, and all dimension with installer documents before installation.
7. Corner weights are given for information only.
8. Net/Shipping weight of optional accessories should be added to unit weight when ordering factory or field installed accessories.




PACKAGED GAS / ELECTRICAL  
RIGGING AND CENTER OF GRAVITY



PACKAGED GAS / ELECTRIC  
CLEARANCE



PACKAGED GAS / ELECTRIC  
DOWNFLOW TYPICAL ROOF OPENING








SWING DIAMETER - HINGED DOOR(S) OPTION  
ACCESSORY



NOTES:


1. VERIFY WEIGHT, CONNECTION, AND ALL DIMENSION WITH INSTALLER DOCUMENTS BEFORE INSTALLATION





ROOF TOP CURB (BAYCURB043)

ACCESSORY







ACCESSORY - BAROMETRIC RELIEF DAMPER HOOD



## **General**

The units shall be convertible airflow. The operating range shall be between 115°F and 0°F in cooling as standard from the factory for units with microprocessor controls. Operating range for units with electromechanical controls shall be between 115°F and 40°F. Cooling performance shall be rated in accordance with ARI testing procedures. All units shall be factory assembled, internally wired, fully charged with R-410A, and 100 percent run tested to check cooling operation, fan and blower rotation, and control sequence before leaving the factory. Wiring internal to the unit shall be color-coded and numbered for simplified identification. Units shall be cULus listed and labeled, classified in accordance for Central Cooling Air Conditioners.

## **Casing**

Unit casing shall be constructed of zinc coated, heavy gauge, galvanized steel. Exterior surfaces shall be cleaned, phosphatized, and finished with a weather-resistant baked enamel finish. Unit's surface shall be tested 672 hours in a salt spray test in compliance with ASTM B117. Cabinet construction shall allow for all maintenance on one side of the unit. Service panels shall have lifting handles and be removed and reinstalled by removing two fasteners while providing a water and air tight seal. All exposed vertical panels and top covers in the indoor air section shall be insulated with a cleanable foil-faced, fire-retardant permanent, odorless glass fiber material. The base of the unit shall be insulated with 1/8 inch, foil-faced, closed-cell insulation. All insulation edges shall be either captured or sealed. The unit's base pan shall have no penetrations within the perimeter of the curb other than the raised 1 1/8 inch high downflow supply/return openings to provide an added water integrity precaution, if the condensate drain backs up. The base of the unit shall have provisions for forklift and crane lifting, with forklift capabilities on three sides of the unit.

## **Unit Top**

The top cover shall be one piece construction or, where seams exist, it shall be double-hemmed and gasket-sealed. The ribbed top adds extra strength and enhances water removal from unit top.

## **Two-Inch Pleated Filters**

2" pleated media filters shall be available on all models.

## **Compressors**

All units shall have direct-drive, hermetic, scroll type compressors with centrifugal type oil pumps. Motor shall be suction gas-cooled and shall have a voltage utilization range of plus or minus 10 percent of unit nameplate voltage. Internal overloads shall be provided with the scroll compressors.

Dual compressors are outstanding for humidity control, light load cooling conditions and system back-up applications. Dual compressors are available on 7½-10 ton models and allow for efficient cooling utilizing 3-stages of compressor operation for all high efficiency models.

## **Indoor Fan**

The following units shall be equipped with a direct drive plenum fan design (T/Y SC120F, T/Y HC074F, T/Y HC092F, T/Y HC102F, 120F). Plenum fan design shall include a backward-curved fan wheel along with an external rotor direct drive variable speed indoor motor. All plenum fan designs will have a variable speed adjustment potentiometer located in the control box.

3 to 5 ton units (high efficiency 3-phase with optional motor) are belt driven, FC centrifugal fans with adjustable motor sheaves. 3 to 5 ton units (standard and high efficiency 3-phase) have multispeed, direct drive motors. All 6 to 8½ ton units (standard efficiency) shall have belt drive motors with an adjustable idler-arm assembly for quick-adjustment to fan belts and motor sheaves. All motors shall be thermally protected. All 10 tons, 6 ton (074), 7½ to 8½ (high efficiency) units have variable speed direct drive motors. All indoor fan motors meet the U.S. Energy Policy Act of 1992 (EPACT).

## **Outdoor Fans**

The outdoor fan shall be direct-drive, statically and dynamically balanced, draw-through in the vertical discharge position. The fan motor shall be permanently lubricated and shall have built-in thermal overload protection.

## **Evaporator and Condenser Coils**



Internally finned, 5/16" copper tubes mechanically bonded to a configured aluminum plate fin shall be standard. Evaporator coils are standard for all 3 to 10 ton standard efficiency models. Microchannel condenser coils are standard for all 3 to 10 ton standard efficiency models and 4, 5, 6, 7.5, 8.5 ton high efficiency models. The microchannel type condenser coil is not offered on the 4 and 5 ton dehumidification model. Due to flat streamlined tubes with small ports, and metallurgical tube-to-fin bond, microchannel coil has better heat transfer performance. Microchannel condenser coil can reduce system refrigerant charge by up to 50% because of smaller internal volume, which leads to better compressor reliability. Compact all-aluminum microchannel coils also help to reduce the unit weight. These all aluminum coils are recyclable. Galvanic corrosion is also minimized due to all aluminum construction. Strong aluminum brazed structure provides better fin protection. In addition, flat streamlined tubes also make microchannel coils more dust resistant and easier to clean. Coils shall be leak tested at the factory to ensure the pressure integrity. The evaporator coil and condenser coil shall be leak tested to 600 psig. The assembled unit shall be leak tested to 465 psig. The condenser coil shall have a patent pending 1+1+1 hybrid coil designed with slight gaps for ease of cleaning. A plastic, dual-sloped, removable and reversible condensate drain pan with through-the-base condensate drain is standard.

### **Tool-less Hail Guards**

Tool-less, hail protection quality coil guards are available for condenser coil protection.

### **Controls**

Unit shall be completely factory-wired with necessary controls and contactor pressure lugs or terminal block for power wiring. Unit shall provide an external location for mounting a fused disconnect device. A choice of microprocessor or electromechanical controls shall be available. Microprocessor controls provide for all 24V control functions. The resident control algorithms shall make all heating, cooling, and/or ventilating decisions in response to electronic signals from sensors measuring indoor and outdoor temperatures. The control algorithm maintains accurate temperature control, minimizes drift from set point, and provides better building comfort. A centralized microprocessor shall provide anti-short cycle timing and time delay between compressors to provide a higher level of machine protection. 24-volt electromechanical control circuit shall include control transformer and contactor

### **High Pressure Control**

All units include High Pressure Cutout as standard.

### **Phase monitor**

Phase monitor shall provide 100% protection for motors and compressors against problems caused by phase loss, phase imbalance, and phase reversal. Phase monitor is equipped with an LED that provides an ON or FAULT indicator. There are no field adjustments. The module will automatically reset from a fault condition.

### **Refrigerant Circuits**

Each refrigerant circuit offer thermal expansion valve as standard. Service pressure ports, and refrigerant line filter driers are factory-installed as standard. An area shall be provided for replacement suction line driers.

### **Gas Heating Section**

The heating section shall have a progressive tubular heat exchanger design using stainless steel burners and corrosion resistant steel throughout. An induced draft combustion blower shall be used to pull the combustion products through the firing tubes. The heater shall use a direct spark ignition (DSI) system. On initial call for heat, the combustion blower shall purge the heat exchanger for 20 seconds before ignition. After three unsuccessful ignition attempts, the entire heating system shall be locked out until manually reset at the thermostat/zone sensor. Units shall be suitable for use with natural gas or propane (field-installed kit) and also comply with the California requirement for low NOx emissions (Gas/Electric Only).

### **Hinged Access Doors**

Sheet metal hinges are available on the Filter/Evaporator, Supply Fan/Heat, and the Compressor/Control Access Doors.

### **Economizer**



This accessory shall be available with or without barometric relief. The assembly includes fully modulating 0-100 percent motor and dampers, minimum position setting, preset linkage, wiring harness with plug, spring return actuator and fixed dry bulb control. The barometric relief shall provide a pressure operated damper that shall be gravity closing and shall prohibit entrance of outside air during the equipment off cycle. Optional solid state or differential enthalpy control shall be available for either factory or field installation. The economizer arrives in the shipping position and shall be moved to the operating position by the installing contractor.

#### **Through the Base Electrical Access**

An electrical service entrance shall be provided allowing electrical access for both control and main power connections inside the curb and through the base of the unit. Option will allow for field installation of liquid-tight conduit and an external field-installed disconnect switch.

#### **Through the Base Electrical with Disconnect Switch**

This 3-pole, molded case, disconnect switch with provisions for through the base electrical connections are available. The disconnect switch will be installed in the unit in a water tight enclosure with access through a swinging door. Wiring will be provided from the switch to the unit high voltage terminal block. The switch will be UL/CSA agency recognized.

#### **Note:**

The disconnect switch will be sized per NEC and UL guidelines but will not be used in place of unit overcurrent protection.

#### **Accessory - Roof Curb**

The roof curb shall be designed to mate with the unit's downflow supply and return and provide support and a water tight installation when installed properly. The roof curb design shall allow field fabricated rectangular supply/return ductwork to be connected directly to the curb. Curb design shall comply with NRCA requirements. Curb shall be shipped knocked down for field assembly and shall include wood nailer strips.

#### **Sequence of Operation**

##### **System Operating Modes:**

The System Controller shall send the equipment controllers Occupied/Unoccupied, Morning Warm-up/Pre-cool, and Heat/Cool modes. If communication is lost, the equipment controllers shall operate using default modes and setpoints.

##### **Night Setback:**

During unoccupied mode, the system shall shut off. If the zone temperature drifts to the unoccupied heating or cooling setpoint, the system shall start up to heat or cool the zone, while the OA damper remains closed (unless economizing).

##### **Optimal Start:**

The System Controller shall automatically determine the optimal start time, such that each zone reaches its occupied setpoint just in time for scheduled occupancy.

##### **Demand-Controlled Ventilation:**

For those zones equipped with an occupancy sensor or CO2 sensor, outdoor airflow shall be reset based on occupancy status and/or measured CO2 concentration.

#### **Sequence of Operation (Changeover Bypass System)**

##### **Occupied Heat/Cool:**

Each VAV terminal shall use pressure-independent control, with airflow measurement, to vary primary airflow to maintain zone temperature at its occupied setpoint. The RTU shall modulate the bypass damper to maintain duct static pressure at setpoint and modulate (or cycle) compressors, modulate (or stage) heat, and/or enable airside economizing based on current zone cooling/heating demands. The OA damper shall open to bring in the required amount of ventilation.

##### **Morning Warm-Up/Pre-Cool:**

Each VAV terminal unit shall vary primary airflow to raise/lower zone temperature to its occupied setpoint. The RTU shall modulate the bypass damper to maintain duct static pressure at setpoint and modulate (or cycle) compressors or modulate (or stage) heat based on current zone cooling/heating demands. The OA damper shall remain closed, unless economizing.

**Cooling/Heating Change over Logic:**

The System Controller shall determine the overall system cooling/heating mode based on "voting" from each zone. When the majority of zones require cooling, the RTU shall operate in cooling mode and any zone that requires heating shall reduce primary airflow to minimum. When the majority of zones require heating, the RTU shall operate in heating mode and any zone that requires cooling shall reduce primary airflow to minimum.



## 3-10 Ton R-410A PKGD Unitary Gas/Electric Rooftop

### Job Information

Name	Lees Summit Senior	Tag	RTU-IL1A
Address		Quantity	1
Sales Team	Kansas City Main Office	Model Number	YSC072H3RMA-- D0C1A10000000000 000000000000
Comments			

### General

Unit function	DX cooling, gas heat	Airflow	Convertible configuration
Airflow Application	Downflow	Design Airflow	2280 cfm
Fresh air selection	Econ-dry bulb 0-100% w/ bar relief 3ph	Tonnage	6 Ton Single compressor
Cooling Entering DB	78.20 F	Cooling Entering WB	65.90 F
Ent Air Relative Humidity	52.40 %	Ambient Temp	105.00 F
Heating capacity	Medium gas heat 3ph	Heating EAT	60.00 F
Voltage	208-230/60/3	Design ESP	0.750 in H2O
Evaporator rows	3.00 Each	Evaporator fin spacing	192 Per Foot
Evaporator face area	9.89 sq ft	Evaporator face velocity	231 ft/min
Min. unit operating weight	710.0 lb	Max. unit operating weight	1045.0 lb
ASHRAE 90.1	Yes	Rated capacity (AHRI)	71.00 MBh

### Main Cooling

Evap Coil Leaving Air Temp (DB)	58.42 F	Evap Coil Leaving Air Temp (WB)	56.02 F
Cooling Leaving Unit DB	60.14 F	Cooling Leaving Unit WB	56.69 F
Gross Total Capacity	68.30 MBh	Gross Sensible Capacity	48.71 MBh
Gross Latent Capacity	19.59 MBh	Net Total Capacity	64.80 MBh
Net Sensible Capacity	45.21 MBh	Net Sensible Heat Ratio	0.70 Number
Fan motor heat	3.51 MBh	Dew Point	54.40 F
Refrig charge (HFC-410A) - ckt 1	5.5 lb	Saturated Discharge Temp Circuit 1	124.42 F
Saturated Suction Temp Circuit 1	48.26 F		

### Main Heating

Input Heating Capacity	120.00 MBh	Output Heating Capacity	97.20 MBh
Output Heating Cap. w/Fan	100.71 MBh	Heating LAT	99.70 F
Heating Delta T	39.70 F		

### Motor/Electrical

Component SP	0.192 in H2O	Total Static Pressure	0.958 in H2O
Field supplied drive kit required	None	Indoor mtr operating power	1.10 bhp
Indoor RPM	926 rpm	Indoor Motor Power	0.82 kW
Outdoor Motor Power	0.58 kW	Compressor Power	5.95 kW
System Power	7.35 kW	EER @ AHRI Conditions	11.2 EER
MCA	35.00 A	MOP	50.00 A
Compressor 1 RLA	22.40 A	Compressor 2 RLA	0.00 A
Condenser fan FLA	3.30 A	Evaporator fan FLA	3.40 A
SEER/IEER	12.70		

### Baseunit

Height	3.41 ft	Width	4.44 ft
--------	---------	-------	---------



Length	7.39 ft
--------	---------


Fan			
Indoor Fan Type	FC Centrifugal	Indoor Fan Drive Type	Belt
Outdoor Fan Type	Propeller	Outdoor Fan Drive Type	Direct
Outdoor Fan Quantity	1		

Heat			
Heating Type	Gas Heat	Heating Stages	1

DX Cooling, Gas Heat 3-10 Ton			
Unit controls	Microprocessor controls 3ph	Condenser coil protection	Std condenser coil w/hail guard 3ph
Through the base provisions	Through the base electrical 3ph	Disconnect sw/circuit breaker	Non-fused disconnect

Field installed accessories	
Roof curb	Roof curb





1"




## ELECTRICAL / GENERAL DATA

<div>GENERAL<div>(2)(4)(6)</div></div>			<div>HEATING PERFORMANCE</div> <div>HEATING - GENERAL DATA</div>		
<div>Model:YSC072H</div> <div>Oversized Motor</div> <div>Unit Operating Voltage:187-253</div> <div>MCA: N/A</div> <div>Unit Primary Voltage:208</div> <div>MFS: N/A</div> <div>Unit Secondary Voltage:230</div> <div>MCB: N/A</div> <div>Unit Hertz:60</div> <div>Unit Phase:3</div> <div>EER11.2</div> <div>Standard Motor</div> <div>MCA:35.0</div> <div>MCA: N/A</div> <div>MFS:50.0</div> <div>MFS: N/A</div> <div>MCB:50.0</div> <div>MCB: N/A</div>			<div>Heating Model:Medium</div> <div>Heating Input (BTU):120,000</div> <div>Heating Output (BTU):96,000</div> <div>No. Burners:3</div> <div>No. Stages:1</div> <div>Gas Inlet Pressure</div> <div>Natural Gas (Min/Mix):4 1/2"/14"</div> <div>LP (Min/Max):11"/14"</div> <div>Gas Pipe Connection Size:1/2"</div>		
<div>INDOOR MOTOR</div> <div>Standard Motor</div> <div>Oversized Motor</div> <div>Field Installed Oversized Motor</div> <div>Number:1</div> <div>Number: N/A</div> <div>Number: N/A</div> <div>Horsepower:1.0</div> <div>Horsepower: N/A</div> <div>Horsepower: N/A</div> <div>Motor Speed (RPM):-</div> <div>Motor Speed (RPM): N/A</div> <div>Motor Speed (RPM): N/A</div> <div>Phase:3</div> <div>Phase: N/A</div> <div>Phase: N/A</div> <div>Full Load Amps:3.4</div> <div>Full Load Amps: N/A</div> <div>Full Load Amps: N/A</div> <div>Locked Rotor Amps:32.2</div> <div>Locked Rotor Amps: N/A</div> <div>Locked Rotor Amps: N/A</div>					
<div>COMPRESSOR</div> <div>Circuit 1/2</div> <div>Number:</div> <div>Horsepower:</div> <div>Phase:</div> <div>Rated Load Amps:</div> <div>Locked Rotor Amps:</div>			<div>OUTDOOR MOTOR</div> <div>Number:1</div> <div>Horsepower:0.70</div> <div>Motor Speed (RPM):1100</div> <div>Phase:1</div> <div>Full Load Amps:3.3</div> <div>Locked Rotor Amps:12.3</div>		
<div>POWER EXHAUST ACCESSORY<div>(3)</div></div> <div>(Field Installed Power Exhaust)</div> <div>Phase:N/A</div> <div>Horsepower:N/A</div> <div>Motor Speed (RPM):N/A</div> <div>Full Load Amps:N/A</div> <div>Locked Rotor Amps:N/A</div>		<div>FILTERS</div> <div>Type:Throwaway</div> <div>Furnished:Yes</div> <div>Number:4</div> <div>Recommended:16"x25"x2"</div>		<div>REFRIGERANT<div>(2)</div></div> <div>Type</div> <div>Factory Charge</div> <div>Circuit #15.5lb</div> <div>Circuit #2N/A</div>	

### NOTES:

1. Maximum (HACR) Circuit Breaker sizing is for installations in the United States only.
2. Refrigerant charge is an approximate value. For a more precise value, see unit nameplate and service instructions.
3. Value does not include Power Exhaust Accessory.
4. Value includes oversized motor.
5. Value does not include Power Exhaust Accessory.
6. EER is rated at AHRI conditions and in accordance with DOE test procedures.




PACKAGED GAS / ELECTRICAL  
CORNER WEIGHT


INSTALLED ACCESSORIES NET WEIGHT DATA

ACCESSORY					WEIGHTS		
ECONOMIZER					36.0lb		
MOTORIZED OUTSIDE AIR DAMPER							
MANUAL OUT SIDE AIR DAMPER							
BAROMETRIC RELIEF							
OVERSIZED MOTOR							
BELT DRIVE MOTOR							
POWER EXHAUST							
THROUGH THE BASE ELECTRICAL/GAS (FIOPS)					13.0lb		
UNIT MOUNTED CIRCUIT BREAKER (FIOPS)							
UNIT MOUNTED DISCONNECT (FIOPS)					5.0 lb		
POWERED CONVENIENCE OUTLET (FIOPS)							
HINGED DOORS (FIOPS)					12.0lb		
HAIL GUARD					20.0lb		
SMOKE DETECTOR, SUPPLY / RETURN							
NOVAR CONTROL							
STAINLESS STEEL HEAT EXCHANGER							
REHEAT							
ROOF CURB					78.0lb		
BASIC UNIT WEIGHTS		CORNER WEIGHTS			CENTER OF GRAVITY		
SHIPPING	NET	(A)	222.0 lb	(C)	121.0 lb	(E) LENGHT	(F) WIDTH
806.0lb	710.0 lb	(B)	217.0 lb	(D)	150.0 lb	41"	22"


- NOTE:
1. All weights are approximate.
  2. Weights for options that are not list refer to Installation guide.
  3. The actual weight are listed on the unit nameplate.
  4. Refer to unit nameplate and installation guide for weights before scheduling transportation and installation of unit.
  5. The weight shown represents the typical unit operating weight for the configuration selected. Estimated at +/- 10 % of the nameplate weight. .
  6. Verify weight, connection, and all dimension with installer documents before installation.
  7. Corner weights are given for information only.
  8. Net/Shipping weight of optional accessories should be added to unit weight when ordering factory or field installed accessories.




PACKAGED GAS / ELECTRICAL  
RIGGING AND CENTER OF GRAVITY



PACKAGED GAS / ELECTRIC  
CLEARANCE








PACKAGED GAS / ELECTRIC  
DOWNFLOW TYPICAL ROOF OPENING



SWING DIAMETER - HINGED DOOR(S) OPTION  
ACCESSORY






NOTES:  
1. VERIFY WEIGHT, CONNECTION, AND ALL DIMENSION WITH  
INSTALLER DOCUMENTS BEFORE INSTALLATION



ROOF TOP CURB (BAYCURB043)

ACCESSORY





ACCESSORY - BAROMETRIC RELIEF DAMPER HOOD





## **General**

The units shall be convertible airflow. The operating range shall be between 115°F and 0°F in cooling as standard from the factory for units with microprocessor controls. Operating range for units with electromechanical controls shall be between 115°F and 40°F. Cooling performance shall be rated in accordance with ARI testing procedures. All units shall be factory assembled, internally wired, fully charged with R-410A, and 100 percent run tested to check cooling operation, fan and blower rotation, and control sequence before leaving the factory. Wiring internal to the unit shall be color-coded and numbered for simplified identification. Units shall be cULus listed and labeled, classified in accordance for Central Cooling Air Conditioners.

## **Casing**

Unit casing shall be constructed of zinc coated, heavy gauge, galvanized steel. Exterior surfaces shall be cleaned, phosphatized, and finished with a weather-resistant baked enamel finish. Unit's surface shall be tested 672 hours in a salt spray test in compliance with ASTM B117. Cabinet construction shall allow for all maintenance on one side of the unit. Service panels shall have lifting handles and be removed and reinstalled by removing two fasteners while providing a water and air tight seal. All exposed vertical panels and top covers in the indoor air section shall be insulated with a cleanable foil-faced, fire-retardant permanent, odorless glass fiber material. The base of the unit shall be insulated with 1/8 inch, foil-faced, closed-cell insulation. All insulation edges shall be either captured or sealed. The unit's base pan shall have no penetrations within the perimeter of the curb other than the raised 1 1/8 inch high downflow supply/return openings to provide an added water integrity precaution, if the condensate drain backs up. The base of the unit shall have provisions for forklift and crane lifting, with forklift capabilities on three sides of the unit.

## **Unit Top**

The top cover shall be one piece construction or, where seams exist, it shall be double-hemmed and gasket-sealed. The ribbed top adds extra strength and enhances water removal from unit top.

## **Two-Inch Pleated Filters**

2" pleated media filters shall be available on all models.

## **Compressors**

All units shall have direct-drive, hermetic, scroll type compressors with centrifugal type oil pumps. Motor shall be suction gas-cooled and shall have a voltage utilization range of plus or minus 10 percent of unit nameplate voltage. Internal overloads shall be provided with the scroll compressors.

Dual compressors are outstanding for humidity control, light load cooling conditions and system back-up applications. Dual compressors are available on 7½-10 ton models and allow for efficient cooling utilizing 3-stages of compressor operation for all high efficiency models.

## **Indoor Fan**

The following units shall be equipped with a direct drive plenum fan design (T/Y SC120F, T/Y HC074F, T/Y HC092F, T/Y HC102F, 120F). Plenum fan design shall include a backward-curved fan wheel along with an external rotor direct drive variable speed indoor motor. All plenum fan designs will have a variable speed adjustment potentiometer located in the control box.

3 to 5 ton units (high efficiency 3-phase with optional motor) are belt driven, FC centrifugal fans with adjustable motor sheaves. 3 to 5 ton units (standard and high efficiency 3-phase) have multispeed, direct drive motors. All 6 to 8½ ton units (standard efficiency) shall have belt drive motors with an adjustable idler-arm assembly for quick-adjustment to fan belts and motor sheaves. All motors shall be thermally protected. All 10 tons, 6 ton (074), 7½ to 8½ (high efficiency) units have variable speed direct drive motors. All indoor fan motors meet the U.S. Energy Policy Act of 1992 (EPACT).

## **Outdoor Fans**

The outdoor fan shall be direct-drive, statically and dynamically balanced, draw-through in the vertical discharge position. The fan motor shall be permanently lubricated and shall have built-in thermal overload protection.

## **Evaporator and Condenser Coils**



Internally finned, 5/16" copper tubes mechanically bonded to a configured aluminum plate fin shall be standard. Evaporator coils are standard for all 3 to 10 ton standard efficiency models. Microchannel condenser coils are standard for all 3 to 10 ton standard efficiency models and 4, 5, 6, 7.5, 8.5 ton high efficiency models. The microchannel type condenser coil is not offered on the 4 and 5 ton dehumidification model. Due to flat streamlined tubes with small ports, and metallurgical tube-to-fin bond, microchannel coil has better heat transfer performance. Microchannel condenser coil can reduce system refrigerant charge by up to 50% because of smaller internal volume, which leads to better compressor reliability. Compact all-aluminum microchannel coils also help to reduce the unit weight. These all aluminum coils are recyclable. Galvanic corrosion is also minimized due to all aluminum construction. Strong aluminum brazed structure provides better fin protection. In addition, flat streamlined tubes also make microchannel coils more dust resistant and easier to clean. Coils shall be leak tested at the factory to ensure the pressure integrity. The evaporator coil and condenser coil shall be leak tested to 600 psig. The assembled unit shall be leak tested to 465 psig. The condenser coil shall have a patent pending 1+1+1 hybrid coil designed with slight gaps for ease of cleaning. A plastic, dual-sloped, removable and reversible condensate drain pan with through-the-base condensate drain is standard.

### **Tool-less Hail Guards**

Tool-less, hail protection quality coil guards are available for condenser coil protection.

### **Controls**

Unit shall be completely factory-wired with necessary controls and contactor pressure lugs or terminal block for power wiring. Unit shall provide an external location for mounting a fused disconnect device. A choice of microprocessor or electromechanical controls shall be available. Microprocessor controls provide for all 24V control functions. The resident control algorithms shall make all heating, cooling, and/or ventilating decisions in response to electronic signals from sensors measuring indoor and outdoor temperatures. The control algorithm maintains accurate temperature control, minimizes drift from set point, and provides better building comfort. A centralized microprocessor shall provide anti-short cycle timing and time delay between compressors to provide a higher level of machine protection. 24-volt electromechanical control circuit shall include control transformer and contactor

### **High Pressure Control**

All units include High Pressure Cutout as standard.

### **Phase monitor**

Phase monitor shall provide 100% protection for motors and compressors against problems caused by phase loss, phase imbalance, and phase reversal. Phase monitor is equipped with an LED that provides an ON or FAULT indicator. There are no field adjustments. The module will automatically reset from a fault condition.

### **Refrigerant Circuits**

Each refrigerant circuit offer thermal expansion valve as standard. Service pressure ports, and refrigerant line filter driers are factory-installed as standard. An area shall be provided for replacement suction line driers.

### **Gas Heating Section**

The heating section shall have a progressive tubular heat exchanger design using stainless steel burners and corrosion resistant steel throughout. An induced draft combustion blower shall be used to pull the combustion products through the firing tubes. The heater shall use a direct spark ignition (DSI) system. On initial call for heat, the combustion blower shall purge the heat exchanger for 20 seconds before ignition. After three unsuccessful ignition attempts, the entire heating system shall be locked out until manually reset at the thermostat/zone sensor. Units shall be suitable for use with natural gas or propane (field-installed kit) and also comply with the California requirement for low NOx emissions (Gas/Electric Only).

### **Hinged Access Doors**

Sheet metal hinges are available on the Filter/Evaporator, Supply Fan/Heat, and the Compressor/Control Access Doors.

### **Economizer**



This accessory shall be available with or without barometric relief. The assembly includes fully modulating 0-100 percent motor and dampers, minimum position setting, preset linkage, wiring harness with plug, spring return actuator and fixed dry bulb control. The barometric relief shall provide a pressure operated damper that shall be gravity closing and shall prohibit entrance of outside air during the equipment off cycle. Optional solid state or differential enthalpy control shall be available for either factory or field installation. The economizer arrives in the shipping position and shall be moved to the operating position by the installing contractor.

#### **Through the Base Electrical Access**

An electrical service entrance shall be provided allowing electrical access for both control and main power connections inside the curb and through the base of the unit. Option will allow for field installation of liquid-tight conduit and an external field-installed disconnect switch.

#### **Through the Base Electrical with Disconnect Switch**

This 3-pole, molded case, disconnect switch with provisions for through the base electrical connections are available. The disconnect switch will be installed in the unit in a water tight enclosure with access through a swinging door. Wiring will be provided from the switch to the unit high voltage terminal block. The switch will be UL/CSA agency recognized.

#### **Note:**

The disconnect switch will be sized per NEC and UL guidelines but will not be used in place of unit overcurrent protection.

#### **Accessory - Roof Curb**

The roof curb shall be designed to mate with the unit's downflow supply and return and provide support and a water tight installation when installed properly. The roof curb design shall allow field fabricated rectangular supply/return ductwork to be connected directly to the curb. Curb design shall comply with NRCA requirements. Curb shall be shipped knocked down for field assembly and shall include wood nailer strips.

#### **Sequence of Operation**

##### **System Operating Modes:**

The System Controller shall send the equipment controllers Occupied/Unoccupied, Morning Warm-up/Pre-cool, and Heat/Cool modes. If communication is lost, the equipment controllers shall operate using default modes and setpoints.

##### **Night Setback:**

During unoccupied mode, the system shall shut off. If the zone temperature drifts to the unoccupied heating or cooling setpoint, the system shall start up to heat or cool the zone, while the OA damper remains closed (unless economizing).

##### **Optimal Start:**

The System Controller shall automatically determine the optimal start time, such that each zone reaches its occupied setpoint just in time for scheduled occupancy.

##### **Demand-Controlled Ventilation:**

For those zones equipped with an occupancy sensor or CO2 sensor, outdoor airflow shall be reset based on occupancy status and/or measured CO2 concentration.

#### **Sequence of Operation (Changeover Bypass System)**

##### **Occupied Heat/Cool:**

Each VAV terminal shall use pressure-independent control, with airflow measurement, to vary primary airflow to maintain zone temperature at its occupied setpoint. The RTU shall modulate the bypass damper to maintain duct static pressure at setpoint and modulate (or cycle) compressors, modulate (or stage) heat, and/or enable airside economizing based on current zone cooling/heating demands. The OA damper shall open to bring in the required amount of ventilation.

##### **Morning Warm-Up/Pre-Cool:**

Each VAV terminal unit shall vary primary airflow to raise/lower zone temperature to its occupied setpoint. The RTU shall modulate the bypass damper to maintain duct static pressure at setpoint and modulate (or cycle) compressors or modulate (or stage) heat based on current zone cooling/heating demands. The OA damper shall remain closed, unless economizing.

**Cooling/Heating Change over Logic:**

The System Controller shall determine the overall system cooling/heating mode based on "voting" from each zone. When the majority of zones require cooling, the RTU shall operate in cooling mode and any zone that requires heating shall reduce primary airflow to minimum. When the majority of zones require heating, the RTU shall operate in heating mode and any zone that requires cooling shall reduce primary airflow to minimum.



## 3-10 Ton R-410A PKGD Unitary Gas/Electric Rooftop

### Job Information

Name	Lees Summit Senior	Tag	RTU-ILA
Address		Quantity	1
Sales Team	Kansas City Main Office	Model Number	YSC090H3RMA-- D1C1A10000000000 000000000000
Comments			

### General

Unit function	DX cooling, gas heat	Airflow	Convertible configuration
Airflow Application	Downflow	Design Airflow	2640 cfm
Fresh air selection	Econ-dry bulb 0-100% w/ bar relief 3ph	Tonnage	7.5 Ton Single compressor
Cooling Entering DB	79.10 F	Cooling Entering WB	65.50 F
Ent Air Relative Humidity	48.59 %	Ambient Temp	105.00 F
Heating capacity	Medium gas heat 3ph	Heating EAT	60.00 F
Voltage	208-230/60/3	Design ESP	1.500 in H2O
Supply fan/drive/type/motor	Oversize motor	Evaporator rows	4.00 Each
Evaporator fin spacing	192 Per Foot	Evaporator face area	9.89 sq ft
Evaporator face velocity	267 ft/min	Min. unit operating weight	832.0 lb
Max. unit operating weight	1167.0 lb	ASHRAE 90.1	Yes
Rated capacity (AHRI)	87.00 MBh		

### Main Cooling

Evap Coil Leaving Air Temp (DB)	56.12 F	Evap Coil Leaving Air Temp (WB)	54.83 F
Cooling Leaving Unit DB	58.90 F	Cooling Leaving Unit WB	55.94 F
Gross Total Capacity	83.97 MBh	Gross Sensible Capacity	65.51 MBh
Gross Latent Capacity	18.46 MBh	Net Total Capacity	77.22 MBh
Net Sensible Capacity	58.76 MBh	Net Sensible Heat Ratio	0.76 Number
Fan motor heat	6.75 MBh	Dew Point	53.93 F
Refrig charge (HFC-410A) - ckt 1	7.5 lb	Saturated Discharge Temp Circuit 1	124.33 F
Saturated Suction Temp Circuit 1	47.49 F		

### Main Heating

Input Heating Capacity	150.00 MBh	Output Heating Capacity	120.00 MBh
Output Heating Cap. w/Fan	126.75 MBh	Heating LAT	102.30 F
Heating Delta T	42.30 F		

### Motor/Electrical

Component SP	0.194 in H2O	Total Static Pressure	1.728 in H2O
Field supplied drive kit required	None	Indoor mtr operating power	2.16 bhp
Indoor RPM	1273 rpm	Indoor Motor Power	1.61 kW
Outdoor Motor Power	0.68 kW	Compressor Power	7.20 kW
System Power	9.49 kW	EER @ AHRI Conditions	11.2 EER
MCA	44.00 A	MOP	60.00 A
Compressor 1 RLA	25.00 A	Compressor 2 RLA	0.00 A
Condenser fan FLA	3.30 A	Evaporator fan FLA	9.40 A
SEER/IEER	12.70		




<b>Baseunit</b>			
Height	<b>3.41 ft</b>	Width	<b>4.44 ft</b>
Length	<b>7.39 ft</b>		

<b>Fan</b>			
Indoor Fan Type	<b>FC Centrifugal</b>	Indoor Fan Drive Type	<b>Belt</b>
Outdoor Fan Type	<b>Propeller</b>	Outdoor Fan Drive Type	<b>Direct</b>
Outdoor Fan Quantity	<b>1</b>		

<b>Heat</b>			
Heating Type	<b>Gas Heat</b>	Heating Stages	<b>2</b>

<b>DX Cooling, Gas Heat 3-10 Ton</b>			
Unit controls	<b>Microprocessor controls 3ph</b>	Condenser coil protection	<b>Std condenser coil w/hail guard 3ph</b>
Through the base provisions	<b>Through the base electrical 3ph</b>	Disconnect sw/circuit breaker	<b>Non-fused disconnect</b>

<b>Field installed accessories</b>	
Roof curb	<b>Roof curb</b>



1"




## ELECTRICAL / GENERAL DATA

<div>(2)(4)(6)</div> <div>GENERAL</div> <div><div>Model: YSC090H</div><div>Oversized Motor</div><div>Unit Operating Voltage: 187-253</div><div>MCA: 44.0</div><div>Unit Primary Voltage: 208</div><div>MFS: 60.0</div><div>Unit Secondary Voltage: 230</div><div>MCB: 60.0</div><div>Unit Hertz: 60</div><div>EER 11.2</div><div>Unit Phase: 3</div><div>Standard Motor</div><div>MCA: 38.0</div><div>MFS: 60.0</div><div>MCB: 60.0</div><div>Field Installed Oversized Motor</div><div>MCA: N/A</div><div>MFS: N/A</div><div>MCB: N/A</div></div>			<div>HEATING PERFORMANCE</div> <div>HEATING - GENERAL DATA</div> <div><div>Heating Model: Medium</div><div>Heating Input (BTU): 150,000/105,000</div><div>Heating Output (BTU): 120,000/84,000</div><div>No. Burners: 3</div><div>No. Stages: 2</div><div>Gas Inlet Pressure</div><div>Natural Gas (Min/Mix): 4 1/2"/14"</div><div>LP (Min/Max): 11"/14"</div><div>Gas Pipe Connection Size: 3/4"</div></div>		
<div>INDOOR MOTOR</div> <div><div>Standard Motor</div><div>Oversized Motor</div><div>Field Installed Oversized Motor</div><div><div>Number: Number: Number: N/A</div><div>Horsepower: Horsepower: N/A</div><div>Motor Speed (RPM): Motor Speed (RPM): N/A</div><div>Phase: Phase: N/A</div><div>Full Load Amps: Full Load Amps: N/A</div><div>Locked Rotor Amps: Locked Rotor Amps: N/A</div></div></div>					
<div>COMPRESSOR</div> <div>Circuit 1/2</div> <div><div>Number: 1</div><div>Horsepower: 6.7</div><div>Phase: 3</div><div>Rated Load Amps: 25.0</div><div>Locked Rotor Amps: 164.0</div></div>			<div>OUTDOOR MOTOR</div> <div><div>Number: 1</div><div>Horsepower: 0.7</div><div>Motor Speed (RPM): 1100</div><div>Phase: 1</div><div>Full Load Amps: 3.3</div><div>Locked Rotor Amps: 12.3</div></div>		
<div>POWER EXHAUST ACCESSORY</div> <div>(3)</div> <div>(Field Installed Power Exhaust)</div> <div><div>Phase: N/A</div><div>Horsepower: N/A</div><div>Motor Speed (RPM): N/A</div><div>Full Load Amps: N/A</div><div>Locked Rotor Amps: N/A</div></div>		<div>FILTERS</div> <div><div>Type: Throwaway</div><div>Furnished: Yes</div><div>Number: 4</div><div>Recommended: 16"x25"x2"</div></div>		<div>REFRIGERANT</div> <div>(2)</div> <div>Type</div> <div><div>Factory Charge</div><div>Circuit #1 7.5lb</div><div>Circuit #2 N/A</div></div>	

### NOTES:

1. Maximum (HACR) Circuit Breaker sizing is for installations in the United States only.
2. Refrigerant charge is an approximate value. For a more precise value, see unit nameplate and service instructions.
3. Value does not include Power Exhaust Accessory.
4. Value includes oversized motor.
5. Value does not include Power Exhaust Accessory.
6. EER is rated at AHRI conditions and in accordance with DOE test procedures.






PACKAGED GAS / ELECTRICAL  
CORNER WEIGHT

## INSTALLED ACCESSORIES NET WEIGHT DATA


ACCESSORY				WEIGHTS			
ECONOMIZER				36.0lb			
MOTORIZED OUTSIDE AIR DAMPER							
MANUAL OUTSIDE AIR DAMPER							
BAROMETRIC RELIEF							
OVERSIZED MOTOR							
BELT DRIVE MOTOR							
POWER EXHAUST							
THROUGHT THE BASE ELECTRICAL/GAS (FIOPS)				13.0lb			
UNIT MOUNTED CIRCUIT BREAKER (FIOPS)							
UNIT MOUNTED DISCONNECT (FIOPS)				5.0 lb			
POWERED CONVENIENCE OUTLET (FIOPS)							
HINGED DOORS (F IOPS)				12.0lb			
HAIL GUARD				20.0lb			
SMOKE DETECTOR, SUPPLY / RETURN							
NOVAR CONTROL							
STAINLESS STEEL HEAT EXCHANGER							
REHEAT							
ROOF CURB				78.0lb			
BASIC UNIT WEIGHTS		CORNER WEIGHTS				CENTER OF GRAVITY	
SHIPPING	NET	(A)	206.0 lb	(C)	127.0 lb	(E) LENGHT	(F) WIDTH
853.0lb	760.0 lb	(B)	237.0 lb	(D)	190.0 lb	36"	22"

### NOTE:


1. All weights are approximate.
2. Weights for options that are not listed refer to Installation guide.
3. The actual weight are listed on the unit nameplate.
4. Refer to unit nameplate and installation guide for weights before scheduling transportation and installation of unit.
5. The weight shown represents the typical unit operating weight for the configuration selected. Estimated at +/- 10 % of the nameplate weight.
6. Verify weight, connection, and all dimension with installer documents before installation.
7. Corner weights are given for information only.
8. Net/Shipping weight of optional accessories should be added to unit weight when ordering factory or field installed accessories.




PACKAGED GAS / ELECTRICAL  
RIGGING AND CENTER OF GRAVITY



PACKAGED GAS / ELECTRIC  
CLEARANCE








PACKAGED GAS / ELECTRIC  
DOWNFLOW TYPICAL ROOF OPENING



SWING DIAMETER - HINGED DOOR(S) OPTION  
ACCESSORY


NOTES:



1. VERIFY WEIGHT, CONNECTION, AND ALL DIMENSION WITH INSTALLER DOCUMENTS BEFORE INSTALLATION



ROOF TOP CURB (BAYCURB043)

ACCESSORY





ACCESSORY - BAROMETRIC RELIEF DAMPER HOOD



## **General**

The units shall be convertible airflow. The operating range shall be between 115°F and 0°F in cooling as standard from the factory for units with microprocessor controls. Operating range for units with electromechanical controls shall be between 115°F and 40°F. Cooling performance shall be rated in accordance with ARI testing procedures. All units shall be factory assembled, internally wired, fully charged with R-410A, and 100 percent run tested to check cooling operation, fan and blower rotation, and control sequence before leaving the factory. Wiring internal to the unit shall be color-coded and numbered for simplified identification. Units shall be cULus listed and labeled, classified in accordance for Central Cooling Air Conditioners.

## **Casing**

Unit casing shall be constructed of zinc coated, heavy gauge, galvanized steel. Exterior surfaces shall be cleaned, phosphatized, and finished with a weather-resistant baked enamel finish. Unit's surface shall be tested 672 hours in a salt spray test in compliance with ASTM B117. Cabinet construction shall allow for all maintenance on one side of the unit. Service panels shall have lifting handles and be removed and reinstalled by removing two fasteners while providing a water and air tight seal. All exposed vertical panels and top covers in the indoor air section shall be insulated with a cleanable foil-faced, fire-retardant permanent, odorless glass fiber material. The base of the unit shall be insulated with 1/8 inch, foil-faced, closed-cell insulation. All insulation edges shall be either captured or sealed. The unit's base pan shall have no penetrations within the perimeter of the curb other than the raised 1 1/8 inch high downflow supply/return openings to provide an added water integrity precaution, if the condensate drain backs up. The base of the unit shall have provisions for forklift and crane lifting, with forklift capabilities on three sides of the unit.

## **Unit Top**

The top cover shall be one piece construction or, where seams exist, it shall be double-hemmed and gasket-sealed. The ribbed top adds extra strength and enhances water removal from unit top.

## **Two-Inch Pleated Filters**

2" pleated media filters shall be available on all models.

## **Compressors**

All units shall have direct-drive, hermetic, scroll type compressors with centrifugal type oil pumps. Motor shall be suction gas-cooled and shall have a voltage utilization range of plus or minus 10 percent of unit nameplate voltage. Internal overloads shall be provided with the scroll compressors.

Dual compressors are outstanding for humidity control, light load cooling conditions and system back-up applications. Dual compressors are available on 7½-10 ton models and allow for efficient cooling utilizing 3-stages of compressor operation for all high efficiency models.

## **Indoor Fan**

The following units shall be equipped with a direct drive plenum fan design (T/Y SC120F, T/Y HC074F, T/Y HC092F, T/Y HC102F, 120F). Plenum fan design shall include a backward-curved fan wheel along with an external rotor direct drive variable speed indoor motor. All plenum fan designs will have a variable speed adjustment potentiometer located in the control box.

3 to 5 ton units (high efficiency 3-phase with optional motor) are belt driven, FC centrifugal fans with adjustable motor sheaves. 3 to 5 ton units (standard and high efficiency 3-phase) have multispeed, direct drive motors. All 6 to 8½ ton units (standard efficiency) shall have belt drive motors with an adjustable idler-arm assembly for quick-adjustment to fan belts and motor sheaves. All motors shall be thermally protected. All 10 tons, 6 ton (074), 7½ to 8½ (high efficiency) units have variable speed direct drive motors. All indoor fan motors meet the U.S. Energy Policy Act of 1992 (EPACT).

## **Outdoor Fans**

The outdoor fan shall be direct-drive, statically and dynamically balanced, draw-through in the vertical discharge position. The fan motor shall be permanently lubricated and shall have built-in thermal overload protection.

## **Evaporator and Condenser Coils**



Internally finned, 5/16" copper tubes mechanically bonded to a configured aluminum plate fin shall be standard. Evaporator coils are standard for all 3 to 10 ton standard efficiency models. Microchannel condenser coils are standard for all 3 to 10 ton standard efficiency models and 4, 5, 6, 7.5, 8.5 ton high efficiency models. The microchannel type condenser coil is not offered on the 4 and 5 ton dehumidification model. Due to flat streamlined tubes with small ports, and metallurgical tube-to-fin bond, microchannel coil has better heat transfer performance. Microchannel condenser coil can reduce system refrigerant charge by up to 50% because of smaller internal volume, which leads to better compressor reliability. Compact all-aluminum microchannel coils also help to reduce the unit weight. These all aluminum coils are recyclable. Galvanic corrosion is also minimized due to all aluminum construction. Strong aluminum brazed structure provides better fin protection. In addition, flat streamlined tubes also make microchannel coils more dust resistant and easier to clean. Coils shall be leak tested at the factory to ensure the pressure integrity. The evaporator coil and condenser coil shall be leak tested to 600 psig. The assembled unit shall be leak tested to 465 psig. The condenser coil shall have a patent pending 1+1+1 hybrid coil designed with slight gaps for ease of cleaning. A plastic, dual-sloped, removable and reversible condensate drain pan with through-the-base condensate drain is standard.

#### **Tool-less Hail Guards**

Tool-less, hail protection quality coil guards are available for condenser coil protection.

#### **Controls**

Unit shall be completely factory-wired with necessary controls and contactor pressure lugs or terminal block for power wiring. Unit shall provide an external location for mounting a fused disconnect device. A choice of microprocessor or electromechanical controls shall be available. Microprocessor controls provide for all 24V control functions. The resident control algorithms shall make all heating, cooling, and/or ventilating decisions in response to electronic signals from sensors measuring indoor and outdoor temperatures. The control algorithm maintains accurate temperature control, minimizes drift from set point, and provides better building comfort. A centralized microprocessor shall provide anti-short cycle timing and time delay between compressors to provide a higher level of machine protection. 24-volt electromechanical control circuit shall include control transformer and contactor

#### **High Pressure Control**

All units include High Pressure Cutout as standard.

#### **Phase monitor**

Phase monitor shall provide 100% protection for motors and compressors against problems caused by phase loss, phase imbalance, and phase reversal. Phase monitor is equipped with an LED that provides an ON or FAULT indicator. There are no field adjustments. The module will automatically reset from a fault condition.

#### **Refrigerant Circuits**

Each refrigerant circuit offer thermal expansion valve as standard. Service pressure ports, and refrigerant line filter driers are factory-installed as standard. An area shall be provided for replacement suction line driers.

#### **Gas Heating Section**

The heating section shall have a progressive tubular heat exchanger design using stainless steel burners and corrosion resistant steel throughout. An induced draft combustion blower shall be used to pull the combustion products through the firing tubes. The heater shall use a direct spark ignition (DSI) system. On initial call for heat, the combustion blower shall purge the heat exchanger for 20 seconds before ignition. After three unsuccessful ignition attempts, the entire heating system shall be locked out until manually reset at the thermostat/zone sensor. Units shall be suitable for use with natural gas or propane (field-installed kit) and also comply with the California requirement for low NOx emissions (Gas/Electric Only).

#### **Hinged Access Doors**

Sheet metal hinges are available on the Filter/Evaporator, Supply Fan/Heat, and the Compressor/Control Access Doors.

#### **Economizer**





This accessory shall be available with or without barometric relief. The assembly includes fully modulating 0-100 percent motor and dampers, minimum position setting, preset linkage, wiring harness with plug, spring return actuator and fixed dry bulb control. The barometric relief shall provide a pressure operated damper that shall be gravity closing and shall prohibit entrance of outside air during the equipment off cycle. Optional solid state or differential enthalpy control shall be available for either factory or field installation. The economizer arrives in the shipping position and shall be moved to the operating position by the installing contractor.

#### **Through the Base Electrical Access**

An electrical service entrance shall be provided allowing electrical access for both control and main power connections inside the curb and through the base of the unit. Option will allow for field installation of liquid-tight conduit and an external field-installed disconnect switch.

#### **Through the Base Electrical with Disconnect Switch**

This 3-pole, molded case, disconnect switch with provisions for through the base electrical connections are available. The disconnect switch will be installed in the unit in a water tight enclosure with access through a swinging door. Wiring will be provided from the switch to the unit high voltage terminal block. The switch will be UL/CSA agency recognized.

#### **Note:**

The disconnect switch will be sized per NEC and UL guidelines but will not be used in place of unit overcurrent protection.

#### **Accessory - Roof Curb**

The roof curb shall be designed to mate with the unit's downflow supply and return and provide support and a water tight installation when installed properly. The roof curb design shall allow field fabricated rectangular supply/return ductwork to be connected directly to the curb. Curb design shall comply with NRCA requirements. Curb shall be shipped knocked down for field assembly and shall include wood nailer strips.

#### **Sequence of Operation**

##### **System Operating Modes:**

The System Controller shall send the equipment controllers Occupied/Unoccupied, Morning Warm-up/Pre-cool, and Heat/Cool modes. If communication is lost, the equipment controllers shall operate using default modes and setpoints.

##### **Night Setback:**

During unoccupied mode, the system shall shut off. If the zone temperature drifts to the unoccupied heating or cooling setpoint, the system shall start up to heat or cool the zone, while the OA damper remains closed (unless economizing).

##### **Optimal Start:**

The System Controller shall automatically determine the optimal start time, such that each zone reaches its occupied setpoint just in time for scheduled occupancy.

##### **Demand-Controlled Ventilation:**

For those zones equipped with an occupancy sensor or CO2 sensor, outdoor airflow shall be reset based on occupancy status and/or measured CO2 concentration.

#### **Sequence of Operation (Changeover Bypass System)**

##### **Occupied Heat/Cool:**

Each VAV terminal shall use pressure-independent control, with airflow measurement, to vary primary airflow to maintain zone temperature at its occupied setpoint. The RTU shall modulate the bypass damper to maintain duct static pressure at setpoint and modulate (or cycle) compressors, modulate (or stage) heat, and/or enable airside economizing based on current zone cooling/heating demands. The OA damper shall open to bring in the required amount of ventilation.

##### **Morning Warm-Up/Pre-Cool:**

Each VAV terminal unit shall vary primary airflow to raise/lower zone temperature to its occupied setpoint. The RTU shall modulate the bypass damper to maintain duct static pressure at setpoint and modulate (or cycle) compressors or modulate (or stage) heat based on current zone cooling/heating demands. The OA damper shall remain closed, unless economizing.

**Cooling/Heating Change over Logic:**

The System Controller shall determine the overall system cooling/heating mode based on "voting" from each zone. When the majority of zones require cooling, the RTU shall operate in cooling mode and any zone that requires heating shall reduce primary airflow to minimum. When the majority of zones require heating, the RTU shall operate in heating mode and any zone that requires cooling shall reduce primary airflow to minimum.



## 12 1/2 -25 Ton Packaged Unitary Gas/Elec Rooftop - CTO

### Job Information

Name	Lees Summit Senior	Tag	RTU-AL1A
Address		Quantity	1
Sales Team	Kansas City Main Office	Model Number	YSD210G3RL--- D0C1A100000000- 000000000000
Comments			

### General

Unit function	Gas/Electric	Unit controls	Reliatel
Design Airflow	6680 cfm	Fresh air selection	Econ-Dry Bulb 0- 100% w/ bar ref
Tonnage	17.5 Ton	Cooling Entering Dry Bulb	76.60 F
Cooling Entering Wet Bulb	62.20 F	Ent Air Rel Humidity	44.35 %
Ambient Temp	105.00 F	Heating capacity	Gas Heat - Low
Heating EAT	60.00 F	Voltage	208-230/60/3
Design ESP	1.500 in H2O	Evaporator Rows	2
Evaporator Face Area	23.00 sq ft	Evaporator Fin Spacing	192 Per Foot
Evaporator Face Velocity	290 ft/min	Min. Unit Operating Weight	1915.0 lb
Max Unit Operating Weight	2276.0 lb	Rated capacity (AHRI)	196.00 MBh
ASHRAE 90.1	Yes		

### Main Cooling

Evap Coil Leav Air Temp (DB)	53.95 F	Evap Coil Leav Air Temp (WB)	52.86 F
Cooling Leaving Unit DB	56.79 F	Cooling Leaving Unit WB	54.04 F
Gross Total Capacity	175.96 MBh	Gross Sensible Capacity	163.41 MBh
Gross Latent Capacity	12.55 MBh	Net Total Capacity	158.88 MBh
Net Sensible Capacity	146.33 MBh	Net Sensible Heat Ratio	0.92 Number
Fan Motor Heat	17.08 MBh	Dew Point Temp	52.06 F
Refrig charge (HFC- 410A) - ckt 1	12.6 lb	Refrig charge (HFC- 410A) - ckt 2	6.8 lb
Saturated Discharge Temp Circuit 1	130.30 F	Saturated Suction Temp Circuit 1	47.34 F
Saturated Discharge Temp Circuit 2	125.50 F	Saturated Suction Temp Circuit 2	47.03 F

### Main Heating

Output Htg Capacity	200.00 MBh	Output Htg Capacity w/Fan	217.08 MBh
Heating LAT	87.59 F	Heating Temp Rise	27.59 F

### Motor/Electrical

Field Supplied Drive Kit Required	High Static Drive Kit	Component SP Add	0.262 in H2O
Total Static Pressure	1.803 in H2O	Indoor Mtr. Operating Power	5.42 bhp
Indoor RPM	866 rpm	Indoor Motor Power	4.04 kW
Outdoor Motor Power	1.48 kW	Compressor Power	15.10 kW
System Power	20.62 kW	EER @ AHRI Conditions	11.0 EER
MCA	77.00 A	MOP	100.00 A
Compressor 1 RLA	29.44 A	Compressor 2 RLA	15.61 A
Condenser Fan FLA	3.80 A	Evaporator Fan FLA	16.70 A
IEER Rating	12.20		



<b>Acoustics</b>			
Ducted Discharge - 63 Hz	<b>92 dB</b>	Ducted Discharge - 125 Hz	<b>88 dB</b>
Ducted Discharge - 250 Hz	<b>83 dB</b>	Ducted Discharge - 500 Hz	<b>86 dB</b>
Ducted Discharge - 1k Hz	<b>79 dB</b>	Ducted Discharge - 2k Hz	<b>76 dB</b>
Ducted Discharge - 4k Hz	<b>76 dB</b>	Ducted Discharge - 8k Hz	<b>70 dB</b>
Ducted Inlet - 63 Hz	<b>94 dB</b>	Ducted Inlet - 125Hz	<b>88 dB</b>
Ducted Inlet - 500 Hz	<b>77 dB</b>	Ducted Inlet - 1k Hz	<b>72 dB</b>
Ducted Inlet - 2k Hz	<b>67 dB</b>	Ducted Inlet - 4k Hz	<b>66 dB</b>
Ducted Inlet - 8k Hz	<b>61 dB</b>	Outdoor Noise - 63 Hz	<b>93 dB</b>
Outdoor Noise - 125 Hz	<b>98 dB</b>	Outdoor Noise - 250 Hz	<b>95 dB</b>
Outdoor Noise - 500 Hz	<b>92 dB</b>	Outdoor Noise - 1k Hz	<b>89 dB</b>
Outdoor Noise - 2k Hz	<b>85 dB</b>	Outdoor Noise - 4k Hz	<b>82 dB</b>
Outdoor Noise - 8k Hz	<b>79 dB</b>	Ducted Inlet - 250 Hz	<b>80 dB</b>


<b>Baseunit</b>			
Width	<b>7.02 ft</b>	Length	<b>10.14 ft</b>
Height	<b>4.68 ft</b>		

<b>Fan</b>			
T24_SZVZV	<b>NA</b>	Indoor Fan Type	<b>FC Centrifugal</b>
Indoor Fan Drive Type	<b>Belt</b>	Outdoor Fan Type	<b>Propeller</b>
Outdoor Fan Quantity	<b>2</b>	Outdoor Fan Drive Type	<b>Direct</b>

<b>Heat</b>			
Heating Type	<b>Gas</b>	Heating Stages	<b>2</b>

<b>DX cooling</b>			
Condenser coil protection	<b>Std cond coil w/hail guard</b>	Through the base provisions	<b>Through the base electric</b>
Disconnect sw/circuit breaker	<b>Unit mounted non-fused disconnect</b>		

<b>Field installed accessories</b>	
Roof curb	<b>Roof curb</b>



PACKAGED GAS/ELECTRIC - DOWNFLOW  
PLAN VIEW DRAWING



## ELECTRICAL / GENERAL DATA

GENERAL PERFORMANCE			
Model (Ton):	YSD210G (17.5)	Standard Motor <sup>(1) (3)</sup>	
Unit Operating Voltage Range:	187-253	Minimum Circuit Ampacity:	77.0/77.0
Unit Primary Voltage:	208	Maximum Fuse Size:	100.0/100.0
Unit Secondary Voltage:	230	Maximum (HACR) Circuit Breaker:	100.0/100.0
Unit Hertz:	60	Oversized Motor <sup>(1) (4)</sup>	Field Installed Oversized Motor <sup>(1) (4)</sup>
Unit Phase:	3	MCA:	N/A
		MFS:	N/A
EER: <sup>(5)</sup>	11.0	MCB (HACR):	N/A
			MCB (HACR): N/A

GAS HEATING	COMPRESSOR
Heating Models:	Circuit(s)
Heating and 1 Stage Input (Btu/h):	250000/175000
Heating and 1 Stage Output (Btu/h):	200000/140000
Min/Max. Gas Input -	
Pressure Natural or LP:	2.5 / 14.0
Gas Connection Pipe Size:	1/2"


INDOOR MOTOR			
Number: <sup>(3)</sup>		Oversized Motor <sup>(4)</sup>	
Horsepower:	5.00	Number:	N/A
Motor Speed (RPM):	3,450	Horsepower:	N/A
Phase:	3	Motor Speed (RPM):	N/A
Full Load Amps:	16.7	Phase:	N/A
Locked Rotor Amps:	109.0	Full Load Amps:	N/A
		Locked Rotor Amps:	N/A
		Field Installed Oversized Motor <sup>(4)</sup>	
		Number:	N/A
		Hp:	N/A
		Motor Speed (RPM):	N/A
		Phase:	N/A
		FLA:	N/A
		LRA:	N/A

OUTDOOR MOTOR	POWER EXHAUST (Field Installed Power Exhaust)	COMBUSTION BLOWER MOTOR (Gas-Fired Heating only)	
Number:	2	Horsepower:	0.1
Horsepower:	1.00	Motor Speed (RPM):	3,500/2,800
Motor speed (RPM):	1,125	Phase:	1
Phase:	3	Full Load Amps:	0.8
Full Load Amps:	3.8	Locked Rotor Amps:	2.00
Locked Rotor Amps:	16.42		


FILTER	REFRIGERANT <sup>(2)</sup>
Type:	Throwaway
Furnished:	Yes
Number:	4 / 4
Recommended Size:	20"x20"x2" / 20"x25"x2"
	Circuit #1 / 2
	Type:
	Factory Charge
	Circuit #1 / 2:

### NOTES:


- Maximum (HACR) Circuit Breaker sizing is for installations in the United States only.
- Refrigerant charge is an approximate value. For a more precise value, see unit nameplate and service instructions.
- Value includes oversized motor.
- Value does not include Power Exhaust Accessory.
- EER is rated at AHRI conditions and in accordance with DOE test procedures.



DOWNFLOW-PACKAGED GAS/ELECTRIC CLEARANCE



DOWNFLOW-PACKAGED GAS/ELECTRIC ROOF OPENING CLEARANCE



CORNER WEIGHT

### Base Unit and Corner Weights only



Base unit weights		Corner Weights				Center of Gravity	
SHIPPING	NET	(A)	(B)	(C)	(D)	E	F
2326.0 lb	1894.0 lb	604.0 lb	511.0 lb	371.0 lb	409.0 lb	57"	35"

1. All weights are approximate.
2. The actual weight are listed on the unit nameplate.
3. Refer to unit nameplate and installation guide for weights before scheduling transportation and installation of unit.
4. The weight shown represents the typical unit operating weight for the configuration selected. Estimated at +/- 10 % of the nameplate weight. .
5. Verify weight, connection, and all dimension with installer documents before installation.
6. Corner weights are given for information only.
7. Net/Shipping weight of optional accessories should be added to unit weight when ordering factory or field installed accessories.

### Installed Options Net Weight Data


Accessory	Weight
Economizer, Manual and Motorized Outside Air Damper	80.0 lb
Power Exhaust	
Roof Curb	235.0 lb
Oversized Motor	
Hall Guard	43.0 lb
Hinged Access Doors	27.0 lb
Power Conv. Outlet	
Through the Base Electrical	23.0 lb
Circuit Breaker	
Disconnect	10.0 lb
Smoke Detector	
Novar	
Zone Sensor	
High/Low Static Drive Kit	
LP Gas Conversion	
Stainless Steel Heat Exchanger	
Stainless Steel Drain Pan	
VFD	
High Efficiency Motor	

1. Weights for options are approximate.
2. Weights for options that are not list refer to Installation guide.




PACKAGED GAS/ELECTRIC  
RIGGING AND CENTER OF GRAVITY







THROUGH THE BASE ELECTRICAL  
ACCESSORY-PLAN VIEW




THROUGH THE BASE ELECTRICAL ROOF CURB  
ACCESSORY-PLAN VIEW




HINGING ACCESS DOORS  
ACCESSORY



ECONOMIZER HOOD  
PLAN VIEW DRAWING



ACCESSORY-ROOF CURB



ACCESSORY-DOWNFLOW DUCT CONNECTIONS



### **General - Downflow**

The units shall be dedicated downflow airflow. The operating range shall be between 115°F and 0°F in cooling as standard from the factory for all units. Cooling performance shall be rated in accordance with ARI testing procedures. All units shall be factory assembled, internally wired, fully charged with R-410A, and 100 percent run tested to check cooling operation, fan and blower rotation and control sequence, before leaving the factory. Wiring internal to the unit shall be colored and numbered for simplified identification. Units shall be UL listed and labeled, classified in accordance to UL 1995/C 22.2, 236-05 3rd Edition.

Packaged Rooftop units cooling, heating capacities, and efficiencies are AHRI certified within scope of AHRI Standard 340/360 (I-P) and ANSI Z21.47 and 10 CFR Part 431 pertaining to Commercial Warm Air Furnaces (gas heating units).

### **Casing - Downflow**

Unit casing shall be constructed of zinc coated, heavy gauge, galvanized steel. Exterior surfaces shall be cleaned, phosphatized, and finished with a weather-resistant baked enamel finish. Unit's surface shall be tested 672 hours in a salt spray test in compliance with ASTM B117. Cabinet construction shall allow for all maintenance on one side of the unit. In order to ensure a water and air tight seal, service panels shall have lifting handles and no more than three screws to remove. All exposed vertical panels and top covers in the indoor air section shall be insulated with a 1/2 inch, 1 pound density foil-faced, fire-resistant, permanent, odorless, glass fiber material. The base of the downflow unit shall be insulated with 1/2 inch, 1 pound density foil-faced, closed-cell material. The downflow unit's base pan shall have no penetrations within the perimeter of the curb other than the raised 11/8 inch high supply/return openings to provide an added water integrity precaution, if the condensate drain backs up. The base of the unit shall have provisions for forklift and crane lifting.

### **Unit Top**

The top cover shall be one piece, or where seams exist, double hemmed and gasket sealed to prevent water leakage.

### **Filters**

Two inch standard filters shall be factory supplied on all units

### **Compressors**

All units shall have direct-drive, hermetic, scroll type compressors with centrifugal type oil pumps. Motor shall be suction gas-cooled and shall have a voltage utilization range of plus or minus 10 percent of nameplate voltage. Internal overloads shall be provided with the scroll compressors. All models shall have crankcase heaters, phase monitors and low and high pressure control as standard. Dual compressors are available on all standard efficiency models and 12.5 to 20 tons high efficiency models and allow for efficient cooling utilizing 3 stages of compressor operation (high efficiency models only). 25 tons high efficiency units have 3 compressors for up to 4 stages of compressor operation.

### **Crankcase Heaters**

These band heaters provide improved compressor reliability by warming the oil to prevent migration during off-cycles or low ambient conditions.

### **Refrigerant Circuits**

Each refrigerant circuit shall have service pressure ports, and refrigerant line filter driers factory installed as standard. An area shall be provided for replacement suction line driers.

### **Evaporator and Condenser Coils**

Evaporator Coils (only on TYS\*150, 180, 210, 240, 300G models)-

Microchannel evaporator coils will be burst tested by the manufacturer. Internally finned, 5/16" copper tubes mechanically bonded to a configured aluminum plate fin shall be standard for evaporator coils.

Coils shall be leak tested to ensure the pressure integrity. The evaporator coil shall be leak tested to 225 psig and pressure tested to 450 psig.



Condenser Coils (available on T/Y\*\*150, 180, 210, 240, 300G models) - Microchannel condenser coils shall be standard on all units. Coils shall be leak tested to ensure the pressure integrity. The condenser coil shall be leak tested to 225 psig and pressure tested to 450 psig.

### **Gas Heating Section**

The heating section shall have a drum and tube heat exchanger design using corrosion resistant steel components. A forced combustion blower shall supply premixed fuel to a single burner ignited by a pilotless hot surface ignition system.

In order to provide reliable operation, a negative pressure gas valve shall be used on standard furnaces and a pressure switch on furnaces with modulating heat that requires blower operation to initiate gas flow. On an initial call for heat, the combustion blower shall purge the heat exchanger 45 seconds before ignition.

After three unsuccessful ignition attempts, the entire heating system shall be locked out until manually reset at the thermostat. Units shall be suitable for use with natural gas shall also comply with California requirements for low NOx emissions.

### **Condenser Coil**

The microchannel type condenser coil is standard for the standard efficiency models.

Due to flat streamlined tubes with small ports, and metallurgical tube-to-fin bond, microchannel coil has better heat transfer performance. Microchannel condenser coil can reduce system refrigerant charge by up to 50% because of smaller internal volume, which leads to better compressor reliability. Compact all-aluminum microchannel coils also help to reduce the unit weight. All-aluminum construction improves re-cyclability. Galvanic corrosion is also minimized due to all aluminum construction. Strong aluminum brazed structure provides better fin protection. In addition, flat streamlined tubes also make microchannel coils more dust resistant and easier to clean. Coils shall be leak tested at the factory to ensure the pressure integrity. The evaporator coil and condenser coil shall be leak tested to 600 psig. The assembled unit shall be leak tested to 465 psig.

### **Outdoor Fans**

The outdoor fan shall be direct-drive, statically and dynamically balanced, draw-through in the vertical discharge position. The fan motor(s) shall be permanently lubricated and shall have built-in thermal overload protection.

### **Indoor Fan**

Units above shall have belt driven, FC centrifugal fans with adjustable motor sheaves. Units with standard motors shall have an adjustable idler-arm assembly for quick-adjustment of fan belts and motor sheaves. All motors shall be thermally protected. All indoor fan motors meet the U.S. Energy Policy Act of 1992 (EPA CT).

### **Controls**

Unit shall be completely factory wired with necessary controls and contactor pressure lugs or terminal block for power wiring. Unit shall provide an external location for mounting a fused disconnect device. ReliaTel controls shall be provided for all 24 volt control functions. The resident control algorithms shall make all heating, cooling, and/or ventilating decisions in response to electronic signals from sensors measuring indoor and outdoor temperatures. The control algorithm maintains accurate temperature control, minimizes drift from set point, and provides better building comfort. A centralized control shall provide anti-short cycle timing and time delay between compressors to provide a higher level of machine protection.

### **High Pressure Cutout**

This option is offered for units that do not have High Pressure cutout as standard.

### **Discharge Line Thermostat**



A bi-metal element discharge line thermostat is installed as a standard option on the discharge line of each system. This standard option provides extra protection to the compressors against high discharge temperatures in case of loss of charge, extremely high ambient and other conditions which could drive the discharge temperature higher. Discharge line thermostat is wired in series with high pressure control. When the discharge temperature rises above the protection limit, the bi-metal disc in the thermostat switches to the off position, opening the 24 VAC circuit. When the temperature on the discharge line cools down, the bi-metal disc closes the contactor circuit, providing power to the compressor. When the thermostat opens the fourth time, the ReliaTel control must be manually reset to resume operation on that stage.

#### **Tool-less Hail Guards**

Tool-less, hail protection quality coil guards are available for condenser coil protection.

#### **Through the Base Electrical with Disconnect Switch**

Three-pole, molded case, disconnect switch with provisions for through the base electrical connections are available. The disconnect switch will be installed in the unit in a water tight RT-PRC028-EN 121 enclosure with access through a swinging door. Factory wiring will be provided from the switch to the unit high voltage terminal block. The switch will be UL/CSA agency recognized.

#### **Note :**

The disconnect switch will be sized per NEC and UL guidelines but will not be used in place of unit overcurrent protection.

#### **Hinged Access Doors**

Sheet metal hinges are available on the Filter/Evaporator Access Door and the Compressor/Control Access Door. This option is available on all downflow models.

#### **Two-Inch Pleated Filters (MERV 8 & 13)**

Two inch pleated media filters shall be available on all models.

#### **Accessory - Roof Curb - Downflow**

The roof curb shall be designed to mate with the downflow unit and provide support and a water tight installation when installed properly. The roof curb design shall allow field-fabricated rectangular supply/return ductwork to be connected directly to the curb. Curb design shall comply with NRCA requirements. Curb shall be shipped knocked down for field assembly and shall include wood nailer strips.

#### **Sequence of Operation**

##### **System Operating Modes :**

The System Controller shall send the equipment controllers Occupied/Unoccupied, Morning Warm-up/Pre-cool, and Heat/Cool modes. If communication is lost, the equipment controllers shall operate using default modes and setpoints.

##### **Night Setback:**

During unoccupied mode, the system shall shut off. If the zone temperature drifts to the unoccupied heating or cooling setpoint, the system shall start up to heat or cool the zone, while the OA damper remains closed (unless economizing).

##### **Optimal Start:**

The System Controller shall automatically determine the optimal start time, such that each zone reaches its occupied setpoint just in time for scheduled occupancy.

##### **Dem and-Controlled Ventilation:**



For those zones equipped with an occupancy sensor or CO2 sensor, outdoor airflow shall be reset based on occupancy status and/or measured CO2 concentration.

### **Sequence of Operation (Changeover Bypass System)**

#### **Occupied Heat/Cool:**

Each VAV terminal shall use pressure-independent control, with airflow measurement, to vary primary airflow to maintain zone temperature at its occupied setpoint. The RTU shall modulate the bypass damper to maintain duct static pressure at setpoint and modulate (or cycle) compressors, modulate (or stage) heat, and/or enable airside economizing based on current zone cooling/heating demands. The OA damper shall open to bring in the required amount of ventilation.

#### **Morning Warm-Up/Pre-Cool:**

Each VAV terminal unit shall vary primary airflow to raise/lower zone temperature to its occupied setpoint. The RTU shall modulate the bypass damper to maintain duct static pressure at setpoint and modulate (or cycle) compressors or modulate (or stage) heat based on current zone cooling/heating demands. The OA damper shall remain closed, unless economizing.

#### **Cooling/Heating Changeover Logic:**

The System Controller shall determine the overall system cooling/heating mode based on "voting" from each zone. When the majority of zones require cooling, the RTU shall operate in cooling mode and any zone that requires heating shall reduce primary airflow to minimum. When the majority of zones require heating, the RTU shall operate in heating mode and any zone that requires cooling shall reduce primary airflow to minimum.