

Beaumont LED	Outdoor	Sconce
BMW Series		

Features

This outdoor LED light is ideal for security and general lighting. Decorative metal accents. Provides lighting in indoor or outdoor residential, commercial, and hospitality applications. Fixture mounts to a standard junction box (not included).

Construction

Input 120-277 VAC / 60 HZ. Compatible with 0-10V dimmers.

Finish

Textured grey or textured bronze powder coated finish.

Diffuser

Diffuser is .100" thick matte white acrylic.

Electrical

Input 120-277V VAC / 60 Hz. Compatible with 0-10V dimmers. Minimum starting temp -20°F.

LED

Integrated LED modules capable of producing: 14-3/4" - 19W, 1800 source lumens 21" - 24W, 2800 source lumens 3000K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for outdoor wet locations.

Option

Photocell (PC) included.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.



Textured Grey	
BMW5171800L30MVTG	
BMW5171800L30MVTG-PC	
BMW5212800L30MVTG	
BMW5212800L30MVTG-PC	

Textured Bronze	
BMW5171800L30MVBZ	
BMW5171800L30MVBZ-PC	
BMW5212800L30MVBZ	
BMW5212800L30MVBZ-PC	


LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	





14-3/4" Textured Grey

21" Textured Bronze




w 4-3/4" 4-3/8" 4-3/4" 4-3/8" 4-3/4"

4-3/4"

D

4-1/2"

4-1/2



		Jource		
ronze	LED	Lumens	ССТ	H
OL30MVBZ	19W	1800	3000K	14-3/4"
OL30MVBZ-PC	19W	1800	3000K	14-3/4"
DOL30MVBZ	24W	2800	3000K	21"
DOL30MVBZ-PC	24W	2800	3000K	21"

Source