

CATALOG

CL-SSP

SIZE/GAUGE

4011 - 4" Square/11ga
(available on 18', 20' and 25' poles)
4007 - 4" Square/7ga
(available on 25' and 30' poles)
5011 - 5" Square/11ga
(available on 25' poles)
5007 - 5" Square/7ga
(available on 25', 28' and 30' poles)

HEIGHT

18 - 18'
 20 - 20'
25 - 25'
 28 - 28'
 30 - 30'

MOUNTING

OT - Open Top
 TT - Tenon Top
 D1 - Drilled for Single
 D2 - Drilled for Double at 180°
 D3 - Drilled for Double at 90°
 D5 - Drilled for Triple at 90°
D6 - Drilled for Quad at 90°

FINISH

Polyester Powder Coat Finish
BZ - Bronze
 SV - Silver
 BK - Black
 WH - White

SHAFT

- ASTM A-500 Grade B carbon steel
- Minimum 46,000 P.S.I. yield strength
- Drilled top includes removable cap
- Tenon top includes 2-3/8" O.D. x 4.0" H x .25" Thick tenon

BASE PLATE

- ASTM A-36 hot rolled carbon steel
- Minimum 36,000 P.S.I. yield strength
- Removable Base Cover
- 8.0" Square Base Plate (4" Poles)
- 11.0" Square Base Plate (5" Poles)
- 0.75" Thick Base Plate (11ga. Poles)
- 0.75" Thick Base Plate (7ga. 4" Poles)
- 1.0" Thick Base Plate (7ga. 5" Poles)
- ø8.5" Bolt Circle (4" Poles)
- ø10.5-11.5" Bolt Circle (5" Poles)
- 1.0" Bolt Holes (11ga. Poles)
- 1.25" Bolt Holes (7ga. Poles)
- 5.66" - 6.36" Bolt Pattern Measurement (4" poles)
- 7.43" - 8.13" Bolt Pattern Measurement (5" Poles)

ANCHOR BOLTS

- F1554 Grade
- Minimum 55,000 P.S.I. yield strength
- Fully galvanized
- 20.0" L x 0.75" Dia. J Bolts (11ga. Poles)
- 40.0" L x 1.0" Dia. J Bolts (7ga. Poles)
- Includes two hex nuts and two flat washers

HAND HOLE

- 3.0" x 5.0" Hand Hole w/ Cover
- Located 14.0" above base

ACCESSORIES

Templates

CS006S05 (4"/11ga Poles)
 CS006S06 (5"/11ga Poles)
 CS006S07 (5"/7ga Poles)

Anchor Bolts

CZ066X01R0 (11ga Poles)
 CZ066X03R0 (7ga Poles)

WARRANTY

One-year limited warranty. Certain exclusions apply. For details, visit www.cree.com/lighting/ILS.



INTEGRATED LIGHTING SOLUTIONS

© 2013 Cree, Inc. All Rights Reserved. The information in this document is subject to change without notice. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.


Square Steel Poles

CL-SSP Series

POLE DATA

Pole Selection	DIMENSIONS										EPA/WINDLOADING (sq. ft.)			
	Pole Size	Pole Gage	DIM "A" Pole Height	DIM "B" Base Plate	DIM "C" Min. Bolt Pattern	DIM "D" Max. Bolt Pattern	DIM "E" Bolt Circle	DIM "F" Anchor Bolt Diameter	DIM "G" Anchor Bolt Height	DIM "H" Anchor Bolt Width	80*	90*	100*	120*
CL-SSP-4011-18	4"	11ga.	18'	8" SQ.	5.66"	6.36"	ø8.5"	0.75"	17"	3"	11.1	9.0	7.2	5.1
CL-SSP-4011-20	4"	11ga.	20'	8" SQ.	5.66"	6.36"	ø8.5"	0.75"	17"	3"	9.0	7.3	5.9	4.2
CL-SSP-4011-25	4"	11ga.	25'	8" SQ.	5.66"	6.36"	ø8.5"	0.75"	17"	3"	4.1	3.3	2.6	1.8.
CL-SSP-4007-25	4"	7ga.	25'	8" SQ.			ø8.5"	0.75"			9.7	7.8	6.3	4.5
CL-SSP-5011-25	5"	11ga.	25'	11" SQ.	7.43"	8.13"	ø10.5-11.5"	0.75"	17"	3"	8.5	6.9	5.6	4.0
CL-SSP-5007-25	5"	7ga.	25'	11" SQ.	7.43"	8.13"	ø10.5-11.5"	1"	37"	4"	17.5	14.2	11.4	8.1
CL-SSP-5007-28	5"	7ga.	28'	11" SQ.	7.43"	8.13"	ø10.5-11.5"	1"	37"	4"	11.4	9.2	7.4	5.3
CL-SSP-5007-30	5"	7ga.	30'	11" SQ.	7.43"	8.13"	ø10.5-11.5"	1"	37"	4"	10.6	8.6	6.9	4.9

* Includes 1.3 gust factor.



INTEGRATED LIGHTING SOLUTIONS

© 2013 Cree, Inc. All Rights Reserved. The information in this document is subject to change without notice. Cree Integrated Lighting Solutions offers a full line of quality lighting products from Cree, Inc. and other manufacturers, including the product depicted above.

Cree, Inc. 9201 Washington Ave | Racine, WI 53406 | Phone: 800-288-8650 | Fax: (800) 236-7500 | nationalaccounts@cree.com | www.cree.com/lighting/ILS