

DRAINAGE DESIGN SUMMARY

FOR

DCI Lee's Summit

Lee's Summit, Jackson County, Missouri

July 25, 2019

Revised August 23, 2019; November 6, 2019; November 26, 2019; January 8, 2020;
June 23, 2020; **June 29, 2020**



Prepared for:
Dialysis Clinic, Inc.
1633 Church Street, Suite 500
Nashville, TN 37203
(615) 327-3061

Prepared by:
Catalyst Design Group
5100 Tennessee Avenue
Nashville, TN 37209
(615) 622-7200





DCI Lee's Summit

Lee's Summit, Jackson County, Missouri

Table of Contents

General Information	3
Methodology	3
Existing Conditions Analysis	3
Proposed Conditions Analysis	4
Detention and Water Quality Analysis	4
Storm Drainage Design.....	5
Conclusions and Recommendations	5
Attachments.....	5
Attachment 1: Site Drainage Area Maps	6
Attachment 2: Hydraflow Hydrographs Routing Calculations	7
Attachment 3: Hydraflow Storm Sewers Calculations	8
Attachment 4: Water Quality Calculations	9
Attachment 5: Supporting Documents	10



DCI Lee's Summit

Lee's Summit, Jackson County, Missouri

Drainage Design Summary

General Information

The proposed project consists of constructing a 10,220 sf +/- dialysis clinic with associated parking and site improvements. The existing site is located at 2023 NW Shamrock Avenue in Lee's Summit on Parcel ID 62-240-99-04-00-0-00-000. The property is bordered by NW Shamrock Avenue to the North and NW Pryor Road to the East. The project site is located within the southeast corner of Section 2, Township 47N, Range 32W in the Little Blue River watershed of Kansas City.

Methodology

The following methods were used in this drainage design study to model existing and proposed conditions for stormwater runoff:

- Hydraflow Hydrographs 2018 software
 - SCS/NRCS Curve Number Method
 - 24-Hour SCS Type II Rainfall Distribution
 - SCS TR-55 Method for Time of Concentration

Existing Conditions Analysis

Currently, the ±2.225-acre site is undeveloped with pasture-like land cover. The site is generally drains via sheet flow and shallow concentrated flow from the North to the Southeast corner of the property. Stormwater runoff exiting the site discharges into the existing public stormwater system in NW Pryor Road which eventually discharges into the Little Blue River.

In analyzing the existing conditions, the site was split into two drainage areas. The majority of the site is included in the North Drainage Area with the site outfall point in the Southeast corner of the property. Runoff from the North Drainage Area discharges into the public storm system in NW Pryor Road. The southern edge of the site is included in the South Drainage Area also with the site outfall point in the Southeast corner of the property. Runoff from the South Drainage Area discharges towards the neighboring property to the South and enters the public storm system further south along NW Pryor Road. Since both drainage areas discharge to the same final outfall, the public storm system in NW Pryor Road, the peak flows for the North and South Drainage Areas were combined in the analysis of the pre vs. post peak flows.

The North Drainage Area is 1.94 acres with a curve number of 84 and a time of concentration of 10.0 minutes. The South Drainage Area is 0.29 acres with a curve number of 84 and a time of concentration of 9.7 minutes.

The project site does not lie within a special flood hazard area per the federal emergency management agency, (FIRM) map no. 29095C0416G dated January 20, 2017.

The majority of the existing soil within the project site is Greenton-Urban land complex. A sliver of the existing soil near the Northwest corner of the property is Sharpsburg-Urban land complex. Both soil types are classified as Type D soil. The NRCS Soils Map can be found in Attachment 5.

A pre-developed drainage area map is included in Attachment 1 for a detailed view of the pre-developed site. Routing calculations produced by Autodesk Storm and Sanitary Analysis 2019 software are included in Attachment 2. Modeling has been performed using Autodesk Storm and Sanitary Analysis software so that the revised pond outlet structure in the post developed condition could be modeled effectively. The previous software



used, Hydraflow Hydrographs 2018, does not have the capability to model the revised design of the outlet structure.

The pre-development flows to the site outfall point is as follows:

Pre-Development Peak Flows	
Storm Event	Existing Site Peak Flows (cfs)
2-year	6.2
10-year	11.3
100-year	18.1

Proposed Conditions Analysis

The proposed project consists of constructing a 10,220 sf +/- dialysis clinic with associated parking and site improvements. The proposed dialysis clinic is to be located centrally on the site. Proposed stormwater runoff is to be directed via sheet flow, shallow concentrated flow, and channel flow to an extended dry detention pond that is to be located at the south end of the site. A small portion of the south and eastern edge of the site will bypass the proposed extended dry detention pond and discharge to the public storm system along NW Pryor Road as in the existing conditions. A post-developed drainage area map is included in Attachment 1 for a detailed view of the post-developed site.

Detention and Water Quality Analysis

Per Section 5600 of the Kansas City Metropolitan Chapter APWA Standard Specification & Design Criteria manual, the maximum post-developed peak discharge rates from any development shall not exceed those as follows:

- 50% storm peak rate less than or equal to 0.5 cfs per site acre
- 10% storm peak rate less than or equal to 2.0 cfs per site acre
- 1% storm peak rate less than or equal to 3.0 cfs per site acre

Also, for comprehensive control a 40-hour extended detention of runoff from the local 90% mean annual event (1.37"/24-hour rainfall) must be achieved for the water quality volume.

The required water quality treatment volume was calculated to be 5,015 cf (0.115 ac-ft). See Attachment 4 for the water quality treatment volume calculations.

The proposed BMP practice chosen for this site is the extended dry detention basin. Calculations were generated following Chapter 8.10 of the Manual of Best Management Practices for Stormwater Quality. The proposed extended dry detention pond has a volume of 19,672 cf. The water quality treatment volume to be discharged over 40 hours is met at the elevation 963.5 in the proposed pond. The proposed outlet structure in the pond is to consist of a perforated riser with 5 holes with 4" vertical spacing up to the treatment volume elevation. Stormwater runoff exceeding the water quality treatment volume will discharge through four 4" orifices at an elevation of 963.8 and then a 24" pipe to the existing storm system in NW Pryor Road. The grated casting of the outlet structure is set at 966.20 to serve as an additional emergency overflow weir at the 100 year storm elevation calculated to be 966.2 per the Storm and Sanitary Analysis model which provides 2.6' of freeboard in normal operation. This grated casting on the primary outlet is also designed to operate in conjunction with an emergency spillway located on the East edge of the pond set at elevation 966.7 to pass the 100-Year storm from the contributing drainage area, however to be conservative the grated inlet was not utilized in the routing of the 100-year clogged/zero available storage condition and is solely routed through the earthen berm emergency spillway which result in a maximum water elevation of 967.0. The top of berm elevation for the proposed pond is 968.8 providing 1.8' of freeboard exceeding the minimum 1' of freeboard to the top of the berm assuming zero available storage in the ponds and zero flow through the primary outlet. See Attachment 2 for detention routing calculations. An additional Hydraflow Hydrographs Report has been provided for the clogged/zero available storage condition.



The overall post-development peak flows to the outfall are as follows:

Post-Development Peak Flows	
Storm Event	Proposed Site Peak Flows (cfs)
2-year	1.0
10-year	3.1
100-year	4.9

Storm Drainage Design

All stormwater pipes and structures have been designed to convey the 10-year storm event. Tailwater elevations were considered to be between the crown and critical depth of the pipes.

Pipe and structures calculations were compiled using Hydraflow Storm Sewers 2018 software and are included as Attachment 3. An Inlet Drainage Area Map detailing the areas discharging to each proposed inlet is included in Attachment 1.

Downstream Structure Analysis

The receiving storm system has been analyzed to ensure that the proposed development will not adversely impact the existing downstream system. The Inlet Drainage Area Map in Attachment 1 includes the drainage area for the receiving storm system, which is the 24" RCP leaving the proposed tie in structure (AI #1202) that runs south. The system has a capacity of 22.62 CFS at 1% slope. This capacity was calculated per Manning's Equation for full pipe flow as shown below:

$$Q_{cap} = VA$$

$$V = \frac{k}{n} \left(\frac{A}{P} \right)^{2/3} s^{1/2}$$

Where:

Q_{cap} = full flow capacity

V = Average velocity in the pipe

A = Area of pipe

k = Unit conversion factor: k=1.49 for English units

P = Perimeter of pipe

s = Downward slope of pipe

n = Manning's Roughness Coefficient

For the 10-Year Storm Event, the Lee's Summit Fire Station #3 (to the west of the site) is expected to send 2.16 cfs to structure AI #1202, per the development's Storm Water Drainage Study dated 01/16/2018. In addition, per this study the DCI project is expected to send 3.4 cfs to structure AI #1202 for the 10-year storm event. The 3.95-acre offsite drainage area is expected to send approximately 8.96 cfs to structure AI #1202 for the 10-year storm event. In total, the receiving storm system is expected to have a flow rate of 14.52 cfs for the 10-year storm event, which is well below the pipe's capacity.



Conclusions and Recommendations

The stormwater management system for the proposed development has been designed per Section 5600 of the Kansas City Metropolitan Chapter APWA Standard Specifications Design Criteria and the Manual of Best Management Practices for Stormwater Quality. Due to the increase in impervious area for the proposed development, water quality and detention requirements are to be met by the use of a proposed extended dry detention basin located on the South portion of the project site. The water quality treatment volume calculated to be 5,015 cf is to be released over 40 hours through a perforated riser. The detention requirements specify maximum release rates based on the lesser of either pre-developed peak flow rates or a predetermined flow rate per site acreage. The post-developed peak flow rates calculated for the 2-year, 10-year, and 100-year storm events are less than their respective allowable peak flow rates. The extended dry detention pond also has more than 2 feet of freeboard for all storm events in order to provide exceptional flood protection during extreme storm events.


Pre- and Post- Peak Flows Comparison					
Storm Event	Pre-dev. Peak Flow (cfs)	Allowable Post-Dev. Peak Flow (cfs)		Post-Dev. Peak Flows (cfs)	Difference (+/-)
2-year	6.2	(0.5 cfs/2.225 ac)	1.1	1.0	-0.1
10-year	11.3	(2.0 cfs/2.225 ac)	4.5	3.1	-1.4
100-year	18.1	(3.0 cfs/2.225 ac)	6.7	4.9	-1.8

Attachments:

- Attachment 1 Site Drainage Area Maps
- Attachment 2 Autodesk Storm and Sanitary Analysis Routing Calculations
- Attachment 3 Hydraflow Storm Sewers Calculations
- Attachment 4 Water Quality Calculations
- Attachment 5 Supporting Documents

Attachment 1
Site Drainage Area Maps

P:\2018\20180111\Engineering\dwg\20180111_2019-11-01_Post Drainage Area Map.dwg-POST Nov. 01, 2019 cwalker



NORTH DRAINAGE AREA
76,330 SF (1.75 AC)
CN: 90

PERVIOUS AREA
34,146 SF (0.78 AC)

IMPERVIOUS AREA
42,184 SF (0.97 AC)

BYPASS IMPERVIOUS AREA
441 SF (0.01 AC)

LOT 1
2001 NW SHAMROCK AVENUE
OWNER: CITY OF LEE'S SUMMIT, MISSOURI /
ZONED: RP-3 (PLANNED RESIDENTIAL MIXED USE)

**WEST VILLAGE
COMMERCIAL
DEVELOPMENT,
LOTS 1 - 3**

IMPERVIOUS AREA
INCLUDED IN LOT 1
DRAINAGE DESIGN
3,854 SF (0.09 AC)

BYPASS IMPERVIOUS AREA
638 SF (0.01 AC)

BYPASS DRAINAGE AREA
16,787 SF (0.38 AC)
CN: 81

FOUND 1/2" STEEL ROD WITH CAP
STAMPED "ASC KLS3 MLS76D"
ON PROPERTY CORNER

NOTE: TIME OF CONCENTRATION CONSIDERED TO BE 5 MIN.


STORM WATER LEGEND
CB #1170
TOP ELEVATION = 980.66
F/L NORTH 15" RCP = 975.46
F/L SOUTHEAST 15" HDPE = 974.81
CB #1206
TOP ELEVATION = 981.70
F/L SOUTH 15" RCP = 976.20
F/L EAST = 976.70
(UNKNOWN PIPE SIZE & TYPE)
TCB = 980.76
CB #1173
TOP ELEVATION = 980.74
F/L SOUTH 15" RCP = 976.04
CB #1115
TOP ELEVATION = 968.97
F/L NORTH 15" RCP = 964.47
F/L SOUTH 15" RCP = 963.62
F/L EAST 15" RCP = 963.97
TCB = 968.01
AI #1202
TOP ELEVATION = 959.95
F/L NORTHEAST 15" RCP = 952.24
F/L SOUTH 24" RCP = 948.65
TCB = 958.57
CB #1085
TOP ELEVATION = 961.05
F/L NORTH 15" RCP = 954.50
F/L SOUTHWEST 15" RCP = 954.30
TCB = 960.10
AI #2081
TOP ELEVATION = 973.94
F/L EAST 15" RCP = 967.09
SWMH #1148
TOP ELEVATION = 978.52
F/L NORTH 15" RCP = 972.38
F/L SOUTH 15" RCP = 972.28
F/L NORTHWEST 15" HDPE = 974.04

SEWER LEGEND
SSMH #1019
TOP ELEVATION = 959.22
F/L NORTHEAST 6" PVC = 947.82
F/L SOUTH 6" PVC = 947.67


BENCHMARK LEGEND
BM #1148
TOP ELEVATION RIM OF SWMH = 978.52
DATUM = NAVD88



Know what's below.
Call before you dig.




DIALYSIS CLINIC, INC.
1633 CHURCH STREET, STE 500
NASHVILLE, TN 37203
615.327.3061



CONSTRUCTION DRAWINGS
DCI - LEE'S SUMMIT
2001 NW SHAMROCK AVENUE
LEE'S SUMMIT, MISSOURI, 64081
JACKSON COUNTY

NO.	DATE	DESCRIPTION

DRAWING TITLE
**POST DEVELOPED
DRAINAGE AREA
MAP**
PROJECT NUMBER
20180111
DRAWING NUMBER
POST



STRUCTURE TABLE		
CODE	DESCRIPTION	TOP GRATE
A1	POND OUTLET	966.20
A2	JUNCTION MANHOLE	971.20
B1	HEADWALL	NA
B2	CLEANOUT	978.70
B3	CATCH BASIN	976.50
B4	CLEANOUT	977.10
B5	CLEANOUT	979.00
B6	CLEANOUT	978.75
B7	CLEANOUT	978.40
B8	CLEANOUT	978.15
B9	CLEANOUT	978.30
C1	CLEANOUT	978.70
C2	CLEANOUT	978.28
C3	CLEANOUT	978.25
C4	CLEANOUT	978.67
C5	CLEANOUT	NA
D1	HEADWALL	965.60
D2	SINGLE CURB INLET	975.80
D3	SINGLE CURB INLET	975.80
D4	DOUBLE CURB INLET	977.60
EX A1 #2081	EXISTING POND OUTLET	973.94
EX AL#1202	EXISTING CATCH BASIN	959.95

FORM WATER LEGEND

CB #1170
TOP ELEVATION = 980.66
F/L NORTH 15° RCP = 975.46
F/L SOUTHEAST 15° HDPE = 974.81

CB #1206
TOP ELEVATION = 981.70
F/L SOUTH 15° RCP = 976.20
F/L EAST = 976.70
(UNKNOWN PIPE SIZE & TYPE)
TCB = 980.76

CB #1173
TOP ELEVATION = 980.74
F/L SOUTH 15° RCP = 976.04

CB #1115
TOP ELEVATION = 968.97
F/L NORTH 15° RCP = 964.47
F/L SOUTH 15° RCP = 963.62
F/L EAST 15° RCP = 963.97
TCB = 968.01

AI #1202
TOP ELEVATION = 959.95
F/L NORTHEAST 15° RCP = 952.24
F/L SOUTH 24° RCP = 948.65
TCB = 958.57

CB #1085
TOP ELEVATION = 961.05
F/L NORTH 15° RCP = 954.50
F/L SOUTHWEST 15° RCP = 954.30
TCB = 960.10

AI #2081
TOP ELEVATION = 973.94
F/L EAST 15° RCP = 967.09


SWMH #1148
TOP ELEVATION = 978.52
F/L NORTH 15° RCP = 972.38
F/L SOUTH 15° RCP = 972.38
F/L NORTHWEST 15° HDPE = 974.04

SEWER LEGEND
SSMH #1019
 TOP ELEVATION = 959.22
 F/L NORTHEAST 6" PVC = 947.82
 F/L SOUTH 6" PVC = 947.67


BENCHMARK LEGEND
BM #1148
 TOP ELEVATION RIM OF SWMH = 978.52
 DATUM = NAVD88



**Know what's below
Call before you dig**



DIALYSIS CLINIC, INC.
1633 CHURCH STREET, STE 500
NASHVILLE, TN 37203
615.327.3061



CONSTRUCTION DRAWINGS

DCI - LEE'S SUMMIT

2001 NW SHAMROCK AVENUE
LEE'S SUMMIT, MISSOURI, 64081
JACKSON COUNTY


[illegible]

DRAWING TITLE

INLET DRAINAGE
AREA MAP

PROJECT NUMBER
20180111

INLET



Attachment 2

Autodesk Storm and Sanitary Analysis Routing Calculations

File Name 20180111_2020-06-29 Pre.SPF

Project Options

Flow Units CFS
Elevation Type Elevation
Hydrology Method SCS TR-55
Time of Concentration (TOC) Method SCS TR-55
Link Routing Method Hydrodynamic
Enable Overflow Ponding at Nodes YES
Skip Steady State Analysis Time Periods NO

Analysis Options

Start Analysis On Jun 29, 2020 00:00:00
End Analysis On Jul 02, 2020 00:05:00
Start Reporting On Jun 29, 2020 00:00:00
Antecedent Dry Days 0 days
Runoff (Dry Weather) Time Step 0 01:00:00 days hh:mm:ss
Runoff (Wet Weather) Time Step 0 00:05:00 days hh:mm:ss
Reporting Time Step 0 00:05:00 days hh:mm:ss
Routing Time Step 30 seconds

Number of Elements

	Qty
Rain Gages	1
Subbasins.....	2
Nodes.....	1
<i>Junctions</i>	0
<i>Outfalls</i>	1
<i>Flow Diversions</i>	0
<i>Inlets</i>	0
<i>Storage Nodes</i>	0
Links.....	0
<i>Channels</i>	0
<i>Pipes</i>	0
<i>Pumps</i>	0
<i>Orifices</i>	0
<i>Weirs</i>	0
<i>Outlets</i>	0
Pollutants	0
Land Uses	0

Rainfall Details

SN	Rain Gage ID	Data Source	Data Source ID	Rainfall Type	Rain Units	State	County	Return Period (years)	Rainfall Depth (inches)	Rainfall Distribution
1	Rain Gage-01	Time Series	2 year	Cumulative	inches	Missouri	Jackson	2	3.50	SCS Type II 24-hr

Subbasin Summary

SN Subbasin ID	Area	Weighted Curve Number	Total Rainfall	Total Runoff	Total Runoff Volume	Peak Runoff	Time of Concentration
	(ac)		(in)	(in)	(ac-in)	(cfs)	(days hh:mm:ss)
1 ExistingNorth	1.94	84.00	3.50	1.94	3.76	5.46	0 00:08:02
2 ExistingSouth	0.29	84.00	3.50	1.94	0.56	0.77	0 00:10:09

Node Summary

SN	Element ID	Element Type	Invert Elevation	Ground/Rim (Max) Elevation	Initial Water Elevation	Surcharge Elevation	Ponded Area	Peak Inflow	Max HGL Elevation Attained	Max Surcharge Depth Attained	Min Freeboard Attained	Time of Peak Flooding Occurrence	Total Flooded Volume	Total Time Flooded
			(ft)	(ft)	(ft)	(ft)	(ft²)	(cfs)	(ft)	(ft)	(ft)	(days hh:mm)	(ac-in)	(min)
1	Outfall	Outfall	960.00					0.00	0.00					

File Name 20180111_2020-06-29 Pre.SPF

Project Options

Flow Units CFS
Elevation Type Elevation
Hydrology Method SCS TR-55
Time of Concentration (TOC) Method SCS TR-55
Link Routing Method Hydrodynamic
Enable Overflow Ponding at Nodes YES
Skip Steady State Analysis Time Periods NO

Analysis Options

Start Analysis On Jun 29, 2020 00:00:00
End Analysis On Jul 02, 2020 00:05:00
Start Reporting On Jun 29, 2020 00:00:00
Antecedent Dry Days 0 days
Runoff (Dry Weather) Time Step 0 01:00:00 days hh:mm:ss
Runoff (Wet Weather) Time Step 0 00:05:00 days hh:mm:ss
Reporting Time Step 0 00:05:00 days hh:mm:ss
Routing Time Step 30 seconds

Number of Elements

	Qty
Rain Gages	1
Subbasins.....	2
Nodes.....	1
<i>Junctions</i>	0
<i>Outfalls</i>	1
<i>Flow Diversions</i>	0
<i>Inlets</i>	0
<i>Storage Nodes</i>	0
Links.....	0
<i>Channels</i>	0
<i>Pipes</i>	0
<i>Pumps</i>	0
<i>Orifices</i>	0
<i>Weirs</i>	0
<i>Outlets</i>	0
Pollutants	0
Land Uses	0

Rainfall Details

SN	Rain Gage ID	Data Source	Data Source ID	Rainfall Type	Rain Units	State	County	Return Period (years)	Rainfall Depth (inches)	Rainfall Distribution
1	Rain Gage-01	Time Series	10 year	Cumulative	inches	Missouri	Jackson	10	5.30	SCS Type II 24-hr

Subbasin Summary

SN Subbasin ID	Area	Weighted Curve Number	Total Rainfall	Total Runoff	Total Runoff Volume	Peak Runoff	Time of Concentration
	(ac)		(in)	(in)	(ac-in)	(cfs)	(days hh:mm:ss)
1 ExistingNorth	1.94	84.00	5.30	3.55	6.88	9.87	0 00:08:02
2 ExistingSouth	0.29	84.00	5.30	3.55	1.03	1.39	0 00:10:09

Node Summary

SN	Element ID	Element Type	Invert Elevation	Ground/Rim (Max) Elevation	Initial Water Elevation	Surcharge Elevation	Ponded Area	Peak Inflow	Max HGL Elevation Attained	Max Surcharge Depth Attained	Min Freeboard Attained	Time of Peak Flooding Occurrence	Total Flooded Volume	Total Time Flooded
			(ft)	(ft)	(ft)	(ft)	(ft²)	(cfs)	(ft)	(ft)	(ft)	(days hh:mm)	(ac-in)	(min)
1	Outfall	Outfall	960.00					0.00	0.00					

File Name 20180111_2020-06-29 Pre.SPF

Project Options

Flow Units CFS
Elevation Type Elevation
Hydrology Method SCS TR-55
Time of Concentration (TOC) Method SCS TR-55
Link Routing Method Hydrodynamic
Enable Overflow Ponding at Nodes YES
Skip Steady State Analysis Time Periods NO

Analysis Options

Start Analysis On Jun 29, 2020 00:00:00
End Analysis On Jul 02, 2020 00:05:00
Start Reporting On Jun 29, 2020 00:00:00
Antecedent Dry Days 0 days
Runoff (Dry Weather) Time Step 0 01:00:00 days hh:mm:ss
Runoff (Wet Weather) Time Step 0 00:05:00 days hh:mm:ss
Reporting Time Step 0 00:05:00 days hh:mm:ss
Routing Time Step 30 seconds

Number of Elements

	Qty
Rain Gages	1
Subbasins.....	2
Nodes.....	1
<i>Junctions</i>	0
<i>Outfalls</i>	1
<i>Flow Diversions</i>	0
<i>Inlets</i>	0
<i>Storage Nodes</i>	0
Links.....	0
<i>Channels</i>	0
<i>Pipes</i>	0
<i>Pumps</i>	0
<i>Orifices</i>	0
<i>Weirs</i>	0
<i>Outlets</i>	0
Pollutants	0
Land Uses	0

Rainfall Details

SN	Rain Gage ID	Data Source	Data Source ID	Rainfall Type	Rain Units	State	County	Return Period (years)	Rainfall Depth (inches)	Rainfall Distribution
1	Rain Gage-01	Time Series	100 year	Cumulative	inches	Missouri	Jackson	100	7.70	SCS Type II 24-hr

Subbasin Summary

SN Subbasin ID	Area	Weighted Curve Number	Total Rainfall	Total Runoff	Total Runoff Volume	Peak Runoff	Time of Concentration
	(ac)		(in)	(in)	(ac-in)	(cfs)	(days hh:mm:ss)
1 ExistingNorth	1.94	84.00	7.70	5.81	11.27	15.84	0 00:08:02
2 ExistingSouth	0.29	84.00	7.70	5.81	1.68	2.23	0 00:10:09

Node Summary

SN	Element ID	Element Type	Invert Elevation	Ground/Rim (Max) Elevation	Initial Water Elevation	Surcharge Elevation	Ponded Area	Peak Inflow	Max HGL Elevation Attained	Max Surcharge Depth Attained	Min Freeboard Attained	Time of Peak Flooding Occurrence	Total Flooded Volume	Total Time Flooded
			(ft)	(ft)	(ft)	(ft)	(ft²)	(cfs)	(ft)	(ft)	(ft)	(days hh:mm)	(ac-in)	(min)
1	Outfall	Outfall	960.00					0.00	0.00					

File Name 20180111_2020-06-29 Post.SPF

Project Options

Flow Units CFS
Elevation Type Elevation
Hydrology Method SCS TR-55
Time of Concentration (TOC) Method SCS TR-55
Link Routing Method Hydrodynamic
Enable Overflow Ponding at Nodes YES
Skip Steady State Analysis Time Periods NO

Analysis Options

Start Analysis On Jun 29, 2020 00:00:00
End Analysis On Jul 02, 2020 00:05:00
Start Reporting On Jun 29, 2020 00:00:00
Antecedent Dry Days 0 days
Runoff (Dry Weather) Time Step 0 01:00:00 days hh:mm:ss
Runoff (Wet Weather) Time Step 0 00:05:00 days hh:mm:ss
Reporting Time Step 0 00:05:00 days hh:mm:ss
Routing Time Step 30 seconds

Number of Elements

	Qty
Rain Gages	1
Subbasins.....	2
Nodes.....	3
<i>Junctions</i>	1
<i>Outfalls</i>	1
<i>Flow Diversions</i>	0
<i>Inlets</i>	0
<i>Storage Nodes</i>	1
Links.....	10
<i>Channels</i>	0
<i>Pipes</i>	1
<i>Pumps</i>	0
<i>Orifices</i>	9
<i>Weirs</i>	0
<i>Outlets</i>	0
Pollutants	0
Land Uses	0

Rainfall Details

SN	Rain Gage ID	Data Source	Data Source ID	Rainfall Type	Rain Units	State	County	Return Period (years)	Rainfall Depth (inches)	Rainfall Distribution
1	Rain Gage-01	Time Series	2 year	Cumulative	inches	Missouri	Jackson	2	3.50	SCS Type II 24-hr

Subbasin Summary

SN	Subbasin ID	Area	Weighted Curve Number	Total Rainfall	Total Runoff	Total Runoff Volume	Peak Runoff	Time of Concentration
		(ac)		(in)	(in)	(ac-in)	(cfs)	(days hh:mm:ss)
1	BYPASS	0.32	81.13	3.50	1.72	0.55	0.87	0 00:05:00
2	ProposedNorth	1.75	89.98	3.50	2.45	4.28	6.65	0 00:05:00

Node Summary

SN	Element ID	Element Type	Invert Elevation	Ground/Rim (Max) Elevation	Initial Water Elevation	Surcharge Elevation	Ponded Area	Peak Inflow	Max HGL Elevation Attained	Max Surcharge Depth Attained	Min Freeboard Attained	Time of Peak Flooding Occurrence	Total Flooded Volume	Total Time Flooded
			(ft)	(ft)	(ft)	(ft)	(ft²)	(cfs)	(ft)	(ft)	(ft)	(days hh:mm)	(ac-in)	(min)
1	A1	Junction	957.84	966.20	0.00	0.00	0.00	0.87	958.03	0.00	8.17	0 00:00	0.00	0.00
2	OUTFALL	Outfall	948.85					1.02	949.04					
3	POND	Storage Node	961.00	6.00	961.00		0.00	6.64	964.23				0.00	4011.00

DCI Lee's Summit
06/30/20
Link Summary

Post-Developed 2-year

SN	Element ID	Element Type	From (Inlet) Node	To (Outlet) Node	Length (ft)	Inlet Invert Elevation (ft)	Outlet Invert Elevation (ft)	Average Slope (%)	Diameter or Height (in)	Manning's Roughness	Peak Flow (cfs)	Design Flow Capacity (cfs)	Peak Flow/ Design Flow Ratio	Peak Flow Velocity (ft/sec)	Peak Flow Depth (ft)	Peak Flow Depth/ Total Depth Ratio	Total Time Reported (min)	Surcharged Condition
1	Link-03	Pipe	A1	OUTFALL	160.20	957.84	948.85	5.6100	24.000	0.0150	0.87	46.45	0.02	5.60	0.19	0.10	0.00	Calculated
2	Orifice1	Orifice	POND	A1		961.00	957.84		1.000		0.04							
3	Orifice2	Orifice	POND	A1		961.00	957.84		1.000		0.04							
4	Orifice3	Orifice	POND	A1		961.00	957.84		1.000		0.04							
5	Orifice4	Orifice	POND	A1		961.00	957.84		1.000		0.03							
6	Orifice5	Orifice	POND	A1		961.00	957.84		1.000		0.03							
7	Orifice6	Orifice	POND	A1		961.00	957.84		4.000		0.17							
8	Orifice7	Orifice	POND	A1		961.00	957.84		4.000		0.17							
9	Orifice8	Orifice	POND	A1		961.00	957.84		4.000		0.17							
10	Orifice9	Orifice	POND	A1		961.00	957.84		4.000		0.17							

DCI Lee's Summit
06/30/20

Post-Developed 2-year

Junction Input

SN	Element ID	Invert Elevation	Ground/Rim (Max) Elevation (ft)	Ground/Rim (Max) Offset (ft)	Initial Water Elevation (ft)	Initial Water Depth (ft)	Surcharge Elevation (ft)	Surcharge Depth (ft)	Ponded Area (ft²)	Minimum Pipe Cover (in)
1	A1	957.84	966.20	8.36	0.00	-957.84	0.00	-966.20	0.00	0.00

DCI Lee's Summit
06/30/20

Post-Developed 2-year

Junction Results

SN	Element ID	Peak Inflow	Peak Lateral Inflow	Max HGL Elevation Attained	Max HGL Depth Attained	Max Surcharge Depth Attained	Min Freeboard Attained	Average HGL Elevation Attained	Average HGL Depth Attained	Time of Max HGL Occurrence	Time of Peak Flooding Occurrence	Total Flooded Volume	Total Time Flooded
		(cfs)	(cfs)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(days hh:mm)	(days hh:mm)	(ac-in)	(min)
1	A1	0.87	0.00	958.03	0.19	0.00	8.17	957.87	0.03	0 12:20	0 00:00	0.00	0.00

Pipe Input

SN	Element ID	Length	Inlet Invert Elevation	Inlet Invert Offset	Outlet Invert Elevation	Outlet Invert Offset	Total Drop	Average Pipe Slope	Pipe Shape	Pipe Diameter or Height	Pipe Width	Manning's Roughness	Entrance Losses	Exit/Bend Losses	Additional Losses	Initial Flow	Flap Gate	No. of Barrels
		(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(%)		(in)	(in)					(cfs)		
1	Link-03	160.20	957.84	0.00	948.85	0.00	8.99	5.6100	CIRCULAR	24.000	24.000	0.0150	0.5000	0.5000	0.0000	0.00	No	1

DCI Lee's Summit
06/30/20

Post-Developed 2-year

Pipe Results

SN	Element ID	Peak Flow	Time of Peak Flow Occurrence	Design Flow Capacity	Peak Flow/ Design Flow Ratio	Peak Flow Velocity	Travel Time	Peak Flow Depth	Peak Flow Depth/ Total Depth Ratio	Total Time Surcharged	Froude Number	Reported Condition
		(cfs)	(days hh:mm)	(cfs)		(ft/sec)	(min)	(ft)		(min)		
1	Link-03	0.87	0 12:20	46.45	0.02	5.60	0.48	0.19	0.10	0.00		Calculated

Storage Nodes

Storage Node : POND

Input Data


Invert Elevation (ft)	961.00
Max (Rim) Elevation (ft)	6.00
Max (Rim) Offset (ft)	-955.00
Initial Water Elevation (ft)	961.00
Initial Water Depth (ft)	0.00
Ponded Area (ft²)	0.00
Evaporation Loss	0.00

Storage Area Volume Curves

Storage Curve : Pond

Stage	Storage Area	Storage Volume
(ft)	(ft²)	(ft³)
0	0	0
1	1586.00	793
2	3180.00	3180
3	4723.33	7085
4	6092.50	12185
5	7326.00	18315
5.2	7566.15	19672
6	8517.67	25553
7	9702.57	33959
7.7	10536.10	40564

Storage Area Volume Curves



Outflow Orifices

SN	Element ID	Orifice Type	Orifice Shape	Flap Gate	Circular Orifice Diameter (in)	Rectangular Orifice Height (in)	Rectangular Orifice Width (in)	Orifice Invert Elevation (ft)	Orifice Coefficient
	1 Orifice1	Side	CIRCULAR	No	1.00			961.52	0.61
	2 Orifice2	Side	CIRCULAR	No	1.00			961.85	0.61
	3 Orifice3	Side	CIRCULAR	No	1.00			962.18	0.61
	4 Orifice4	Side	CIRCULAR	No	1.00			962.51	0.61
	5 Orifice5	Side	CIRCULAR	No	1.00			962.84	0.61
	6 Orifice6	Side	CIRCULAR	No	4.00			963.90	0.61
	7 Orifice7	Side	CIRCULAR	No	4.00			963.90	0.61
	8 Orifice8	Side	CIRCULAR	No	4.00			963.90	0.61
	9 Orifice9	Side	CIRCULAR	No	4.00			963.90	0.61

Output Summary Results

Peak Inflow (cfs)	6.64
Peak Lateral Inflow (cfs)	6.64
Peak Outflow (cfs)	0.87
Peak Exfiltration Flow Rate (cfm)	0.00
Max HGL Elevation Attained (ft)	964.23
Max HGL Depth Attained (ft)	3.23
Average HGL Elevation Attained (ft)	962.14
Average HGL Depth Attained (ft)	1.14
Time of Max HGL Occurrence (days hh:mm)	0 12:20
Total Exfiltration Volume (1000-ft³)	0.000
Total Flooded Volume (ac-in)	0
Total Time Flooded (min)	4011
Total Retention Time (sec)	0.00

File Name 20180111_2020-06-29 Post.SPF

Project Options

Flow Units CFS
Elevation Type Elevation
Hydrology Method SCS TR-55
Time of Concentration (TOC) Method SCS TR-55
Link Routing Method Hydrodynamic
Enable Overflow Ponding at Nodes YES
Skip Steady State Analysis Time Periods NO

Analysis Options

Start Analysis On Jun 29, 2020 00:00:00
End Analysis On Jul 02, 2020 00:05:00
Start Reporting On Jun 29, 2020 00:00:00
Antecedent Dry Days 0 days
Runoff (Dry Weather) Time Step 0 01:00:00 days hh:mm:ss
Runoff (Wet Weather) Time Step 0 00:05:00 days hh:mm:ss
Reporting Time Step 0 00:05:00 days hh:mm:ss
Routing Time Step 30 seconds

Number of Elements

	Qty
Rain Gages	1
Subbasins.....	2
Nodes.....	3
<i>Junctions</i>	1
<i>Outfalls</i>	1
<i>Flow Diversions</i>	0
<i>Inlets</i>	0
<i>Storage Nodes</i>	1
Links.....	10
<i>Channels</i>	0
<i>Pipes</i>	1
<i>Pumps</i>	0
<i>Orifices</i>	9
<i>Weirs</i>	0
<i>Outlets</i>	0
Pollutants	0
Land Uses	0

Rainfall Details

SN	Rain Gage ID	Data Source	Data Source ID	Rainfall Type	Rain Units	State	County	Return Period (years)	Rainfall Depth (inches)	Rainfall Distribution
1	Rain Gage-01	Time Series	10 year	Cumulative	inches	Missouri	Jackson	10	5.30	SCS Type II 24-hr

Subbasin Summary

SN	Subbasin ID	Area	Weighted Curve Number	Total Rainfall	Total Runoff	Total Runoff Volume	Peak Runoff	Time of Concentration
		(ac)		(in)	(in)	(ac-in)	(cfs)	(days hh:mm:ss)
1	BYPASS	0.32	81.13	5.30	3.26	1.04	1.65	0 00:05:00
2	ProposedNorth	1.75	89.98	5.30	4.16	7.29	11.02	0 00:05:00

Node Summary

SN	Element ID	Element Type	Invert Elevation	Ground/Rim (Max) Elevation	Initial Water Elevation	Surcharge Elevation	Ponded Area	Peak Inflow	Max HGL Elevation Attained	Max Surcharge Depth Attained	Min Freeboard Attained	Time of Peak Flooding Occurrence	Total Flooded Volume	Total Time Flooded
			(ft)	(ft)	(ft)	(ft)	(ft²)	(cfs)	(ft)	(ft)	(ft)	(days hh:mm)	(ac-in)	(min)
1	A1	Junction	957.84	966.20	0.00	0.00	0.00	2.01	958.13	0.00	8.07	0 00:00	0.00	0.00
2	OUTFALL	Outfall	948.85					3.14	949.13					
3	POND	Storage Node	961.00	6.00	961.00		0.00	11.01	965.13				0.00	4101.00

DCI Lee's Summit
06/30/20
Link Summary

Post-Developed 10-year

SN	Element ID	Element Type	From (Inlet) Node	To (Outlet) Node	Length	Inlet Invert Elevation	Outlet Invert Elevation	Average Slope	Diameter or Height	Manning's Roughness	Peak Flow	Design Flow Capacity	Peak Flow/ Design Flow Ratio	Peak Flow Velocity	Peak Flow Depth	Peak Flow Depth/ Total Depth Ratio	Total Time Reported	Surcharged Condition
					(ft)	(ft)	(ft)	(%)	(in)		(cfs)	(cfs)		(ft/sec)	(ft)		(min)	
1	Link-03	Pipe	A1	OUTFALL	160.20	957.84	948.85	5.6100	24.000	0.0150	2.02	46.45	0.04	7.29	0.29	0.14	0.00	Calculated
2	Orifice1	Orifice	POND	A1		961.00	957.84		1.000		0.05							
3	Orifice2	Orifice	POND	A1		961.00	957.84		1.000		0.05							
4	Orifice3	Orifice	POND	A1		961.00	957.84		1.000		0.05							
5	Orifice4	Orifice	POND	A1		961.00	957.84		1.000		0.04							
6	Orifice5	Orifice	POND	A1		961.00	957.84		1.000		0.04							
7	Orifice6	Orifice	POND	A1		961.00	957.84		4.000		0.44							
8	Orifice7	Orifice	POND	A1		961.00	957.84		4.000		0.44							
9	Orifice8	Orifice	POND	A1		961.00	957.84		4.000		0.44							
10	Orifice9	Orifice	POND	A1		961.00	957.84		4.000		0.44							

Junction Input

SN	Element ID	Invert Elevation	Ground/Rim (Max) Elevation	Ground/Rim (Max) Offset	Initial Water Elevation	Initial Water Depth	Surcharge Elevation	Surcharge Depth	Ponded Area	Minimum Pipe Cover
		(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft²)	(in)
1	A1	957.84	966.20	8.36	0.00	-957.84	0.00	-966.20	0.00	0.00

DCI Lee's Summit
06/30/20

Post-Developed 10-year

Junction Results

SN	Element ID	Peak Inflow	Peak Lateral Inflow	Max HGL Elevation Attained	Max HGL Depth Attained	Max Surcharge Depth Attained	Min Freeboard Attained	Average HGL Elevation Attained	Average HGL Depth Attained	Time of Max HGL Occurrence	Time of Peak Flooding Occurrence	Total Flooded Volume	Total Time Flooded
		(cfs)	(cfs)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(days hh:mm)	(days hh:mm)	(ac-in)	(min)
1	A1	2.01	0.00	958.13	0.29	0.00	8.07	957.88	0.04	0 12:15	0 00:00	0.00	0.00

SN Element ID	Length	Inlet Invert Elevation	Inlet Invert Offset	Outlet Invert Elevation	Outlet Invert Offset	Total Drop	Average Pipe Slope	Pipe Shape	Pipe Diameter or Height	Pipe Width	Manning's Roughness	Entrance Losses	Exit/Bend Losses	Additional Losses	Initial Flow	Flap Gate	No. of Barrels
	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(%)		(in)	(in)					(cfs)		
1 Link-03	160.20	957.84	0.00	948.85	0.00	8.99	5.6100	CIRCULAR	24.000	24.000	0.0150	0.5000	0.5000	0.0000	0.00	No	1

DCI Lee's Summit
06/30/20

Post-Developed 10-year

Pipe Results

SN	Element ID	Peak Flow	Time of Peak Flow Occurrence	Design Flow Capacity	Peak Flow/ Design Flow Ratio	Peak Flow Velocity	Travel Time	Peak Flow Depth	Peak Flow Depth/ Total Depth Ratio	Total Time Surcharged	Froude Number	Reported Condition
		(cfs)	(days hh:mm)	(cfs)		(ft/sec)	(min)	(ft)		(min)		
1	Link-03	2.02	0 12:15	46.45	0.04	7.29	0.37	0.29	0.14	0.00		Calculated

Storage Nodes

Storage Node : POND

Input Data


Invert Elevation (ft)	961.00
Max (Rim) Elevation (ft)	6.00
Max (Rim) Offset (ft)	-955.00
Initial Water Elevation (ft)	961.00
Initial Water Depth (ft)	0.00
Ponded Area (ft²)	0.00
Evaporation Loss	0.00

Storage Area Volume Curves

Storage Curve : Pond

Stage	Storage Area	Storage Volume
(ft)	(ft²)	(ft³)
0	0	0
1	1586.00	793
2	3180.00	3180
3	4723.33	7085
4	6092.50	12185
5	7326.00	18315
5.2	7566.15	19672
6	8517.67	25553
7	9702.57	33959
7.7	10536.10	40564

Storage Area Volume Curves



Outflow Orifices

SN	Element ID	Orifice Type	Orifice Shape	Flap Gate	Circular Orifice Diameter (in)	Rectangular Orifice Height (in)	Rectangular Orifice Width (in)	Orifice Invert Elevation (ft)	Orifice Coefficient
1	Orifice1	Side	CIRCULAR	No	1.00			961.52	0.61
2	Orifice2	Side	CIRCULAR	No	1.00			961.85	0.61
3	Orifice3	Side	CIRCULAR	No	1.00			962.18	0.61
4	Orifice4	Side	CIRCULAR	No	1.00			962.51	0.61
5	Orifice5	Side	CIRCULAR	No	1.00			962.84	0.61
6	Orifice6	Side	CIRCULAR	No	4.00			963.90	0.61
7	Orifice7	Side	CIRCULAR	No	4.00			963.90	0.61
8	Orifice8	Side	CIRCULAR	No	4.00			963.90	0.61
9	Orifice9	Side	CIRCULAR	No	4.00			963.90	0.61

Output Summary Results

Peak Inflow (cfs)	11.01
Peak Lateral Inflow (cfs)	11.01
Peak Outflow (cfs)	2.01
Peak Exfiltration Flow Rate (cfm)	0.00
Max HGL Elevation Attained (ft)	965.13
Max HGL Depth Attained (ft)	4.13
Average HGL Elevation Attained (ft)	962.28
Average HGL Depth Attained (ft)	1.28
Time of Max HGL Occurrence (days hh:mm)	0 12:14
Total Exfiltration Volume (1000-ft³)	0.000
Total Flooded Volume (ac-in)	0
Total Time Flooded (min)	4101
Total Retention Time (sec)	0.00

File Name 20180111_2020-06-29 Post.SPF

Project Options

Flow Units CFS
Elevation Type Elevation
Hydrology Method SCS TR-55
Time of Concentration (TOC) Method SCS TR-55
Link Routing Method Hydrodynamic
Enable Overflow Ponding at Nodes YES
Skip Steady State Analysis Time Periods NO

Analysis Options

Start Analysis On Jun 29, 2020 00:00:00
End Analysis On Jul 02, 2020 00:05:00
Start Reporting On Jun 29, 2020 00:00:00
Antecedent Dry Days 0 days
Runoff (Dry Weather) Time Step 0 01:00:00 days hh:mm:ss
Runoff (Wet Weather) Time Step 0 00:05:00 days hh:mm:ss
Reporting Time Step 0 00:05:00 days hh:mm:ss
Routing Time Step 30 seconds

Number of Elements

Qty
Rain Gages 1
Subbasins..... 2
Nodes..... 3
 Junctions 1
 Outfalls 1
 Flow Diversions 0
 Inlets 0
 Storage Nodes 1
Links..... 10
 Channels 0
 Pipes 1
 Pumps 0
 Orifices 9
 Weirs 0
 Outlets 0
Pollutants 0
Land Uses 0

Rainfall Details

SN	Rain Gage ID	Data Source	Data Source ID	Rainfall Type	Rain Units	State	County	Return Period (years)	Rainfall Depth (inches)	Rainfall Distribution
1	Rain Gage-01	Time Series	100 year	Cumulative	inches	Missouri	Jackson	100	7.70	SCS Type II 24-hr

06/30/20

Subbasin Summary

SN	Subbasin ID	Area	Weighted Curve Number	Total Rainfall	Total Runoff	Total Runoff Volume	Peak Runoff	Time of Concentration
		(ac)		(in)	(in)	(ac-in)	(cfs)	(days hh:mm:ss)
1	BYPASS	0.32	81.13	7.70	5.47	1.75	2.72	0 00:05:00
2	ProposedNorth	1.75	89.98	7.70	6.51	11.39	16.77	0 00:05:00

Node Summary

SN	Element ID	Element Type	Invert Elevation	Ground/Rim (Max) Elevation	Initial Water Elevation	Surcharge Elevation	Ponded Area	Peak Inflow	Max HGL Elevation Attained	Max Surcharge Depth Attained	Min Freeboard Attained	Time of Peak Flooding Occurrence	Total Flooded Volume	Total Time Flooded
			(ft)	(ft)	(ft)	(ft)	(ft²)	(cfs)	(ft)	(ft)	(ft)	(days hh:mm)	(ac-in)	(min)
1	A1	Junction	957.84	966.20	0.00	0.00	0.00	2.78	958.18	0.00	8.02	0 00:00	0.00	0.00
2	OUTFALL	Outfall	948.85					4.91	949.18					
3	POND	Storage Node	961.00	6.00	961.00		0.00	16.76	966.20				0.00	4166.00

SN	Element ID	Element Type	From (Inlet) Node	To (Outlet) Node	Length	Inlet Invert Elevation	Outlet Invert Elevation	Average Slope	Diameter or Height	Manning's Roughness	Peak Flow	Design Flow Capacity	Peak Flow/ Design Flow Ratio	Peak Flow Velocity	Peak Flow Depth	Peak Flow Depth/ Total Depth Ratio	Total Time Reported	Surcharged Condition
					(ft)	(ft)	(ft)	(%)	(in)		(cfs)	(cfs)		(ft/sec)	(ft)		(min)	
1	Link-03	Pipe	A1	OUTFALL	160.20	957.84	948.85	5.6100	24.000	0.0150	2.78	46.45	0.06	7.92	0.34	0.17	0.00	Calculated
2	Orifice1	Orifice	POND	A1		961.00	957.84		1.000		0.06							
3	Orifice2	Orifice	POND	A1		961.00	957.84		1.000		0.06							
4	Orifice3	Orifice	POND	A1		961.00	957.84		1.000		0.05							
5	Orifice4	Orifice	POND	A1		961.00	957.84		1.000		0.05							
6	Orifice5	Orifice	POND	A1		961.00	957.84		1.000		0.05							
7	Orifice6	Orifice	POND	A1		961.00	957.84		4.000		0.63							
8	Orifice7	Orifice	POND	A1		961.00	957.84		4.000		0.63							
9	Orifice8	Orifice	POND	A1		961.00	957.84		4.000		0.63							
10	Orifice9	Orifice	POND	A1		961.00	957.84		4.000		0.63							

Junction Input

SN	Element ID	Invert Elevation	Ground/Rim (Max) Elevation	Ground/Rim (Max) Offset	Initial Water Elevation	Initial Water Depth	Surcharge Elevation	Surcharge Depth	Ponded Area	Minimum Pipe Cover
		(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft²)	(in)
1	A1	957.84	966.20	8.36	0.00	-957.84	0.00	-966.20	0.00	0.00

DCI Lee's Summit
06/30/20

Post-Developed 100-year

Junction Results

SN	Element ID	Peak Inflow	Peak Lateral Inflow	Max HGL Elevation Attained	Max HGL Depth Attained	Max Surcharge Depth Attained	Min Freeboard Attained	Average HGL Elevation Attained	Average HGL Depth Attained	Time of Max HGL Occurrence	Time of Peak Flooding Occurrence	Total Flooded Volume	Total Time Flooded
		(cfs)	(cfs)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(days hh:mm)	(days hh:mm)	(ac-in)	(min)
1	A1	2.78	0.00	958.18	0.34	0.00	8.02	957.90	0.06	0 12:14	0 00:00	0.00	0.00

06/30/20

Pipe Input

SN Element ID	Length	Inlet Invert Elevation	Inlet Invert Offset	Outlet Invert Elevation	Outlet Invert Offset	Total Drop	Average Pipe Slope	Pipe Shape	Pipe Diameter or Height	Pipe Width	Manning's Roughness	Entrance Losses	Exit/Bend Losses	Additional Losses	Initial Flow	Flap Gate	No. of Barrels
	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(%)		(in)	(in)					(cfs)		
1 Link-03	160.20	957.84	0.00	948.85	0.00	8.99	5.6100	CIRCULAR	24.000	24.000	0.0150	0.5000	0.5000	0.0000	0.00	No	1

Pipe Results

SN	Element ID	Peak Flow	Time of Peak Flow Occurrence	Design Flow Capacity	Peak Flow/ Design Flow Ratio	Peak Flow Velocity	Travel Time	Peak Flow Depth	Peak Flow Depth/ Total Depth Ratio	Total Time Surcharged	Froude Number	Reported Condition
		(cfs)	(days hh:mm)	(cfs)		(ft/sec)	(min)	(ft)		(min)		
1	Link-03	2.78	0 12:14	46.45	0.06	7.92	0.34	0.34	0.17	0.00		Calculated

Storage Nodes

Storage Node : POND

Input Data


Invert Elevation (ft)	961.00
Max (Rim) Elevation (ft)	6.00
Max (Rim) Offset (ft)	-955.00
Initial Water Elevation (ft)	961.00
Initial Water Depth (ft)	0.00
Ponded Area (ft²)	0.00
Evaporation Loss	0.00

Storage Area Volume Curves

Storage Curve : Pond

Stage	Storage Area	Storage Volume
(ft)	(ft²)	(ft³)
0	0	0
1	1586.00	793
2	3180.00	3180
3	4723.33	7085
4	6092.50	12185
5	7326.00	18315
5.2	7566.15	19672
6	8517.67	25553
7	9702.57	33959
7.7	10536.10	40564

Storage Area Volume Curves



Outflow Orifices

SN	Element ID	Orifice Type	Orifice Shape	Flap Gate	Circular Orifice Diameter (in)	Rectangular Orifice Height (in)	Rectangular Orifice Width (in)	Orifice Invert Elevation (ft)	Orifice Coefficient
1	Orifice1	Side	CIRCULAR	No	1.00			961.52	0.61
2	Orifice2	Side	CIRCULAR	No	1.00			961.85	0.61
3	Orifice3	Side	CIRCULAR	No	1.00			962.18	0.61
4	Orifice4	Side	CIRCULAR	No	1.00			962.51	0.61
5	Orifice5	Side	CIRCULAR	No	1.00			962.84	0.61
6	Orifice6	Side	CIRCULAR	No	4.00			963.90	0.61
7	Orifice7	Side	CIRCULAR	No	4.00			963.90	0.61
8	Orifice8	Side	CIRCULAR	No	4.00			963.90	0.61
9	Orifice9	Side	CIRCULAR	No	4.00			963.90	0.61

Output Summary Results


Peak Inflow (cfs)	16.76
Peak Lateral Inflow (cfs)	16.76
Peak Outflow (cfs)	2.78
Peak Exfiltration Flow Rate (cfm)	0.00
Max HGL Elevation Attained (ft)	966.20
Max HGL Depth Attained (ft)	5.2
Average HGL Elevation Attained (ft)	962.52
Average HGL Depth Attained (ft)	1.52
Time of Max HGL Occurrence (days hh:mm)	0 12:14
Total Exfiltration Volume (1000-ft³)	0.000
Total Flooded Volume (ac-in)	0
Total Time Flooded (min)	4166
Total Retention Time (sec)	0.00



**CLOGGED/ ZERO AVAILABLE STORAGE ROUTING
100-YEAR EVENT**

Watershed Model Schematic

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020



Hydrograph Summary Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	17.14	2	718	40,898	-----	-----	-----	EXISTING NORTH
2	SCS Runoff	2.350	2	720	6,305	-----	-----	-----	EXISTING SOUTH
3	SCS Runoff	17.48	2	716	38,772	-----	-----	-----	PROPOSED NORTH
4	SCS Runoff	2.838	2	716	5,946	-----	-----	-----	PROPOSED BYPASS
5	Combine	19.36	2	718	47,203	1, 2,	-----	-----	EXISTING SITE
6	Reservoir	16.85	2	718	35,243	3	967.00	25,531	PROPOSED TO DET
7	Combine	19.60	2	718	41,189	4, 6	-----	-----	PROPOSED SITE
20180111_2019-11-01 ROUTING CALCULATIONS (Clogged 800 Year Capacity).gpxThursday, 01 / 9 / 2020									

Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020


Thursday, 01 / 9 / 2020

Hyd. No. 3

PROPOSED NORTH

Hydrograph type	= SCS Runoff	Peak discharge	= 17.48 cfs
Storm frequency	= 100 yrs	Time to peak	= 716 min
Time interval	= 2 min	Hyd. volume	= 38,772 cuft
Drainage area	= 1.750 ac	Curve number	= 90*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= User	Time of conc. (Tc)	= 5.00 min
Total precip.	= 7.70 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = $[(0.780 \times 80) + (0.970 \times 98)] / 1.750$



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020


Thursday, 01 / 9 / 2020

Hyd. No. 6

PROPOSED TO DET

Hydrograph type	= Reservoir	Peak discharge	= 16.85 cfs
Storm frequency	= 100 yrs	Time to peak	= 718 min
Time interval	= 2 min	Hyd. volume	= 35,243 cuft
Inflow hyd. No.	= 3 - PROPOSED NORTH	Max. Elevation	= 967.00 ft
Reservoir name	= Detention Pond	Max. Storage	= 25,531 cuft

Storage Indication method used. Wet pond routing start elevation = 966.20 ft.



Pond No. 1 - Detention Pond

Pond Data

Contours -User-defined contour areas. Average end area method used for volume calculation. Beginning Elevation = 961.00 ft

Stage / Storage Table

Stage (ft)	Elevation (ft)	Contour area (sqft)	Incr. Storage (cuft)	Total storage (cuft)
0.00	961.00	10	0	0
1.00	962.00	1,575	793	793
2.00	963.00	3,200	2,388	3,180
3.00	964.00	4,610	3,905	7,085
4.00	965.00	5,590	5,100	12,185
5.00	966.00	6,670	6,130	18,315
5.20	966.20	6,895	1,357	19,672
6.00	967.00	7,809	5,881	25,553
7.00	968.00	9,002	8,405	33,958
7.70	968.70	9,869	6,605	40,563


Culvert / Orifice Structures

	[A]	[B]	[C]	[PrfRsr]
Rise (in)	= 24.00	Inactive	Inactive	Inactive
Span (in)	= 24.00	8.00	0.00	1.00
No. Barrels	= 1	1	0	6
Invert El. (ft)	= 958.00	963.80	0.00	961.52
Length (ft)	= 162.00	1.00	0.00	1.65
Slope (%)	= 5.61	0.50	0.00	n/a
N-Value	= .013	.013	.013	n/a
Orifice Coeff.	= 0.60	0.60	0.60	0.60
Multi-Stage	= n/a	Yes	No	Yes

Weir Structures

	[A]	[B]	[C]	[D]
Crest Len (ft)	Inactive	40.00	Inactive	Inactive
Crest El. (ft)	= 966.20	966.70	0.00	0.00
Weir Coeff.	= 2.60	2.60	3.33	3.33
Weir Type	= Broad	Broad	---	---
Multi-Stage	= Yes	Yes	No	No
Exfil.(in/hr)	= 0.000 (by Wet area)			
TW Elev. (ft)	= 0.00			

Note: Culvert/Orifice outflows are analyzed under inlet (ic) and outlet (oc) control. Weir risers checked for orifice conditions (ic) and submergence (s).



Hydrograph Report


Hydraflow Hydrographs Extension for Autodesk® Civil 3D® 2019 by Autodesk, Inc. v2020

Thursday, 01 / 9 / 2020

Hyd. No. 7

PROPOSED SITE

Hydrograph type	= Combine	Peak discharge	= 19.60 cfs
Storm frequency	= 100 yrs	Time to peak	= 718 min
Time interval	= 2 min	Hyd. volume	= 41,189 cuft
Inflow hyds.	= 4, 6	Contrib. drain. area	= 0.320 ac



Channel Report

Hydraflow Express Extension for Autodesk® AutoCAD® Civil 3D® by Autodesk, Inc.

Thursday, Aug 22 2019

Emergency Spillway

Trapezoidal


Bottom Width (ft) = 40.00
Side Slopes (z:1) = 3.00, 3.00
Total Depth (ft) = 1.00
Invert Elev (ft) = 966.70
Slope (%) = 1.00
N-Value = 0.150

Calculations

Compute by: Known Q
Known Q (cfs) = 34.51


Highlighted

Depth (ft) = 0.91
Q (cfs) = 34.51
Area (sqft) = 38.88
Velocity (ft/s) = 0.89
Wetted Perim (ft) = 45.76
Crit Depth, Yc (ft) = 0.29
Top Width (ft) = 45.46
EGL (ft) = 0.92



Attachment 3
Hydraflow Storm Sewers Calculations

Hydraflow Storm Sewers Extension for Autodesk® AutoCAD® Civil 3D® Plan



Project File: 20180111_2020-06-23 Storm Sewers-field conditions.stm	Number of lines: 20	Date: 6/23/2020
---	---------------------	-----------------

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	B2-B1	2.29	12	Cir	99.99	963.50	972.32	8.821	964.32	972.97	n/a	972.97 j	End	Manhole
2	B3-B2	1.23	12	Cir	17.74	972.32	972.50	1.015	972.97	972.97	n/a	972.97 j	1	Grate
3	B4-B3	0.69	10	Cir	68.55	972.70	973.39	1.007	973.02	973.76	0.02	973.76	2	Manhole
4	B5-B4	0.36	10	Cir	72.55	973.39	974.11	0.992	973.76	974.37	n/a	974.37 j	3	Manhole
5	B6-B5	0.29	10	Cir	25.08	974.11	974.36	0.997	974.37	974.59	n/a	974.59 j	4	Manhole
6	B7-B6	0.09	10	Cir	41.25	974.36	974.77	0.994	974.59	974.90	n/a	974.90 j	5	Manhole
7	B8-B7	0.03	10	Cir	32.00	974.77	975.09	1.000	974.90	975.16	n/a	975.16 j	6	Manhole
8	B9-B8	0.03	10	Cir	13.88	975.09	975.23	1.009	975.16	975.30	n/a	975.30	7	Manhole
9	C1-B2	1.06	10	Cir	7.84	972.32	973.31	12.631	972.97	973.77	n/a	973.77 j	1	Manhole
10	C2-C1	0.99	10	Cir	31.16	973.31	973.62	0.995	973.77	974.06	n/a	974.06 j	9	Manhole
11	C3-C2	0.79	10	Cir	59.30	973.62	974.22	1.012	974.06	974.61	n/a	974.61 j	10	Manhole
12	C4-C3	0.53	10	Cir	70.00	974.22	974.92	1.000	974.61	975.24	n/a	975.24 j	11	Manhole
13	C5-C4	0.26	10	Cir	38.21	974.92	975.30	0.994	975.24	975.52	n/a	975.52 j	12	Manhole
14	D2-D1	4.67	12	Cir	34.62	963.50	969.00	15.888	964.45	969.90	n/a	969.90 j	End	Curb-Horiz
15	D3-D2	3.54	12	Cir	30.05	969.20	971.30	6.988	969.90	972.10	n/a	972.10	14	Curb-Horiz
16	D4-D3	2.55	12	Cir	190.01	971.50	973.50	1.053	972.12	974.18	n/a	974.18	15	Curb-Horiz
17	EX AL#1202-OUTFALL	8.04	24	Cir	91.74	947.73	948.65	1.003	949.23	949.66	n/a	949.66 j	End	Grate
18	A1-EX AL#1202	5.20	24	Cir	160.20	948.85	957.84	5.612	949.66	958.64	n/a	958.64 j	17	Grate
19	A2-A1	2.16	15	Cir	72.03	958.04	962.63	6.372	958.64	963.22	n/a	963.22 j	18	Manhole
20	EX A3-A2	2.16	15	Cir	56.15	966.58	967.09	0.908	967.09	967.68	n/a	967.68	19	Grate

Project File: 20180111_2020-06-23 Storm Sewers-field conditions.stm

Number of lines: 20

Run Date: 6/23/2020

NOTES: Return period = 10 Yrs. ; j - Line contains hyd. jump.

Storm Sewer Tabulation

Station		Len	Drng Area		Rnoff coeff	Area x C		Tc		Rain (l)	Total flow	Cap full	Vel	Pipe		Invert Elev		HGL Elev		Grnd / Rim Elev		Line ID	
Line	To Line		Incr	Total		Incr	Total	Inlet	Syst					Size	Slope	Dn	Up	Dn	Up	Dn	Up		
		(ft)	(ac)	(ac)	(C)			(min)	(min)	(in/hr)	(cfs)	(cfs)	(ft/s)	(in)	(%)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		
1	End	99.99	0.00	0.39	0.00	0.00	0.33	0.0	5.0	7.0	2.29	10.58	3.79	12	8.82	963.50	972.32	964.32	972.97	965.10	978.70	B2-B1	
2	1	17.74	0.13	0.23	0.60	0.08	0.18	5.0	5.0	7.0	1.23	3.59	2.85	12	1.01	972.32	972.50	972.97	972.97	978.70	977.67	B3-B2	
3	2	68.55	0.05	0.10	0.95	0.05	0.10	5.0	5.0	7.0	0.69	2.20	3.28	10	1.01	972.70	973.39	973.02	973.76	977.67	977.10	B4-B3	
4	3	72.55	0.01	0.05	0.95	0.01	0.05	5.0	5.0	7.0	0.36	2.18	2.01	10	0.99	973.39	974.11	973.76	974.37	977.10	979.00	B5-B4	
5	4	25.08	0.03	0.04	0.95	0.03	0.04	5.0	5.0	7.0	0.29	2.19	2.16	10	1.00	974.11	974.36	974.37	974.59	979.00	978.75	B6-B5	
6	5	41.25	0.01	0.01	0.95	0.01	0.01	5.0	5.0	7.0	0.09	2.18	1.22	10	0.99	974.36	974.77	974.59	974.90	978.75	978.40	B7-B6	
7	6	32.00	0.00	0.00	0.00	0.00	0.00	0.0	5.0	7.0	0.03	2.19	0.86	10	1.00	974.77	975.09	974.90	975.16	978.40	978.15	B8-B7	
8	7	13.88	0.00	0.00	0.95	0.00	0.00	5.0	5.0	7.0	0.03	2.20	1.23	10	1.01	975.09	975.23	975.16	975.30	978.15	978.30	B9-B8	
9	1	7.84	0.01	0.16	0.95	0.01	0.15	5.0	5.0	7.0	1.06	7.78	2.89	10	12.63	972.32	973.31	972.97	973.77	978.70	978.70	C1-B2	
10	9	31.16	0.03	0.15	0.95	0.03	0.14	5.0	5.0	7.0	0.99	2.18	3.31	10	0.99	973.31	973.62	973.77	974.06	978.70	978.28	C2-C1	
11	10	59.30	0.04	0.12	0.95	0.04	0.11	5.0	5.0	7.0	0.79	2.20	2.92	10	1.01	973.62	974.22	974.06	974.61	978.28	978.25	C3-C2	
12	11	70.00	0.04	0.08	0.95	0.04	0.08	5.0	5.0	7.0	0.53	2.19	2.43	10	1.00	974.22	974.92	974.61	975.24	978.25	978.67	C4-C3	
13	12	38.21	0.04	0.04	0.95	0.04	0.04	5.0	5.0	7.0	0.26	2.18	1.82	10	0.99	974.92	975.30	975.24	975.52	978.67	978.80	C5-C4	
14	End	34.62	0.17	0.93	0.95	0.16	0.67	5.0	5.0	7.0	4.67	14.19	6.18	12	15.89	963.50	969.00	964.45	969.90	965.60	976.30	D2-D1	
15	14	30.05	0.15	0.76	0.95	0.14	0.51	5.0	5.0	7.0	3.54	9.41	5.65	12	6.99	969.20	971.30	969.90	972.10	976.30	976.30	D3-D2	
16	15	190.01	0.61	0.61	0.60	0.37	0.37	5.0	5.0	7.0	2.55	3.65	4.74	12	1.05	971.50	973.50	972.12	974.18	976.30	977.60	D4-D3	
17	End	91.74	0.00	0.00	0.00	0.00	0.00	5.0	5.0	0.0	8.04	22.65	4.12	24	1.00	947.73	948.65	949.23	949.66	950.00	959.95	EX AL#1202-OUT	
18	17	160.20	0.00	0.00	0.00	0.00	0.00	0.0	0.0	0.0	5.20	53.58	4.39	24	5.61	948.85	957.84	949.66	958.64	959.95	966.20	A1-EX AL#1202	
19	18	72.03	0.00	0.00	0.00	0.00	0.00	0.0	0.0	0.0	2.16	16.30	3.75	15	6.37	958.04	962.63	958.64	963.22	966.20	971.20	A2-A1	
20	19	56.15	0.00	0.00	0.00	0.00	0.00	0.0	0.0	0.0	2.16	6.15	4.20	15	0.91	966.58	967.09	967.09	967.68	971.20	973.94	EX A3-A2	
Project File: 20180111_2020-06-23 Storm Sewers-field conditions.stm																Number of lines: 20				Run Date: 6/23/2020			
NOTES:Intensity = 66.71 / (Inlet time + 12.50) ^ 0.79; Return period =Yrs. 10 ; Pipe travel time suppressed. ; c = cir e = ellip b = box																							

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	B2-B1	3.20	12	Cir	99.99	963.50	972.32	8.821	964.38	973.09	n/a	973.09 j	End	Manhole
2	B3-B2	1.72	12	Cir	17.74	972.32	972.50	1.015	973.09	973.06	n/a	973.06 j	1	Grate
3	B4-B3	0.96	10	Cir	68.55	972.70	973.39	1.007	973.09	973.82	0.03	973.82	2	Manhole
4	B5-B4	0.50	10	Cir	72.55	973.39	974.11	0.992	973.82	974.42	n/a	974.42 j	3	Manhole
5	B6-B5	0.41	10	Cir	25.08	974.11	974.36	0.997	974.42	974.64	n/a	974.64 j	4	Manhole
6	B7-B6	0.13	10	Cir	41.25	974.36	974.77	0.994	974.64	974.92	n/a	974.92 j	5	Manhole
7	B8-B7	0.04	10	Cir	32.00	974.77	975.09	1.000	974.92	975.17	n/a	975.17 j	6	Manhole
8	B9-B8	0.04	10	Cir	13.88	975.09	975.23	1.009	975.17	975.31	0.03	975.31	7	Manhole
9	C1-B2	1.48	10	Cir	7.84	972.32	973.31	12.631	973.09	973.85	n/a	973.85 j	1	Manhole
10	C2-C1	1.38	10	Cir	31.16	973.31	973.62	0.995	973.85	974.15	n/a	974.15 j	9	Manhole
11	C3-C2	1.11	10	Cir	59.30	973.62	974.22	1.012	974.15	974.69	n/a	974.69 j	10	Manhole
12	C4-C3	0.74	10	Cir	70.00	974.22	974.92	1.000	974.69	975.30	n/a	975.30 j	11	Manhole
13	C5-C4	0.37	10	Cir	38.21	974.92	975.30	0.994	975.30	975.56	n/a	975.56 j	12	Manhole
14	D2-D1	6.51	12	Cir	34.62	963.50	969.00	15.888	964.48	969.97	n/a	969.97 j	End	Curb-Horiz
15	D3-D2	4.94	12	Cir	30.05	969.20	971.30	6.988	969.97	972.21	0.76	972.21	14	Curb-Horiz
16	D4-D3	3.56	12	Cir	190.01	971.50	973.50	1.053	972.30	974.30	n/a	974.30	15	Curb-Horiz
17	EX AL#1202-OUTFALL	9.26	24	Cir	91.74	947.73	948.65	1.003	949.27	949.74	n/a	949.74 j	End	Grate
18	A1-EX AL#1202	6.42	24	Cir	160.20	948.85	957.84	5.612	949.74	958.74	n/a	958.74	17	Grate
19	A2-A1	3.38	15	Cir	72.03	958.04	962.63	6.372	958.74	963.37	n/a	963.37	18	Manhole
20	EX A3-A2	3.38	15	Cir	56.15	966.58	967.09	0.908	967.24	967.83	n/a	967.83	19	Grate

Project File: 20180111_2020-06-23 Storm Sewers-field conditions.stm

Number of lines: 20


Run Date: 6/23/2020

NOTES: Return period = 100 Yrs. ; j - Line contains hyd. jump.

Storm Sewer Tabulation

Station		Len (ft)	Drng Area		Rnoff coeff (C)	Area x C		Tc		Rain (l) (in/hr)	Total flow (cfs)	Cap full (cfs)	Vel (ft/s)	Pipe		Invert Elev		HGL Elev		Grnd / Rim Elev		Line ID	
Line	To Line		Incr (ac)	Total (ac)		Incr (min)	Total (min)	Inlet (min)	Syst (min)					Size (in)	Slope (%)	Dn (ft)	Up (ft)	Dn (ft)	Up (ft)	Dn (ft)	Up (ft)		
1	End	99.99	0.00	0.39	0.00	0.00	0.33	0.0	5.0	9.7	3.20	10.58	4.66	12	8.82	963.50	972.32	964.38	973.09	965.10	978.70	B2-B1	
2	1	17.74	0.13	0.23	0.60	0.08	0.18	5.0	5.0	9.7	1.72	3.59	3.24	12	1.01	972.32	972.50	973.09	973.06	978.70	977.67	B3-B2	
3	2	68.55	0.05	0.10	0.95	0.05	0.10	5.0	5.0	9.7	0.96	2.20	3.62	10	1.01	972.70	973.39	973.09	973.82	977.67	977.10	B4-B3	
4	3	72.55	0.01	0.05	0.95	0.01	0.05	5.0	5.0	9.7	0.50	2.18	2.22	10	0.99	973.39	974.11	973.82	974.42	977.10	979.00	B5-B4	
5	4	25.08	0.03	0.04	0.95	0.03	0.04	5.0	5.0	9.7	0.41	2.19	2.38	10	1.00	974.11	974.36	974.42	974.64	979.00	978.75	B6-B5	
6	5	41.25	0.01	0.01	0.95	0.01	0.01	5.0	5.0	9.7	0.13	2.18	1.34	10	0.99	974.36	974.77	974.64	974.92	978.75	978.40	B7-B6	
7	6	32.00	0.00	0.00	0.00	0.00	0.00	0.0	5.0	9.7	0.04	2.19	0.94	10	1.00	974.77	975.09	974.92	975.17	978.40	978.15	B8-B7	
8	7	13.88	0.00	0.00	0.95	0.00	0.00	5.0	5.0	9.7	0.04	2.20	1.34	10	1.01	975.09	975.23	975.17	975.31	978.15	978.30	B9-B8	
9	1	7.84	0.01	0.16	0.95	0.01	0.15	5.0	5.0	9.7	1.48	7.78	3.37	10	12.63	972.32	973.31	973.09	973.85	978.70	978.70	C1-B2	
10	9	31.16	0.03	0.15	0.95	0.03	0.14	5.0	5.0	9.7	1.38	2.18	3.75	10	0.99	973.31	973.62	973.85	974.15	978.70	978.28	C2-C1	
11	10	59.30	0.04	0.12	0.95	0.04	0.11	5.0	5.0	9.7	1.11	2.20	3.28	10	1.01	973.62	974.22	974.15	974.69	978.28	978.25	C3-C2	
12	11	70.00	0.04	0.08	0.95	0.04	0.08	5.0	5.0	9.7	0.74	2.19	2.70	10	1.00	974.22	974.92	974.69	975.30	978.25	978.67	C4-C3	
13	12	38.21	0.04	0.04	0.95	0.04	0.04	5.0	5.0	9.7	0.37	2.18	2.01	10	0.99	974.92	975.30	975.30	975.56	978.67	978.80	C5-C4	
14	End	34.62	0.17	0.93	0.95	0.16	0.67	5.0	5.0	9.7	6.51	14.19	8.35	12	15.89	963.50	969.00	964.48	969.97	965.60	976.30	D2-D1	
15	14	30.05	0.15	0.76	0.95	0.14	0.51	5.0	5.0	9.7	4.94	9.41	7.11	12	6.99	969.20	971.30	969.97	972.21	976.30	976.30	D3-D2	
16	15	190.01	0.61	0.61	0.60	0.37	0.37	5.0	5.0	9.7	3.56	3.65	5.28	12	1.05	971.50	973.50	972.30	974.30	976.30	977.60	D4-D3	
17	End	91.74	0.00	0.00	0.00	0.00	0.00	5.0	5.0	0.0	9.26	22.65	4.44	24	1.00	947.73	948.65	949.27	949.74	950.00	959.95	EX AL#1202-OUT	
18	17	160.20	0.00	0.00	0.00	0.00	0.00	0.0	0.0	0.0	6.42	53.58	4.74	24	5.61	948.85	957.84	949.74	958.74	959.95	966.20	A1-EX AL#1202	
19	18	72.03	0.00	0.00	0.00	0.00	0.00	0.0	0.0	0.0	3.38	16.30	4.64	15	6.37	958.04	962.63	958.74	963.37	966.20	971.20	A2-A1	
20	19	56.15	0.00	0.00	0.00	0.00	0.00	0.0	0.0	0.0	3.38	6.15	4.80	15	0.91	966.58	967.09	967.24	967.83	971.20	973.94	EX A3-A2	
Project File: 20180111_2020-06-23 Storm Sewers-field conditions.stm																Number of lines: 20				Run Date: 6/23/2020			
NOTES:Intensity = 170.80 / (Inlet time + 18.20) ^ 0.91; Return period =Yrs. 100 ; Pipe travel time suppressed. ; c = cir e = ellip b = box																							

100-YR Hydraulic Profile
EXISTING POND TO EXISTING OUTLET THROUGH PROPOSED POND



Attachment 4
Water Quality Calculations

Date: 7/25/2019

Revised: 8/23/2019; 11/1/2019; 06/29/2020

Proposed Conditions

Drainage Area	Pervious Area (ac)	Impervious Area (ac)	Total Area, DA (ac)	Total Area, DA (sf)	Percent Site Impervious, I	Volumetric Runoff Coefficient, Rv = .05+.009I	Required WQ Treatment Volume, WQv=P(Rv) (in)	Required WQ Treatment Volume, WQv=P(Rv)(DA) (cf)
North	0.78	0.97	1.75	76,330	56.0%	0.554	0.759	4,827.75
Bypass	0.36	0.02	0.38	16,756	5.3%	0.098	0.134	186.90
Sum=							5014.64	

Extended Dry Detention Pond

Elevation-Area-Volume Table		
Elevation	Area (sf)	Volume (cf)
961	10	0
962	1,575	793
963	3,200	3,180
963.5	3,905	5,132
964	4,610	7,085
965	5,590	12,185
966	6,670	18,315
966.2	6,895	19,672

*WQv elevation


Extended Dry Detention Pond	Return Event (years)	Max Water Surface Elevation (ft)	Freeboard (ft)
	2	964.23	4.47
	10	965.13	3.57
	100	966.2	2.5

Perforated Riser


WQv Treatment Depth Above Lowest Orifice, Zwq	2.5 ft
Water Quality Volume	5,132 cf
Water Quality Volume	0.118 ac-ft
Recommended Max Outlet Area per Row, Ao	1.35 sq. in
$A_o = \frac{WQ_v}{(0.013(Z_{wq})^2 + 0.22(Z_{wq}) - 0.10)}$	
Number of columns, nc	1 column
Design circular perforation diameter, Dperf	1 in
Number of rows (4" vertical spacing), nr	5 rows
Perforation 1 Elevation	961.52
Perforation 2 Elevation	961.85
Perforation 3 Elevation	962.18
Perforation 4 Elevation	962.51
Perforation 5 Elevation	962.84

Attachment 5
Supporting Documents

Hydrologic Soil Group—Jackson County, Missouri (DCI Lee's Summit Location Map)



Map Scale: 1:20,000 if printed on A portrait (8.5" x 11") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 15N WGS84

* - Site Location



Natural Resources
Conservation Service

Web Soil Survey
National Cooperative Soil Survey

7/8/2019
Page 1 of 4

Hydrologic Soil Group—Jackson County, Missouri (DCI Lee's Summit)



MAP LEGEND

Area of Interest (AOI)

 Area of Interest (AOI)

Soils

Soil Rating Polygons

 A
 A/D
 B
 B/D
 C
 C/D
 D
 Not rated or not available

Soil Rating Lines

 A
 A/D
 B
 B/D
 C
 C/D
 D
 Not rated or not available

Soil Rating Points

 A
 A/D
 B
 B/D

 C
 C/D
 D
 Not rated or not available

Water Features

 Streams and Canals

Transportation

 Rails
 Interstate Highways
 US Routes
 Major Roads
 Local Roads

Background

 Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:24,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
Web Soil Survey URL:
Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Jackson County, Missouri
Survey Area Data: Version 19, Sep 13, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Jun 11, 2017—Sep 22, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Hydrologic Soil Group

Map unit symbol	Map unit name	Rating	Acres in AOI	Percent of AOI
10024	Greenton-Urban land complex, 5 to 9 percent slopes	D	2.2	97.6%
10128	Sharpsburg-Urban land complex, 2 to 5 percent slopes	D	0.1	2.4%
Totals for Area of Interest			2.2	100.0%

Description

Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The soils in the United States are assigned to four groups (A, B, C, and D) and three dual classes (A/D, B/D, and C/D). The groups are defined as follows:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

If a soil is assigned to a dual hydrologic group (A/D, B/D, or C/D), the first letter is for drained areas and the second is for undrained areas. Only the soils that in their natural condition are in group D are assigned to dual classes.

Rating Options

Aggregation Method: Dominant Condition


Component Percent Cutoff: None Specified

Tie-break Rule: Higher

National Flood Hazard Layer FIRMette



38°55'10.28"N



0 250 500 1,000 1,500 2,000 Feet 1:6,000

USGS-The National Map: Orthoimagery. Data refreshed April, 2019.

Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT

SPECIAL FLOOD HAZARD AREAS		Without Base Flood Elevation (BFE) Zone A, V, A99
		With BFE or Depth Zone AE, AO, AH, VE, AR
		Regulatory Floodway
OTHER AREAS OF FLOOD HAZARD		0.2% Annual Chance Flood Hazard, Areas of 1% annual chance flood with average depth less than one foot or with drainage areas of less than one square mile Zone X
		Future Conditions 1% Annual Chance Flood Hazard Zone X
		Area with Reduced Flood Risk due to Levee. See Notes. Zone X
		Area with Flood Risk due to Levee Zone D
OTHER AREAS		NO SCREEN Area of Minimal Flood Hazard Zone X
		Effective LOMRs
		Area of Undetermined Flood Hazard Zone D
GENERAL STRUCTURES		Channel, Culvert, or Storm Sewer
		Levee, Dike, or Floodwall
OTHER FEATURES		20.2 Cross Sections with 1% Annual Chance
		17.5 Water Surface Elevation
		513 Coastal Transect
		Base Flood Elevation Line (BFE)
		Limit of Study
		Jurisdiction Boundary
		Coastal Transect Baseline
MAP PANELS		Digital Data Available
		No Digital Data Available
		Unmapped



The pin displayed on the map is an approximate point selected by the user and does not represent an authoritative property location.

This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on 7/9/2019 at 8:48:53 AM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.