

Aria Lee's Summit Retaining Walls

Lee's Summit, Jackson County, Missouri

1. MATERIALS

A. BACKFILL SOILS

- a. REINFORCED STRUCTURAL BACKFILL MATERIALS SHALL BE APPROVED BY THE OWNER OR OWNER'S REPRESENTATIVE AND SHALL MEET THE STRENGTH REQUIREMENTS AS DEFINED IN SECTION 5.0. THE REINFORCED BACKFILL MATERIAL SHALL BE:
- MODOT TYPE 1, TYPE 5, OR 1" CLEAN.

- b. FURTHERMORE, REINFORCED BACKFILL AND RETAINED SOIL/FILL MATERIALS SHALL BE FREE OF EXCESS MOISTURE, ROOTS, MUCK, SOD, SNOW, FROZEN LUMPS, ORGANIC MATTER OR OTHER DELETERIOUS MATERIALS. ALL ROCK PARTICLES AND HARD EARTH CLODS SHALL BE LESS THAN THREE INCHES IN THE LONGEST DIMENSION. REINFORCED BACKFILL MATERIALS WHICH DO NOT MEET THIS CRITERION SHALL BE CONSIDERED UNSUITABLE AND SHALL BE REMOVED.

- c. DRAINAGE FILL BEHIND BASKET FACE SHALL CONSIST OF CLEAN CRUSHED STONE OR CRUSHED GRAVEL (1" CLEAN).

- B. GEOGRID REINFORCING SHALL BE SYNTEN GEOTRIDS AS SHOWN OR APPROVED EQUAL

2. TECHNICAL REQUIREMENTS

- A. PRIOR TO CONSTRUCTION OF THE WALLS, THE GRADING CONTRACTOR SHALL CLEAR AND GRUB THE REINFORCED BACKFILL ZONE AREA, REMOVING TOP SOILS, BRUSH, SOD OR OTHER ORGANIC MATERIALS. ANY UNSUITABLE SOILS SHALL BE OVER-EXCAVATED, REPLACED AND COMPACTED WITH REINFORCED BACKFILL MATERIAL TO PROTECT SPECIFICATIONS OR OTHERWISE DIRECTED BY THE OWNER'S GEOTECHNICAL ENGINEER.

- B. THE GEOTECHNICAL ENGINEER SHALL CONFIRM THAT THE SITE HAS BEEN PROPERLY PREPARED AND THE DESIGN PARAMETERS IN SECTION 5 ARE APPROPRIATE PRIOR TO FILL PLACEMENT. A WRITTEN CONFIRMATION SHALL BE PROVIDED TO CROCKETT ENGINEERING PRIOR TO FILL PLACEMENT.

- C. FILL SHALL BE PLACED IN HORIZONTAL LAYERS NOT EXCEEDING 10 INCHES IN UNCOMPACTED THICKNESS FOR HEAVY COMPACTION EQUIPMENT. FOR ZONES WHERE COMPACTION IS ACCOMPLISHED WITH HAND OPERATED EQUIPMENT, FILL SHALL BE PLACED IN HORIZONTAL LAYERS NOT EXCEEDING 6 INCHES IN UNCOMPACTED THICKNESS. ONLY HAND-OPERATED EQUIPMENT SHALL BE ALLOWED WITHIN THREE FEET OF THE BACK FACE WALL.

- D. FILL MATERIALS SHALL BE PLACED FROM THE BACK OF THE FACING UNITS TOWARDS THE ENDS OF THE GEOGRID TO ENSURE FURTHER TENSIONING.

- E. FILL SHALL BE COMPACTED AS SPECIFIED BY PROJECT SPECIFICATIONS OR TO A MINIMUM 95 PERCENT OF THE MAXIMUM DRY DENSITY AS DETERMINED IN ACCORDANCE WITH ASTM D-698.

- F. TESTING METHODS, FREQUENCY, VERIFICATION OF MATERIAL SPECIFICATIONS, AND COMPACTION SHALL BE THE RESPONSIBILITY OF THE OWNER'S GEOTECHNICAL ENGINEER. A COPY OF THE REPORT SHALL BE PROVIDED TO CROCKETT ENGINEERING.

- G. CAP UNITS SHALL BE PERMANENTLY SECURED TO THE BLOCK UNITS USING AN OUTDOOR CONSTRUCTION ADHESIVE.

3. GEOGRID PLACEMENT

- A. GEOGRID SHALL BE PLACED AT THE LOCATIONS AND ELEVATIONS SHOWN ON THE DRAWINGS. REINFORCED FILL ZONE LENGTH IS MEASURED FROM THE BACK FACE OF THE WALL UNITS, EXTENDING TO THE END OF THE GEOGRID.

- B. GEOGRID REINFORCEMENT SHALL BE CONTINUOUS THROUGHOUT THEIR EMBEDMENT LENGTH(S).

- C. PRIOR TO PLACING FILL, THE GEOGRID MATERIALS SHALL BE PLACED IN BETWEEN BLOCK COURSES, THE SLACK REMOVED AND ANCHORED.

- D. CONSTRUCTION EQUIPMENT SHALL NOT BE OPERATED DIRECTLY ON THE GEOGRID. A MINIMUM FILL THICKNESS OF SIX INCHES IS REQUIRED FOR OPERATION OF TRACKED VEHICLES OVER THE GEOGRID. TURNING OF TRACKED VEHICLES SHOULD BE KEPT TO A MINIMUM TO PREVENT TRACKS FROM DISPLACING THE FILL AND/OR THE GEOGRID.

- E. GEOGRID SHALL BE ROLLED OUT WITH THE LONG AXIS OF THE APERTURES (MACHINE DIRECTION) PERPENDICULAR TO THE WALL FACE.

- F. A MINIMUM OF 3 INCHES OF FILL MATERIAL SHALL BE REQUIRED BETWEEN OVERLAPPING LAYERS OF GEOGRID AND FILTER FABRIC, UNLESS OTHERWISE SHOWN.

4. DRAINAGE

- A. AT THE END OF EACH WORK DAY, BACKFILL SURFACE SHALL BE COMPACTED WITH A SMOOTH PLATE COMPACTOR TO MINIMIZE PONDING OF WATER AND SATURATION OF THE BACKFILL.

- B. PERMANENT SURFACE WATER DIVERSION SHALL BE AS REQUIRED AND PROVIDED BY THE OWNER OR OWNER'S REPRESENTATIVE.

5. DESIGN PARAMETERS

- A. DESIGN OF THE REINFORCED SOIL STRUCTURE IS BASED ON THE FOLLOWING PARAMETERS BASED ON SITE EXPOSED ROCK ENTIRE WALL SURFACE:

	EFFECTIVE FRICTION ANGLE	EFFECTIVE COHESION	MOIST UNIT WT
REINFORCED FILL	34	0	125
RETAINED SOILS	23	0	120
FOUNDATION SOILS	23	0	120

MINIMUM BEARING CAPACITY 2,500 PSF

- B. DESIGN METHODOLOGY: NCMa GUIDELINES

C. FACTOR OF SAFETY:

INTERNAL STABILITY: STATIC

MINIMUM FACTOR OF SAFETY (FOS) FOR UNCERTAINTIES = 1.5

MINIMUM FOS FOR GEOGRID PULLOUT = 1.5

MINIMUM FOS FOR CONNECTION = 1.5

MINIMUM FOS FOR FACING STABILITY = 1.5

MINIMUM FOS FOR SLIDING AT LOWEST GEOGRID = 1.5

SOIL - GEOGRID INTERACTION COEFFICIENT = 0.8

PERCENT COVERAGE OF GEOGRID = 100%

D. EXTERNAL STABILITY

MINIMUM FACTOR OF SAFETY FOR OVERTURNING = 1.5

MINIMUM FACTOR OF SAFETY FOR SLIDING = 1.5

E. SURCHARGE LOADING

100 PSF SIDEWALKS/PARKING LOTS

6. SPECIAL PROVISIONS

- A. THE DESIGN PRESENTED HEREIN IS BASED ON SOIL PARAMETERS, FOUNDATION CONDITIONS, GROUNDWATER CONDITIONS, AND LOADINGS STATED IN SECTION 5.

- B. WALL ELEVATION VIEWS AND LOCATIONS AND GEOMETRY OF EXISTING STRUCTURES AND GRADE ABOVE AND BELOW WALLS MUST BE VERIFIED BY THE CONTRACTOR, TO MATCH ELEVATIONS SHOWN IN THE CONTRACT DOCUMENTS, PRIOR TO CONSTRUCTION.

- C. THE ENGINEER OF RECORD IS RESPONSIBLE FOR THE SEGMENTED RETAINING WALL & REINFORCED SOIL IN ITS FINAL CONDITION ONLY. GLOBAL STABILITY, BEARING CAPACITY, AND SETTLEMENT ANALYSIS IS THE RESPONSIBILITY OF THE OWNER'S GEOTECHNICAL ENGINEER. ANY CHANGES TO THE WALL REQUIRED BASED ON THE GEOTECHNICAL ANALYSIS SHOULD BE COORDINATED BY THE GEOTECHNICAL ENGINEER PRIOR TO WALL CONSTRUCTION.

- D. REFER TO BLOCK MANUFACTURE'S WRITTEN INSTALLATION INSTRUCTIONS FOR SEGMENTED RETAINING WALL INSTALLATION, SPECIFICALLY REGARDING CONNECTIONS FROM BLOCK TO BLOCK AND GEOGRID INSTALLATION.

- E. THE SOIL DESIGN PARAMETERS STATED IN SECTION 5.0 SHALL BE VERIFIED BY THE PROJECT GEOTECHNICAL ENGINEER. WRITTEN VERIFICATION OF DESIGN PARAMETERS SHALL BE SUBMITTED TO CROCKETT ENGINEERING AND PRIOR TO COMMENCING WITH CONSTRUCTION.

- F. ANY REVISIONS TO DESIGN PARAMETERS STATED IN SECTION 5.0 OR STRUCTURE GEOMETRY SHALL REQUIRE DESIGN MODIFICATIONS PRIOR TO PROCEEDING WITH CONSTRUCTION.

7. GUARDRAIL SPEC

- A. SHALL BE 42" TALL ABOVE ADJACENT WALKING SURFACE.

- B. SHALL NOT HAVE OPENINGS LARGE ENOUGH TO PASS A 4" SPHERE.

- C. MAIN RAILS SHALL RESIST 50 POUND PER LINEAL FOOT LATERALLY AT THE TOP RAIL OR 200 POUNDS CONCENTRATED LOAD LATERALLY.

- D. INTERMEDIATE RAILS SHALL RESIST A CONCENTRATED LOAD OF 50 POUNDS LATERALLY.

INDEX OF SHEETS

GENERAL DATA	RW1
PARTIAL SITE PLAN	RW2
RETAINING WALL PROFILE	RW3-RW10
DETAILS	RW11

REVISIONS:

No.	Date
PHASE 1--PERMIT	02/04/2021

THIS SHEET HAS BEEN SIGNED, SEALED AND DATED ELECTRONICALLY.



GREGORY L. LINNEMAN - PE
MO LICENSE - 2005001013



CLIENT:
**CENTRAL STATES
CONSTRUCTION**
4215 PHILLIPS FARM RD
COLUMBIA, MISSOURI

ARIA LEE'S SUMMIT APARTMENTS

LEE'S SUMMIT, JACKSON COUNTY, MISSOURI

DRAWING INCLUDES:


GENERAL
STRUCTURAL DATA

DESIGNED: JWV

DRAWN: SEH

PROJECT NO.: 190299

SHEET:
RW1



1 RW2 RETAINING WALL PLAN NOT TO SCALE

Table with 2 columns: No., Date. Row 1: PHASE 1 - PERMIT, 02/04/2021.

Professional Engineer Seal for Gregory L. Linneman, Missouri License #2005001013.


Structural Engineer: CROCKETT ENGINEERING CONSULTANTS, LLC. 1000 W. N. Highway, Columbia, Missouri 65203.

Client: CENTRAL STATES CONSTRUCTION, 4215 PHILLIPS FARM RD, COLUMBIA, MISSOURI.

Project Title: ARIA LEE'S SUMMIT APARTMENTS. Location: LEE'S SUMMIT, JACKSON COUNTY, MISSOURI.

DRAWING INCLUDES: PARTIAL SITE PLAN


Table with 2 columns: Field, Value. Rows: DESIGNED: JWV, DRAWN: SEH, PROJECT NO.: 190299, SHEET: RW2.



1
RW3

RETAINING WALL 1 (AREA 880 SQ. FT.)


SCALE: 1/4" = 1'-0"



2
RW3

RETAINING WALL 1 (AREA 880 SQ. FT.)

SCALE: 1/4" = 1'-0"




3
RW3

RETAINING WALL 1 (AREA 880 SQ. FT.)

SCALE: 1/4" = 1'-0"

REVISIONS:	
No.	Date
PHASE 1 - PERMIT	02/04/2021



STRUCTURAL ENGINEER:

CROCKETT
ENGINEERING CONSULTANTS
1000 W. N. Highway 100
Columbia, Missouri 65203
(314) 447-0292
www.crockettengineering.com
Crockett Engineering Consultants, LLC
Missouri Professional Engineer License No. 2005001013

CLIENT:

**CENTRAL STATES
CONSTRUCTION**
4215 PHILIPS FARM RD
COLUMBIA, MISSOURI

ARIA LEE'S SUMMIT APARTMENTS

LEE'S SUMMIT, JACKSON COUNTY, MISSOURI

DRAWING INCLUDES:


RETAINING WALL
PROFILE

DESIGNED: JWV

DRAWN: SEH

PROJECT NO.: 190299

SHEET: RW3



REVISIONS:

No.	Date
PHASE 1--PERMIT	02/04/2021

THIS SHEET HAS BEEN SIGNED, SEALED AND DATED ELECTRONICALLY

STATE OF MISSOURI

GREGORY L LINNEMAN

REGISTERED PROFESSIONAL ENGINEER

NUMBER PE-2005001013

EXPIRATION DATE 12/31/2024

GREGORY L LINNEMAN - PE
MO LICENSE - 2005001013

STRUCTURAL ENGINEER:

CROCKETT

ENGINEERING CONSULTANTS

1000 W. N. Highway 100
Columbia, Missouri 65203
(314) 447-0292

www.crockettengineering.com

Crockett Engineering Consultants, LLC

Missouri Professional Engineer Authority

2005001013

CLIENT:

CENTRAL STATES CONSTRUCTION

4215 PHILIPS FARM RD

COLUMBIA, MISSOURI

ARIA LEE'S SUMMIT APARTMENTS

LEE'S SUMMIT, JACKSON COUNTY, MISSOURI

DRAWING INCLUDES:

RETAINING WALL PROFILE

DESIGNED:

JWW

DRAWN:


SEH

PROJECT NO.:

190299

SHEET:


RW4



1
RW5

RETAINING WALL 5 (AREA 746 SQ. FT.)

SCALE: 1/4" = 1'-0"



2
RW5


RETAINING WALL 5 (AREA 746 SQ. FT.)

SCALE: 1/4" = 1'-0"

REVISIONS:

No.	Date
PHASE 1--PERMIT	02/04/2021

THIS SHEET HAS BEEN SIGNED, SEALED
AND DATED ELECTRONICALLY.



GREGORY L. LINNEMAN - PE
MO LICENSE - 2005001013

STRUCTURAL ENGINEER:
CROCKETT
ENGINEERING CONSULTANTS
1000 W. N. Highway 100
Columbia, Missouri 65203
(314) 447-0292
www.crockettengineering.com
Crockett Engineering Consultants, LLC
Missouri Professional Engineer License No. 2005001013

CLIENT:
**CENTRAL STATES
CONSTRUCTION**
4215 PHILIPS FARM RD
COLUMBIA, MISSOURI

ARIA LEE'S SUMMIT APARTMENTS
LEE'S SUMMIT, JACKSON COUNTY, MISSOURI

DRAWING INCLUDES:

RETAINING WALL
PROFILE

DESIGNED: JWV


DRAWN: SEH

PROJECT NO.: 190299

SHEET:
RW5

[illegible]

THIS SHEET HAS BEEN SIGNED, SEALED
AND DATED ELECTRONICALLY



GREGORY L. LINNEMAN - PE
MO LICENSE - 2005001013

STRUCTURAL ENGINEER:

CRACKETT

ENGINEERING CONSULTANTS

1000 W. Nifong Blvd., Bldg. 1
Columbia, Missouri 65203
(373) 447-0292

www.crockettengineering.com

Crockett Engineering Consultants, LLC
Missouri Certificate of Authority
20000151801

CLIENT: CENTRAL STATES
CONSTRUCTION
4215 PHILIPS FARM RD
COLUMBIA, MISSOURI

ARIA LEE'S SUMMIT APARTMENTS

LEE'S SUMMIT, JACKSON COUNTY, MISSOURI

DRAWING INCLUDES:


RETAINING WALL
PROFILE

DESIGNED:	JWV
-----------	-----

DRAWN:	SEH
--------	-----

PROJECT NO.:	190299
SHEET:	

RW6



REVISIONS:	
No.	Date
PHASE 1--PERMIT	02/04/2021

THIS SHEET HAS BEEN SIGNED, SEALED AND DATED ELECTRONICALLY.

STATE OF MISSOURI

GREGORY L LINNEMAN
NUMBER PE-2005001013

GREGORY L LINNEMAN - PE
MO LICENSE - 2005001013

STRUCTURAL ENGINEER:

CROCKETT

ENGINEERING & ARCHITECTS
1000 W. N. Highway 100
Columbia, Missouri 65203
(314) 447-0292
www.crockettengineering.com
Crockett Engineering Consultants, LLC
Missouri Professional Seal No. 2005001013

CLIENT:

CENTRAL STATES CONSTRUCTION

4215 PHILIPS FARM RD
COLUMBIA, MISSOURI

ARIA LEE'S SUMMIT APARTMENTS

LEE'S SUMMIT, JACKSON COUNTY, MISSOURI

DRAWING INCLUDES:


RETAINING WALL
PROFILE

DESIGNED: JWV

DRAWN: SEH

PROJECT NO.: 190299

SHEET: RW7



1
RW8

RETAINING WALL 8 (AREA 402 SQ. FT.)

SCALE: 1/4" = 1'-0"

REVISIONS:

No.	Date
PHASE 1--PERMIT	02/04/2021

THIS SHEET HAS BEEN SIGNED, SEALED
AND DATED ELECTRONICALLY



GREGORY L. LINNEMAN - PE
MO LICENSE - 2005001013

STRUCTURAL ENGINEER:
CROCKETT
ENGINEERING CONSULTANTS
1000 W. N. Highway 100
Columbia, Missouri 65203
(314) 447-0292
www.crockettengineering.com
Crockett Engineering Consultants, LLC
Missouri Professional Authority
200001013.01

CLIENT:
**CENTRAL STATES
CONSTRUCTION**
4215 PHILLIPS FARM RD
COLUMBIA, MISSOURI

ARIA LEE'S SUMMIT APARTMENTS
LEE'S SUMMIT, JACKSON COUNTY, MISSOURI

DRAWING INCLUDES:


RETAINING WALL
PROFILE

DESIGNED: JWV

DRAWN: SEH

PROJECT NO.: 190299


SHEET:
RW8



1
RW9

RETAINING WALL 9 (AREA 1,541 SQ. FT.)

SCALE: 1/4" = 1'-0"




2
RW9

RETAINING WALL 9 (AREA 1,541 SQ. FT.)

SCALE: 1/4" = 1'-0"

REVISIONS:	
No.	Date
PHASE 1-PERMIT	02/04/2021




STRUCTURAL ENGINEER:
CROCKETT
ENGINEERING
1000 W. N. Highway
Columbia, Missouri 65203
(314) 447-0292
www.crockettengineering.com
Crockett Engineering Consultants, LLC
Missouri Engineers 01

CLIENT:
**CENTRAL STATES
CONSTRUCTION**
4215 PHILIPS FARM RD
COLUMBIA, MISSOURI

ARIA LEE'S SUMMIT APARTMENTS

LEE'S SUMMIT, JACKSON COUNTY, MISSOURI

DRAWING INCLUDES:	
RETAINING WALL PROFILE	
DESIGNED:	JWW
DRAWN:	SEH
PROJECT NO.:	190299
SHEET:	RW9



REVISIONS:

No.	Date
PHASE 1 - PERMIT	02/04/2021

THIS SHEET HAS BEEN SIGNED, SEALED AND DATED ELECTRONICALLY

STATE OF MISSOURI

GREGORY L LINNEMAN

PE-2005001013

1000 W. N. Highway 100
Columbia, Missouri 65203
(314) 447-0292

GREGORY L LINNEMAN - PE
MO LICENSE - 2005001013

STRUCTURAL ENGINEER:

CROCKETT

ENGINEERING CONSULTANTS

1000 W. N. Highway 100
Columbia, Missouri 65203
(314) 447-0292

www.crockettengineering.com
Crockett Engineering Consultants, LLC
Missouri Engineers & Architects
2005001013

CLIENT:

CENTRAL STATES CONSTRUCTION

4215 PHILIPS FARM RD
COLUMBIA, MISSOURI

ARIA LEE'S SUMMIT APARTMENTS

LEE'S SUMMIT, JACKSON COUNTY, MISSOURI

DRAWING INCLUDES:

RETAINING WALL PROFILE

DESIGNED:

JWW

DRAWN:

SEH

PROJECT NO.:

190299

SHEET:

RW10

RW11