GENERAL NOTES	
1. BLACK TRIM RINGS TO BE FACTORY PAINTED SHERWIN WILLIAMS CARBIDE BLACK POLANE T (RAL# F63B12), AND ARE NOTED BY A -b IN THE FIXTURE TAG.	

2. ALL LAMPS SHALL BE SYLVANIA, PHILIPS, SATCO, OR TCP, UNLESS NOTED OTHERWISE AND PROVIDED BY G.C.

3. ALL INTERIOR AND EXTERIOR SURFACE AND RECESSED LIGHT FIXTURES SHALL BE LABELED "U.L. LISTED."

4. BATTERY PACKS PROVIDED FOR ALL EXIT SIGNS AND EMERGENCY EGRESS FIXTURES SHALL BE RATED FOR MINIMUM 90 MINUTE OPERATION AT FULL OUTPUT.

5. REFER TO ARCHITECTURAL REFLECTED CEILING PLANS AND/OR THE MISCELLANEOUS LIGHTING DETAIL SHEETS FOR EXACT LOCATIONS OF LIGHT FIXTURES.

6. FOR ALL LIGHTOLIER/DAYBRITE/GARDCO/PHILIPS/CHLORIDE LIGHTING FIXTURES, CONTACT JULIE BLANKENHEIM, 630-488-7403.

	TVDC	MANUFACTURES (MORE) "				KTURE SCHEDULE	01141-
	TYPE	MANUFACTURER / MODEL #	LAMP	VOLTAGE	WATTS VA	DESCRIPTION	QUANTI
1		DAYBRITE 2EVG54LH8304DUNVDIM	INTEGRAL LED	UNIVERSAL	55	2'X4', RECESSED 3000K LED TROFFER, PRISMATIC LENS AND ELECTRONIC BALLAST, @ B.O.H.	29
1-E		DAYBRITE 2EVG54LH8304DUNVDIM-EMLED	INTEGRAL LED	UNIVERSAL	55	2'X4', RECESSED 3000K LED TROFFER, PRISMATIC LENS, ELECTRONIC BALLAST AND EMERGENCY BATTERY PACK FOR TWO LAMPS RATED FOR 1100 TO 1400 LUMENS, @ B.O.H.	11
3	<b>&gt;</b>	DAYBRITE T232-UNV-1/2-EB-IOP232-LWN-FKR-126-CG-4 INSTANT START BALLAST	(2) 14WTLED PHILIPS INSTANT FIT- 3000K	UNIVERSAL	28	4'-0", STANDARD STRIP WITH 2-LAMP T8, AND ELECTRONIC BALLAST, WITH WIRE GUARD AND CHAIN HANGER KIT	2
3-E	<b>—</b>	DAYBRITE T232-120-1/2-EB10R-E5-FKR-126-CG-4 INSTANT START BALLAST & EMERGENCY BATTERY PACK	(2) 14WTLED PHILIPS INSTANT FIT- 3000K	UNIVERSAL	28	4'-0", STANDARD STRIP WITH 2-LAMP T8, AND ELECTRONIC BALLAST AND EMERGENCY BATTERY PACK, WITH WIRE GUARD AND CHAIN HANGER KIT	2
ļ		DAYBRITE 2EVG30L830-2-D-UNV-DIM	(2) 14WTLED PHILIPS INSTANT FIT- 3000K	UNIVERSAL	28	2'X2', RECESSED DIMMABLE 3000K LED @ B.O.H.	1
S1		NOVA FLEX NF-PRO-0-120-24V-2700K	WARM WHITE LED, LAMP INTEGRAL	12V	PER DRIVER	DIMMING COMPATIBILITY TO BE VERIFIED BY PROJECT, 0-10V AND MLV DIMMING DRIVERS ARE AVAILABLE. REFER TO RCP & MISC. LIGHTING DETAIL SHEETS FOR QUANTITY/LOCATION. LED TAPE LIGHT. SURFACE MOUNTED w/ LOW PROFILE CHANNEL (CONCEALED). CLEAR PANEL USEL FOR TASK	45 D
33		ONMILIGHT FIXTURE: GEN-27-SHO-CC LEADER:-	2700K LED	24V	5.3 / FT	LIGHTING AND AND SOFT PANEL USED FOR MILLWORK & SUSPENDED BARREL LIGHTING  DIMMING COMPATIBILITY TO BE VERIFIED BY PROJECT, 0-10V AND MLV DIMMING DRIVERS ARE  AVAILABLE.  REFER TO RCP & MISC. LIGHTING DETAIL SHEETS FOR QUANTITY/LOCATION.	6
2-b	0	DRIVERS AS REQUIRED PER PLAN LIGHTOLIER FRAME: 4RN ENGINE: C4L10827MZ10U TRIM: C4RDLCL - PAINT BLACK	2700K LED	120V	11	STRIP LIGHT AT MILLWORK WINE DISPLAYS  4" LED RECESSED DOWNLIGHT - DIMMABLE WITH 0-10V DIMMER  (INTERNAL LENS STANDARD IS APPROVED FOR OVER FOOD SERVICE)  BLACK FLANGE. MEDIUM SPREAD BEAM.  1000 LUMENS - USE FOR CEILING HEIGHTS BETWEEN 9' AND 12'	76
3-b	0	LIGHTOLIER FRAME: 3RN ENGINE: C3RA10927NSZ10U TRIM: C3RAPBKBK - PAINT BLACK	2700K LED	120V	13	3" RECESSED ADJUSTABLE PINHOLE APERTURE DOWNLIGHT - DIMMABLE WITH 0-10V DIMMER PINHOLE SPOT LIGHT. BLACK FLANGE 1000 LUMENS - USED TO LIGHT TABLES	32
5		LIGHTOLIER FRAME: 3RN ENGINE: C3RA10927FLZ10U TRIM: C3RACL	2700K LED	120V	13	3" RECESSED ADJUSTABLE APERTURE 1,000 LUMEN LED ACCENT LIGHT. DIMMABLE WITH 0-10V DIMMER WHITE FLANGE WIDE FLOOD-USED FOR CEILING HEIGHTS 10'-12'	11
5-b	0	LIGHTOLIER FRAME: 3RN ENGINE: C3RA10927FLZ10U TRIM: C3RACL - PAINTED BLACK	2700K LED	120V	13	3" RECESSED ADJUSTABLE APERTURE 1,000 LUMEN LED ACCENT LIGHT. DIMMABLE WITH 0-10V DIMMER BLACK FLANGE WIDE FLOOD-USED FOR CEILING HEIGHTS 10'-12'	17
6		LIGHTOLIER LYTECASTER FRAME-IN-KIT: L3NZ10U LIGHT ENGINE: L308927NF ROUND TRIM: L3RAPW	2700K LED	120V		RECESSED ADJUSTABLE LED DOWNLIGHT WITH PINHOLE APERTURE. DIMMABLE WITH 0-10V DIMMER WHITE FLANGE USED FOR CEILING HEIGHTS BETWEEN 8'-10'	6
6-b	0	LIGHTOLIER LYTECASTER FRAME-IN-KIT: L3NZ10U LIGHT ENGINE: L308927NF ROUND TRIM: L3RAPW - PAINTED BLACK	2700K LED	120V		RECESSED ADJUSTABLE LED DOWNLIGHT WITH PINHOLE APERTURE. DIMMABLE WITH 0-10V DIMMER BLACK FLANGE USED FOR CEILING HEIGHTS BETWEEN 8'-10'	12
		LIGHTOLIER FRAME IN KIT: 4RN LIGHT ENGINE: P4RDL20827CLZ10U LUCIFER LIGHTING COMPANY	2700K LED 4.3W AC LED	120V 120V/12V	4.3	4" ROUND DOWNLIGHT WHITE FLANGE USED IN RESTROOMS SEMI-RECESSED PUK LIGHT WITH BLACK TRIM RING. PROVIDE WITH REMOTE POWER SUPPLY.	18
-b		PUKLED LPK SEMI-RECESSED LED LPK-1-80L-02A-27-B  JUNO - TRAC MASTER AVANT GARDE	2700K 80 CRI	120V	15	REFER TO RCP & MISC. LIGHTING DETAIL SHEETS FOR QUANTITY/LOCATION AND INSTALLATION TYPE. USED FOR MILLWORK LIGHTING SURFACE MOUNTED MONOPOINT WITH CANOPY AND ELV TRANSFORMER	34
-		CYLINDRA T254L 27K 80CRI PDIM SP B	15W LED SP			- = MONOPOINT W/ NO STEM a = MONOPOINT W/ 12" STEM b = MONOPOINT W/ 18" STEM c = MONOPOINT W/ 24" STEM	
						* NOTE: STEMS CAN BE COMBINED FOR ADDITIONAL LENGTHS AND ARE NOTED BY TWO LETTERS SURFACE MOUNTED MONOPOINT WITH CANOPY AND ELV TRANSFORMER	
						- = MONOPOINT W/ NO STEM a = MONOPOINT W/ 12" STEM b = MONOPOINT W/ 18" STEM c = MONOPOINT W/ 24" STEM	
						* NOTE: STEMS CAN BE COMBINED FOR ADDITIONAL LENGTHS AND ARE NOTED BY TWO LETTERS	
	$\nabla$	LIGHTOLIER MODEL: LT08RNF827BKVA/6074BK	2700K LED	120V	9	LED TRACK HEAD, 2700K IN BLACK NARROW FLOOD DISTRIBUTION, ELV DIMMING BLACK FINISH. 18" STEM.	43
36	TR4	LIGHTOLIER 6006NBK 6' TRACK 6048NBK LIVE END				LIGHTOLIER BASIC LYTESPAN SINGLE CIRCUIT TRACK BLACK FINISH REFER TO PLAN FOR TRACK HEADS	7
18	TR4	LIGHTOLIER 6008NBK 8' TRACK 6048NBK LIVE END				LIGHTOLIER BASIC LYTESPAN SINGLE CIRCUIT TRACK BLACK FINISH REFER TO PLAN FOR TRACK HEADS	4

Т	ГҮРЕ	MANUFACTURER / MODEL #	LAMP	VOLTAGE	WATTS	VA	DESCRIPTION	QUANTITY
CF		FANIMATION SPITFIRE (DAMP RATED) MODEL: MA6721BK BLADES: B6720		120V			MOTOR ASSEMBLY: MATTE GREIGE FAN ASSEMBLY BLADES: 60" SWEEP SPITFIRE NATURAL WOOD BLADE SET W/ FAN CONTROL BY LUTRON MODEL #DVFSQ-F-BL	4
RH-2		SOLAIRA ICR SERIES MODEL: SICR4024OB-SMART34-DV-SM-WSD		208V	3,000		ELECTRIC HEATER AT PATIO, SOLAIRA SMART 16A DUAL VOLTAGE VARIABLE CONTROL, 34.5"L x 10"W x 4.33"D DUAL VOLTAGE DIGITAL CONTROLLER: SMART34-DV WALL SWITCH FOR SMART34-DV: SM-WSD BLACK FINISH MOUNT HEATER AT 45 DEGREE ANGLE W/ STANDARD FACTORY BRACKET	8
X2-b	0	Y079GKHWVB MODEL#: SJ1DL6D-18W30		110V	18W		RECESSED LED DOWNLIGHT. UL WET LOCATION LISTED. BLACK FLANGE USED FOR EXTERIOR CANOPY DOWNLIGHTING PROVIDED BY CANOPY MANUFACTURER	2
X3	$\nabla$	RAB LIGHTING LFP16B	(1) 7 WATT TCP LED7P1627KFL	120V	60		LAMP BEAM ANGLE TO BE 30 DEGREE SPREAD BLACK FINISH SURFACE LIGHTING USED AT REGULAR HARD LID PATIO CANOPIES	20
X5-E M	٠	GARDCO 121-16L-700-WW-G4-3-EBPC-120-BK	LED	120V			SURFACE MOUNTED 2 LAMP LED WALL PACK WITH MEDIUM THROW CUT OFF OPTICS AND EMERGENCY BATTERY OPTION. BLACK FINISH	9
XSC1	5	DECORATIVE SCONCE MFR: WAC LIGHTING STYLE: MRUBIX DOUBLE WALL MOUNT MODEL: WS-W2505-BK	3000K LED	120V	30W		FINISH: BLACK SIZE: 5" W X 5" H X 6-1/2"D LOCATION: EXTERIOR WALL REFER TO ELEVATIONS FOR MOUNTING HEIGHT	4

TY	/PE	MANUFACTURER / MODEL #	LAMP	VOLTAGE	WATTS VA	DESCRIPTION	QUANTIT
EM1		EXITRONIX LED-90	LED	120V	12	EMERGENCY LIGHTING FOR FRONT OF HOUSE. WHITE HOUSING	2
M1-b	4 4	EXITRONIX LED-90BL	LED	120V	12	EMERGENCY LIGHTING FOR FRONT OF HOUSE. BLACK HOUSING	21
M5	4 4	PHILIPS - CHLORIDE FUSION III F3-N-B-31KIC	T-5 WEDGE BASE TUNGSTEN LAMP	120V	5.4	RECESSED DECORATIVE ARCHITECTURAL EMERGENCY LIGHT, UL DAMP LOCATION LISTED BLACK FINISH	1
X1	$\otimes$	PHILIPS - CHLORIDE CALIBER SERIES CN6RWW21C	LED INCLUDED WITH UNIT	120V	3.8	SINGLE-SIDED, WALL OR CEILING MOUNTED, EDGE-LIT, LED EXIT SIGN TO BE USED IN FRONT OF HOUSE. WHITE FINISH	1
X1-b	$\otimes$	PHILIPS - CHLORIDE CALIBER SERIES CN6RWB21C	LED INCLUDED WITH UNIT	120V	3.8	WALL OR CEILING MOUNTED, EDGE-LIT, LED EXIT SIGN TO BE USED IN FRONT OF HOUSE BLACK FINISH	13
X2	$\otimes$	PHILIPS CHLORIDE VE SERIES VERWEM	LED INCLUDED WITH UNIT	120V	3.62	LED EXIT SIGN WITH THERMOPLASTIC HOUSING AND 2 STENCIL FACES TO BE USED IN BACK OF HOUSE WHITE FINISH	5

		DECORAT	<b>IVE LIC</b>	SHT F	IXT	URE SCHEDULE	
TYPE	MANUFACTURER / MODEL #	LAMP	VOLTAGE	WATTS	VA	DESCRIPTION	QUANTITY
P1	DECORATIVE PENDANT MFR: KUZCO LIGHTING STYLE: DECO MODEL: PD61412-CL/BK	3000K INTEGRAL LED DIMMABLE	120V	29W		FINISH: BLACK/CLEAR SIZE: 17.75" W X 14" H LOCATION: BAR MOUNT AT 7'-6" A.F.F.	5
P2	DECORATIVE PENDANT  MRF: TROY LIGHTING  STYLE: ELLIOT  MODEL: F6223	(8) SATCO S2954T 4W DIMMABLE LED / G9 WEDGEBASE XENON / 2700K	120V	32W		FINISH: TEXTURED BLACK SIZE: 44" DIA x 25" H LOCATION: DINING, MOUNT AT 8'-0" A.F.F.	5
· · · · · · · · · · · · · · · · · · ·	DECORATIVE PENDANT MRF: TROY LIGHTING STYLE: RAEF MODEL: F6313	(1) MAXLITE T8 JA8 4W DIMMABLE LED / 2700K	120V	4W		FINISH: TEXTURED BRONZE BRUSHED BRASS SIZE: 7"W x 15"H LOCATION: DINING ROOM PULLMAN BOOTHS, REFER TO INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS	6
4	DECORATIVE PENDANT MRF: TROY LIGHTING STYLE: BERLIN MODEL: F5852	(1) 14W LED / BULB INCLUDED	120V	14W		FINISH: GUN METAL SIZE: 15.5"W x 13.75"H LOCATION: DINING ROOM U-BOOTHS, REFER TO INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS	4
<b>1</b> 5	DECORATIVE PENDANT MRF: TROY LIGHTING STYLE: DISTRICT MODEL: F5571	(1) SATCO S9582 6.5W DIMMABLE LED / T9 (8") / E26 / CLEAR / 2700K	120V	6.5W		FINISH: SATIN BLACK/TOPAZ GLASS SIZE: 8"W x 15.75"H LOCATION: PRIVATE DINING ROOM, REFER TO ENLARGED PLAN FOR MOUNTING HEIGHTS	10
сı Ђ	WALL SCONCE MFR: ONE FOURTY THREE STYLE: WALLACE LAMP MODEL:	(1) SATCO S9564 6.5W DIMMABLE LED E25 / CLEAR /2700K	120V	6.5W		FINISH: BLACK LAMP W/ BRASS SHADE/BRASS HARDWARE SIZE: 5" PLATE X 17" H X 12" D LOCATION: RETAIL	7
SC2	WALL SCONCE MFR: MITZI STYLE: BELINDA MODEL: H415101A-OB	(1) SATCO S9564 6.5W DIMMABLE LED E26 / CLEAR / 2700K	120V	6.5W		FINISH: OLD BRONZE SIZE: 6" W X 14" W X 7" H LOCATION: BATHROOMS	9
BL1	TABLE LAMP MFR: PAGE ONE LIGHTING STYLE: CENTURY LED TABLE LAMP MODEL:	3000K INTEGRAL LED DIMMABLE	120V	7W		FINISH: SATIN FARK GRAY WITH SMOKE GLASS SIZE: 5.9" DIA X 17.6" H LOCATION: HOST STAND	1

830 North Blvd. Oak Park, Illinois 60301


708-445-8400 ariainc.com

40 NW CHIPMAN OAD, LEE'S SUMMIT, IO 64086


COOPER'S HIAWK

FIELD VERIFICATION
Contractor shall verify all figured dimensions and conditions at the job site and notify Aria Group Architects, Inc. of any dimensional errors, omissions or discrepancies before beginning or fabricating any work. Do not scale these drawings.

COPYRIGHT
Aria Group Architects, Inc. shall retain all common law, statutory and other reserved rights. These drawings and related documents shall not be duplicated, disclosed or otherwise



without written consent of Aria Group Architects, Inc.



LIGHT FIXTURE
SCHEDULE

ob No.
204530 Dra

Date
T.S. 08/19/2021

eet No.

Δ23