Rev 7.0.2 Release (06/26/2018)

## ATC TOWER INSPECTION FORM



Photos:

Photos: Photos:

Photos:

Photos:

Photos:

f any comments exceed one row

please expand the row height so that

all of the text is visible. To expand

rows automatically, click the Select All button. then click AutoFit Row

Height in the Cells/Format box.

ge 1

ANSI-TIA-222 Complia	nt	CORPORATION		Pa
		SECTION A - SITE INFORMATION		
ATC Site Number	: 306042	ATC Site Name, Stat	e : Woods Ch	apel MO
Site Address	: 1204 NE Woods Chapel Road	Number of Compour	nds :	•
City/State	: Lees Summit, MO	Date of Inspection	: 3/21/19	
Contractor Name	: FDH Infrastructure Services	Tower Elevation Pho	to : 306042 (88	8).JPG
Inspection Completed By	: Mike Sloat/Kyle Edwards	SC Tagged Out?	:	
	:	SECTION B - TOWER INFORMATION		
Structure Type	: Monopole	# of Tower Legs	: Monopole	
Tower Height	: 152.0	Safety Climb Installe	d? : Yes	Location: Monopole
Overall Structure Height	: 153.3	Safety Climb Manuf.	: DBI Sala	Climbing Facil. Step Bolts
Tower Manufacturer	: Not Posted	AM Detuning ?	: No	
	SECTI	ON C - SITE INFORMATION CATEGORIES		
SECTION B - Tower Information SECTION H - Grounding Comments   SECTION C - Tower Information Summary Comments SECTION I - Guy Anchors & Wires Comments   SECTION D - Summary of Deficiencies SECTION J - AM Detuning Comments   SECTION E - Tower Foundation Comments SECTION K - Compliance   SECTION F - Tower Structure Comments SECTION K - Compliance				
	SEC	TION D- SUMMARY OF OBSERVATIONS		
Instructions: List Comme	nts in Sections E through J as ap	pplicable. Section D Summary will automatically po	oulate.	
1.			Photos:	
2.			Photos:	
3.			Photos:	
4.			Photos:	
5.			Photos:	
0.			Photos:	
8			Photos:	
9			Photos:	
10.			Photos:	
11.			Photos:	
12.			Photos:	
13.			Photos:	
14.			Photos:	

# **SECTION E - TOWER FOUNDATION**

### Instructions

12. 13. 14. 15.

16.

17.

18.

19.

20.

Tower base should be visually inspected for spalling and cracking of the concrete. The soil surrounding the tower base foundation should be inspected for evidence of settlement. Any such settlement or movement should be noted.

Base drains (if present) should be clear of any obstructions. Penetrate drain with object to ensure drains functioning.

Base insulators (if present) - The porcelain surface should be wiped clean with a soft cloth to remove any salt deposits or other foreign substance. A check should be made for any evidence of deterioration or cracks in the porcelain surface.

All discrepancies must be marked with masking tape and magic marker.

All discrepancies <u>must</u> be noted and photographed and numbered.

Is tower center pin in place?

Is tower center pin free of corrosion?

Are all base plate bolts, nuts, and washers present?

Is the tower foundation in good condition? (No cracking, spalling, or settling)

Is the concrete tower base free from standing water?

Are base drains clear and free flowing? (Drains required only under tubular legs.)

Is porcelain surface of base insulators in good condition? (No deterioration or cracking)

Is the soil around the foundation in good condition? (No settling or movement)

## **Comments:**

1.	Photos:
2.	Photos:
3.	Photos:
4.	Photos:
5.	Photos:
6.	Photos:
7.	Photos:
8.	Photos:

9.	Photos:
10.	Photos:

## **SECTION F - TOWER STRUCTURE**

Page 2

### Instructions

**Corrosion** - If corrosion is observed, the source should be determined and noted.

Damaged or faulty members - A visual inspection must be made of the entire tower structure to determine if any of the members have been deformed or damaged. Any bowed, bent or damaged member/bolt should be noted as to part number, size, location on tower, nature and magnitude of deformation or damage. Do not remove any tower member for replacement unless authorized by ATC Engineering Dept - Signed/Sealed Construction Drawings are required if a All discrepancies must be marked with masking tape and magic marker. All discrepancies must be noted and photographed before and after repair.

Is the tower free of rust? (If "No", be specific in the comments below.) Are all structural members straight and not damaged, bent, and/or missing? Is the tower finish in good condition? (No obvious signs of cracking)

#### Comments:

1.	Photos:
2.	Photos:
3.	Photos:
4.	Photos:
5.	Photos:
6.	Photos:
7.	Photos:
8.	Photos:
9.	Photos:
10.	Photos:
11.	Photos:
12.	Photos:
13.	Photos:
14.	Photos:
15.	Photos:
16.	Photos:
17.	Photos:
18.	Photos:
19.	Photos:
20.	Photos:
21.	Photos:
22.	Photos:
23.	Photos:
24.	Photos:
25.	Photos:

## **SECTION G - SAFETY**

### **Instructions**

Safety is paramount- Report anything that makes it unsafe to operate or maintain this tower to ATC immediately.

All discrepancies must be marked with masking tape and magic marker. All discrepancies must be noted and photographed before and after repair.

Is there a safety climb system?

Are all components of the safety climb system free of rust?

Is the cable free from kinks, fraying, broken wires or strands or other damage?

Is the climbing path free from obstructions allowing a clear path for the cable?

Is the cable secured by properly spaced cable guides?

Is the total system properly installed including the top connection? If No, correct and note.

Is the FCC and ATC signage apparent and placed properly.

#### **Comments:**

1.	Photos:
2.	Photos:
3.	Photos:
4.	Photos:
5.	Photos:
6.	Photos:
7.	Photos:
8.	Photos:
9.	Photos:
10.	Photos:

### **SECTION H - GROUNDING**

#### **Instructions**

**Connections** - The connections above grade should be visually checked for loose fittings, ensure wires are snug in mechanical connections or well bonded with exothermic connections at the base of the tower.

Ground Wires - The ground wires at the base should be cad welded to each leg.

Take a photo of the grounding at the base and at each anchor.

All discrepancies must be marked with masking tape and magic marker. All discrepancies must be noted and photographed before and after repair.

Is the tower base properly grounded?

Are the guy cables and/or guy anchor heads properly grounded?

Are ground wires and connections in satisfactory condition?

Is the lightning rod mounted such that it is secured to the structure and not at risk of falling?

Comments:	
1.	Photos:
2.	Photos:
3.	Photos:
4.	Photos:
5.	Photos:
6.	Photos:
7.	Photos:
8.	Photos:
9.	Photos:
10.	Photos:

## **SECTION I - GUY ANCHORS & WIRES**

Copyright © ATC IP, LLC - All Rights Reserved

Page 3

<u>Instructions</u> All discrepancies <u>must</u> be marked with masking tape and magic marker and must be noted and photographed.

Are the guy cables & paths clear of brush, vegetation, fencing or any other obstruction?

Are the anchor heads and rods free from any bends and/or fractures?

Are the anchor heads and turnbuckle hardware free from soil build-up?

Are exposed guy anchor foundations free from cracking, weathering?

Do the turnbuckles have room for adjusting tensions? (Not fully extended or contracted?)

Are the anchor heads free of corrosion? Is guy anchor rod laterally aligned?

Are guy wires free of broken strands or insulators?

Are the guy dampers secured and in good condition?

Are all shackles, clevises, thimbles, cotter pins, and Crosby clamps properly installed?

Are the dead-end grips in good condition?

Are the dead-end grip end-sleeves (ice-clips) installed?

Are guy wires and guy hardware free of corrosion?

Is each turnbuckle safety wire properly installed and secure? If not, make corrections.

Are guy wire connections in satisfactory condition?

Are guy attachment points to tower in good condition?

#### Note - If anchor shafts show signs of heavy corrosion at any point, stop digging immediately and complete the remainder of the inspection.

Comments:

1.	Photos:
2.	Photos:
3.	Photos:
4.	Photos:
5.	Photos:
6.	Photos:
7.	Photos:
8.	Photos:
9.	Photos:
10.	Photos:
11.	Photos:
12.	Photos:
13.	Photos:
14.	Photos:
15.	Photos:

### **SECTION J- AM DETUNING**

#### **Instructions**

All discrepancies <u>must</u> be marked with masking tape and magic marker and must be noted and photographed.

Note: If the tower has a base insulator (decommissioned AM hot tower) the box next to the tower with a single wire feed is NOT an AM detuning device.

Is there an AM Detuning system on the tower?

Are the AM Detuning skirt wires securely attached to the tower?

Are the AM Detuning wires in good condition? (Broken, sharp bends, etc)

Is the AM Detuning box securely attached to the tower or other mounting system?

Is the AM Detuning box in good condition? (Sealed, loose or missing hardware, etc)

Is the exterior of the AM Detuning box free of rust and corrosion?

Is the AM Detuning system properly grounded?

### Comments:

5.	Photos:	
4.	Photos:	
3.	Photos:	
2.	Photos:	
1.	Photos:	

### **SECTION K - COMPLIANCE**

#### By signing this report:

- I understand that this information and form are the sole property of American Tower Corporation (ATC) and may not be copied or shared without written permission from ATC.

- I certify that any conditions or items omitted in this report were observed to be in acceptable condition per the criteria specifed in the ATC Standard of Care and my own professional experience and judgement.

- I certify this report to be accurate and complete to the best of my knowledge and belief.

Name

Date :

Company :

