


**LEGEND:**

- A/E - ACCESS EASEMENT
- BC - BACK OF CURB
- B/B - BACK TO BACK
- BM - BENCHMARK
- BL or B.L. - BUILDING LINE
- CO - CLEANOUT
- TJB - TELEPHONE JUNCTION BOX
- C&G - CURB AND GUTTER
- D/E - DRAINAGE EASEMENT
- E/E - ELECTRICAL EASEMENT
- EL - ELEVATION
- FL - FLOW LINE
- G/E - GAS LINE EASEMENT
- HDPE - HIGH-DENSITY POLYETHYLENE
- L/E - LANDSCAPE EASEMENT
- MSFE - MINIMUM SERVICEABLE FLOOR ELEVATION
- PVC - POLYVINYL CHLORIDE
- P/L - PROPERTY LINE
- PUB/E - PUBLIC EASEMENT
- RCP - REINFORCED CONCRETE PIPE
- ROW or RW - RIGHT-OF-WAY
- S/E - SANITARY SEWER EASEMENT
- SL - SERVICE LINE
- SW - SIDEWALK
- TE - TOP ELEVATION
- U/E - UTILITY EASEMENT
- WSE - WATER SURFACE ELEVATION
- W/E - WATERLINE EASEMENT

- ASPHALT PAVEMENT - EXISTING
- ASPHALT PAVEMENT - PROPOSED
- CONCRETE PAVEMENT - EXISTING
- CONCRETE SIDEWALK - EXISTING
- CONCRETE SIDEWALK - PROPOSED
- CURB & GUTTER
- CURB & GUTTER - EXISTING
- TREELINE
- EXISTING LOT AND R/W LINES
- EXISTING PLAT LINES
- P/L PROPERTY LINES
- ROW RIGHT-OF-WAY
- SANITARY SEWER MAIN
- SANITARY SEWER MAIN - EXIST.
- STORM SEWER
- STORM SEWER - EXISTING
- CABLE TV - EXISTING
- FIBER OPTIC CABLE - EXISTING
- TELEPHONE LINE - EXIST.
- ELECTRIC LINE - EXISTING
- OVERHEAD POWER LINE - EXIST.
- UNDERGROUND ELECTRIC - EX.
- GAS LINE - EXISTING
- WATERLINE - EXISTING
- LIGHT - EXISTING
- EXISTING MANHOLE
- CLEANOUT
- EXISTING SANITARY MANHOLE
- PROPOSED SANITARY MANHOLE
- EXISTING AREA INLET
- EXISTING CURB INLET
- EXISTING GRATE INLET
- EXISTING JUNCTION BOX
- EXISTING STORM MANHOLE



**UTILITY CONTACTS:**

**MISSOURI DEPARTMENT OF TRANSPORTATION (MODOT)**  
Steve Holloway  
600 NE Colbern Road  
Lee's Summit, MO 64086  
(816) 607-2186

**MISSOURI GAS ENERGY (MGE)**  
Brent Jones  
3025 SE Clover Drive  
Lee's Summit, MO 64082  
(816) 399-9633  
brent.jones@spireenergy.com

**KANSAS CITY POWER & LIGHT COMPANY (KCP&L)**  
Ron Dejamette  
1300 SE Hamblin Road  
Lee's Summit, MO 64081  
Office: (816) 347-4316  
Cell: (816) 810-5234  
ron.dejamette@kcpcl.com

**CITY OF LEES SUMMIT PUBLIC WORKS**  
Dena Mezger  
220 SE Green Street  
Lee's Summit, MO 64063  
(816) 969-1800

**AT&T**  
Mark Manion or Marty Loper  
500 E. 8th Street, Room 370  
Kansas City, MO 64106  
(816) 275-2341 or (816) 275-1550

**COMCAST CABLE**  
John Meadows  
4700 Little Blue Parkway  
Independence, MO 64057  
(816) 795-2257

**CITY OF LEE'S SUMMIT WATER UTILITIES**  
Mark Schaffer  
1200 SE Hamblin Road  
Lee's Summit, MO 64081  
(816) 969-1900

# STREET, STORMWATER, AND MASTER DRAINAGE PLAN

## FOR

# CORNERSTONE AT BAILEY FARMS, FIRST PLAT

## IN THE CITY OF LEE'S SUMMIT

## JACKSON COUNTY, MISSOURI

**GENERAL NOTES:**

1. ALL CONSTRUCTION TO FOLLOW THE CITY OF LEE'S SUMMIT DESIGN AND CONSTRUCTION MANUAL AS ADOPTED BY ORDINANCE 5813.
2. ALL WORKMANSHIP AND MATERIALS SHALL BE SUBJECT TO THE INSPECTION AND APPROVAL OF THE ENGINEERING DEPARTMENT OF THE CITY OF LEE'S SUMMIT, MISSOURI.
3. LINEAL FOOT MEASUREMENTS SHOWN ON THE PLANS ARE HORIZONTAL MEASUREMENTS, NOT SLOPE MEASUREMENTS. ALL PAYMENTS SHALL BE MADE ON HORIZONTAL MEASUREMENTS.
4. NO GEOLOGICAL INVESTIGATION HAS BEEN PERFORMED ON THE SITE.
5. THE UTILITY LOCATIONS SHOWN ON THESE PLANS ARE TAKEN FROM UTILITY COMPANY RECORDS AND APPARENT FIELD LOCATIONS. THE CONTRACTOR SHALL VERIFY THE LOCATION AND DEPTH OF ALL UTILITIES PRIOR TO CONSTRUCTION.
6. THE CONTRACTOR SHALL ADHERE TO THE PROVISIONS OF THE SENATE BILL NUMBER 583, 78TH GENERAL ASSEMBLY OF THE STATE OF MISSOURI. THE BILL REQUIRES THAT ANY PERSON OR FIRM DOING EXCAVATION ON PUBLIC RIGHT OF WAY DO SO ONLY AFTER GIVING NOTICE TO, AND OBTAINING INFORMATION FROM, UTILITY COMPANIES. STATE LAW REQUIRES 48 HOURS ADVANCE NOTICE. THE CONTRACTOR MAY ALSO UTILIZE THE FOLLOWING TOLL FREE PHONE NUMBER PROVIDED BY "MISSOURI ONE CALL SYSTEM, INC.": 1-800-DIG-RITE. THIS PHONE NUMBER IS APPLICABLE ANYWHERE WITHIN THE STATE OF MISSOURI. PRIOR TO COMMENCEMENT OF WORK, THE CONTRACTOR SHALL NOTIFY ALL THOSE COMPANIES WHICH HAVE FACILITIES IN THE NEAR VICINITY OF THE CONSTRUCTION TO BE PERFORMED.
7. PRIOR TO ORDERING PRECAST STRUCTURES, SHOP DRAWING SHALL BE SUBMITTED TO THE DESIGN ENGINEER FOR APPROVAL. AFTER APPROVAL OF THE SHOP DRAWINGS, A COPY OF THE APPROVED AND SIGNED SHOP DRAWINGS SHALL BE PROVIDED TO THE CITY INSPECTOR UPON REQUEST.
8. THE CONTRACTOR SHALL PROTECT ALL MAJOR TREES FROM DAMAGE. NO TREE SHALL BE REMOVED WITHOUT PERMISSION OF THE OWNER, UNLESS SHOWN OTHERWISE.
9. CLEARING AND GRUBBING OPERATIONS AND DISPOSAL OF ALL DEBRIS THEREFROM SHALL BE PERFORMED BY THE CONTRACTOR IN STRICT ACCORDANCE WITH ALL LOCAL CODES AND ORDINANCES.
10. ALL WASTE MATERIAL RESULTING FROM THE PROJECT SHALL BE DISPOSED OF OFF-SITE BY THE CONTRACTOR, OR AS DIRECTED BY THE OWNER.
11. ALL EXCAVATIONS SHALL BE UNCLASSIFIED. NO SEPARATE PAYMENT WILL BE MADE FOR ROCK EXCAVATION.
12. THE CONTRACTOR SHALL CONTROL THE EROSION AND SILTATION DURING ALL PHASED OF CONSTRUCTION, AND SHALL KEEP THE STREETS CLEAN OF MUD AND DEBRIS.
13. ALL MANHOLES, CATCH BASINS, UTILITY VALVES AND METER PITS TO BE ADJUSTED OR REBUILT TO GRADE AS REQUIRED.
14. THE CONTRACTOR SHALL CONTACT DEVELOPMENT SERVICES INSPECTIONS AT: 816-969-1200 TO OBTAIN A DEVELOPMENT SERVICES CONSTRUCTION PERMIT. A MINIMUM 48 HOUR NOTICE SHALL BE GIVEN PRIOR TO PERMIT ISSUANCE.
15. THE CONTRACTOR SHALL CONTACT THE RIGHT OF WAY INSPECTOR AT 816-969-1800 PRIOR TO ANY LAND DISTURBANCE ACTIVITIES WITHIN THE RIGHT OF WAY. THESE ACTIVITIES MAY REQUIRE A PERMIT.
16. THE CONTRACTOR SHALL PROVIDE AND MAINTAIN ALL TRAFFIC HANDLING MEASURES NECESSARY TO ENSURE THAT THE GENERAL PUBLIC IS PROTECTED AT ALL TIMES. TRAFFIC CONTROL SHALL CONFORM TO THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD-LATEST EDITION).

**STREET NOTES:**

1. ALL STREET CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE CITY OF LEE'S SUMMIT DESIGN AND CONSTRUCTION MANUAL. ALL APPLICABLE AASHTO STANDARDS HAVE BEEN MET.
2. ALL INSPECTION OF STREET CONSTRUCTION TO BE PERFORMED BY THE CITY OF LEE'S SUMMIT DEVELOPMENT ENGINEERING.
3. CURB RETURN RADII SHALL BE 25' AT BACK OF CURB UNLESS OTHERWISE NOTED.
4. SUBGRADE TO BE COMPACTED TO 95% STANDARD PROCTOR DENSITY.
5. ASSUMED DESIGN SPEED = 25 MPH (COLLECTOR).
6. MINIMUM STOPPING SIGHT DISTANCE = 155 FEET.
7. MINIMUM K, SAG CURVE = 26 (14 WITH LIGHTING), CREST CURVE = 12.
8. GRADE INTERSECTIONS TO DRAIN AS SHOWN.
9. SSD = STOPPING SIGHT DISTANCE.
10. ALL ADA SIDEWALK RAMPS SHALL BE CONSTRUCTED BY THE DEVELOPER WITH THE PUBLIC INFRASTRUCTURE.

**EARTHWORK:**


1. It is recommended that a Geotechnical Engineer observe and document all earthwork activities.
2. Contours have been shown at 1-foot or 2-foot intervals, as indicated. Grading shall consist of completing the earthwork required to bring the physical ground elevations of the existing site to the finished grade (or sub-grade) elevations provided on the plans as spot grades, contours or others means as indicated on the plans.
3. The existing site topography depicted on the plans by contouring has been established by aerial photography and field verified by g.p.s. observation near 2-20-19. The contour elevations provided may not be exact ground elevations, but rather interpretations of such. Accuracy shall be considered to be such that not more than 10 percent of spot elevation checks shall be in error by more than one-half the contour interval provided, as defined by the National Map Accuracy Standards. Any quantities provided for earthwork volumes are established using this topography contour accuracy, and therefore the inherent accuracy of any earthwork quantity is assumed from the topography accuracy.
4. Proposed contours are to approximate finished grade.
5. Unless otherwise noted, payment for earthwork shall include backfilling of the curb and gutter, sidewalk and further manipulation of utility trench spoils. The site shall be left in a movable condition and positive drainage maintained throughout.
6. Unless otherwise noted, all earthwork is considered Unclassified. No additional compensation will be provided for rock or shale excavation, unless specifically stated otherwise.
7. Prior to earthwork activities, pre-disturbance erosion and sediment control devices shall be in place per the Storm Water Pollution Prevention plan and/or the Erosion and Sediment Control Plan prepared for this site.
8. All topsoil shall be stripped from all areas to be graded and stockpiled adjacent to the site at an area specified by the project owner or his appointed representative. Vegetation, trash, trees, brush, tree roots and limbs, rock fragments greater than 6-inches and other deleterious materials shall be removed and properly disposed of offsite or as directed by the owner or his appointed representative.
9. Unless otherwise specified in the Geotechnical Report, all fills shall be placed in maximum 6-inch lifts and compacted to 95-percent of maximum density as defined using a standard proctor test (AASHTO T99/ASTM 698).
10. Fill materials shall be per Geotechnical Report and shall not include organic matter, debris or topsoil. All fills placed on slopes greater than 6:1 shall be benched.
11. The Contractor shall be responsible for redistributing the topsoil over proposed turf and landscaped areas to a minimum depth of 6-inches below final grade.
12. All areas shall be graded for positive drainage. Unless noted otherwise the following grades shall apply:
  - a. Turf Areas - 2.5% Minimum, 4H:1V Maximum
  - b. Paved Areas - 1.2% Minimum, 5% Maximum
13. All disturbed areas shall be fertilized, seeded and mulched immediately after earthwork activities have ceased. Seeding shall be per the Erosion and Sediment Control Plan and/or Landscape Plan. If not specified seeding shall be per APWA Section 2400, latest edition. Unless otherwise noted, seeding shall be subsidiary to the contract price for earthwork and grading activities.
14. All disturbed areas in the right-of-way shall be sodded.
15. Underdrains are recommended for all paved areas adjacent to irrigated turf and landscaped beds.
16. Contractor shall adhere to the reporting requirements outlined in the Storm Water Pollution Prevention Plan (SWPPP) prepared for this project. Erosion and Sediment control devices shall be properly maintained and kept clean of silt and debris and in good working order. Additional erosion and sediment control measures shall be installed as required.

**UTILITIES:**

1. Existing utilities have been shown to the greatest extent possible based upon information provided to the Engineer. The contractor is responsible for contacting the respective utility companies and field locating utilities prior to construction and identifying any potential conflicts. All conflicts shall immediately be brought to the attention of the Engineer.
2. The contractor shall be responsible for coordinating any required utility relocations. Utilities damaged through the negligence of the contractor shall be repaired at the contractor's expense.
3. Contractor shall verify flow-lines and structure tops prior to construction, and shall notify Engineer of any discrepancies. Provide shop drawings for all precast and manufactured utility structures for review by the Engineer prior to construction of the structures.
4. Utility Separation: Waterlines shall have a minimum of 10 feet horizontal and 2 feet vertical separation from all sanitary sewer lines, manholes, and sanitary sewer service laterals, as measured from edge to edge. If minimum separations can not be obtained, concrete encasement of the sanitary line shall be required 10 feet in each direction of the conflict.
5. Payment for trenching, backfilling, pipe embedment, flowable fill, backfill materials, clean up, seeding, sodding and any other items necessary for the construction of the utility line shall be included in the contract price for the utility installation.
6. The Contractor shall be responsible for contacting respective utility companies 48-hours in advance for the inspection of any proposed utility main extension or service line or service connection to any existing main.
7. Trench spoils shall be neatly placed onsite adjacent to the trench, and compacted to prevent saturation and excess sediment runoff. Unsuitable materials, excess rock and shale, asphalt, concrete, trees, brush etc. shall be properly disposed of offsite. Materials may be wasted onsite at the direction of the Owner or his appointed representative.
8. All excavation is considered unclassified, unless noted otherwise. Unclassified excavation for utility trenching is subsidiary to the unit price provided for the pipe. Any quantity provided for rock excavation is estimated based on the best information provided to the Project Engineer. The Engineer has the authority to identify and define the physical characteristics to determine the classification. Unit price quantities for rock excavation will be paid at a trench width of the nominal pipe diameter of the installed main plus 18 inches. Contractor is required to dispose of excess rock from their trenches by disposing it in areas as specified by the Project Engineer.

Sheet List Table	
Sheet Number	Sheet Title
1	COVER SHEET
2	GENERAL LAYOUT
3	MASTER DRAINAGE PLAN-GRADING PLAN
4	MASTER DRAINAGE PLAN - SWALE GRADING PLAN
5	SE CRONIN ST PLAN AND PROFILE
6	SE SILO ST PLAN AND PROFILE
7	SE WINDBREAK DR (WEST) AND ARBORETUM DR PLAN AND PROFILE
8	INTERSECTION DETAILS
9	MASTER DRAINAGE PLAN-DRAINAGE AREA MAP
10	MASTER DRAINAGE PLAN-DRAINAGE CALCULATIONS
11	STORM PLAN
12	STORM PROFILE 1
13	STORM PROFILE 2
14	DETENTION BASIN DESIGN
15	STREET DETAILS 1
16	STREET DETAILS 2
17	STORM DETAILS
18	STORM DETAILS 2
19	SIGNAGE PLAN
20	SIGN POST DETAILS
21	SIGN MOUNTING DETAILS
22	STREET NAME SIGN DETAILS
23	OM-4 SIGN DETAILS

PREPARED BY:



SCHLAGEL & ASSOCIATES, P.A.

APPROVED BY:

CITY ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_  
APPROVED FOR ONE YEAR FROM THIS DATE

OWNER/DEVELOPER:

CLAYTON PROPERTIES GROUP INC., DBA SUMMIT HOMES  
BRADLEY KEMPFF  
120 SE 30TH STREET  
LEE'S SUMMIT, MO 64082  
p (816) 246-6700  
BRADLEY@SUMMITHOMESKC.COM



**MISSOURI GEOGRAPHIC REFERENCE SYSTEM BENCHMARK:**

BM JA-45, IS A KC METRO ALUMINUM GRS DISK SET IN CONCRETE AND ABOUT 3 INCHES BELOW THE PAVEMENT ON THE SHOULDER OF SE RANSON ROAD. IT IS STAMPED JA45, 1987.

ELEV. = 1046.25

SUMMARY OF QUANTITIES		
ITEM	QUANTITY	UNITS
1	CLEARING AND GRUBBING	1 LS
2	GRADING	1 LS
3	8" ASPHALT PAVEMENT - LOCAL-RESIDENTIAL STREET	5025 SY
4	FLY ASH OR COMPACTED AGGREGATE BASE	6150 SY
5	CURB AND GUTTER (INLET TRANSITIONS NOT INCLUDED) SUBSIDIARY TO CG-2 IS ALL CG-2 DRY NEEDED)	3024 LF
6	5' CONC. SIDEWALK	57 LF
7	TYPE A SIDEWALK RAMP	2 EA
8	TYPE M SIDEWALK RAMP	4 EA
9	6'X4' CURB INLET	12 EA
10	6'X5' CURB INLET	1 EA
11	6'X6' CURB INLET	2 EA
12	8'X4' CURB INLET	1 EA
13	4'X4' JUNCTION BOX	1 EA
14	4'X5' JUNCTION BOX	1 EA
15	5'X5' JUNCTION BOX	1 EA
16	4'X4' AREA INLET WITH ONE OPENING	1 EA
17	4'X4' AREA INLET WITH TWO OPENINGS	1 EA
18	WATER QUALITY STRUCTURE ( STRUCTURE 3901) STRUCTURE TO INCLUDE, 8" PVC, RISER PIPE, CONCRETE BLOCK, TRASH RACK, ETC.	1 LS

19	FAIRCLOTH SKIMMER - INCLUDE SKIMMER, CONCRETE BLOCK, RISER PIPE, REMOVAL AND REPLACEMENT WITH PERMANENT STRUCTURE	1	LS
20	24" END SECTION WITH TOE WALL	1	EA
21	30" END SECTION WITH TOE WALL	2	EA
22	36" END SECTION WITH TOE WALL	1	EA
23	50# STONE RIPRAP WITH FILTER FABRIC	12	EA
24	100# STONE RIPRAP WITH FILTER FABRIC	12	CY
25	150# STONE RIPRAP WITH FILTER FABRIC	7	CY
26	15" HDPE	460	LF
27	18" HDPE	150	LF
28	24" HDPE	425	LF
29	30" HDPE	385	LF
30	36" HDPE	670	LF
31	TURF REINFORCEMENT MAT	412	SY
32	EROSION CONTROL	1	LS
33	END OF ROAD MARKERS (OM 4-1)	6	EA
34	SEEDING AND MULCHING ALL DISTURBED AREAS	1	LS

THESE QUANTITIES ARE SUPPLIED FOR THE CONTRACTOR'S BENEFIT. CONTRACTOR SHALL VERIFY QUANTITIES AND DISCREPANCIES WHEN PLACING THEIR BID

CORNERSTONE AT BAILEY FARMS, FIRST PLAT STREET, STORMWATER, AND MASTER DRAINAGE PLAN  
SE BAILEY ROAD AND SE RANSON ROAD LEE'S SUMMIT, MISSOURI


REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

DRAWN BY: JRU	CHECKED BY: JLL	DATE PREPARED: 12/20/21	PROJ. NUMBER: 21-138
---------------	-----------------	-------------------------	----------------------

COVER SHEET

SHEET

PREPARED BY:



SCHLAGEL & ASSOCIATES, P.A.

**CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER DRAINAGE  
 PLAN**  
**SE BAILEY ROAD AND SE RANSON ROAD  
 LEE'S SUMMIT, MISSOURI**


REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

GENERAL LAYOUT  
 SHEET  
**2**

**BASIS OF BEARINGS:**  
 MISSOURI STATE PLANE COORDINATE SYSTEM  
 (NAD) 1983, MISSOURI, WEST ZONE

**NOTES:**  
 ALL CONSTRUCTION ON THIS PROJECT SHALL CONFORM TO THE  
 CITY OF LEES SUMMIT TECHNICAL SPECIFICATIONS.

THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL  
 EXISTING UTILITY LOCATIONS PRIOR TO EXCAVATION.





**BASIS OF BEARINGS:**  
 MISSOURI STATE PLANE COORDINATE SYSTEM  
 (NAD) 1983, MISSOURI, WEST ZONE

**NOTES:**  
 ALL CONSTRUCTION ON THIS PROJECT SHALL CONFORM TO THE CITY OF LEES SUMMIT TECHNICAL SPECIFICATIONS.


THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL EXISTING UTILITY LOCATIONS PRIOR TO EXCAVATION.

**GRADING LEGEND:**  
 - - - 1023 - - - EXISTING CONTOUR  
 ——— 1023 ——— PROPOSED CONTOUR

- NOTES:**
- MBOE = MINIMUM BUILDING OPENING ELEVATION FOR HOUSES ADJACENT TO ENGINEERED OVERFLOW SWALES SHALL BE MINIMUM 2 FEET ABOVE THE 100-YEAR WATER SURFACE ELEVATION.
  - EGL = ENERGY GRADE LINE (100-YEAR)
  - WSE = WATER SURFACE ELEVATION (100-YEAR)
  - ENGINEERED SWALES TO BE GRADED TO NORMAL DEPTH OF FLOW (WATER SURFACE ELEVATION) OR 1.0 FT, WHICHEVER IS GREATER. MINIMUM SLOPE OF ENGINEERED SWALES SHALL BE AS NOTED.
  - MINIMUM BUILDING OPENING ELEVATIONS (MBOEs) ADJACENT TO SUMPED INLETS SHALL BE A MINIMUM OF 1' ABOVE TOP OF ADJACENT BERM

LOT NUMBER	BASEMENT TYPE	MBOE
1	STANDARD	
2	DAYLIGHT	
3	DAYLIGHT	
4	DAYLIGHT	
5	WALKOUT	
6	WALKOUT	
7	WALKOUT	
8	WALKOUT	
9	DAYLIGHT	
10*	STANDARD	1012
11*	STANDARD	1014
12*	STANDARD	1014
13*	STANDARD	1015
14*	STANDARD	1015
15*	STANDARD	1012
16*	STANDARD	1012
17*	STANDARD	1012
18*	STANDARD	1012
19*	DAYLIGHT	1012
20	DAYLIGHT	
21*	DAYLIGHT	1014
22*	DAYLIGHT	1014
23	DAYLIGHT	
24	DAYLIGHT	
25*	STANDARD	1018
26*	STANDARD	1019
27	STANDARD	
28	STANDARD	
29	STANDARD	
30*	STANDARD	1019
31*	STANDARD	1018
32	STANDARD	
33	STANDARD	
34	STANDARD	
35	STANDARD	
36	STANDARD	
37	STANDARD	

\* LOTS WHICH REQUIRE AN "AS-GRADED PLOT PLAN" BEFORE OCCUPANCY.



**SCHLAGEL**  
 ENGINEERS PLANNERS SURVEYORS LANDSCAPE ARCHITECTS  
 14920 West 107th Street • Lenexa, Kansas 66215  
 (913) 492-5158 • Fax: (913) 492-8400  
 WWW.SCHLAGELASSOCIATES.COM  
 Missouri State Certificate of Authority  
 #E200203690F #LAC201005237 #LS200200869F

PREPARED BY:  
 JAMES L. LONG  
 NUMBER PE-201401495  
 PROFESSIONAL ENGINEER  
 5/19/2022  
 SCHLAGEL & ASSOCIATES, P.A.

CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER DRAINAGE  
 PLAN  
 SE BAILEY ROAD AND SE RANSON ROAD  
 LEES SUMMIT, MISSOURI

REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

DRAWN BY: JRJ  
 CHECKED BY: JLL  
 DATE PREPARED: 12/20/21  
 PROJ. NUMBER: 21-136

MASTER DRAINAGE PLAN-GRADING PLAN

I:\PROJECTS\2021\21-136\3.0 DWG Plans\6.0 SS\21-136-SS-GRAD.dwg, 5/19/2022 6:18:07 AM, 1:1



**BASIS OF BEARINGS:**  
MISSOURI STATE PLANE COORDINATE SYSTEM (NAD) 1983, MISSOURI, WEST ZONE

**NOTES:**  
ALL CONSTRUCTION ON THIS PROJECT SHALL CONFORM TO THE CITY OF LEES SUMMIT TECHNICAL SPECIFICATIONS.

THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL EXISTING UTILITY LOCATIONS PRIOR TO EXCAVATION.

**GRADING LEGEND:**  
--- 1023 --- EXISTING CONTOUR  
— 1023 — PROPOSED CONTOUR

A A DENOTES OVERFLOW SWALE  
○ EL:000.00 DENOTES FINISHED GRADE ELEVATION  
○ EL:000.00 (EX.) DENOTES EXISTING GRADE ELEVATION  
● HP 000.00 DENOTES LOT HIGH POINT ELEVATION

- NOTES:**
- MBOE = MINIMUM BUILDING OPENING ELEVATION FOR HOUSES ADJACENT TO ENGINEERED OVERFLOW SWALES SHALL BE MINIMUM 2 FEET ABOVE THE 100-YEAR WATER SURFACE ELEVATION.
  - EGL = ENERGY GRADE LINE (100-YEAR)
  - WSE = WATER SURFACE ELEVATION (100-YEAR)
  - ENGINEERED SWALES TO BE GRADED TO NORMAL DEPTH OF FLOW (WATER SURFACE ELEVATION) OR 1.0 FT, WHICHEVER IS GREATER. MINIMUM SLOPE OF ENGINEERED SWALES SHALL BE AS NOTED.
  - MINIMUM BUILDING OPENING ELEVATIONS (MBOE) ADJACENT TO SUMPED INLETS SHALL BE A MINIMUM OF 1' ABOVE TOP OF ADJACENT BERM


WEIR CALCULATIONS (Q = CLH<sup>3/2</sup>)

SECTION	DRAINAGE AREA (AC.)	Q100 (CFS)	Q10 (CFS)	DESIGN OVERFLOW (CFS)	WEIR ELEVATION	WEIR COEFFICIENT	LENGTH (FT.)	HEAD REQUIRED (FT.)	WSE
1-1	0.60	5.11	2.91	2.20	1016.30	3.33	10	0.16	1016.46


100 YEAR OVERFLOW SWALES

SECTION	DRAINAGE AREA (AC.)	Q100 (CFS)	Q10 (CFS)	DESIGN OVERFLOW (CFS)	BED SLOPE (%)	BASE WIDTH (FT.)	SIDE SLOPE	TOP WIDTH (FT.)	NORMAL DEPTH (FT.)	VELOCITY (FPS)	VELOCITY HEAD (FT.)	EGL (FT.)
E-E	0.76	6.47	3.69	2.78	2.2	5	4:1	4.00	0.50	2.78	0.12	0.62
F-F	3.21	27.33	15.57	11.76	2.0	5	4:1	8.84	0.48	3.54	0.19	0.67
G-G	3.56	30.31	17.27	13.04	2.4	0	4:1	6.96	0.87	4.31	0.29	1.16
H-H	8.77	74.67	42.54	32.12	5.3	5	4:1	10.04	0.63	6.78	0.71	1.34


**RUNOFF CALCULATIONS:**  
 $Q = K \cdot C \cdot I \cdot A$   
 $K_{10} = 1.0 \quad K_{100} = 1.25 \quad C = 0.66 \quad I = \text{INTENSITY}$   
 DESIGN OVERFLOW =  $Q_{\text{OVERFLOW}} = Q_{100} \cdot C_{10}$   
 MANNINGS "n" = 0.030 FOR SWALES



100 YEAR OVERFLOW SWALE SECTIONS



PREPARED BY:




SCHLAGEL & ASSOCIATES, P.A.

CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER DRAINAGE  
 PLAN  
 SE BAILEY ROAD AND SE RANSON ROAD  
 LEES SUMMIT, MISSOURI

REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

MASTER DRAINAGE PLAN - SWALE GRADING PLAN

I:\PROJECTS\2021\21-136-SS-GRAD.dwg, 5/19/2022 7:47:08 AM, 1:1



**MISSOURI GEOGRAPHIC REFERENCE SYSTEM BENCHMARK:**


BM JA-45, IS A KC METRO ALUMINUM CRS DISK SET IN CONCRETE AND ABOUT 3 INCHES BELOW THE PAVEMENT ON THE SHOULDER OF SE RANSON ROAD. IT IS STAMPED JA45, 1987.

ELEV. = 1046.25

**NOTES:**


ALL CONSTRUCTION ON THIS PROJECT SHALL CONFORM TO THE CITY OF LEES SUMMIT TECHNICAL SPECIFICATIONS.

THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL EXISTING UTILITY LOCATIONS PRIOR TO EXCAVATION.



**SCHLAGEL**  
 ENGINEERS PLANNERS SURVEYORS LANDSCAPE ARCHITECTS  
 14920 West 107th Street • Lenexa, Kansas 66215  
 (913) 492-5158 • Fax: (913) 492-8400  
 WWW.SCHLAGELASSOCIATES.COM

PREPARED BY:




5/19/2022  
 SCHLAGEL & ASSOCIATES, P.A.

CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER DRAINAGE  
 PLAN  
 SE BAILEY ROAD AND SE RANSON ROAD  
 LEE'S SUMMIT, MISSOURI

**SE CRONIN STREET**

1" = 50' HORIZ.  
 1" = 10' VERT.




REVISION DATE	DESCRIPTION
02/20/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

SE CRONIN ST  
 PLAN AND  
 PROFILE

SHEET  
**5**

I:\PROJECTS\2021\21-1963.0 Design\3.0 DWG Plans\6.0 SS\21-136-SS-PP.dwg, 5/19/2022 8:20:04 AM, 1:1



**MISSOURI GEOGRAPHIC REFERENCE SYSTEM BENCHMARK:**


BM JA-45, IS A KC METRO ALUMINUM CRS DISK SET IN CONCRETE AND ABOUT 3 INCHES BELOW THE PAVEMENT ON THE SHOULDER OF SE RANSON ROAD. IT IS STAMPED JA45, 1987.

ELEV. = 1046.25

**NOTES:**


ALL CONSTRUCTION ON THIS PROJECT SHALL CONFORM TO THE CITY OF LEES SUMMIT TECHNICAL SPECIFICATIONS.

THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL EXISTING UTILITY LOCATIONS PRIOR TO EXCAVATION.



**SCHLAGEL**  
 ENGINEERS PLANNERS SURVEYORS LANDSCAPE ARCHITECTS  
 14920 West 107th Street • Lenexa, Kansas 66215  
 (913) 492-5158 • Fax: (913) 492-8400  
 WWW.SCHLAGELASSOCIATES.COM


PREPARED BY:



SCHLAGEL & ASSOCIATES, P.A.

CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER DRAINAGE  
 PLAN  
 SE BAILEY ROAD AND SE RANSON ROAD  
 LEE'S SUMMIT, MISSOURI

**SE SILO STREET**





REVISION DATE	DESCRIPTION
02/20/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

SE SILO ST PLAN AND PROFILE

SHEET  
**6**

I:\PROJECTS\2021\21-136-3.0 Design\3.0 DWG Plans\6.0 SS\21-136-SS-PP.dwg, 5/19/2022 8:20:11 AM, 1:1



**MISSOURI GEOGRAPHIC REFERENCE SYSTEM BENCHMARK:**


BM JA-45, IS A KC METRO ALUMINUM CRS DISK SET IN CONCRETE AND ABOUT 3 INCHES BELOW THE PAVEMENT ON THE SHOULDER OF SE RANSON ROAD. IT IS STAMPED JA45, 1987.

ELEV. = 1046.25

**NOTES:**


ALL CONSTRUCTION ON THIS PROJECT SHALL CONFORM TO THE CITY OF LEES SUMMIT TECHNICAL SPECIFICATIONS.

THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL EXISTING UTILITY LOCATIONS PRIOR TO EXCAVATION.



**SCHLAGEL**  
 ENGINEERS PLANNERS SURVEYORS LANDSCAPE ARCHITECTS  
 14920 West 107th Street • Lenexa, Kansas 66215  
 (913) 492-5158 • Fax: (913) 492-8400  
 WWW.SCHLAGELASSOCIATES.COM

PREPARED BY:



SCHLAGEL & ASSOCIATES, P.A.


CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER  
 DRAINAGE PLAN  
 SE BAILEY ROAD AND SE RANSON ROAD  
 LEE'S SUMMIT, MISSOURI

REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022


DRAWN BY:	JRU
CHECKED BY:	JLL
DATE PREPARED:	1/20/2021
PROJ. NUMBER:	21-186

SE WINDBREAK DR (WEST) AND ARBORETUM DR PLAN AND PROFILE SHEET

**SE ARBORETUM DRIVE (WEST)**



**SE WINDBREAK DRIVE (WEST)**



1" = 50' HORIZ.  
 1" = 10' VERT.

I:\PROJECTS\2021\21-186\3.0 Design\3.0 DWG Plans\6.0 SS\21-186-SS-PP.dwg, 5/19/2022 6:20:22 AM, 1:1







**MISSOURI GEOGRAPHIC REFERENCE SYSTEM BENCHMARK:**  
 BM JA-45, IS A KC METRO ALUMINUM GRS DISK SET IN CONCRETE AND ABOUT 3 INCHES BELOW THE PAVEMENT ON THE SHOULDER OF SE RANSON ROAD. IT IS STAMPED JA45, 1987.  
 ELEV. = 1046.25

**SCHLAGEL**  
 ENGINEERS PLANNERS SURVEYORS LANDSCAPE ARCHITECTS  
 14920 West 107th Street • Lenexa, Kansas 66215  
 (913) 492-5158 • Fax: (913) 492-8400  
 WWW.SCHLAGELASSOCIATES.COM  
 Missouri State Certificates of Authority  
 #E2002003690-F #LAC2001005237 #LS200200869-F


PREPARED BY:  
  
 JAMES L. LONG  
 NUMBER PE-2014010495  
 PROFESSIONAL ENGINEER  
 5/19/2022  
 SCHLAGEL & ASSOCIATES, P.A.

**CORNERSTONE AT BAILEY FARMS, FIRST PLAT STREET, STORMWATER, AND MASTER DRAINAGE PLAN**  
**SE BAILEY ROAD AND SE RANSON ROAD LEE'S SUMMIT, MISSOURI**

REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

MASTER DRAINAGE PLAN-DRAINAGE AREA MAP

SHEET  
**9**



I:\PROJECTS\2021\21-136-3.0 Design\3.0 DWG Plans\6.0 SS\21-136-SS-DRAINAGE.dwg, 5/19/2022 6:22:11 AM, 1:1

10-YEAR RUNOFF CALCULATIONS

Design Storm:		10																						
"K" Value:		1.00																						
"F" Factor:		1.00																						
Runoff Calculations		Runoff										Pipe Properties												
Inlet #	Area (acres)	"C" Value	Cumul. Area (acres)	Cumul. CxA	To Intensity	To Inlet	Cumul. Runoff	Pipe Cap.	Pipe Vel.	Up Piped Inlet 1	Up Piped Inlet 2	Up Area (acres)	Up CxA	Up Inlet	Down Inlet	Pipe Type	"n" Value	Pipe Size	Slope %	Drop In Inlet	FL Up	FL Down	Inlet Top	
DS TAILWATER @ STR #200																								
201	0.00	0.66	8.09	5.34	7.7	6.60	0.00	35.27	34.42	7.01		0.00	0.00	201	200	HDPE	0.012	30	184.94	0.60	0.20	1002.61	1001.50	1008.75
202	0.69	0.66	8.09	5.34	7.4	6.68	3.04	35.64	39.74	8.10		0.00	0.00	202	201	HDPE	0.012	30	135.90	0.80	1.50	1003.90	1002.81	1013.49
203	0.39	0.66	7.40	4.88	7.3	6.70	1.72	32.71	21.92	6.98		0.00	0.00	203	202	HDPE	0.012	24	35.04	0.80	0.50	1005.68	1005.40	1013.50
204	0.51	0.66	7.01	4.63	7.2	6.74	2.27	31.20	21.92	6.98	301	1.85	1.22	204	203	HDPE	0.012	24	75.49	0.80	0.50	1006.78	1006.18	1015.11
205	0.55	0.66	4.65	3.07	7.1	6.76	2.46	20.76	21.92	6.98		0.00	0.00	205	204	HDPE	0.012	24	35.00	0.80	0.50	1007.56	1007.28	1015.11
206	0.14	0.66	4.10	2.71	7.0	6.79	0.63	18.38	21.92	6.98		0.00	0.00	206	205	HDPE	0.012	24	41.74	0.80	0.20	1008.40	1008.06	1015.83
DS TAILWATER @ STR #700																								
701	0.00	0.66	1.98	1.31	5.7	7.14	0.00	9.33	21.92	6.98		0.00	0.00	701	700	HDPE	0.012	24	61.51	0.80	0.50	1000.13	999.64	1009.24
702	0.24	0.66	1.98	1.31	5.5	7.20	1.14	9.40	34.66	11.03		0.00	0.00	702	701	HDPE	0.012	24	135.04	2.00	0.30	1003.33	1000.63	1014.47
703	0.32	0.66	1.74	1.15	5.5	7.21	1.52	8.28	34.66	11.03	901	0.74	0.49	703	702	HDPE	0.012	24	35.00	2.00	0.40	1004.33	1003.63	1014.47
704	0.30	0.66	0.68	0.45	5.4	7.23	1.43	3.24	34.66	11.03		0.00	0.00	704	703	HDPE	0.012	18	41.96	3.00	0.40	1005.99	1004.73	1015.29
705	0.38	0.66	0.38	0.25	5.0	7.35	1.84	1.84	9.90	8.06		0.00	0.00	705	704	HDPE	0.012	15	195.23	2.00	0.40	1010.30	1006.39	1017.49
706	0.88	0.66	0.88	0.58	5.0	7.35	4.27	4.27	9.90	8.06		0.00	0.00	706	705	HDPE	0.012	15	38.73	2.00	N/A	1011.47	1010.70	1017.78
Drop in Inlet 703																								
801	0.41	0.66	1.12	0.74	5.3	7.28	1.97	5.38	16.09	9.11		0.00	0.00	801	703	HDPE	0.012	18	97.97	2.00	0.50	1006.79	1004.83	1014.92
802	0.71	0.66	0.71	0.47	5.0	7.35	3.45	3.45	9.90	8.06		0.00	0.00	802	801	HDPE	0.012	15	122.16	2.00	N/A	1009.74	1007.29	1015.80
Drop in Inlet 704																								
901	0.74	0.66	0.74	0.49	5.0	7.35	3.59	3.59	9.90	8.06		0.00	0.00	901	704	HDPE	0.012	15	35.06	2.00	N/A	1007.19	1006.49	1015.06
DS TAILWATER @ STR #1000																								
1001	0.00	0.66	14.65	10.02	8.3	6.45	0.00	64.59	67.78	9.59		0.00	0.00	1001	1000	HDPE	0.012	36	35.00	0.88	0.30	999.49	999.18	1010.90
1002	1.18	0.66	14.65	10.02	8.1	6.50	0.00	65.12	72.26	10.22		0.00	0.00	1002	1001	HDPE	0.012	36	135.00	1.00	0.30	1001.14	999.79	1010.90
1003	0.11	0.66	14.65	10.02	7.7	6.60	5.14	66.16	64.63	9.14	1101	0.30	0.20	1003	1002	HDPE	0.012	36	232.81	0.80	0.40	1003.30	1001.44	1014.95
1004	0.15	0.66	13.17	9.04	7.5	6.65	0.48	60.10	64.63	9.14		0.00	0.00	1004	1003	HDPE	0.012	36	94.66	0.80	0.40	1004.46	1003.70	1016.07
1005	0.06	0.66	13.06	8.97	7.3	6.70	0.66	60.11	64.63	9.14		0.00	0.00	1005	1004	HDPE	0.012	36	118.84	0.80	0.40	1005.81	1004.86	1017.25
Drop in Inlet 1002																								
1101	0.30	0.66	0.30	0.20	5.0	7.35	1.46	1.46	12.12	9.88		0.00	0.00	1101	1002	HDPE	0.012	15	36.19	3.00	N/A	1003.97	1002.89	1014.88

100-YEAR RUNOFF CALCULATIONS

Design Storm:		100																						
"K" Value:		1.25																						
"F" Factor:		1.00																						
Runoff Calculations		Runoff										Pipe Properties												
Inlet #	Area (acres)	"C" Value	Cumul. Area (acres)	Cumul. CxA	To Intensity	To Inlet	Cumul. Runoff	Pipe Cap.	Pipe Vel.	Up Piped Inlet 1	Up Piped Inlet 2	Up Area (acres)	Up CxA	Up Inlet	Down Inlet	Pipe Type	"n" Value	Pipe Size	Slope %	Drop In Inlet	FL Up	FL Down	Inlet Top	
DS TAILWATER @ STR #200																								
201	0.00	0.66	8.09	5.34	7.7	9.31	0.00	62.14	34.42	7.01		0.00	0.00	201	200	HDPE	0.012	30	184.94	0.60	0.20	1002.61	1001.50	1008.75
202	0.69	0.66	8.09	5.34	7.4	9.41	5.35	62.78	39.74	8.10		0.00	0.00	202	201	HDPE	0.012	30	135.90	0.80	1.50	1003.90	1002.81	1013.49
203	0.39	0.66	7.40	4.88	7.3	9.44	3.04	57.60	21.92	6.98		0.00	0.00	203	202	HDPE	0.012	24	35.04	0.80	0.50	1005.68	1005.40	1013.50
204	0.51	0.66	7.01	4.63	7.2	9.50	4.00	54.93	21.92	6.98	301	1.85	1.22	204	203	HDPE	0.012	24	75.49	0.80	0.50	1006.78	1006.18	1015.11
205	0.55	0.66	4.65	3.07	7.1	9.53	4.32	36.55	21.92	6.98		0.00	0.00	205	204	HDPE	0.012	24	35.00	0.80	0.50	1007.56	1007.28	1015.11
206	0.14	0.66	4.10	2.71	7.0	9.56	1.10	32.35	21.92	6.98		0.00	0.00	206	205	HDPE	0.012	24	41.74	0.80	0.20	1008.40	1008.06	1015.83
DS TAILWATER @ STR #700																								
701	0.00	0.66	1.98	1.31	5.7	10.03	0.00	16.38	21.92	6.98		0.00	0.00	701	700	HDPE	0.012	24	61.51	0.80	0.50	1000.13	999.64	1009.24
702	0.24	0.66	1.98	1.31	5.5	10.11	2.00	16.52	34.66	11.03		0.00	0.00	702	701	HDPE	0.012	24	135.04	2.00	0.30	1003.33	1000.63	1014.47
703	0.32	0.66	1.74	1.15	5.5	10.13	2.67	14.54	34.66	11.03	901	0.74	0.49	703	702	HDPE	0.012	24	35.00	2.00	0.40	1004.33	1003.63	1014.47
704	0.30	0.66	0.68	0.45	5.4	10.16	2.51	5.70	19.71	11.15		0.00	0.00	704	703	HDPE	0.012	18	41.96	3.00	0.40	1005.99	1004.73	1015.29
705	0.38	0.66	0.38	0.25	5.0	10.32	3.24	3.24	9.90	8.06		0.00	0.00	705	704	HDPE	0.012	15	195.23	2.00	0.40	1010.30	1006.39	1017.49
706	0.88	0.66	0.88	0.58	5.0	10.32	7.49	7.49	9.90	8.06		0.00	0.00	706	705	HDPE	0.012	15	38.73	2.00	N/A	1011.47	1010.70	1017.78
Drop in Inlet 703																								
801	0.41	0.66	1.12	0.74	5.3	10.22	3.46	9.44	16.09	9.11		0.00	0.00	801	703	HDPE	0.012	18	97.97	2.00	0.50	1006.79	1004.83	1014.92
802	0.71	0.66	0.71	0.47	5.0	10.32	6.05	6.05	9.90	8.06		0.00	0.00	802	801	HDPE	0.012	15	122.16	2.00	N/A	1009.74	1007.29	1015.80
Drop in Inlet 704																								
901	0.74	0.66	0.74	0.49	5.0	10.32	6.30	6.30	9.90	8.06		0.00	0.00	901	704	HDPE	0.012	15	35.06	2.00	N/A	1007.19	1006.49	1015.06
DS TAILWATER @ STR #1000																								
1001	0.00	0.66	14.65	10.02	8.3	9.09	0.00	113.91	67.78	9.59		0.00	0.00	1001	1000	HDPE	0.012	36	35.00	0.88	0.30	999.49	999.18	1010.90
1002	1.18	0.66	14.65	10.02	8.1	9.17	0.00	114.81	72.26	10.22		0.00	0.00	1002	1001	HDPE	0.012	36	135.00	1.00	0.30	1001.14	999.79	1010.90
1003	0.11	0.66	14.65	10.02	7.7	9.31	9.06	116.58	64.63	9.14	1101	0.30	0.20	1003	1002	HDPE	0.012	36	232.81	0.80	0.40	1003.30	1001.44	1014.95
1004	0.15	0.66	13.17	9.04	7.5	9.37	0.85	105.88	64.63	9.14		0.00	0.00	1004	1003	HDPE	0.012	36	94.66	0.80	0.40	1004.46	1003.70	1016.07
1005	0.06	0.66	13.06	8.97	7.3	9.44	1.17	105.87	64.63	9.14		0.00	0.00	1005	1004	HDPE	0.012	36	118.84	0.80	0.40	1005.81	1004.86	1017.25
Drop in Inlet 1002																								
1101	0.30	0.66	0.30	0.20	5.0	10.32	2.55	2.55	12.12	9.88		0.00	0.00	1101	1002	HDPE	0.012	15	36.19	3.00	N/A	1003.97	1002.89	1014.88


GUTTER SPREAD AND INLET CAPACITY CALCULATIONS

DESIGN STORM		10																	
"K" FACTOR		1.00																	
										CURB TYPE "A" = LAZY BACK									
										CURB TYPE "B" = HIGH BACK									
RUNOFF CALCULATIONS										INLET DESIGN									



Storm Sewer Construction Notes	
Structure	Notes
200	STA 0+00.00, LINE 200 INSTALL 30" HDPE FLARED END SECTION W/ TOEWALL AND 7 CU. YD (16'X8'X2.5') STONE RIP-RAP USING A MIN. 100# (D50=15") STONE. PLACE FILTER FABRIC PRIOR TO INSTALLATION OF RIP-RAP. N 992676.4508 E 2832604.7511
201	STA 1+84.94, LINE 200 INSTALL 5 X 4 JUNCTION BOX N 992857.6387 E 2832641.8233
202	STA 3+20.54, LINE 200 INSTALL 6 X 4 CURB INLET N 992856.6502 E 2832777.4172
203	STA 3+55.57, LINE 200 INSTALL 6 X 4 CURB INLET N 992852.4044 E 2832812.1893
204	STA 4+31.15, LINE 200 INSTALL 6 X 4 CURB INLET N 992921.0453 E 2832843.8274
205	STA 4+66.15, LINE 200 INSTALL 6 X 4 CURB INLET N 992956.0449 E 2832844.0066
206	STA 5+07.89, LINE 200 INSTALL 6 X 4 CURB INLET N 992985.7268 E 2832814.6582
700	STA -0+00.00, LINE 700 INSTALL 24" HDPE FLARED END SECTION W/ TOEWALL AND 5 CU. YD (14'X6'X1.5') STONE RIP-RAP USING A MIN. 50# (D50=12") STONE. PLACE FILTER FABRIC PRIOR TO INSTALLATION OF RIP-RAP. N 992476.2527 E 2832696.4116
701	STA 0+61.50, LINE 700 INSTALL 4 X 4 JUNCTION BOX N 992466.5519 E 2832757.1471
702	STA 1+97.26, LINE 700 INSTALL 6 X 4 CURB INLET N 992518.4477 E 2832882.5904
703	STA 2+32.26, LINE 700 INSTALL 6 X 4 CURB INLET N 992536.8697 E 2832912.3499
704	STA 2+77.85, LINE 700 INSTALL 6 X 4 CURB INLET N 992581.8404 E 2832919.8570
705	STA 4+73.08, LINE 700 INSTALL 6 X 4 CURB INLET N 992667.1149 E 2833095.4758
706	STA 5+11.81, LINE 700 INSTALL 6 X 4 CURB INLET N 992705.1565 E 2833102.7289
801	STA 0+92.98, LINE 800 INSTALL 4 X 4 AREA INLET OPEN TO EAST N 992462.0478 E 2832967.5530

Storm Sewer Construction Notes	
Structure	Notes
802	STA 2+15.14, LINE 800 INSTALL 4 X 4 AREA INLET OPEN TO EAST & WEST N 992521.0360 E 2833074.5302
901	STA 0+35.06, LINE 900 INSTALL 6 X 4 CURB INLET N 992611.0492 E 2832900.4685
1000	STA 0+00.00, LINE 1000 INSTALL 30" HDPE FLARED END SECTION W/ TOEWALL AND 12 CU. YD. (18'X9'X2) STONE RIP-RAP USING A MIN. 100# (D50=15") STONE. PLACE FILTER FABRIC PRIOR TO INSTALLATION OF RIP-RAP. N 992433.0590 E 2832665.5966
1001	STA 0+35.00, LINE 1000 INSTALL 5 X 5 JUNCTION BOX N 992411.5375 E 2832693.1978
1002	STA 1+70.00, LINE 1000 INSTALL 8 X 4 CURB INLET N 992328.5259 E 2832799.6593
1003	STA 4+02.81, LINE 1000 INSTALL 6 X 6 CURB INLET N 992352.7296 E 2833031.2069
1004	STA 4+97.47, LINE 1000 INSTALL 6 X 5 CURB INLET N 992399.9823 E 2833113.2254
1005	STA 6+16.30, LINE 1000 INSTALL 6 X 6 CURB INLET N 992427.8021 E 2833228.7610
1101	STA 0+36.19, LINE 1100 INSTALL 6 X 4 CURB INLET N 992319.7811 E 2833046.1733
3900	STA -0+00.00, LINE 3900 INSTALL 30" HDPE FLARED END SECTION W/ TOEWALL AND 7 CU. YD (16'X8'X2.5') STONE RIP-RAP USING A MIN. 200# (D50=24") STONE. PLACE FILTER FABRIC PRIOR TO INSTALLATION OF RIP-RAP. N 992087.6378 E 2832542.7072
3901	STA 0+89.50, LINE 3900 INSTALL 4 X 5 JUNCTION BOX N 992174.2309 E 2832565.3322



CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
STREET, STORMWATER, AND MASTER  
DRAINAGE PLAN  
SE BAILEY ROAD AND SE RANSON ROAD  
LEE'S SUMMIT, MISSOURI

REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

DRAWN BY:	DATE PREPARED:
JRJ	1/22/2021

CHECKED BY:	PROJ. NUMBER:
JLL	21-138





I:\PROJECTS\2021\21-138\3.0 DWG Plans\3.0 DWG Plans\3.0 SS\21-138-SS-STORM.PFD.dwg, 5/19/2022 6:23:42 AM, 1:1




REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

STORM PROFILE  
2

SHEET  
**13**



I:\PROJECTS\2021\21-136\3.0 DWG Plans\3.0 DWG Plans\6.0 SS\21-136-SS-STORM-PP.dwg, 5/19/2022 6:24:04 AM, 11




## WATER QUALITY STRUCTURE 3901 (NOT TO SCALE)

**DETENTION STORAGE:**  
 100 YEAR, 24 HR. RAINFALL - MAXIMUM WSE = 1006.64  
 (SEE FINAL STORMWATER MGMT. PLAN)

EMERGENCY SPILLWAY FLOWLINE SET AT 0.5 FEET ABOVE MAX. WSE, SPILLWAY ELEV. = 1007.14




EMERGENCY SPILLWAY DESIGN:  
 $Q(100) = 260.19 \text{ CFS}$ ,  $Q = CLH^{3/2}$ ,  $C = 3.33$ ,  
 $L = 220 \text{ FT.}$ ,  $260.19 \text{ CFS} = 3.33 * 220 \text{ FT.} * (H^{3/2})$ ,  $H = 0.5 \text{ FT.}$

WATER SURFACE ELEVATION THROUGH SPILLWAY = 1007.64  
 + ONE (1) FOOT OF FREEBOARD = 1008.64  
 SET BASIN TOP AT 1008.64



DETENTION BASIN STORAGE VOLUME	
DESIGN STORM	VOLUME (CUBIC FEET)
2-YEAR	164,409
10-YEAR	249,634
100-YEAR	352,702

**NOTE:**  
 DETENTION / SEDIMENT BASIN SHALL BE CONSTRUCTED ALONG WITH ALL OTHER EROSION CONTROL AND SEDIMENT CONTROL DEVICES AND PRIOR TO ANY INFRASTRUCTURE BEING CONSTRUCTED.



REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022


DRAWN BY: JRL  
 CHECKED BY: JLL  
 DATE PREPARED: 12/20/21  
 PROJ. NUMBER: 21-136

**DETENTION BASIN DESIGN**


**TABLE LS-2: MINIMUM ASPHALT PAVEMENT THICKNESSES**

Street Classification	Pavement Option	AC Surface (in.)	AC Base (in.)	Aggregate Base (in.)	Chemical Subgrade Stabilization (in.)	Geogrid / Geotextile <sup>(1)</sup>
Residential Local/Access	A	2	4	6	6	--
	B	2	4	12	--	Geogrid / Geotextile
Residential Collector	A	2	5.5	6	9	--
	B	2	5.5	12	--	Geogrid / Geotextile
Commercial Industrial Local/Collector	A	2	7.5	6	9	--
	B	2	7.5	12	--	Geogrid / Geotextile

Notes:  
**(1)** Geogrid shall be polypropylene material and Geotextile shall be woven, polypropylene as shown in the City's Approved Products List



ASPHALT MIX:  
 Surface: 5-01  
 Base: 5-01



NOTE:  
 1. ASPHALT CAP OR FULL DEPTH CONCRETE SHALL BE DETERMINED BY CITY INSPECTOR.


<b>LS</b>	<b>LEE'S SUMMIT</b> MISSOURI	Date: 04/17
	PUBLIC WORKS ENGINEERING DIVISION   220 SE GREEN STREET   LEE'S SUMMIT, MO 64083	Drawn By: MIF
	<b>TRENCHING/PATCHING ROADWAYS DETAIL</b>	Checked By: DL
		<b>GEN-5</b>

LS5200

17

July 2020

PREPARED BY:



SCHLAGEL & ASSOCIATES, P.A.


CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER DRAINAGE PLAN  
 SE BAILEY ROAD AND SE RANSON ROAD  
 LEE'S SUMMIT, MISSOURI

REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

STREET DETAILS  
1

I:\PROJECTS\2021\21-1863.0 Design\3.0 DWG Plans\6.0 SS\21-136-SS-DET.dwg, 5/19/2022, 8:24:30 AM, 1:1

PREPARED BY:



SCHLAGEL & ASSOCIATES, P.A.

CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER  
 DRAINAGE PLAN  
 SE BAILEY ROAD AND SE RANSON ROAD  
 LEE'S SUMMIT, MISSOURI

REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

DRAWN BY: JRL	CHECKED BY: JLL	DATE PREPARED: 1/22/2021	PROJ. NUMBER: 21-136
---------------	-----------------	--------------------------	----------------------

**3-D VIEW TYPE A SIDEWALK/SHARED-USE RAMP**  
Not to Scale

**3-D VIEW TYPE B SIDEWALK/SHARED-USE RAMP**  
Not to Scale

**LEGEND**

- R SIDEWALK RAMP
- TS TURNING SPACE
- DETECTABLE WARNING SURFACE
- T TRANSITION

**3-D VIEW TYPE A SIDEWALK/SHARED-USE RAMP**

**3-D VIEW TYPE B SIDEWALK/SHARED-USE RAMP**

**ALTERNATE DETECTABLE SURFACE LAYOUT**

**TYPE A SIDEWALK/SHARED-USE RAMP**  
Not to Scale

**TYPE B SIDEWALK/SHARED-USE RAMP**  
Not to Scale

**SECTION A-A**

**SECTION B-B**

**SECTION C-C**

**CONTRACTION JOINT**

**JOINT DETAILS**  
Not to Scale

**SIDEWALK CURB DETAIL**  
Not to Scale

**CONTRACTION JOINT**

**ISOLATION JOINT**

**CURB & GUTTER DETAIL AT RAMP**  
Not to Scale

**GENERAL NOTES:**

- CURB RAMP OPENING, NOT INCLUDING FLARES, SHALL MATCH EXISTING SIDEWALK WIDTH AND OPENING SHALL BE AT LEAST 48" WIDE.
- USE 18" LONG #4 EPOXY COATED BARS @ 24" O.C. EMBED THE BARS 9" IN EACH DIRECTION.
- ALL RAMP, SIDEWALK, SHARED-USE PATHS SUBGRADE MUST BE OF STABLE, COMPACTED EARTH AND SHALL BE OVERLAIN WITH 4" COMPACTED DENSE GRADED AGGREGATE BASE.
- LONGITUDINAL JOINT SPACING TO MATCH WIDTH OF SIDEWALK.
- ISOLATION JOINTS SHALL BE PLACED WHERE WALK ABUTS DRIVEWAYS AND SIMILAR STRUCTURES, AND 150' CENTER MAX.
- ADA MAXIMUM RAMP SLOPE = 0.33%  
ADA MAXIMUM CROSS SLOPE = 2.0%
- HORIZONTAL EXCEPTION:** WHERE EXISTING ROAD PROFILE GRADE DOES NOT ALLOW RAMP TO MEET RAMP SLOPE REQUIREMENT OF 0.33% OR LESS, THE RAMP SHALL BE EXTENDED TO A LENGTH OF 15 FEET TO MATCH EXISTING SIDEWALK. CROSS SLOPE OF RAMP SHALL BE 1.5% ±0.5%.
- TURNING SPACES SHALL BE 1.5% ±0.5% SLOPE IN ANY DIRECTION. TURNING SPACES SHALL HAVE A MINIMUM 4'x4' TURNING AREA. TURNING SPACES WITH A SIDEWALK CURB, SHALL HAVE A 5' TURNING AREA PERPENDICULAR TO THE SIDEWALK CURB.
- FOR RETROFIT WORK, SLOPES TO BE DETERMINED IN FIELD BY CONTRACTOR AND APPROVED BY CITY INSPECTOR.
- RAMP EXTENSION AREA SHALL NOT BE USED AS TRANSITION TO EXISTING SIDEWALK. ANY TRANSITIONS REQUIRED TO MATCH RAMP TO EXISTING SIDEWALK SHALL REQUIRE REMOVAL AND REPLACEMENT OF ADDITIONAL SIDEWALK BEYOND THE RAMP AREA. SIDEWALK TRANSITION LENGTH SHALL BE EQUAL TO OR GREATER THAN THE WIDTH OF THE EXISTING SIDEWALK. RAMP EXTENSIONS SHALL BE A CONTINUOUS SLOPE.
- ALL SIDEWALK AND RAMP CONSTRUCTION SHALL MEET CURRENT PUBLIC RIGHT OF WAY ACCESSIBILITY GUIDELINES (PROWAG).

STANDARD DETAILS  
 CITY OF LEE'S SUMMIT, MO  
 LEE'S SUMMIT, JACKSON COUNTY, MO  
 PUBLIC WORKS ENGINEERING DIVISION | 230 S. GREEN STREET | LEE'S SUMMIT, MO 66643

Drawn By: MAF  
 Checked By: JS  
 Date: 05/13/21  
 Proj. #

GEN-1

STANDARD DETAILS  
 CITY OF LEE'S SUMMIT, MO  
 LEE'S SUMMIT, JACKSON COUNTY, MO  
 PUBLIC WORKS ENGINEERING DIVISION | 230 S. GREEN STREET | LEE'S SUMMIT, MO 66643

Drawn By: MAF  
 Checked By: JS  
 Date: 05/13/21  
 Proj. #

GEN-3A

**DRIVEWAY WITH BUFFER**  
NOT TO SCALE

**DRIVEWAY TYPICAL SECTION (NO SIDEWALK OR SHARED-USE PATH)**  
NOT TO SCALE

**DRIVEWAY TYPICAL SECTION (SIDEWALK OR SHARED-USE PATH WITH BUFFER)**  
NOT TO SCALE

**DRIVEWAY TYPICAL SECTION (SIDEWALK OR SHARED-USE PATH WITHOUT BUFFER)**  
NOT TO SCALE

**DRIVEWAY WITHOUT BUFFER**  
NOT TO SCALE

**GENERAL NOTES:**

- SUBGRADE SHALL BE STABLE, COMPACTED EARTH AND SHALL BE OVERLAIN WITH 4" COMPACTED DENSE GRADED AGGREGATE BASE.
- ALL DRIVE APPROACHES SHALL MEET CURRENT PUBLIC RIGHT OF WAY ACCESSIBILITY GUIDELINES (PROWAG) FOR SLOPE REQUIREMENTS WHEN SIDEWALK IS REQUIRED (SEE ADA RAMP RETROFIT DETAIL).
- JOINT AT BACK OF CURB LINE SHALL BE AN ISOLATION JOINT FOR RESIDENTIAL DRIVEWAYS.
- KCMBB 4K CONCRETE MIX IS REQUIRED FOR ALL CURBS.
- COMMERCIAL DRIVEWAYS AND DRIVEWAY APPROACHES, IN THE PUBLIC RIGHT OF WAY, SHALL BE KCMBB 4K CONCRETE MIX.
- A JOINT MUST BE INSTALLED AT THE RIGHT OF WAY BOUNDARY FOR PROPERTY DELINEATION.
- WHITE CURING COMPOUND MUST BE APPLIED UNIFORMLY TO THE CONCRETE SURFACE IMMEDIATELY AFTER FINAL FINISHING.
- 3/4" FROM TOP OF CURB TO FLOWLINE AT DRIVEWAY (TYPE CG-1 CURB ONLY). MUST MAINTAIN ORIGINAL FLOWLINE OF CURB.
- SIDEWALK ADJOINING CURB SHALL BE 6" THICK, EXTENDING 3' FROM THE DRIVEWAY.
- THE MAXIMUM WIDTH OF A RESIDENTIAL DRIVEWAY IS 36 FEET WITHIN THE RIGHT OF WAY.

STANDARD DETAILS  
 CITY OF LEE'S SUMMIT, MO  
 LEE'S SUMMIT, JACKSON COUNTY, MO  
 PUBLIC WORKS ENGINEERING DIVISION | 230 S. GREEN STREET | LEE'S SUMMIT, MO 66643

Drawn By: MAF  
 Checked By: JS  
 Date: 05/13/21  
 Proj. #

GEN-1

STANDARD DETAILS  
 CITY OF LEE'S SUMMIT, MO  
 LEE'S SUMMIT, JACKSON COUNTY, MO  
 PUBLIC WORKS ENGINEERING DIVISION | 230 S. GREEN STREET | LEE'S SUMMIT, MO 66643

Drawn By: MAF  
 Checked By: JS  
 Date: 05/13/21  
 Proj. #

GEN-3A

**STRAIGHT CURB (TYPE C-1)**

**DOWELLED CURB (TYPE DC)**

**STRAIGHT BACK CURB & GUTTER (TYPE CG-1)**

**ROLL BACK CURB & GUTTER (TYPE CG-2)**

**STRAIGHT BACK DRY CURB & GUTTER (TYPE CG-1 DRY)**

**ROLL BACK DRY CURB & GUTTER (TYPE CG-2 DRY)**

**CURB & GUTTER DETAIL AT RAMP (ADA SLOPE REQUIREMENTS)**

**CURB REPLACEMENT DETAIL**

**GENERAL NOTES:**

- 3/4" ISOLATION JOINTS WITH 3 (2'-#5 BAR) SMOOTH DOWELS SHALL BE PLACED AT RADIUS POINTS AND AT 150' INTERVALS. THESE DOWEL BARS SHALL BE GREASED AND WRAPPED ON ONE END WITH EXPANSION TUBES.
- 3" DEEP CONTRACTION JOINTS SHALL BE INSTALLED AT APPROXIMATELY 10' INTERVALS. THESE JOINTS SHALL PASS ACROSS THE ENTIRE CURB SECTION.
- CONCRETE FILL SHALL HAVE UNIFORM AND SMOOTH FINISH.
- KCMBB 4K CONCRETE SHALL BE USED FOR ALL CURB.
- ASPHALTIC CONCRETE SURFACE COURSE SHALL CONFORM TO STANDARD SPECIFICATIONS SECTION 2205.2.
- CURBS FOR NEW STREETS SHALL BE BUILT ON ASPHALT OR AGGREGATE BASE AS SHOWN IN TYPICAL SECTION DETAIL.
- WHITE CURING COMPOUND MUST BE APPLIED UNIFORMLY TO THE CONCRETE SURFACE IMMEDIATELY AFTER FINAL FINISHING.

STANDARD DETAILS  
 CITY OF LEE'S SUMMIT, MO  
 LEE'S SUMMIT, JACKSON COUNTY, MO  
 PUBLIC WORKS ENGINEERING DIVISION | 230 S. GREEN STREET | LEE'S SUMMIT, MO 66643

Drawn By: MAF  
 Checked By: JS  
 Date: 05/13/21  
 Proj. #

GEN-4

STANDARD DETAILS  
 CITY OF LEE'S SUMMIT, MO  
 LEE'S SUMMIT, JACKSON COUNTY, MO  
 PUBLIC WORKS ENGINEERING DIVISION | 230 S. GREEN STREET | LEE'S SUMMIT, MO 66643

Drawn By: MAF  
 Checked By: JS  
 Date: 05/13/21  
 Proj. #

GEN-3B

**3-D VIEW TYPE M SIDEWALK/SHARED-USE RAMP**  
Not to Scale

**3-D VIEW SIDEWALK/SHARED-USE RAMP AT DRIVEWAY**  
Not to Scale

**TYPE M SIDEWALK/SHARED-USE RAMP**  
Not to Scale

**SIDEWALK/SHARED USE RAMP AT DRIVEWAY WITH ADJOINING CURB**  
Not to Scale

**SECTION A-A**

**SECTION B-B**

**SECTION C-C**

**SIDEWALK CURB DETAIL**  
Not to Scale

**LEGEND**

- R SIDEWALK RAMP
- TS TURNING SPACE
- DETECTABLE WARNING SURFACE
- T TRANSITION

**GENERAL NOTES:**

- CURB RAMP OPENING, NOT INCLUDING FLARES, SHALL MATCH EXISTING SIDEWALK WIDTH AND OPENING SHALL BE AT LEAST 48" WIDE.
- USE 18" LONG #4 EPOXY COATED BARS @ 24" O.C. EMBED THE BARS 9" IN EACH DIRECTION.
- ALL RAMP, SIDEWALK, SHARED-USE PATHS SUBGRADE MUST BE OF STABLE, COMPACTED EARTH AND SHALL BE OVERLAIN WITH 4" COMPACTED DENSE GRADED AGGREGATE BASE.
- LONGITUDINAL JOINT SPACING TO MATCH WIDTH OF SIDEWALK.
- ISOLATION JOINTS SHALL BE PLACED WHERE WALK ABUTS DRIVEWAYS AND SIMILAR STRUCTURES, AND 150' CENTER MAX.
- ADA MAXIMUM RAMP SLOPE = 0.33%  
ADA MAXIMUM CROSS SLOPE = 2.0%
- HORIZONTAL EXCEPTION:** WHERE EXISTING ROAD PROFILE GRADE DOES NOT ALLOW RAMP TO MEET RAMP SLOPE REQUIREMENT OF 0.33% OR LESS, THE RAMP SHALL BE EXTENDED TO A LENGTH OF 15 FEET TO MATCH EXISTING SIDEWALK. CROSS SLOPE OF RAMP SHALL BE 1.5% ±0.5%.
- TURNING SPACES SHALL BE 1.5% ±0.5% SLOPE IN ANY DIRECTION. TURNING SPACES SHALL HAVE A MINIMUM 4'x4' TURNING AREA. TURNING SPACES WITH A SIDEWALK CURB, SHALL HAVE A 5' TURNING AREA PERPENDICULAR TO THE SIDEWALK CURB.
- FOR RETROFIT WORK, SLOPES TO BE DETERMINED IN FIELD BY CONTRACTOR AND APPROVED BY CITY INSPECTOR.
- RAMP EXTENSION AREA SHALL NOT BE USED AS TRANSITION TO EXISTING SIDEWALK. ANY TRANSITIONS REQUIRED TO MATCH RAMP TO EXISTING SIDEWALK SHALL REQUIRE REMOVAL AND REPLACEMENT OF ADDITIONAL SIDEWALK BEYOND THE RAMP AREA. SIDEWALK TRANSITION LENGTH SHALL BE EQUAL TO OR GREATER THAN THE WIDTH OF THE EXISTING SIDEWALK. RAMP EXTENSIONS SHALL BE A CONTINUOUS SLOPE.
- ALL SIDEWALK AND RAMP CONSTRUCTION SHALL MEET CURRENT PUBLIC RIGHT OF WAY ACCESSIBILITY GUIDELINES (PROWAG).

STANDARD DETAILS  
 CITY OF LEE'S SUMMIT, MO  
 LEE'S SUMMIT, JACKSON COUNTY, MO  
 PUBLIC WORKS ENGINEERING DIVISION | 230 S. GREEN STREET | LEE'S SUMMIT, MO 66643

Drawn By: MAF  
 Checked By: JS  
 Date: 05/13/21  
 Proj. #


GEN-4

STANDARD DETAILS  
 CITY OF LEE'S SUMMIT, MO  
 LEE'S SUMMIT, JACKSON COUNTY, MO  
 PUBLIC WORKS ENGINEERING DIVISION | 230 S. GREEN STREET | LEE'S SUMMIT, MO 66643

Drawn By: MAF  
 Checked By: JS  
 Date: 05/13/21  
 Proj. #

GEN-3B





PIPE DIAM.	MINIMUM RECOMMENDED COVER BASED ON VEHICLE LOADING CONDITIONS	
	SURFACE LIVE LOADING CONDITION	
	H-25	HEAVY CONSTRUCTION (75T AXLE LOAD) *
12" - 48"	12"	48"
54" - 60"	24"	60"


\* VEHICLES IN EXCESS OF 75T MAY REQUIRE ADDITIONAL COVER

RECOMMENDED MINIMUM TRENCH WIDTHS


PIPE DIAM.	MIN. TRENCH WIDTH
4"	21"
6"	23"
8"	26"
10"	28"
12"	30"
15"	34"
18"	39"
24"	48"
30"	56"
36"	64"
42"	72"
48"	80"
54"	88"
60"	96"

NOTES:

- ALL PIPE SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321, "STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF THERMOPLASTIC PIPE FOR SEWERS AND OTHER GRAVITY FLOW APPLICATIONS", LATEST EDITION
- MEASURES SHOULD BE TAKEN TO PREVENT MIGRATION OF NATIVE FINES INTO BACKFILL MATERIAL, WHEN REQUIRED.
- FOUNDATION:** WHERE THE TRENCH BOTTOM IS UNSTABLE, THE CONTRACTOR SHALL EXCAVATE TO A DEPTH REQUIRED BY THE ENGINEER AND REPLACE WITH SUITABLE MATERIAL AS SPECIFIED BY THE ENGINEER. AS AN ALTERNATIVE AND AT THE DISCRETION OF THE DESIGN ENGINEER, THE TRENCH BOTTOM MAY BE STABILIZED USING A GEOTEXTILE MATERIAL.
- BEDDING:** SUITABLE MATERIAL SHALL BE CLASS I, II OR III. THE CONTRACTOR SHALL PROVIDE DOCUMENTATION FOR MATERIAL SPECIFICATION TO ENGINEER. UNLESS OTHERWISE NOTED BY THE ENGINEER, MINIMUM BEDDING THICKNESS SHALL BE 4" (100mm) FOR 4"-24" (100mm-600mm); 6" (150mm) FOR 30"-60" (750mm-900mm).
- INITIAL BACKFILL:** SUITABLE MATERIAL SHALL BE CLASS I, II OR III IN THE PIPE ZONE EXTENDING NOT LESS THAN 6" ABOVE CROWN OF PIPE. THE CONTRACTOR SHALL PROVIDE DOCUMENTATION FOR MATERIAL SPECIFICATION TO ENGINEER. MATERIAL SHALL BE INSTALLED AS REQUIRED IN ASTM D2321, LATEST EDITION.
- MINIMUM COVER:** MINIMUM COVER, H, IN NON-TRAFFIC APPLICATIONS (GRASS OR LANDSCAPE AREAS) IS 12" FROM THE TOP OF PIPE TO GROUND SURFACE. ADDITIONAL COVER MAY BE REQUIRED TO PREVENT FLOATATION. FOR TRAFFIC APPLICATIONS, MINIMUM COVER, H, IS 12" UP TO 48" DIAMETER PIPE AND 24" OF COVER FOR 54"-60" DIAMETER PIPE, MEASURED FROM TOP OF PIPE TO BOTTOM OF FLEXIBLE PAVEMENT OR TO TOP OF RIGID PAVEMENT.



- GENERAL NOTES:
- LOCATE RING AND COVER OVER OUTLET ON BLANK WALL.
  - USE 3/4" CHAMFER ON ALL EXPOSED CONCRETE CORNERS.
  - FLOOR OF INLET GROUTED AND SHAPED TO MATCH PIPE INVERT TO PROVIDE SMOOTH FLOW.
  - STEPS REQUIRED AT 16" O.C. WHEN DEPTH FROM TOP OF CASTING TO INVERT EXCEEDS 3' ON BLANK WALL IF POSSIBLE.
  - BOXOUTS WILL NOT BE ALLOWED TO PROJECT THROUGH THE CORNERS OF THE STRUCTURE.
  - THE MINIMUM REINFORCING SHALL BE 1 H-BAR OVER A CAST-IN-PLACE PIPE AND 2 H-BARS OVER A PRECAST BOXOUT.
  - SHOW FIELD INLET ORIENTATION ON PLANS PLUS NUMBER AND SIDE OF OPENINGS.
  - PRECAST LIDS SHALL BE PINNED, SEALED WITH NON-SHRINKABLE GROUT AND REMOVABLE FOR FUTURE MAINTENANCE.
  - FOR RING AND COVER SEE THE STORMWATER APPROVED PRODUCT LIST.



\*COVER AND FRAME MODEL INFORMATION REFER TO THE STORMWATER APPROVED PRODUCTS LIST.

**LEE'S SUMMIT MISSOURI**  
PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64083

DATE: 04/17  
DRAWN BY: MJF  
CHECKED BY: DL

**STM-7**

**LEE'S SUMMIT MISSOURI**  
PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64083

STANDARD DETAILS  
CITY OF LEE'S SUMMIT, MO  
LEE'S SUMMIT, JACKSON COUNTY, MO

FIELD INLET DETAIL  
STM-2

**SCHLAGEL**  
ENGINEERS PLANNERS SURVEYORS LANDSCAPE ARCHITECTS  
14920 West 107th Street • Lenexa, Kansas 66215  
(913) 492-5158 • Fax: (913) 492-8400  
WWW.SCHLAGELASSOCIATES.COM  
Missouri State Certificates of Authority  
#E200200360P-F #LAC2001005237 #LS200200869F

PREPARED BY:  
**JAMES L. LONG**  
PROFESSIONAL ENGINEER  
NUMBER PE-2014010495  
5/19/2022  
SCHLAGEL & ASSOCIATES, P.A.


CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
STREET, STORMWATER, AND MASTER  
DRAINAGE PLAN  
SE BAILEY ROAD AND SE RANSON ROAD  
LEE'S SUMMIT, MISSOURI

REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

DRAWN BY:	JRJ
CHECKED BY:	JLL
DATE PREPARED:	1/22/2021
PROJ. NUMBER:	21-136



STORM DETAILS

I:\PROJECTS\2021\21-136\3.0 Design\3.0 DWG Plans\6.0 SS\21-136-SS-DET.dwg, 5/19/2022, 8:24:46 AM, 1:1





**LEE'S SUMMIT MISSOURI**  
 PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

STANDARD DETAILS  
 CITY OF LEE'S SUMMIT, MO  
 LEE'S SUMMIT, JACKSON COUNTY, MO  
 CURB INLET DETAIL  
 Drawn By: MIF  
 Checked By: DL  
 Date: 04/27  
 Proj #: STM-1



**LEE'S SUMMIT MISSOURI**  
 PUBLIC WORKS ENGINEERING DIVISION | 220 SE GREEN STREET | LEE'S SUMMIT, MO 64063

STANDARD DETAILS  
 CITY OF LEE'S SUMMIT, MO  
 LEE'S SUMMIT, JACKSON COUNTY, MO  
 JUNCTION BOX DETAIL  
 Drawn By: MIF  
 Checked By: DL  
 Date: 04/17  
 Proj #: STM-3



**SCHLAGEL**  
 ENGINEERS PLANNERS SURVEYORS LANDSCAPE ARCHITECTS  
 14920 West 107th Street • Lenexa, Kansas 66215  
 (913) 492-5158 • Fax: (913) 492-8400  
 WWW.SCHLAGELASSOCIATES.COM  
 Missouri State Certificates of Authority  
 #E220020360P #LAC201005237 #LS200200869F

PREPARED BY:  
 JAMES L. LONG  
 NUMBER PE-2014010495  
 5/19/2022  
 SCHLAGEL & ASSOCIATES, P.A.

CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER  
 DRAINAGE PLAN  
 SE BAILEY ROAD AND SE RANSON ROAD  
 LEE'S SUMMIT, MISSOURI


REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

DRAWN BY: JRJ  
 CHECKED BY: JLL  
 DATE PREPARED: 1/22/2021  
 PROJ. NUMBER: 21-138

**STORM DETAILS**  
 2

SHEET  
 18

PREPARED BY:



SCHLAGEL & ASSOCIATES, P.A.

**CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER DRAINAGE PLAN**  
**SE BAILEY ROAD AND SE RANSON ROAD  
 LEE'S SUMMIT, MISSOURI**


REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

DRAWN BY:	JRJ
CHECKED BY:	JLL
DATE PREPARED:	1/22/2021
PROJ. NUMBER:	21-136

SIGNAGE PLAN

SHEET

**19**









STANDARD ABBREVIATION LISTS

NAMED STREETS		NUMBERED STREETS	
AVENUE	Ave	FIRST	ST
BOULEVARD	Blvd	SECOND	ND
CIRCLE	Cir	THIRD	RD
CREEK	Cr	FOURTH TO TENTH	TH
COURT	Ct		
CROSSING	Xing		
DRIVE	Dr		
HIGHWAY	Hwy		
LANE	Ln		
PARKWAY	Pkwy		
PLACE	Pl		
ROAD	Rd		
STREET	St		
TERRACE	Ter		
TRAIL	Trl		
WAY	Way		




NAMED STREET NAME SIGN DETAIL  
 \* USE HIGHWAY SERIES B (MIXED CASE) IN LIEU OF SERIES C IF NECESSARY TO FIT TEXT ON A 36" SIGN BLANK.

STREET NAME SIGN FACE DETAILS  
 POST MOUNTED 2-LANE ALL SPEEDS AND MULTI-LANE UNDER 40 MPH




NAMED STREET NAME SIGN DETAIL  
 \* USE HIGHWAY SERIES B (MIXED CASE) IN LIEU OF SERIES C IF NECESSARY TO FIT TEXT ON A 36" SIGN BLANK.


STREET NAME SIGN FACE DETAILS  
 POST MOUNTED MULTI-LANE GREATER THAN 40 MPH




STREET NAME SIGN BLANK DETAILS  
 FOR MOUNTING ON SQUARE STEEL POSTS




NUMBERED STREET NAME SIGN DETAIL  
 STREET NAME SIGN FACE DETAILS  
 POST MOUNTED 2-LANE ALL SPEEDS AND MULTI-LANE UNDER 40 MPH



NUMBERED STREET NAME SIGN DETAIL  
 STREET NAME SIGN FACE DETAILS  
 POST MOUNTED MULTI-LANE GREATER THAN 40 MPH




ARROW DETAIL



PRIVATE STREET TAG DETAIL

- NOTES:
- FOR ALL STREET NAME SIGNS, THE LEGEND SHALL BE WHITE AND THE BACKGROUND SHALL BE GREEN.
  - ARROWS SHALL BE ADDED TO STREET NAME SIGNS WHERE THE NAME OF A STREET CHANGES AT AN INTERSECTION. STREET NAME SIGNS WITH ARROWS ARE TO BE INSTALLED ON EACH SIDE OF THE INTERSECTION TO INDICATE THE CHANGE IN NAMES. ARROWS SHALL BE WHITE.
  - THE "PRIVATE STREET" TAG SHOULD BE ADDED TO THE END OF STREET NAME SIGNS TO INDICATE WHERE A STREET THAT IS OUTSIDE THE RIGHT-OF-WAY INTERSECTS A PUBLIC STREET. THE BACKGROUND FOR THE "PRIVATE STREET" TAG SHALL BE YELLOW.
  - MULTI-LANE IS DEFINED AS HAVING 2 LANES OR MORE IN EACH DIRECTION, EXCLUDING TURN LANES.
  - OVERHEAD SIGN DETAILS MAY BE FOUND ON THE SIGNAL HEAD MOUNTING DETAIL.



SQUARE STEEL POST MOUNTING DETAILS

Width	Sign Name	Post Type	Width	Sign Name	Post Type
66"	SE Bailey Farms Pkwy	D3-1 (SP-1)	36"	SE Cronin St	D3-1 (SP-5)
48"	SE Arboretum Dr	D3-1 (SP-3)	30"	SE Silo St	D3-1 (SP-6)
48"	SE Windbreak Dr	D3-1 (SP-3)			

STREET NAME SIGN INVENTORY

Project: **LEE'S SUMMIT MISSOURI**  
 Description: **STANDARD DETAILS**  
 Sheet Name: **STREET NAME SIGNS**  
 Drawn By: BWC  
 Checked By: MKP  
 Date: 11/2019  
 Project#: STD DETAILS  
**3 OF 3**  
**SN-3**

**SCHLAGEL**  
 ENGINEERS PLANNERS SURVEYORS LANDSCAPE ARCHITECTS  
 14920 West 107th Street • Lenexa, Kansas 66215  
 (913) 492-5158 • Fax: (913) 492-8400  
 WWW.SCHLAGELASSOCIATES.COM  
 Missouri State Certificate of Authority  
 #E200203690F #LAC201005237 #LS200200869F


PREPARED BY:  
  
 SCHLAGEL & ASSOCIATES, P.A.

CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER DRAINAGE PLAN  
 SE BAILEY ROAD AND SE RANSON ROAD  
 LEE'S SUMMIT, MISSOURI

REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022
12/20/2021	DATE PREPARED
21-136	PROJ. NUMBER

STREET NAME SIGN DETAILS

SHEET



ENGINEERS PLANNERS SURVEYORS LANDSCAPE ARCHITECTS  
 14920 West 107th Street • Lenexa, Kansas 66215  
 (913) 492-5158 • Fax: (913) 492-8400  
 WWW.SCHLAGELASSOCIATES.COM  
 Missouri State Certificates of Authority  
 #E2002003600F #LAC201005237 #LS200200869F

**SCHLAGEL**  
 ENGINEERS PLANNERS SURVEYORS LANDSCAPE ARCHITECTS  
 14920 West 107th Street • Lenexa, Kansas 66215  
 (913) 492-5158 • Fax: (913) 492-8400  
 WWW.SCHLAGELASSOCIATES.COM  
 Missouri State Certificates of Authority  
 #E2002003600F #LAC201005237 #LS200200869F

PREPARED BY:  
  
 5/19/2022  
 SCHLAGEL & ASSOCIATES, P.A.

CORNERSTONE AT BAILEY FARMS, FIRST PLAT  
 STREET, STORMWATER, AND MASTER DRAINAGE PLAN  
 SE BAILEY ROAD AND SE RANSON ROAD  
 LEE'S SUMMIT, MISSOURI

REVISION DATE	DESCRIPTION
02/03/2022	PER CITY COMMENTS DATED 01/10/2022
04/20/2022	PER CITY COMMENTS DATED 02/28/2022
05/19/2022	PER CITY COMMENTS DATED 05/13/2022

OM-4 SIGN  
 DETAILS

SHEET  
**23**



30"  
 R1-1  
 STOP SIGN

