

#### **Stormwater Memorandum**

for:

#### **D-Bat**

540 NE Town Centre Drive Lee's Summit, MO 64086

Prepared for: WHD Management PO Box 1059 Lee's Summit, MO 64063

Prepared by:
Davidson Architecture & Engineering, LLC
Paul A. Miller, PE
4301 Indian Creek Parkway
Overland Park, Kansas 66207
913.451.9390 (phone)
913.451.9391 (fax)
www.davidsonae.com









May 20th, 2022

Loic Nguinguiri, I.E. City of Lee's Summit 220 SE Green St Lee's Summit. MO 64063

Re: PL2022043

D-Bat - Town Centre Lot 1C

Lee's Summit, MO

Mr. Nguinguiri,

This letter is intended to accompany the approved Micro Storm Water Study for Lot 1 of Lee's Summit's Town Centre Development and illustrate how the stormwater runoff from the D-Bat Facility will be managed.

The regional detention and private stormwater systems for the entire Town Centre Lot 1 Development, which includes Lots 1A, 1B, 1C & Tract A, are designed to handle the runoff from the fully developed site once all future phases of construction are completed. The D-Bat facility is located on Lot 1C. The Proposed Drainage Area Map for the entire development is attached to this memorandum.

Runoff from the D-Bat site will sheet flow away from the proposed building and drain into private curb inlets located along the back of the curb of the parking lot. The runoff will continue through 15" and 18" HDPE private storm lines and ultimately discharge into the regional detention basin for the entire development. The roof of the proposed building is pitched to drain runoff from the south to the north and discharge through gutters and downspouts on the north side of the building. The runoff will then collect in the gutters of the privates drives north of the building and will flow into private curb inlets and eventually into the detention basin.

Discharge from the detention basin will be controlled by an outlet structure that is designed to control the discharge from the 90% mean annual event to meet the minimum forty-hour extended detention requirement for comprehensive control. All runoff from the D-Bat facility will pass through the detention basin and be subject to the minimum forty-hour extended detention requirement.

The D-Bat Property, which is located on Lot 1C of the Town Centre Development, is made up of 1.99 acres that is currently completely pervious. After development, 1.41 of those acres will be impervious with the addition of the building, parking, and associated infrastructure. The existing peak flow rates from Lot 1C are 3.08 cfs & 4.67 cfs for the 10-year and 100-year storm events, respectively, and sheet flows to the north into an existing pond. After the development of the site and with the increase in impervious ground cover, peak flow rates from the site will increase to 7.50 cfs & 11.37 cfs for the 10-year and 100-year storm events, respectively. The runoff will then







be directed to the proposed regional detention basin and discharge from the basin's outlet structure at a rate less than those specified for the Comprehensive Control Detention Strategy in KCAPWA Section 5608.4.C.1. Please refer to the approved Micro Storm Water Study for Lot 1 of Lee's Summit's Town Centre Development for the complete detention basin calculations and discharge rates. The existing and proposed peak runoff rates and hydrographs for the D-Bat development have been attached to this memorandum.

In conclusion, the proposed D-Bat Facility located on Lot 1C of the Town Centre Development will increase the amount of impervious surface area on Lot 1C by 1.41 acres. An extended dry detention basin will be added to Tract A of the Lee's Summit Town Centre Development to reduce site runoff due to the increase in impervious area. A new private storm sewer system will be added to convey the runoff into the on-site detention basin and eventually into the detention basin on the neighboring property to the east.

Please feel free to contact me with any questions.

Sincerely,

Jon Prueter, E.I.T. jon@davidsonae.com

Davidson Architecture & Engineering

4301 Indian Creek Parkway Overland Park, KS 66207

P: 913.451.9390


Paul A. Miller, P.E. paul@davidsonae.com

Davidson Architecture & Engineering

4301 Indian Creek Parkway Overland Park, KS 66207

P: 913.451.9390





guy wire

end section



 $\boldsymbol{\omega}$ date 02.18.2022 drawn by JMP checked by PAM revisions

development for

sheet number **C3.3** drawing type FDP

project number 20231

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

Thursday, 05 / 19 / 2022

Watershed Model Schematic	1
Hydrograph Return Period Recap	2
2 - Year Summary Report Hydrograph Reports Hydrograph No. 1, Rational, D-Bat Existing Runoff Hydrograph No. 2, Rational, D-Bat Proposed Runoff	4
10 - Year Summary Report Hydrograph Reports Hydrograph No. 1, Rational, D-Bat Existing Runoff	7
Hydrograph No. 2, Rational, D-Bat Proposed Runoff	8
100 - Year Summary Report	<b>10</b>
IDF Report	12

# **Watershed Model Schematic**





#### **Legend**

Hyd.OriginDescription1RationalD-Bat Existing Runoff2RationalD-Bat Proposed Runoff

Project: New.gpw

Thursday, 05 / 19 / 2022

# Hydrograph Return Period Recap

yd.	Hydrograph	Inflow		Hydrograph							
lo. type (origin)	hyd(s)	1-yr	2-yr	3-yr	5-yr	10-yr	25-yr	50-yr	100-yr	Description	
1	Rational		1.511	2.216		2.725	3.084	3.782	3.997	4.672	D-Bat Existing Runoff
2	Rational		3.678	5.392		6.632	7.503	9.204	9.725	11.37	D-Bat Proposed Runoff

Proj. file: New.gpw

Thursday, 05 / 19 / 2022

# **Hydrograph Summary Report**

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

lyd. lo.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	Rational	2.216	1	15	1,994				D-Bat Existing Runoff
2	Rational	5.392	1	15	4,853				D-Bat Proposed Runoff
	w.gpw					Period: 2 Ye			05 / 19 / 2022

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

Thursday, 05 / 19 / 2022


#### Hyd. No. 1

**D-Bat Existing Runoff** 

= 2.216 cfsHydrograph type = Rational Peak discharge Storm frequency = 2 yrsTime to peak = 15 min Time interval = 1 min Hyd. volume = 1,994 cuft

Drainage area Runoff coeff. = 1.990 ac= 0.3

Tc by User = 15.00 min Intensity = 3.712 in/hrIDF Curve = Olathe KS.IDF Asc/Rec limb fact = 1/1




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

Thursday, 05 / 19 / 2022

#### Hyd. No. 2

#### **D-Bat Proposed Runoff**

Hydrograph type = Rational Peak discharge = 5.392 cfsStorm frequency = 2 yrsTime to peak = 15 min Time interval = 1 min Hyd. volume = 4.853 cuftRunoff coeff. Drainage area = 1.990 ac= 0.73Tc by User = 15.00 min Intensity = 3.712 in/hrIDF Curve = Olathe KS.IDF Asc/Rec limb fact = 1/1



# **Hydrograph Summary Report**

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

lyd. Io.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	Rational	3.084	1	15	2,775				D-Bat Existing Runoff
2	Rational	7.503	1	15	6,753				D-Bat Proposed Runoff
Ne	w.gpw				Return I	Period: 10 \	⁄ear	Thursday,	05 / 19 / 2022

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

Thursday, 05 / 19 / 2022


#### Hyd. No. 1

**D-Bat Existing Runoff** 

Hydrograph type = Rational Peak discharge = 3.084 cfsStorm frequency = 10 yrsTime to peak = 15 min Time interval = 1 min Hyd. volume = 2,775 cuft

Drainage area Runoff coeff. = 1.990 ac= 0.3

= 5.165 in/hrTc by User = 15.00 min Intensity IDF Curve = Olathe KS.IDF Asc/Rec limb fact = 1/1



Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

Thursday, 05 / 19 / 2022

#### Hyd. No. 2


**D-Bat Proposed Runoff** 

Hydrograph type = Rational
Storm frequency = 10 yrs
Time interval = 1 min
Drainage area = 1.990 ac
Intensity = 5.165 in/hr
IDF Curve = Olathe KS.IDF

Peak discharge = 7.503 cfs
Time to peak = 15 min
Hyd. volume = 6,753 cuft
Runoff coeff. = 0.73
Tc by User = 15.00 min

= 1/1

Asc/Rec limb fact



# **Hydrograph Summary Report**

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

								bw Hydrographs Extension for Autodesk® Civil 3D® by Autodesk,				
lyd. lo.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description			
1	Rational	4.672	1	15	4,205				D-Bat Existing Runoff			
2	Rational	11.37	1	15	10,231				D-Bat Proposed Runoff			
New.gpw					Return P	eriod: 100	Year	Thursday, 0	Thursday, 05 / 19 / 2022			

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

Thursday, 05 / 19 / 2022


#### Hyd. No. 1

**D-Bat Existing Runoff** 

Hydrograph type = Rational Peak discharge = 4.672 cfsStorm frequency = 100 yrsTime to peak = 15 min Time interval = 1 min Hyd. volume = 4,205 cuft

Runoff coeff. Drainage area = 1.990 ac= 0.3

Intensity = 7.825 in/hrTc by User = 15.00 min IDF Curve = Olathe KS.IDF Asc/Rec limb fact = 1/1




Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

Thursday, 05 / 19 / 2022

#### Hyd. No. 2

#### **D-Bat Proposed Runoff**

= 11.37 cfsHydrograph type = Rational Peak discharge Storm frequency = 100 yrsTime to peak = 15 min Time interval = 1 min Hyd. volume = 10,231 cuft Drainage area Runoff coeff. = 0.73= 1.990 ac= 7.825 in/hrTc by User = 15.00 min Intensity **IDF** Curve = Olathe KS.IDF Asc/Rec limb fact = 1/1



# **Hydraflow Rainfall Report**

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

Thursday, 05 / 19 / 2022

Return Period	Intensity-Du	Intensity-Duration-Frequency Equation Coefficients (FHA)										
(Yrs)	В	D	E	(N/A)								
1	72.6358	19.6000	0.9472									
2	110.7137	16.5000	0.9842									
3	0.0000	0.0000	0.0000									
5	168.3971	19.5000	1.0189									
10	171.3956	18.7000	0.9956									
25	10382.7998	50.1998	1.7718									
50	237.3568	20.0000	1.0036									
100	86.2939	6.3000	0.7848									

File name: Olathe KS.IDF

#### Intensity = $B / (Tc + D)^E$

Return	Intensity Values (in/hr)													
Period (Yrs)	5 min	10	15	20	25	30	35	40	45	50	55	60		
1	3.50	2.94	2.53	2.23	1.99	1.80	1.64	1.51	1.40	1.31	1.22	1.15		
2	5.41	4.40	3.71	3.21	2.83	2.53	2.29	2.09	1.92	1.78	1.66	1.55		
3	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
5	6.47	5.35	4.56	3.98	3.52	3.16	2.86	2.62	2.41	2.24	2.08	1.95		
10	7.33	6.06	5.17	4.50	3.99	3.58	3.25	2.97	2.74	2.54	2.37	2.22		
25	8.51	7.30	6.34	5.56	4.92	4.39	3.94	3.56	3.24	2.96	2.71	2.50		
50	9.38	7.81	6.69	5.85	5.20	4.68	4.25	3.90	3.60	3.34	3.12	2.92		
100	12.87	9.65	7.83	6.63	5.79	5.15	4.65	4.25	3.93	3.65	3.41	3.21		

Tc = time in minutes. Values may exceed 60.

Precip. file name: P:\DAE Civil\Hydraflow Storm Sewer\SCS 24-hr Rainfall.pcp

	Rainfall Precipitation Table (in)												
Storm Distribution	1-yr	2-yr	3-yr	5-yr	10-yr	25-yr	50-yr	100-yr					
SCS 24-hour	2.85	3.50	0.00	4.50	5.30	6.10	6.90	7.50					
SCS 6-Hr	0.00	1.80	0.00	0.00	2.60	2.90	0.00	4.00					
Huff-1st	0.00	1.55	0.00	2.75	4.00	5.38	6.50	8.00					
Huff-2nd	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00					
Huff-3rd	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00					
Huff-4th	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00					
Huff-Indy	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00					
Custom	0.00	1.75	0.00	2.80	3.90	5.25	6.00	7.10					