

A17-RHS1

RAB



PS4-11-15D2

RAB



Technical Specifications (continued)

Construction

Anchor Bolt:

Galvanized anchor bolts and galvanized hardware and anchor bolt template. All bolts have a 3" hook.

Anchor Bolt Templates:

WARNING Template must be printed on 11" x 17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available <u>online</u>.



Bolts can be pre-shipped upon request for additional freight charge

Max EPA's/Max Weights:

70MPH 17.4 ft./450 lb. 80MPH 12.5 ft./440 lb. 90MPH 9.0 ft./440 lb. 100MPH 6.6 ft./440 lb. 110MPH 4.8 ft./435 lb. 120MPH 3.4 ft./435 lb. 130MPH 2.3 ft./435 lb. 140MPH 1.4 ft./430 lb. 150MPH 0.8 ft./420 lb

Other

Terms of Sale:

Pole Terms of Sale is available online.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Features

Designed for ground mounting

Heavy duty TGIC polyester coating

Reinforced hand holes with grounding lug and removable cover for easy wiring access

Pole caps, base covers & bolts are sold separately

Custom manufactured for each application

