

STRUCTURAL CALCULATIONS FOR :**Paragon Container Bar
Lee's Summit, MO**

<u>Section</u>	<u>Description</u>	<u>Page</u>
A	Loads	9
B	Overturn Check	2
C	Anchorage Design	7

**RELEASED FOR CONSTRUCTION**

As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri

12/17/2024

PRCOM20246244



PROJECT RECORD

BSE Structural Engineers LLC
9911 Pflumm Road
Lenexa, Kansas 66215
Phone 913.492.7400
www.BSEstructural.com

From: Travis Jennings - BSE
To: Whom It May Concern
RE: Paragon Container Bar – Overturning Assessment

Date: 11/8/2024
Project No: 24-385

BSE was asked by Finkle + Williams to check the overturning potential of this new container structure against design lateral forces as determined based on the governing International Building Code (IBC) and the American Society of Civil Engineers Minimum Design Loads for Buildings and Other Structures (ASCE 7). We also provide our analysis and design of the container connection points to the existing paving slab design by others.

RELEASED FOR CONSTRUCTION
As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri


12/17/2024

PLAN NOTE LEGEND

- [A] TEXT NOTE
[B] TEXT NOTE


CONSTRUCTION GENERAL NOTES

1. TBD




6 RIGHT ELEVATION

A1.1 SCALE: 1/4" = 1'-0"




4 REAR ELEVATION

A1.1 SCALE: 1/4" = 1'-0"




5 LEFT ELEVATION

A1.1 SCALE: 1/4" = 1'-0"




3 FRONT ELEVATION

A1.1 SCALE: 1/4" = 1'-0"



7 CROSS SECTION

A1.1 SCALE: 1/4" = 1'-0"




2 RCP

A1.1 SCALE: 1/4" = 1'-0"

RELEASED FOR CONSTRUCTION
As Noted on Plan Review
Development Services Department
Lee's Summit, Missouri
12/17/2024

EXCERPT FROM ARCH
DRAWINGS PROVIDED TO
BSE ON 11/4/24
CONTAINER STRUCTURE IS
NOT BY BSE



1 FLOOR PLAN

A1.1 SCALE: 1/4" = 1'-0"

PARAGON -
CONTAINER BAR

1401 NW River Rd.
Lee's Summit, MO 64081

Project No.: 10250.08
Date: 10/25/2024
Issued For: PERMIT
Revision: 01

Project Name: PARAGON -
CONTAINER BAR

Project Location: 1401 NW River Rd.
Lee's Summit, MO 64081

Project Description: PARAGON -
CONTAINER BAR

Project Status: 01

Project Owner: PARAGON -
CONTAINER BAR

Project Architect: FINKLE + WILLIAMS
ARCHITECTURE

Project Engineer: GSA

Project Designer: N/A

Project Foundation: N/A

Project Structural: N/A

Project Plumbing: PMAR

Project Mechanical: PMAR

Project Electrical: PMAR

Project Fire Protection: N/A

Project Contractor: ATSS

Project Registration: 10250.08

Project Not for Construction: 10250.08

Project Finkle + Williams
Architecture

Project Civil: GSA

Project Landscape: N/A

Project Foundations: N/A

Project Structural: N/A

Project Plumbing: PMAR

Project Mechanical: PMAR

Project Electrical: PMAR

Project Fire Protection: N/A

Project Contractor: ATSS

Project Registration: 10250.08

Project Not for Construction: 10250.08

Project Finkle + Williams
Architecture

Project Civil: GSA

Project Landscape: N/A

Project Foundations: N/A

Project Structural: N/A

Project Plumbing: PMAR

Project Mechanical: PMAR

Project Electrical: PMAR

Project Fire Protection: N/A

Project Contractor: ATSS

Project Registration: 10250.08

Project Not for Construction: 10250.08

Project Finkle + Williams
Architecture

Project Civil: GSA

Project Landscape: N/A

Project Foundations: N/A

Project Structural: N/A

Project Plumbing: PMAR

Project Mechanical: PMAR

Project Electrical: PMAR

Project Fire Protection: N/A

Project Contractor: ATSS

Project Registration: 10250.08

Project Not for Construction: 10250.08

Project Finkle + Williams
Architecture

Project Civil: GSA

Project Landscape: N/A

Project Foundations: N/A

Project Structural: N/A

Project Plumbing: PMAR

Project Mechanical: PMAR

Project Electrical: PMAR

Project Fire Protection: N/A

Project Contractor: ATSS

Project Registration: 10250.08

Project Not for Construction: 10250.08

Project Finkle + Williams
Architecture

Project Civil: GSA

Project Landscape: N/A

Project Foundations: N/A

Project Structural: N/A

Project Plumbing: PMAR

Project Mechanical: PMAR

Project Electrical: PMAR

Project Fire Protection: N/A

Project Contractor: ATSS

Project Registration: 10250.08

Project Not for Construction: 10250.08

DESIGN LOADS


RELEASED FOR CONSTRUCTION
As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri

12/17/2024

As Noted on Plan Review

12/17/2024





ASCE Hazards Report

Address:

No Address at This Location



Standard: ASCE/SEI 7-16

Risk Category: II

Soil Class: D - Stiff Soil

Latitude: 38.941479

Longitude: -94.441245

Elevation: 808.513497020725 ft (NAVD 88)


Wind

Results:

Wind Speed

109 Vmph

10-year MRI

76 Vmph

25-year MRI

83 Vmph

50-year MRI

88 Vmph

100-year MRI

94 Vmph

Data Source:

ASCE/SEI 7-16, Fig. 26.5-1B and Figs. CC.2-1–CC.2-4, and Section 26.5.2

Date Accessed:

Fri Nov 08 2024





Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-16 Standard. Wind speeds correspond to approximately a 7% probability of exceedance in 50 years (annual exceedance probability = 0.00143, MRI = 700 years).

Site is not in a hurricane-prone region as defined in ASCE/SEI 7-16 Section 26.2.

Site Soil Class: D - Stiff Soil

Results:

S_S :	0.099	S_{D1} :	0.109
S_1 :	0.068	T_L :	12
F_a :	1.6	PGA :	0.047
F_v :	2.4	PGA _M :	0.075
S_{MS} :	0.158	F_{PGA} :	1.6
S_{M1} :	0.164	I_e :	1
S_{DS} :	0.105	C_v :	0.7



Data Accessed: Fri Nov 08 2024

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-16 and ASCE/SEI 7-16 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-16 Ch. 21 are available from USGS.

RELEASED FOR CONSTRUCTION
As Noted on Plan Review


Development Services Department
Lee's Summit, Missouri
12/17/2024

WIND LOADING

In accordance with ASCE7-16

Using the directional design method

Tedds calculation version 2.1.14



Building data

Type of roof Flat
Length of building $b = 40.00$ ft
Width of building $d = 8.00$ ft
Height to eaves $H = 9.50$ ft
Mean height $h = 9.50$ ft

General wind load requirements

Basic wind speed $V = 110.0$ mph
Risk category II
Velocity pressure exponent coef (Table 26.6-1) $K_d = 0.85$
Ground elevation above sea level $z_{gl} = 809$ ft
Ground elevation factor $K_e = \exp(-0.0000362 \times z_{gl}/1\text{ft}) = 0.97$
Exposure category (cl 26.7.3) B
Enclosure classification (cl.26.12) Enclosed buildings
Internal pressure coef +ve (Table 26.13-1) $GC_{pi_p} = 0.18$
Internal pressure coef -ve (Table 26.13-1) $GC_{pi_n} = -0.18$
Gust effect factor $G_f = 0.85$
Minimum design wind loading (cl.27.1.5) $p_{min_r} = 8$ lb/ft²

Topography

Topography factor not significant $K_{zt} = 1.0$
Velocity pressure equation $q = 0.00256 \times K_z \times K_{zt} \times K_d \times V^2 \times 1\text{psf}/\text{mph}^2$

Velocity pressures table

z (ft)	K_z (Table 26.10-1)	q_z (psf)
9.50	0.57	15.93

Peak velocity pressure for internal pressure

Peak velocity pressure – internal (as roof press.) $q_i = 15.93$ psf

Pressures and forces

Net pressure $p = q \times G_f \times C_{pe} - q_i \times GC_{pi}$
Net force $F_w = p \times A_{ref}$

Roof load case 1 - Wind 0, $GC_{pi} 0.18$, $-C_{pe}$

Zone	Ref. height (ft)	Ext pressure coefficient C_{pe}	Peak velocity pressure q_p (psf)	Net pressure p (psf)	Area A_{ref} (ft ²)	Net force F_w (kips)
A (-ve)	9.50	-1.22	15.93	-19.41	190.00	-3.69

Zone	Ref. height (ft)	Ext pressure coefficient c_{pe}	Peak velocity pressure q_p (psf)	Net pressure p (psf)	Area A_{ref} (ft ²)	Net force F_w (kips)
B (-ve)	9.50	-0.70	15.93	-12.35	130.00	-1.60

Total vertical net force $F_{w,v} = -5.29$ kips

Total horizontal net force $F_{w,h} = 0.00$ kips

Walls load case 1 - Wind 0, GC_{pi} 0.18, $-c_{pe}$

Zone	Ref. height (ft)	Ext pressure coefficient c_{pe}	Peak velocity pressure q_p (psf)	Net pressure p (psf)	Area A_{ref} (ft ²)	Net force F_w (kips)
A	9.50	0.80	15.93	7.97	380.00	3.03
B	9.50	-0.50	15.93	-9.64	380.00	-3.66
C	9.50	-0.70	15.93	-12.35	76.00	-0.94
D	9.50	-0.70	15.93	-12.35	76.00	-0.94

Overall loading

Projected vertical plan area of wall

$$A_{vert_w_0} = b \times H = 380.00 \text{ ft}^2$$

Projected vertical area of roof

$$A_{vert_r_0} = 0.00 \text{ ft}^2$$

Minimum overall horizontal loading

$$F_{w,total_min} = p_{min_w} \times A_{vert_w_0} + p_{min_r} \times A_{vert_r_0} = 6.08 \text{ kips}$$

Leeward net force

$$F_l = F_{w,wB} = -3.7 \text{ kips}$$

Windward net force

$$F_w = F_{w,wA} = 3.0 \text{ kips}$$

Overall horizontal loading

$$F_{w,total} = \max(F_w - F_l + F_{w,h}, F_{w,total_min}) = 6.7 \text{ kips}$$

Roof load case 2 - Wind 0, GC_{pi} -0.18, $-1c_{pe}$

Zone	Ref. height (ft)	Ext pressure coefficient c_{pe}	Peak velocity pressure q_p (psf)	Net pressure p (psf)	Area A_{ref} (ft ²)	Net force F_w (kips)
A (+ve)	9.50	-0.18	15.93	0.43	190.00	0.08
B (+ve)	9.50	-0.18	15.93	0.43	130.00	0.06

Total vertical net force $F_{w,v} = 0.14$ kips

Total horizontal net force $F_{w,h} = 0.00$ kips

DESIGN COMBO
Walls load case 2 - Wind 0, GC_{pi} -0.18, $-1c_{pe}$

Zone	Ref. height (ft)	Ext pressure coefficient c_{pe}	Peak velocity pressure q_p (psf)	Net pressure p (psf)	Area A_{ref} (ft ²)	Net force F_w (kips)
A	9.50	0.80	15.93	13.70	380.00	5.21
B	9.50	-0.50	15.93	-3.90	380.00	-1.48
C	9.50	-0.70	15.93	-6.61	76.00	-0.50
D	9.50	-0.70	15.93	-6.61	76.00	-0.50

Overall loading

Projected vertical plan area of wall

$$A_{vert_w_0} = b \times H = 380.00 \text{ ft}^2$$

Projected vertical area of roof

$$A_{vert_r_0} = 0.00 \text{ ft}^2$$

Minimum overall horizontal loading

$$F_{w,total_min} = p_{min_w} \times A_{vert_w_0} + p_{min_r} \times A_{vert_r_0} = 6.08 \text{ kips}$$

Leeward net force

$$F_l = F_{w,wB} = -1.5 \text{ kips}$$

Windward net force

$$F_w = F_{w,wA} = 5.2 \text{ kips}$$

Overall horizontal loading

$$F_{w,total} = \max(F_w - F_l + F_{w,h}, F_{w,total_min}) = 6.7 \text{ kips}$$

RELEASED FOR CONSTRUCTION
As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri

12/17/2024

Sht. No. 2 of 4

Roof load case 3 - Wind 90, GC_{pi} 0.18, $-c_{pe}$

Zone	Ref. height (ft)	Ext pressure coefficient c_{pe}	Peak velocity pressure q_p (psf)	Net pressure p (psf)	Area A_{ref} (ft ²)	Net force F_w (kips)
A (-ve)	9.50	-0.90	15.93	-15.05	38.00	-0.57
B (-ve)	9.50	-0.90	15.93	-15.05	38.00	-0.57
C (-ve)	9.50	-0.50	15.93	-9.64	76.00	-0.73
D (-ve)	9.50	-0.30	15.93	-6.93	168.00	-1.16

Total vertical net force $F_{w,v} = -3.04$ kips

Total horizontal net force $F_{w,h} = 0.00$ kips

Walls load case 3 - Wind 90, GC_{pi} 0.18, $-c_{pe}$

Zone	Ref. height (ft)	Ext pressure coefficient c_{pe}	Peak velocity pressure q_p (psf)	Net pressure p (psf)	Area A_{ref} (ft ²)	Net force F_w (kips)
A	9.50	0.80	15.93	7.97	76.00	0.61
B	9.50	-0.20	15.93	-5.58	76.00	-0.42
C	9.50	-0.70	15.93	-12.35	380.00	-4.69
D	9.50	-0.70	15.93	-12.35	380.00	-4.69

Overall loading

Projected vertical plan area of wall

$$A_{vert_w_90} = d \times H = 76.00 \text{ ft}^2$$

Projected vertical area of roof

$$A_{vert_r_90} = 0.00 \text{ ft}^2$$

Minimum overall horizontal loading

$$F_{w,total_min} = p_{min_w} \times A_{vert_w_90} + p_{min_r} \times A_{vert_r_90} = 1.22 \text{ kips}$$

Leeward net force

$$F_l = F_{w,wb} = -0.4 \text{ kips}$$

Windward net force

$$F_w = F_{w,wa} = 0.6 \text{ kips}$$

Overall horizontal loading

$$F_{w,total} = \max(F_w - F_l + F_{w,h}, F_{w,total_min}) = 1.2 \text{ kips}$$

RELEASED FOR CONSTRUCTION
As Noted on Plan Review
 Development Services Department
 Lee's Summit, Missouri
 12/17/2024

Roof load case 4 - Wind 90, GC_{pi} -0.18, $+c_{pe}$

Zone	Ref. height (ft)	Ext pressure coefficient c_{pe}	Peak velocity pressure q_p (psf)	Net pressure p (psf)	Area A_{ref} (ft ²)	Net force F_w (kips)
A (+ve)	9.50	-0.18	15.93	0.43	38.00	0.02
B (+ve)	9.50	-0.18	15.93	0.43	38.00	0.02
C (+ve)	9.50	-0.18	15.93	0.43	76.00	0.03
D (+ve)	9.50	-0.18	15.93	0.43	168.00	0.07

Total vertical net force $F_{w,v} = 0.14$ kips

Total horizontal net force $F_{w,h} = 0.00$ kips

Walls load case 4 - Wind 90, GC_{pi} -0.18, $+c_{pe}$

Zone	Ref. height (ft)	Ext pressure coefficient c_{pe}	Peak velocity pressure q_p (psf)	Net pressure p (psf)	Area A_{ref} (ft ²)	Net force F_w (kips)
A	9.50	0.80	15.93	13.70	76.00	1.04
B	9.50	-0.20	15.93	0.16	76.00	0.01
C	9.50	-0.70	15.93	-6.61	380.00	-2.51
D	9.50	-0.70	15.93	-6.61	380.00	-2.51

Overall loading

Projected vertical plan area of wall

$$A_{vert_w_90} = d \times H = 76.00 \text{ ft}^2$$

Projected vertical area of roof

$$A_{vert_r_90} = 0.00 \text{ ft}^2$$

Minimum overall horizontal loading

$$F_{w,total_min} = p_{min_w} \times A_{vert_w_90} + p_{min_r} \times A_{vert_r_90} = 1.22 \text{ kips}$$

Leeward net force







$$F_l = F_{w,wB} = 0.0 \text{ kips}$$

Windward net force

$$F_w = F_{w,wA} = 1.0 \text{ kips}$$

Overall horizontal loading

$$F_{w,total} = \max(F_w - F_l + F_{w,h}, F_{w,total_min}) = 1.2 \text{ kips}$$



RELEASED FOR CONSTRUCTION
As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri

12/17/2024

Seismic Loads on Nonstructural Components: ASCE 7-10, Chapter 13**RELEASED FOR CONSTRUCTION**
As Noted on Plan ReviewDevelopment Services Department
Lee's Summit, Missouri
12/17/2024**Horizontal Load:**

$S_{DS} = 0.1050 \text{ g}$ (Short period spectral response acceleration factor)
 $a_p = 1.0$ (ASCE 7-10, Table 13.5-1 or 13.6-1)
 $R_p = 2.5$ (ASCE 7-10, Table 13.5-1 or 13.6-1)
 $W_p = 8,300 \text{ lbs}$ (Component operating weight)
 $I_p = 1.5$ (Component importance factor per ASCE 7-10, Section 13.1.3)
 $z = 9.5 \text{ ft.}$ (Height to point of attachment with respect to base, ASCE 7-10, Section 13.3.1)
 $h = 9.5 \text{ ft.}$ (Average roof height)

 $F_p = 627 \text{ lbs}$ (ASCE 7-10, EQ.13.3-1) $F_{p,max} = 2,092 \text{ lbs}$ (ASCE 7-10, EQ.13.3-2) $F_{p,min} = 392 \text{ lbs}$ (ASCE 7-10, EQ.13.3-3) **$F_{ph} = 627 \text{ lbs}$** (Force is strength level and can be applied in any horizontal direction)**Vertical Load:**

(ASCE 7-10, Section 13.3.1)

 $F_{pv} = 174 \text{ lbs}$ (Force is strength level and can be upward or downward)BSE - $(13.7+3.9 \text{ PSF}) \times (40 \text{ FT}) \times (9.5 \text{ FT}) = 6688 \text{ lbs.} > 627 \text{ lbs.}$

THEREFORE, WIND GOVERNS LATERAL DESIGN

OVERTURNING CHECK

RELEASED FOR CONSTRUCTION
As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri

12/17/2024

Overturning Check


LOAD

$$DL = 8300\#$$

$$TAB \text{ Between anchors} = 13'-4" (13.33')$$

$$W_D = \left(\frac{8300\#}{40} \right) (13.33) = 2765.98\#$$

$$W_L = (13.7 + 3.9)(9.5')(13.33') = 2229.28\#$$



SINCE DL IS SELF WT, $DL + 0.6W_L$ CONTRAS

$$M_{RES} = W_D (8'/2) = 11063.92\#'$$

$$M_{OVR} = (0.6)(W_{WL})(9.5/2) = 6353.45\#'$$

$$F.S. = \frac{M_{RES}}{M_{OVR}} = 1.74 > 1.5 \quad \therefore \text{Overturning not applicable}$$

Anchors provided are for positive connection to the paving.

RELEASED FOR CONSTRUCTION
As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri


12/17/2024

ANCHORAGE CHECK

RELEASED FOR CONSTRUCTION
As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri

12/17/2024



3A SIDE ANCHOR TO CONCRETE SLAB- OPTION

3 SIDE ANCHOR TO CONCRETE SLAB- OPTION

ASSUMED CONNECTION TO EACH ANCHOR POINT PER THE LAYOUT PROVIDED TO BSE

www.hilti.com

Company:		Page:	1
Address:		Specifier:	
Phone Fax:		E-Mail:	
Design:	Concrete - Nov 6, 2024	Date:	11/6/2024
Fastening point:			

Specifier's comments:

1 Input data

Anchor type and diameter:	Kwik Bolt TZ2 - CS 3/4 (3 3/4) hnom2
Item number:	2210312 KB-TZ2 3/4x6 1/4
Specification text:	Hilti KB-TZ2 stud anchor with 4.5 in embedment, 3/4 (3 3/4) hnom2, Carbon steel, installation per ESR-4266
Effective embedment depth:	$h_{ef,act} = 3.750$ in., $h_{nom} = 4.500$ in.
Material:	Carbon Steel
Evaluation Service Report:	ESR-4266
Issued Valid:	12/1/2023 12/1/2025
Proof:	Design Method ACI 318-19 / Mech
Stand-off installation:	$e_b = 0.000$ in. (no stand-off); $t = 0.500$ in.
Anchor plate ^R :	$l_x \times l_y \times t = 3.000$ in. x 6.750 in. x 0.500 in.; (Recommended plate thickness: not calculated)
Profile:	no profile
Base material:	cracked concrete, 2500 , $f'_c = 2,500$ psi; $h = 6.000$ in.
Installation:	Hammer drilled hole, installation condition: Dry
Reinforcement:	tension: not present, shear: not present; no supplemental splitting reinforcement present edge reinforcement: none or < No. 4 bar




RELEASED FOR CONSTRUCTION
As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri
12/17/2024

Conservative assumption

^R - The anchor calculation is based on a rigid anchor plate assumption.

Geometry [in.] & Loading [lb, in.lb]



ASSUMED PAVING PER CIVIL

www.hilti.com

Company:
Address:
Phone | Fax: |
Design: Concrete - Nov 6, 2024
Fastening point:

Page: 2
Specifier:
E-Mail:
Date: 11/6/2024

1.1 Design results

Case	Description	Forces [lb] / Moments [in.lb]	Seismic	Max. Util. Anchor [%]
1	Combination 1	N = 3,000; V _x = 0; V _y = 0; M _x = 0; M _y = 0; M _z = 0;	no	99


2 Load case/Resulting anchor forces

Anchor reactions [lb]

Tension force: (+Tension, -Compression)

Anchor	Tension force	Shear force	Shear force x	Shear force y
1	3,256	0	0	0
2	3,256	0	0	0

Max. concrete compressive strain: 0.36 [‰]
Max. concrete compressive stress: 1,587 [psi]
Resulting tension force in (x/y)=(0.000/0.000): 6,512 [lb]
Resulting compression force in (x/y)=(1.281/0.000): 3,512 [lb]



Anchor forces are calculated based on the assumption of a rigid anchor plate.

3 Tension load

	Load N _{ua} [lb]	Capacity ϕ N _n [lb]	Utilization $\beta_N = N_{ua} / \phi N_n$	Status
Steel Strength*	3,256	19,009	18	OK
Pullout Strength*	N/A	N/A	N/A	N/A
Concrete Breakout Failure**	6,512	6,608	99	OK

* highest loaded anchor **anchor group (anchors in tension)

RELEASED FOR CONSTRUCTION

As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri

12/17/2024



Hilti PROFIS Engineering 3.1.5

www.hilti.com

Company:
Address:
Phone | Fax: |
Design: Concrete - Nov 6, 2024
Fastening point:

Page: 3
Specifier:
E-Mail:
Date: 11/6/2024

3.1 Steel Strength

N_{sa} = ESR value refer to ICC-ES ESR-4266
 $\phi N_{sa} \geq N_{ua}$ ACI 318-19 Table 17.5.2

Variables

$A_{se,N}$ [in. ²]	f_{uta} [psi]
0.24	105,904

Calculations

N_{sa} [lb]
25,345

Results

N_{sa} [lb]	ϕ_{steel}	ϕN_{sa} [lb]	N_{ua} [lb]
25,345	0.750	19,009	3,256

3.2 Concrete Breakout Failure

$$N_{cbg} = \left(\frac{A_{Nc}}{A_{Nc0}} \right) \psi_{ec,N} \psi_{ed,N} \psi_{c,N} \psi_{cp,N} N_b \quad \text{ACI 318-19 Eq. (17.6.2.1b)}$$

$$\phi N_{cbg} \geq N_{ua} \quad \text{ACI 318-19 Table 17.5.2}$$

$$A_{Nc} \text{ see ACI 318-19, Section 17.6.2.1, Fig. R 17.6.2.1(b)}$$

$$A_{Nc0} = 9 h_{ef}^2 \quad \text{ACI 318-19 Eq. (17.6.2.1.4)}$$

$$\psi_{ec,N} = \left(\frac{1}{1 + \frac{2 e_N}{3 h_{ef}}} \right) \leq 1.0 \quad \text{ACI 318-19 Eq. (17.6.2.3.1)}$$

$$\psi_{ed,N} = 0.7 + 0.3 \left(\frac{c_{a,min}}{1.5 h_{ef}} \right) \leq 1.0 \quad \text{ACI 318-19 Eq. (17.6.2.4.1b)}$$

$$\psi_{cp,N} = \text{MAX} \left(\frac{c_{a,min}}{c_{ac}}, \frac{1.5 h_{ef}}{c_{ac}} \right) \leq 1.0 \quad \text{ACI 318-19 Eq. (17.6.2.6.1b)}$$

$$N_b = k_c \lambda_a \sqrt{f'_c} h_{ef}^{1.5} \quad \text{ACI 318-19 Eq. (17.6.2.2.1)}$$

Variables

h_{ef} [in.]	$e_{c1,N}$ [in.]	$e_{c2,N}$ [in.]	$c_{a,min}$ [in.]	$\psi_{c,N}$
3.750	0.000	0.000	∞	1.000
c_{ac} [in.]	k_c	λ_a	f'_c [psi]	
10.000	21	1.000	2,500	

Calculations

A_{Nc} [in. ²]	A_{Nc0} [in. ²]	$\psi_{ec1,N}$	$\psi_{ec2,N}$	$\psi_{ed,N}$	$\psi_{cp,N}$	N_b [lb]
168.75	126.56	1.000	1.000	1.000	1.000	7,625

Results

N_{cbg} [lb]	$\phi_{concrete}$	ϕN_{cbg} [lb]	N_{ua} [lb]
10,167	0.650	6,608	6,512

RELEASED FOR CONSTRUCTION
As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri

12/17/2024



Hilti PROFIS Engineering 3.1.5

www.hilti.com

Company:		Page:	4
Address:		Specifier:	
Phone Fax:		E-Mail:	
Design:	Concrete - Nov 6, 2024	Date:	11/6/2024
Fastening point:			

4 Shear load

	Load V_{ua} [lb]	Capacity ϕV_n [lb]	Utilization $\beta_v = V_{ua} / \phi V_n$	Status
Steel Strength*	N/A	N/A	N/A	N/A
Steel failure (with lever arm)*	N/A	N/A	N/A	N/A
Pryout Strength*	N/A	N/A	N/A	N/A
Concrete edge failure in direction **	N/A	N/A	N/A	N/A

* highest loaded anchor **anchor group (relevant anchors)

When the input edge distance is set to "infinity", edge breakout verification is not performed in that direction

5 Warnings

- The anchor design methods in PROFIS Engineering require rigid anchor plates per current regulations (AS 5216:2021, ETAG 001/Annex C, EOTA TR029 etc.). This means load re-distribution on the anchors due to elastic deformations of the anchor plate are not considered - the anchor plate is assumed to be sufficiently stiff, in order not to be deformed when subjected to the design loading. PROFIS Engineering calculates the minimum required anchor plate thickness with CBFEM to limit the stress of the anchor plate based on the assumptions explained above. The proof if the rigid anchor plate assumption is valid is not carried out by PROFIS Engineering. Input data and results must be checked for agreement with the existing conditions and for plausibility!
- Condition A applies where the potential concrete failure surfaces are crossed by supplementary reinforcement proportioned to tie the potential concrete failure prism into the structural member. Condition B applies where such supplementary reinforcement is not provided, or where pullout or pryout strength governs.
- Refer to the manufacturer's product literature for cleaning and installation instructions.
- For additional information about ACI 318 strength design provisions, please go to <https://submittals.us.hilti.com/PROFISAnchorDesignGuide/>
- Hilti post-installed anchors shall be installed in accordance with the Hilti Manufacturer's Printed Installation Instructions (MPII). Reference ACI 318-19, Section 26.7.

Fastening meets the design criteria!

RELEASED FOR CONSTRUCTION
As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri

12/17/2024

www.hilti.com

Company:
Address:
Phone | Fax: |
Design: Concrete - Nov 6, 2024
Fastening point:

Page: 5
Specifier:
E-Mail:
Date: 11/6/2024

6 Installation data

Profile: no profile

Hole diameter in the fixture: $d_f = 0.812$ in.

Plate thickness (input): 0.500 in.

Recommended plate thickness: not calculated

Drilling method: Hammer drilled

Cleaning: Manual cleaning of the drilled hole according to instructions for use is required.

Anchor type and diameter: Kwik Bolt TZ2 - CS 3/4 (3 3/4)
hnom2

Item number: 2210312 KB-TZ2 3/4x6 1/4

Maximum installation torque: 1,324 in.lb

Hole diameter in the base material: 0.750 in.


Hole depth in the base material: 4.750 in.

Minimum thickness of the base material: 6.000 in.

Hilti KB-TZ2 stud anchor with 4.5 in embedment, 3/4 (3 3/4) hnom2, Carbon steel, installation per ESR-4266

6.1 Recommended accessories

Drilling	Cleaning	Setting
- Suitable Rotary Hammer - Properly sized drill bit	Manual blow-out pump	- Torque controlled cordless impact tool - Torque wrench - Hammer



RELEASED FOR CONSTRUCTION
As Noted on Plan Review

Development Services Department
Lee's Summit, Missouri

12/17/2024

Coordinates Anchor [in.]

Anchor	x	y	c _{-x}	c _{+x}	c _{-y}	c _{+y}
1	0.000	-1.875	-	-	-	-
2	0.000	1.875	-	-	-	-